



PROJECT REPORT

A Comparative Analysis of HANs, SVMs and XGBoost for Fake News Detection

CS F407 - Artificial Intelligence
Birla Institute of Technology and Science, Pilani
February 20, 2025

Group Members

Aditya Agrawal	2022A7PS0160P
Shikhar Singh	2022A7PS1170P

Abstract

We consider the challenge of tackling the proliferation of fake news critical in today's dynamic socio-political landscape. Acknowledging its societal relevance and urgency, we aim to conduct a comparative analysis of machine learning models to identify those with optimal performance in correctly classifying this misinformation. For this purpose, we focus on the **WELFake dataset**. Traditional models like **SVM** demonstrate competitive performance in specific frameworks, achieving 99% accuracy with supervised FastText embeddings (Hashmi et al., 2024). The proposed approach combines **FastText** for text vectorization followed by a **Hierarchical Attention Network (HAN)** to model contextual and hierarchical features, while also evaluating **XGBoost** and **SVM** for comparative analysis.

Research Papers Summary

Recent advancements in fake news detection highlight the evolution from traditional machine learning (ML) to hybrid deep learning (DL) frameworks. **Hashmi et al. (2024)** pioneered a hybrid model combining **FastText embeddings** with a **CNN-LSTM architecture**, achieving 99% accuracy on datasets like **WELFake** and **FakeNewsNet** by leveraging cross-modal attention and hierarchical syntactic patterns. Their integration of explainable AI (XAI) techniques, such as **LIME** and **Latent Dirichlet Allocation (LDA)**, enhanced model transparency—a critical requirement for real-world deployment.

Sarasa-Cabezuelo et al. (2023) conducted a comprehensive survey categorizing AI-driven detection methods into **deep learning**, **natural language processing (NLP)**, **ensemble learning**, and **graph-based approaches**, emphasizing the transition from rule-based systems to transformer models like **BERT** and knowledge graphs. Their work underscores the need for hybrid models that integrate social context and multi-modal data to address scalability and adversarial robustness challenges.

Hu et al. (2022) systematically reviewed DL paradigms, highlighting **CNN-LSTM hybrids** and **graph neural networks (GNNs)** for modeling propagation patterns. Their analysis demonstrated DL's superiority over traditional ML in capturing semantic dependencies and temporal-structural features, particularly on datasets like **Twitter15/16**, while advocating for weakly supervised learning to mitigate data scarcity.

Granik and Mesyura (2017) established a baseline using **Naive Bayes** on BuzzFeed's dataset, achieving 74% accuracy with bag-of-words. The authors advocate for preprocessing

enhancements (e.g., **stop-word removal**, **stemming**) and dataset expansion to improve generalizability.

Ozbay and Alatas (2020) evaluated **more than 20 supervised algorithms** (e.g., J48, Random Forest) across multiple datasets, finding tree-based models (e.g., Decision Trees) superior on larger datasets like **ISOT** (96.8% accuracy).

Problem Statement and Approach

Problem Statement: Given a news article, determine if it is legitimate or fake.

We employ a comparative framework to evaluate the efficacy of hierarchical neural architectures against traditional machine learning models for fake news detection on the **WELFake dataset**, comprising 72,134 web and social media articles labeled as "fake" or "real". We use **FastText** for word-level embeddings to capture semantic relationships in the preprocessing phase itself, to convert the text data into vector embeddings. For our first model, we plan to use **Hierarchical Attention Network (HAN)** designed to model article-level contextual hierarchies through sentence and word-level attention layers. For baseline comparison, we plan to implement **Support Vector Machine (SVM)** and **XGBoost** with hyperparameter tuning. Text preprocessing includes **lemmatization**, **stop-word removal**, and normalization to mitigate noise, while model performance is assessed using **accuracy**, **precision**, **recall**, **F1-score**, and **Matthews Correlation Coefficient (MCC)** to address class imbalance. We plan to use a cross-validation strategy to ensure robustness. The approach draws on established methodologies: FastText's utility in hybrid architectures (Hashmi et al., 2024), SVM's robustness in feature-engineered setups (Sarasa-Cabezuelo et al., 2023), and XGBoost's ensemble efficacy (Ozbay & Alatas, 2020), while addressing scalability gaps identified in shallow models like Naive Bayes (Granik & Mesyura, 2017).

References

1. **Hashmi, E., Yildirim Yayilgan, S., Yamin, M. M., Ali, S., & Abomhara, M.** (2024). Advancing Fake News Detection: Hybrid Deep Learning With FastText and Explainable AI. *IEEE Access*, 12, 44462–44466. <https://doi.org/10.1109/ACCESS.2024.3381038>
2. **Berrondo-Otermin, M., & Sarasa-Cabezuelo, A.** (2023). Application of Artificial Intelligence Techniques to Detect Fake News: A Review. *Electronics*, 12(24), 5041.

<https://doi.org/10.3390/electronics12245041>

3. **Hu, L., Wei, S., Zhao, Z., & Wu, B.** (2022). Deep learning for fake news detection: A comprehensive survey. *AI Open*, 3, 133–155. <https://doi.org/10.1016/j.aiopen.2022.09.001>
4. **Granik, M., & Mesyura, V.** (2017). Fake News Detection Using Naive Bayes Classifier. *2017 IEEE First Ukraine Conference on Electrical and Computer Engineering (UKRCON)*. <https://doi.org/10.1109/UKRCON.2017.8100379>
5. **Ozbay, F. A., & Alatas, B.** (2020). Fake news detection within online social media using supervised artificial intelligence algorithms. *Physica A: Statistical Mechanics and Its Applications*, 540, 123174. <https://doi.org/10.1016/j.physa.2019.123174>