



UNIVERSITY OF LEEDS

MATH3001: Project in Mathematics

Analysing five examples of extreme UK river floods and assessing
flood mitigation policy, using flood-excess volume

Abbey Chapman

ID: 201005685 | Supervisors: O. Bokhove and T. Kent

School of Mathematics
University of Leeds
2018/2019

Contents

1	To do list	2
2	Introduction	3
3	Definition of flood-excess volume	4
3.1	Approximations of the flood-excess volume	4
4	Verification; The Boxing Day 2015 floods in the county of West Yorkshire	6
4.1	The River Aire	6
4.1.1	Past and planned mitigation projects in Leeds	7
4.2	The River Calder	8
4.2.1	Past and planned mitigation projects in Calderdale	8
5	Verification; The June 2007 flood of the River Don	9
5.1	Past and planned mitigation projects in Sheffield	9
6	The November 2012 flood of the River Avon	10
6.1	The flood in Stratford-upon-Avon	11
6.1.1	Verification of the Stratford-upon-Avon FEV of November 2012	13
6.2	The flood in Warwick	13
6.2.1	Verification of the Warwick FEV of November 2012	14
7	Flood-mitigation cost effectiveness assessment using FEV	15
7.1	Past and planned mitigation projects upstream of Stratford-upon-Avon	15
7.2	Sustainable Urban Drainage Systems (SuDS)	16
7.3	Natural flood management	17
7.3.1	Flow-attenuation features	17
7.3.2	Tree planting	17
7.4	Storage of flood water in reservoirs	17
7.5	Giving room to the River	17
8	Summary and discussion	19
8.1	Futher Reading	19
8.2	Acknowledgements	19
9	References	20
A	Appendix	23

1 To do list

- write report by monday
- compile environment agency emails
- send to mum for spell check
- do graphs for leeds flood mitigation
- do flood mitigation for avon - this is the main work yet to be done
- make sure git hub is up to scratch
- talk about supercritical and sub critical flows, github
- affect of climate, could explain why it would be good to have flood mitigation above fev. include scholarly articles if possible.
- check image referencing and no date
- remove 2.3m from grr graph. talk about verage depth in text (i used when talking about grr longitudinal slope, 0.715m strat and 0.93 war.
- talk about limits of automated code and what you would improve if you could continue.
- order references
- update tables
- antonia verification
- cite google maps.
- remove warwick or calder or don section if necessary

2 Introduction

Major flooding events have had a huge detrimental affect on the UKs' economy, its business and the community at large; "In England and Wales alone, over 4 million people and properties valued at over 200 billion are at risk" [1] while the cost of the flooding across the UK on Boxing Day 2015 was estimated to have topped £5 billion nationwide [2]. Thus, this project aims to use the analysis of flood data from the floods of a range of rivers and subsequently assess, by means of flood-excess volume, the cost efficacy of various proposed and hypothetical flood-mitigation policy with the aim of assisting policy makers, businesses and the general public in reducing the negative affects of floods. One way of achieving this, besides the creation of this report, is to produce an automated code that can produce a value for the flood-excess volume of any flood, thereby allowing policy makers and the general public to analyse floods using flood-excess volume which may be pertinent their interests or to investigate methods of mitigating, or even preventing, future flooding in their area.

To mitigate a flood is to reduce the amount of flooding, and thereby the damage as a result of such flooding, caused when a river breaks its banks. Flood-mitigation has been attempted since the very origins of non-nomadic humanity as the negative financial and social repercussions of a large flood (such as loss of property, crops, infrastructure and even life) are severe. Early examples of attempts to mitigate floods include the construction of stilt-houses by the Yue people in Ancient China around 7000 years ago [3]. In the modern world there are many different methods of flood-mitigation that can be used which include: Sustainable Urban Drainage Systems (SuDS), Natural Flood Management (NFM), the building of dams, high flood walls or barriers, river bed widening and the drawing down of drinking water reservoirs before predicted heavy rainfall. Each of these stated methods will be further explored as part of this report.

Floods can be categorised into 6 broadly different types: coastal, surface water (generally caused by rainfall in an area with poor permeability), river, sewer, groundwater and the flooding that results from the failure of a dam [41]. The focus on this report will be on river flooding, also known as fluvial flooding, and the methods designed to mitigate this specific type of flooding.

Flood-excess volume can be simplistically defined as the difference between the total volume of water discharged at a certain spatial location on a river during the time it is in flood and the maximum volume capacity of the river at this location when not in flood [18]. This makes the flood-excess volume the volume of flood water that is actively causing flooding at that location on the river and therefore, by quantifying the volume of water a certain flood-mitigation policy reduces a flood by as well as the cost of implementing it, it is possible to to evaluate the percentage of flood-excess volume mitigated by said policy. The cost per percent of flood-excess volume mitigated of each policy can then be calculated and it is this method of analyzation that will be employed in this report.

As the integral work forming the basis of some sections in this report was performed as part of a team (comprised of A. Feilden, S. Kennet, M. Saunders, J. Willis and A. Chapman), an outline of the report is included below, highlighting which sections were produced individually and which as part of the wider team.

- A review on the concept of flood-excess volume, introduced above, is performed in §2. This has been interpreted individually by the author based on the work performed by O. Bokhove, T. Kent and M. Kelmanson in [18] and [23].
- Analysis of the 2015 Boxing Day flooding of two rivers, the Rivers Aire in Leeds and Calder in Mytholmroyd, within the county of West Yorkshire is included in §3. This analysis includes calculation of flood-excess volume and based on this an assessment of various proposed flood-mitigation measures is performed. The original analysis and assessment was performed by the whole team, with the assistance of O. Bokhove and T. Kent.

- §4 includes the same processes of analysis and assessment as §3 but for the 2007 floods along the River Don in Sheffield. Again, this was performed by the team.
- The rest of the report includes analysis and assessment individually performed by the author. §5 includes the calculation of the flood-excess volume for the November 2012 floods along the River Avon, looking at two locations along the river; Stratford-upon-Avon and Warwick. Also included is the flood-excess volume calculated by A. Fielden as a verification of the authors results.
- Having analysed flooding of the River Avon in §5, §6 contains a cost efficacy assessment of both proposed and hypothetical flood-mitigation scenarios, using the flood-excess volumes calculated in §5.
- A summary of the report is in §7 and conclusions from the report are drawn there. Acknowledgements and suggested further reading, including a web page created by the team giving instructions on how the general public can calculate the flood-excess volume for themselves, is also included here.

3 Definition of flood-excess volume

The flood-excess volume (henceforth abbreviated to FEV) is defined to be the volume of flood water that causes flooding at a specified location along a flooded river. FEV is therefore dependant on the threshold river level h_T . The definition of h_T is the maximum level a river can reach without flooding; i.e. the river floods if the in situ river level \bar{h} rises above h_T . The flow rate Q is given from a pre determined rating curve which gives Q as a function of \bar{h} . All the floods analysed as part of this report have the same equation relating Q and \bar{h}

$$Q(\bar{h}) = c_k(\bar{h} - a_k)^{b_k}, \quad k = 1, \dots, m, \quad (2.1)$$

where the rating curve coefficients a_k , b_k and c_k are provided by the Environment Agency via email. The dimension of a_k must be the same as the river level \bar{h} it is being subtracted from, i.e. m^3 . As b_k is a power, it must be dimensionless which then forces c_k to have dimension $\text{m}^{3-b_k}/\text{s}$ in order for the dimension of the right side of the equation to match the dimension of the left, $[Q(\bar{h})] = \text{m}^3/\text{s}$. Each value of k corresponds to a range of \bar{h} values, i.e. $h_{k-1} < \bar{h} < h_k$. During flooding events the maximum river level achieved is often higher than the upper bound of the last interval at which point the upper bound can be extrapolated to the maximum value of \bar{h} . As $\bar{h} = \bar{h}(t)$, the rating curve $Q = Q(\bar{h})$ means that the flow rate Q can be found implicitly to be a function of time; $Q(\bar{h}(t)) = Q(t)$.

3.1 Approximations of the flood-excess volume

FEV can be approximated using three different methods, each of varying accuracy. It should be noted that as the FEV is a volume it is in units of m^3 . The total volume V discharged by a river with flow rate $Q(\bar{h})$ over a given time interval can be approximated as

$$V \approx \sum_{i=1}^n (Q(\bar{h}_i)) \Delta t, \quad (2.1a)$$

where n is the number of values for $Q(\bar{h})$ within the time interval and t is the time elapsed between each value of $Q(\bar{h})$. As the FEV (V_e) is defined as the excess volume discharged by the river once it has reach a level above h_T until it is back below h_T , equation 2.1a can easily be used to provide the best approximation for FEV

$$V_e \approx V_{e1} = \sum_{i=1}^n (Q(\bar{h}_i) - Q_T) \Delta t, \quad (2.1b)$$

where $Q_T = Q(h_T)$ is constant as h_T is a fixed value. In this case, n is the number of $Q(\bar{h})$ values from when the river level \bar{h} goes above h_T until it is back below h_T . The time that this takes is therefore the equivalent of the duration of the flood T_f . The time interval between subsequent $Q(\bar{h})$ values is thus $\Delta t = T_f/n$ and so as $n \rightarrow \infty$, $\Delta t \rightarrow 0$ this approximation becomes the exact area between the curve $Q(\bar{h})$ and the constant value Q_T , seen to be the shaded area in Figure 1 b).

A second, less accurate, approximation of V_e is given to be the area of the emboldened rectangle in Figure 1 b)

$$V_e \approx V_{e2} = T_f(Q_m - Q_T), \quad (2.1c)$$

where $Q(h_m) = Q_m$ is the mean flow rate above Q_T . Q_m can be found relatively accurately for each of the floods analysed by first finding the FEV using equation 2.1b and then rearranging equation 2.1c so that

$$Q_m \approx \frac{V_e}{T_f} + Q_T, \quad (2.1d)$$

from which h_m is then found by rearranging equation 2.1.

The least accurate third approximation of V_e is

$$V_e \approx V_{e3} = (h_m - h_T) T_f \frac{Q_{max}}{h_{max}} \quad (2.1e)$$

which is found because $Q_m \approx (Q_{max}/h_{max})h_m$ and similarly $Q_T \approx (Q_{max}/h_{max})h_T$, approximation mostly used when there is no rating curve that explicitly gives $Q(\bar{h})$ [23]. h_{max} and Q_{max} stand for the maximum river level and flow rate value achieved during the period being analysed respectively.

All FEVs calculated for the five floods analysed in this report have been calculated using the most accurate approximation, equation 2.1a, given a Δt of 15 minutes.

4 Verification; The Boxing Day 2015 floods in the county of West Yorkshire

4.1 The River Aire




Figure 1: Flow rate and river height data for the River Aire at the Armely gauging station in Leeds: a) river height (\bar{h} [m]) [18] and catchment rainfall [mm] data [19] for a year starting from May 2015 (note, catchment rainfall data was not available for 2016) and b) quadrant plot for the 2015 Boxing Day floods of the River Aire. The top-left quadrant displays the rating curve (using data provided by Table 1) alongside its linear approximation (the blue dashed line), whilst the top-right and bottom-left quadrants display the river height (\bar{h} [m]) and flow rate (Q [m³/s]), respectively, during the floods. FEV is then the blue area below the flow rate curve (a function of \bar{h} , $Q(\bar{h})$, obtained from the rating curve) and above the flow rate corresponding to a given threshold height, $Q_T = Q(h_T)$. $\bar{h} = \bar{h}(t)$, where t is the number of days after the 25th of December 2015, meaning $Q(\bar{h}) = Q(t)$. Equation 2.1a is applied to provide $V_e \approx V_{e1} = 9.34 \text{ Mm}^3$, the blue shaded area. The emboldened rectangle approximates the FEV using equation 2.1c so that $V_{e2} = (Q_m - Q_T) \cdot T_f \approx V_{e1} = 9.34 \text{ Mm}^3$, thereby providing an approximation of Q_m given fixed $Q_T = 219.1 \text{ m}^3/\text{s}$ and calculated $T_f = 32$ hours. Rearranging the rating curve equation 2.1 will provide an evaluation of $h_m = 4.77 \text{ m}$ from Q_m .

k	h_{k-1} [m]	h_k [m]	c_k [m ^{3-b_k} /s]	b_k [-]	a_k [m]
1	0.2	0.685	30.69	1.115	0.156
2	0.685	1.917	27.884	1.462	0.028
3	1.917	4.17	30.127	1.502	0.153

Table 1: The coefficients a_k , b_k and c_k and their corresponding upper (h_k) and lower (h_{k-1}) bounds on \bar{h} [18] applied in the calculation of the rating curve, using equation 2.1, at the Armley gauging station on the River Aire.

4.1.1 Past and planned mitigation projects in Leeds




Figure 2: Flooding in Stratford-upon-Avon and Warwick: the top left photo is of a plaque in Stratford-upon-Avon displaying historic flood height highs; it was erected before the 2012 flooding event [12]. The top right is a photo of Bancroft in Stratford-upon-Avon during a flood [25]. The bottom two photos are of the famous Warwick Castle, the left [8] unflooded and the right [9] during a flood. The gauging stations in both Warwick and Stratford-upon-Avon are very slightly upstream from the Castle and Bancroft respectively meaning it is these areas of flooding that will be analysed.

4.2 The River Calder




Figure 3: Flow rate and river height data for the River Calder at the Mytholmroyd gauging station: a) river height (\bar{h} [m]) [23] and catchment rainfall [mm] data [19] for a year starting from May 2015 (note, catchment rainfall data was not available for 2016) and b) quadrant plot for the 2015 Boxing Day floods of the River Calder (*cf.* Figure 1 b)).

k	h_{k-1} [m]	h_k [m]	c_k [$\text{m}^{3-b_k}/\text{s}$]	b_k [-]	a_k [m]
1	0	2.107	8.459	2.239	0.342
2	2.107	3.088	21.5	1.37	0.826
3	3.088	5.8	2.086	2.515	-0.856

Table 2: The coefficients a_k , b_k and c_k and their corresponding upper (h_k) and lower (h_{k-1}) bounds on \bar{h} [23] applied in the calculation of the rating curve, using equation 2.1, at the Mytholmroyd gauging station on the River Calder.

4.2.1 Past and planned mitigation projects in Calderdale

5 Verification; The June 2007 flood of the River Don




Figure 4: Flow rate and river height data for the River Don at the Sheffield Hadfields: a) river height (\bar{h} [m]) [23] and catchment rainfall [mm] data [19] for a year starting from January 2007 and b) quadrant plot for the June 2007 floods of the River Don (*cf.* Figure 1 b)), where the time values in this case give the number of days after the 25th of June 2007.

k	h_{k-1} [m]	h_k [m]	c_k [m ^{3-b_k} /s]	b_k [-]	a_k [m]
1	0	0.52	78.4407	1.7742	0.223
2	0.52	0.931	77.2829	1.3803	0.3077
3	0.931	1.436	79.5956	1.2967	0.34
4	1.436	3.58	41.3367	1.1066	-0.5767

Table 3: The coefficients a_k , b_k and c_k and their corresponding upper (h_k) and lower (h_{k-1}) bounds on \bar{h} [23] applied in the calculation of the rating curve, using equation 2.1, at the Sheffield Hadfields gauging station on the River Don.

5.1 Past and planned mitigation projects in Sheffield

6 The November 2012 flood of the River Avon



Figure 5: Flooding in Stratford-upon-Avon and Warwick: the top left photo is of a plaque in Stratford-upon-Avon displaying historic flood height highs; it was erected before the 2012 flooding event [12]. The top right is a photo of Bancroft in Stratford-upon-Avon during a flood [25]. The bottom two photos are of the famous Warwick Castle, the left [8] unflooded and the right [9] during a flood. The gauging stations in both Warwick and Stratford-upon-Avon are very slightly upstream from the Castle and Bancroft respectively meaning it is these areas of flooding that will be analysed.

6.1 The flood in Stratford-upon-Avon




Figure 6: Flow rate and river height for the River Avon at the Cox's Yard gauging station in Stratford-upon-Avon: a) river height (\bar{h} [m]) [24] and catchment rainfall [mm] data [19] for the months of November and December 2012 (note, catchment rainfall data was not available for this gauging station so data was instead obtained for the next nearest geographical station, Alscot Park on the River Stour) and b) quadrant plot for the November 2012 floods of the River Avon at Stratford-upon-Avon (*cf.* Figure 1 b)), where the time values in this case are the number of days from the 21st of November 2012.

k	h_{k-1} [m]	h_k [m]	c_k [$\text{m}^{3-b_k}/\text{s}$]	b_k [-]	a_k [m]
1	0.136	0.938	158.04	2.85438	0.262919
2	0.938	1.427	87.0362	0.962129	0.358741

Table 4: The coefficients a_k , b_k and c_k and their corresponding upper (h_k) and lower (h_{k-1}) bounds on \bar{h} [24] applied in the calculation of the rating curve, using equation 2.1, at the Cox's Yard gauging station on the River Avon.




Figure 7: Stratford-upon-Avon square lake graphs for the November 2012 flood: a) is a visual aid demonstrating the relationship between a chosen h_T and both its corresponding FEV (the red line with crosses) and square lake side length (the light blue line with circles) where b) demonstrates what is meant by square lake side length, the side length of our calculated FEV's (1.83Mm^3) 2m deep square lake being 956.56m. c) shows how the calculated FEV (*cf.* Figure 1 b)) for the seperated peaks (the middle peak corresponds to the green line with triangles, the right peak to the blue line with circles and the leftmost peak, which then disapears above $h_T = 1.6\text{m}$, to the black square) of $Q(t)$ above Q_T (as seen in Figure 4 b)) is then added together to approximate the total FEV (the red line with crosses).

6.1.1 Verification of the Stratford-upon-Avon FEV of November 2012

6.2 The flood in Warwick




Figure 8: Flow rate and river height for the River Avon at the Warwick gauging station: a) river height (\bar{h} [m]) [24] and catchment rainfall [mm] data [19] for the months of November and December 2012. b) quadrant plot for the November 2012 floods of the River Avon at Warwick (*cf.* Figure 1 b)), where the time values in this case are the number of days from the 21st of November 2012.

k	h_{k-1} [m]	h_k [m]	c_k [m ^{3-b_k} /s]	b_k [-]	a_k [m]
1	0.960	3.000	40.6178	1.44854	0.917837

Table 5: The coefficients a_k , b_k and c_k and their corresponding upper (h_k) and lower (h_{k-1}) bounds on \bar{h} [24] applied in the calculation of the rating curve, using equation 2.1, at the Warwick gauging station on the River Avon.




Figure 9: Warwick square lake graphs for the November 2012 flood: a) is a visual aid demonstrating the relationship between a chosen h_T and both its corresponding FEV (the orange line with crosses) and square lake side length (the light blue line with circles) where b) demonstrates what is meant by square lake side length, the side length of our calculated FEV's (0.74Mm^3) 2m deep square lake being 908.28m. c) gives the individual FEV of seperated peaks when they occur ;the leftmost peak corresponds to the black line with squares, the right peak to the blue line with circles and the middle peak, when it does exist, to the green triangles (*cf.* Figure 6 c)). The total FEV is given by the orange line with crosses.

6.2.1 Verification of the Warwick FEV of November 2012

7 Flood-mitigation cost effectiveness assessment using FEV

7.1 Past and planned mitigation projects upstream of Stratford-upon-Avon




Figure 10: Flood-risk map for the stretch of the River Avon in between Warwick and Stratford-upon-Avon [22]. The location of the gauging stations in Warwick and Stratford-upon-Avon are given by the orange and red markers respectively. St. John’s brook is denoted by the green marker and the Racecourse brook by the yellow marker; each of which could potentially provide extra flood water storage.

Warwickshire County Council in association with the Environment Agency and Severn Trent Water have produced a local flood risk management strategy [5] that approaches that task of managing flooding from two angles, non-structural (aimed at mitigating the affects of a flood once it has begun as well as the general public’s preparedness for a flood) and structural flood mitigation (aimed at preventing, or reducing the volume of, a flood). One example of non-structural flood mitigation being explored by the council is the introduction of a comprehensive sandbag protocol so that the public has quick and plentiful access to sandbags in the event of a flood.

However, in order to perform a cost effectiveness assessment using FEV of different methods of flood mitigation, the volume the relevant mitigation policy reduces the FEV by must be quantifiable and as such the assessment in this report will be focussed solely on structural flood mitigation. There are three structural flood mitigation projects suggested in [5] which are the planned building of two brooks (St John's brook in Warwick and Racecourse brook in Stratford-upon-Avon) and the already built portable flood barriers owned by the Environment Agency that can be deployed ahead of a predicted flood.

St John's brook in Warwick (The green marker in Figure **fill in**) is expected to be built less than 50 metres upstream of the river level gauging station in Warwick (the orange marker in Figure **fill in**) and is expected to provide 32000m³ of flood water storage potential at a cost of £1.45M whilst the Racecourse brook in Stratford-upon-Avon (represented by the yellow marker in Figure **fill in**) will give around 16000m³ of storage for £720000 [10]. Both brooks therefore provide 48000m³ (equivalent to 2.62% of the November 2012 flood in Stratford-upon-Avon) of extra flood water storage costing £2.17M, meaning that the price per percentage of FEV mitigated is £0.83M.

The third structural flood mitigation project is the manufacturing of 40km of temporary portable flood barriers by the Environment Agency for use in numerous locations including Stratford-upon-Avon

[39]. This project has recently been completed and a flooding scenario simulation involving the barrier has been undertaken in the centre of Stratford-upon-Avon [25]. The cost per metre of constructing the barrier has been estimated to be between £5 and £10, meaning the cost of constructing 40km is in the range of £[0.2, 0.4]M. The cost of the full 40km is included as it needs to be this length so that it can be used in numerous locations during a flood as if Stratford-upon-Avon is flooded then it is likely other locations near to Stratford-upon-Avon will be flooded and thus need the barriers too. The cost per deployment of these barriers is estimated to be in the range of £[1000, 20000] [37], and this along with the knowledge that the Avon has flooded 10 times (as mention in §fill in since January of 1992, the cumulative costs of deployment over 50 years can be approximated as £[19000, 380000]. Assuming an average annual maintenance cost of £5 per m [26], giving a 50 year maintenance cost of 40km of barrier of £10M, the cost of building, running and maintaining the temporary flood barriers for 50 years is £[10.22, 10.38]M. The temporary nature of the barriers make it difficult to quantify the percentage of FEV mitigated because if the barrier is properly and punctually in place before the flood being then 100% of the FEV is mitigated. If, however, the barrier is not put in place in time then 0% of the FEV will be mitigated. Thus, the cost per percentage of FEV mitigated could potentially be £[0.102, 0.104]M if the barrier is in place every time the river floods; on the other hand, the project cost of £[10.22, 10.38]M may not mitigate the flood at all if it is never in place when the river floods and is therefore a wasted expense. More detailed assessment on the probability of the barrier being in place is therefore needed before any conclusions may be drawn.

Having performed a cost efficacy assessment of flood mitigation tactics in Warwickshire and how they could affect flooding in Stratford-upon-Avon, various hypothetical scenarios will now be similarly assessed and then compared with the nonspeculative methods discussed above.

7.2 Sustainable Urban Drainage Systems (SuDS)

Sustainable Urban Drainage Systems (or SuDS) encompasses flood mitigation techniques aimed at reducing the detrimental effects of urbanisation has on surface water run off rates, which can cause both surface water and flooding [21]. Types of SuDS include green roofs and permeable paving and the potenetial effect of installing 50000m², comprising an area sufficiently smaller than the area comprised of the Stratford-upon-Avon town limits, of each of these kinds of SuDS within Stratford-upon-Avon will be specifically explored. The estimated cost per m² of installing green roofs and permeable pavements is £90 and £40 alongside 50 year maintenance costs of £313 and £20 respectively [42]. Hence, the combined cost over 50 years of 50000m² of green roofs and 50000m² is approximately £22.17M. Models of both green roofs and permeable pavements and their affects on the volume of a flood have shown that about 0.116m³ and 0.138m³ of the flood is mitigated per m² of green roofing and permeable paving respectively [21]. Therefore, the combined effects of 50000m² of each of these methods could mitigate a flood by as much as 12700m³, comprising 0.69% of the FEV. The cost per 1% of FEV is then found to be £32.13M, an extremely large value. The apparent exceedingly poor cost effectiveness of SuDS in relation to the purpose of mitigating a flood may explain why Warwickshire County Council have decided to make it a requirement for any new properties built to have enough SuDS to mitigate their negative effect on surface water flooding [4]; as opposed to simply buying and installing new SuDS themselves.

7.3 Natural flood management

7.3.1 Flow-attenuation features

7.3.2 Tree planting

7.4 Storage of flood water in reservoirs

7.5 Giving room to the River




Figure 11: Giving-room-to-the-river: a) is a heavily simplified transverse profile of the River Avon once it has been widened by 3m at a height of 0.5m where its average average width before the process is 3.96m [13]. The gradient of the new slope (1/b) is approximately the same as before the process ; b) is a zoom in of the top left quadrant of Figure 6. It is a plot of the flow rate $Q(\bar{h})$ against t , cf. Figure 6 b). The threshold level h_T does not change as part of the GRR process but the relationship between \bar{h} and Q , the rating curve, does. The two threshold flow rates on the graph, Q_{Ta} and Q_{Tb} , correspond to the river before it is widened and after respectively. Thus, the FEV mitigated by the GRR process can be quantified as the difference of the FEV's given by the two different threshold flow rates, $V_{ea} - V_{eb} = 1.01\text{m}^3/\text{s}$, which is equivalent to $\approx 55.19\%$ of the FEV before GRR.



Figure 12: Satellite (left) and map (right) view [35] of the proposed stretch of the river to undertake giving-room-to-the-river, i.e. the stretch of river that flows through Stratford-upon-Avon that when flooded puts properties at risk. The right photo gives the approximate length of this stretch of the river as 1.72km.

8 Summary and discussion

8.1 Futher Reading

The main source of information in regards to the flood-excess volume analysis used in this report was provided from the two articles [18] and [23], co-authored by the supervisors of this project, O. Bokhove and T. Kent. As such it would be beneficial to read these articles if there is a wish gain a broader understanding of the subject. Detailed information on the various methods of NFM is provided by the Environment Agency in [34]. More information on what may happen in the future in regards to flood management nation wide is included [1], produced by the Flood and Coastal Defence project of the Foresight programme.

As part of this project the author, with the assistance of A. Feliden, S. Kennet, M. Saunder and J. Willis, has created two web pages, one giving information on the wider project as well as each individuals chosen rivers¹ and another containing all the instruction nessecary to perform the same FEV analysis as in this report². This includes as automated code, written by the author, which only needs the parameters of the rating curve and a chosen h_T to produce a graph and provide an evaluation of the FEV, Q_m , Q_T , h_m and T_f . The code and the graph it produces may be found in the Appendix. There are some limits to the automated nature of this code, such as the fact that if the curve $Q(\bar{h})$ is split into more than one peak above Q_T then, although the FEV calculated will be accurate, T_f and thereby Q_m and h_m will not. The code also will not work if the flood data being analysed does not cover an integer number of days. Therefore, if this project were to be continued, fixing these issues would be strived for. Another web page³ created by the author includes all the data sets and rating curve information integral to the calculations of FEV in this report as well as the basic code for the included graphs.

8.2 Acknowledgements

The author would like to thank and acknowledge the Environment Agency in the West Midlands for contributing river height and flow rate data for the Warwick and Cox's Yard gauging stations, alongside each stations rating curve information, towards this report. This report Contains public sector information licensed under the Open Government Licence v3.0.

¹The web page giving an over arching description of the project, and each team members individual work, can be found on GitHub at <https://github.com/Rivers-Project-2018/Group-Project>

²The web page giving instructions on how to FEV analysis can be found on GitHub at <https://github.com/Rivers-Project-2018/How-to-do-FEV-Analysis>

³The web page containing the data sets, rating curve information and code used in this report can be found on GitHub at <https://github.com/Rivers-Project-2018/Abbey-Chapman>

9 References

References

1. Flood and Coastal Defence Project of the Foresight programme. *Foresight: Future Flooding*. [Online]. 2004. [Accessed 14 March 2019]. Available from: <https://assets.publishing.service.gov.uk/>
2. Burn-Callander, R. *UK flooding: cost of damage to top 5bn but many homes and businesses under-insured*. [Online]. 2015. [Accessed 14 March 2019]. Available from: <https://www.telegraph.co.uk/>
3. Peters, H. *Tattooed Faces and Stilt Houses: Who Were the Ancient Yue?*. [Online]. 1990. [Accessed 14 March 2019]. Available from: <http://sino-platonic.org/>
4. Warwickshire County Council. *Surface Water Management Plan Methodology Report*. [Online]. 2015. [Accessed 14 March 2019]. Available from: <https://apps.warwickshire.gov.uk/>
5. Warwickshire County Council. *Local Flood Risk Management Strategy*. [Online]. 2016. [Accessed 14 March 2019]. Available from: <https://apps.warwickshire.gov.uk/>
6. GaugeMap. *Stratford (River Avon), Warwick (River Avon)*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://www.gaugemap.co.uk/>
7. BBC News *Warwickshire floods: Three swept away in car escape injury*. [Online]. 2012. [Accessed 14 March 2019]. Available from: <https://www.bbc.co.uk/>
8. Brown, E. *Warwick Castle - River Avon, Warwick*. [Online]. 2016. [Accessed 14 March 2019]. Available from: <https://www.flickr.com/>
9. Dimmer, S. *Flood alerts issued for parts of Warwickshire*. [Online]. 2015. [Accessed 14 March 2019]. Available from: <https://www.coventrytelegraph.net/>
10. English Severn & Wye. *Regional Flood Coastal Committee: Tuesday 8 January 2019 agenda*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://assets.publishing.service.gov.uk/>
11. River Levels. *River Avon at Stratford*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://riverlevels.uk/>
12. Smith, C. *Updated: River Avon remains on flood alert despite falling water levels*. [Online]. 2018. [Accessed 14 March 2019]. Available from: <http://www.stratford-herald.com/>
13. UK Waterways Guide. *A brief history of the River Avon*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://www.ukwaterwaysguide.co.uk/>
14. susdrain. *Stroud Rural Suds, Stroud*. [Online]. 2018. [Accessed 14 March 2019]. Available from: <https://www.susdrain.org/>
15. Woodland Trust. *Natural flood management guidance: Woody dams, deflectors and diverters*. [Online]. 2016. [Accessed 14 March 2019]. Available from: <https://www.woodlandtrust.org.uk/>
16. Rural Payments Agency and Natural England. *RP33: Large leaky woody dams*. [Online]. 2017. [Accessed 14 March 2019]. Available from: <https://www.gov.uk/>
17. Flood information service. *River level: River Avon at Stratford*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://flood-warning-information.service.gov.uk/>


18. Bokhove, O., Kelmanson, M. and Kent, T. *On using flood-excess volume in flood mitigation, exemplified for the River Aire Boxing Day Flood of 2015*. [Online]. 2018. [Accessed 14 March 2019]. Available from: <https://eartharxiv.org/>
19. National River Flow Archive. *NERC CEH, Warwick, Armely, Mytholmroyd, Sheffield Hadfields, Alscot Park*. [Online]. 2019. [Accessed 14 March 2019]. Available from: <https://nrfa.ceh.ac.uk/>
20. Environment Agency. *Natural flood management part of the nations flood resilience*. [Online]. 2017. [Accessed 14 March 2019]. Available from: <https://www.gov.uk/>
21. Bayon, J., Charlesworth, S., Jato-Espino and Warwick, F. RainfallRunoff Simulations to Assess the Potential of SuDS for Mitigating Flooding in Highly Urbanized Catchments. *International Journal of Environmental Research and Public Health*. 2016, **13**(1), 149.
22. Environment Agency. *Likelihood of flooding in this area*. [Online]. 2017. [Accessed 14 March 2019]. Available from: <https://flood-map-for-planning.service.gov.uk/>
23. Bokhove, O., Kelmanson, M. and Kent, T. *On using flood-excess volume to assess natural flood management, exemplified for extreme 2007 and 2015 floods in Yorkshire*. [Online]. 2018. [Accessed 14 March 2019]. Available from: <https://eartharxiv.org/>
24. Weston, M. on behalf of the Environment Agency in the West Midlands. *Email to Abbey Chapman*. 20 November, 2018.
25. Lugg, B. *New emergency flood barrier tested in Stratford*. [Online]. 2017. [Accessed 15 March 2019]. Available from: <http://www.stratford-herald.com/>
26. Environment Agency. *Cost estimation for channel management*. [Online]. 2015. [Accessed 14 March 2019]. Available from: <http://evidence.environment-agency.gov.uk/>
27. Environment Agency. *Cost estimation for control assets*. [Online]. 2015. [Accessed 15 March 2019]. Available from: <http://evidence.environment-agency.gov.uk/>
28. The Editors of Encyclopedia Britannica. *River Avon*. [Online]. 2014. [Accessed 15 March 2019]. Available from: <https://www.britannica.com/>
29. Natural England. *Countryside Stewardship Manual: Woodland Creation Grant*. [Online]. 2018. [Accessed 15 March 2019]. Available from: <https://assets.publishing.service.gov.uk/>
30. Route Calculator. *Altitude Stratford-upon-Avon, Warwick, UK*. [Online]. 2019. [Accessed 16 March 2019]. Available from: <https://routecalculator.co.uk/>
31. Doogal. *Measuring distances*. [Online]. 2019. [Accessed 16 March 2019]. Available from: <https://www.doogal.co.uk/>
32. FishXing. *Manning's n Values*. [Online]. 2006. [Accessed 16 March 2019]. Available from: <http://www.fsl.orst.edu/>
33. Okiishi, T., Musnon, B. and Young, D. *Fundamentals of Fluid Mechanics*. [Online]. . [Accessed 16 March 2019]. Available from:
34. Environment Agency. *Working with Natural Processes - Evidence Directory*. [Online]. 2018. [Accessed 16 March 2019]. Available from: <https://assets.publishing.service.gov.uk/>
35. Google Maps. *Google Maps*. [Online]. 2019. [Accessed 17 March 2019]. Available from: <https://www.google.com/>

36. Stanford Ringing Group. *About Stanford Reservoir*. [Online]. 2001. [Accessed 17 March 2019]. Available from: <http://stanfordrg.org.uk/>
37. Shropshire Star. *Protecting Shropshire from floods - this winter cost 45,000 keeping our homes dry*. [Online]. 2016. [Accessed 17 March 2019]. Available from: <https://www.shropshirestar.com/>
38. Water Active. *Sykes provides overpump for Stanford reservoir spillway*. [Online]. 2017. [Accessed 17 March 2019]. Available from: <http://www.wateractive.co.uk/>
39. Environment Agency. *Major flood defence exercise in Stratford*. [Online]. 2017. [Accessed 17 March 2019]. Available from: <https://www.gov.uk/>
40. Uk Water Projects Online. *Stanford Reservoir Spillway Extension*. [Online]. . [Accessed 17 March 2019]. Available from:
41. Environment Agency. *Sources of flooding*. [Online]. 2013. [Accessed 17 March 2019]. Available from: <https://webarchive.nationalarchives.gov.uk//floods/31652.aspx>
42. Environment Agency. *Cost estimation for SuDS - summary of evidence*. [Online]. 2015. [Accessed 16 March 2019]. Available from: <http://evidence.environment-agency.gov.uk/>
43. . . [Online]. . [Accessed 16 March 2019]. Available from:
44. . . [Online]. . [Accessed 16 March 2019]. Available from:
45. . . [Online]. . [Accessed 16 March 2019]. Available from:

A Appendix

The graph that the automated FEV code produces using the example of the 2015 Boxing Day flood of the River Aire at Armley as an example

```
In [79]: runfile('/Users/abbeyelizabethchapman/Rivers Project/Aire Graphs/Automated-Quadrant
9342292.707224404
31.999999992000003
3.9
4.774043185542993
219.09314749264328
300.1894383742403
```



```
In [80]:
```

The automated FEV code- written in the python coding language

```
##Input your own data here:##
#Your chosen threshold height.
ht=3.9

#Your rating curve coefficients, listed starting from those corresponding to
#the lowest range of heights up until the heighest range.
a=[0.156,0.028,0.153]
b=[1.115,1.462,1.502]
c=[30.69,27.884,30.127]

#The upper and lower limits of the ranges of the river heights given for your
#rating curve.
lower_limits=[0.2,0.685,1.917]
upper_limits=[0.685,1.917,4.17]

#You do not have to change the following.
import matplotlib.pyplot as plt
import pandas as pd
```



```

fig , ax = plt.subplots()

#Import your data, your river height data must be saved into a csv file
#(we are using the file 'Aire Data.csv' but you must change what your csv file
#is saved as) within the same folder as this code is saved. The first column must have the
#heading 'Time', with time values converted into days (with the digits beyond the
#decimal point representing what the hours and seconds elapsed are in terms of a
#fraction of a day, more information on how to do this can be found at
#https://github.com/Rivers-Project-2018/How-to-do-FEV-Analysis/blob/master/README.md)
#and the second column must have the heading 'Height'.
Data=pd.read_csv('Aire_Data.csv')
time=Data['Time']
height=Data['Height']

#Once you have run the file, type in your own values for FEV, Tf, ht,hm, qt
#and qm (they will appear in the code output in that order).
#The values inputted here are for the exmaple Aire data.
plt.text(0.4,-0.475,'$T_f$=32.00 hrs', size=15)
plt.text(0.4,-0.55,'$h_T$=3.90m', size=15)
plt.text(0.4,-0.625,'$h_m$=4.77m', size=15)
plt.text(0.4,-0.7,'$Q_T$=219.1m$^3$/s', size=15)
plt.text(0.4,-0.775,'$Q_m$=300.2m$^3$/s', size=15)

#####You do not have to change any of the rest of the code.#####
#But if you wish to change elements such as the colour or the x and y axis
#there are instructions on how to do so.
import bisect
import numpy as np

plt.rcParams["figure.figsize"] = [11,8]
plt.rcParams['axes.edgecolor']='white'
ax.spines['left'].set_position(('center'))
ax.spines['bottom'].set_position(('center'))
ax.spines['left'].set_color('black')
ax.spines['bottom'].set_color('black')

time_increment=(time[1]-time[0])*24*3600

number_of_days=int((len(time)*(time[1]-time[0])))

def scale(x):
    return ((x-min(x))/(max(x)-min(x)))
scaledtime=scale(time)
scaledheight=scale(height)

w=[]
for i in range(len(a)):
    w.append(i)

def Q(x):
    z=0
    while z<w[-1]:
        if x>lower_limits[z] and x<=upper_limits[z]:
            y = (c[z]*((x-a[z])**b[z]))
            break
        elif x>upper_limits[z]:
            z = z+1
    else:
        y = (c[w[-1]]*((x-a[w[-1]])**b[w[-1]]))
    return(y)

```

```

qt = Q(ht)

Flow = []
for i in height:
    Flow.append(Q(i))

scaledFlow = []
for i in Flow:
    scaledFlow.append((i-min(Flow))/(max(Flow)-min(Flow)))

negheight=-scaledheight
negday=-(scaledtime)

#To change the colour, change 'cornflowerblue' to another colour such as 'pink'.
ax.plot(negheight, scaledFlow, 'black', linewidth=2)
ax.plot([0, -1], [0, 1], 'cornflowerblue', linestyle='--', marker='', linewidth=2)
ax.plot(scaledtime, scaledFlow, 'black', linewidth=2)
ax.plot(negheight, negday, 'black', linewidth=2)

scaledht = (ht-min(height))/(max(height)-min(height))
scaledqt = (qt-min(Flow))/(max(Flow)-min(Flow))

QT=[]
for i in scaledFlow:
    i = scaledqt
    QT.append(i)

SF=np.array(scaledFlow)
e=np.array(QT)

ax.fill_between(scaledtime, SF, e, where=SF>=e, facecolor='cornflowerblue')

idx = np.argwhere(np.diff(np.sign(SF - e))).flatten()

f=scaledtime[idx[0]]
g=scaledtime[idx[-1]]

def unscaletime(x):
    return (((max(time)-min(time))*x)+min(time))

C=unscaletime(f)
d=unscaletime(g)

Tf=(d-C)*24

time_increment=(time[1]-time[0])*24*3600

flow = []
for i in Flow:
    if i>=qt:
        flow.append((i-qt)*(time_increment))

FEV=sum(flow)

Tfs=Tf*(60*2)

qm=(FEV/Tfs)+qt
scaledqm = (qm-min(Flow))/(max(Flow)-min(Flow))

hm=((qm/c[-1])** (1/b[-1]))+a[-1]
scaledhm = (hm-min(height))/(max(height)-min(height))

```

```

ax.plot([-scaledht,-scaledht],[-1,scaledqt],'black',linestyle='—',linewidth=1)
ax.plot([-scaledhm,-scaledhm],[-1,scaledqm],'black',linestyle='—',linewidth=1)
ax.plot([-scaledht,1],[scaledqt,scaledqt],'black',linestyle='—',linewidth=1)
ax.plot([-scaledhm,1],[scaledqm,scaledqm],'black',linestyle='—',linewidth=1)

ax.plot([f,f,f],[scaledqt,scaledqm,-1/5],'black',linestyle='—',linewidth=1)
ax.plot([g,g,g],[scaledqt,scaledqm,-1/5],'black',linestyle='—',linewidth=1)
ax.plot([f,f],[scaledqm,scaledqt],'black',linewidth=1.5)
ax.plot([f,g],[scaledqm,scaledqm],'black',linewidth=1.5)
ax.plot([f,g],[scaledqt,scaledqt],'black',linewidth=1.5)
ax.plot([g,g],[scaledqm,scaledqt],'black',linewidth=1.5)
plt.annotate(s='', xy=(f-1/100,-1/5), xytext=(g+1/100,-1/5), arrowprops=dict(arrowstyle='<->'))

h=[]
for i in np.arange(1,number_of_days+1):
    h.append(i/number_of_days)

#If you wish to set the flow to be shown on the axis by a certain increment, change all
#appearances of 50 in lines 163 and 167 to the desired increment, e.g 25 or 100.
#Otherwise leave as is.
l=np.arange(0,max(Flow)+50,50)
m=bisect.bisect(l,min(Flow))

n=[]
for i in np.arange(l[m],max(Flow)+50,50):
    n.append(int(i))

#If you wish to set the height to be shown on the axis by a certain increment, change all
#appearances of 1 in lines 173 and 177 to the desired increment, e.g 0.25 or 0.5.
#Otherwise leave as is.
o=np.arange(0,max(height)+1,1)
p=bisect.bisect(o,min(height))

q=[]
for i in np.arange(o[p],max(height)+1,1):
    q.append(i)

k=[]
for i in q:
    k.append(-(i-min(height))/(max(height)-min(height)))

j=[]
for i in n:
    j.append((i-min(Flow))/(max(Flow)-min(Flow)))

ticks_x=k+h

r=[]
for i in h:
    r.append(-i)

ticks_y=r+j

s=[]
for i in np.arange(1,number_of_days+1):
    s.append(i)

Ticks_x=q+s
Ticks_y=s+n

```

```

ax.set_xticks(ticks_x)
ax.set_yticks(ticks_y)
ax.set_xticklabels(Ticks_x)
ax.set_yticklabels(Ticks_y)

ax.tick_params(axis='x', colors='black', direction='out', length=9, width=1)
ax.tick_params(axis='y', colors='black', direction='out', length=10, width=1)

plt.text(-scaledht+1/100, -1, '$h_T$', size=13)
plt.text(-scaledhm+1/100, -1, '$h_m$', size=13)
plt.text(1, scaledqm, '$Q_m$', size=13)
plt.text(1, scaledqt, '$Q_T$', size=13)
plt.text(((f+g)/2)-1/50, -0.18, '$T_f$', size=13)

plt.text(0.01, 1.05, '$Q_{m^3/s}$ ', size=13)
plt.text(0.95, -0.17, '$t_{day}$ ', size=13)
plt.text(0.01, -1.09, '$t_{day}$ ', size=13)
plt.text(-1.1, 0.02, '$\overline{h}_{[m]}$', size=13)

ax.scatter(0,0,color='white')

print(FEV)
print(Tf)
print(ht)
print(hm)
print(qt)
print(qm)

plt.text(0.4, -0.4, '$FEV_{[m]}$'+ Str(FEV/(10**6))+ '9.34Mm$^3$', size=15)

```