以 datacamp **Python For Data Science NumPy Cheat Sheet**

Learn NumPy online at www.DataCamp.com


Numpy

The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays

Use the following import convention:

>>> import numpy as np

NumPy Arrays



Creating Arrays

```
>>> a = np.array([1.2.3])
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)
>>> c = np.array([[(1.5,2,3), (4,5,6)],[(3,2,1), (4,5,6)]], dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4)) #Create an array of zeros
>>> np.ones((2,3,4),dtype=np.int16) #Create an array of ones
>>> d = np.arange(10,25,5) #Create an array of evenly spaced values (step value)
>>> np.linspace(0,2,9) #Create an array of evenly spaced values (number of samples)
>>> e = np.full((2,2),7) #Create a constant array
>>> f = np.eve(2) #Create a 2X2 identity matrix
>>> np.random.random((2,2)) #Create an array with random values
>>> np.emptv((3.2)) #Create an emptu arrau
```

Saving & Loading On Disk

```
>>> np.save('mv arrav', a)
>>> np.savez('array.npz', a, b)
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")
>>> np.genfromtxt("my_file.csv", delimiter=',')
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Asking For Help

>>> np.info(np.ndarray.dtype)

Inspecting Your Array

```
>>> a.shape #Array dimensions
>>> len(a) #Length of array
>>> b.ndim #Number of array dimensions
>>> e.size #Number of array elements
>>> b.dtype #Data type of array elements
>>> b.dtype.name #Name of data type
>>> b.astype(int) #Convert on array to a different type
```

Data Types

```
>>> np.int64 #Signed 64-bit integer types
>>> np.float32 #Standard double-precision floating point
>>> np.complex #Complex numbers represented by 128 floats
>>> nn.hool #Boolean tune storing TRUE and FALSE values
>>> np.object #Puthon object tupe
>>> np.string_ #Fixed-length string type
>>> np.unicode_ #Fixed-length unicode type
```

Array Mathematics

Arithmetic Operations

```
>>> q = a - b #Subtraction
arrav([[-0.5, 0. , 0. ],
       [-3. , -3. , -3. ]])
>>> np.subtract(a,b) #Subtraction
>>> b + a #Addition
array([[ 2.5, 4. , 6. ]
>>> np.add(b,a) Addition
>>> a / h #Division
array([[ 0.6666667, 1. , 1. ]
        [ 0.25 , 0.4 , 0.5 ]])
>>> np.divide(a,b) #Division
>>> a * b #Multiplication
array([[ 1.5, 4. , 9. ],
        [ 4. , 10. , 18. ]])
>>> np.multiply(a,b) #Multiplication
>>> np.exp(b) #Exponentiation
>>> np.sqrt(b) #Square root
>>> np.sin(a) #Print sines of an array
>>> np.cos(b) #Element-wise cosine
>>> np.log(a) #Element-wise natural logarithm
>>> e.dot(f) #Dot product
array([[ 7., 7.],
```

Comparison

```
>>> a = b #Element-wise comparison
array([[False, True, True],
       [False, False, False]], dtype=bool)
>>> a < 2 #Element-wise comparison
array([True, False, False], dtype=bool)
>>> np.array_equal(a, b) #Array-wise comparison
```

Aggregate Functions

```
>>> a.sum() #Array-wise sum
>>> a.min() #Array-wise minimum value
>>> b.max(axis=0) #Maximum value of an array row
>>> b.cumsum(axis=1) #Cumulative sum of the elements
>>> a.mean() #Mean
>>> np.median(b) #Median
>>> np.corrcoef(a) #Correlation coefficient
>>> np.std(b) #Standard deviation
```

Copying Arrays

```
>>> h = a.view() #Create a view of the array with the same data
>>> np.copy(a) #Create a copy of the array
>>> h = a.copy() #Create a deep copy of the array
```

Sorting Arrays

```
>>> a.sort() #Sort an array
>>> c.sort(axis=0) #Sort the elements of an array's axis
```

Subsetting, Slicing, Indexing

```
>>> a[2] #Select the element at the 2nd index
>>> b[1,2] #Select the element at row 1 column 2 (equivalent to b[1][2])
>>> a[0:2] #Select items at index 0 and 1
```

```
array([1, 2])
>>> b[0:2,1] #Select items at rows 0 and 1 in column 1
array([ 2., 5.])
>>> b[:1] #Select all items at row 0 (equivalent to b[0:1, :])
array([[1.5, 2., 3.]])
>>> c[1,...] #Same as [1,:,:]
array([[[ 3., 2., 1.],
        [ 4., 5., 6.]]])
>>> a[ : :-1] #Reversed array a array([3, 2, 1])
```

```
>>> a[a<2] #Select elements from a less than 2 \,
                                                                                    1 2 3
array([1])
```

```
>>> b[[1, 0, 1, 0],[0, 1, 2, 0]] #Select elements (1,0),(0,1),(1,2) and (0,0)
array([ 4. , 2. , 6. , 1.5]) 
>>> b[[1, 0, 1, 0]][:,[0,1,2,0]] #Select a subset of the matrix's rows and columns
array([[ 4. ,5. , 6. , 4. ],
        [ 1.5, 2. , 3. , 1.5],
         [4.,5.,6.,4.]
        [ 1.5, 2. , 3. , 1.5]])
```

Array Manipulation

```
>>> i = np.transpose(b) #Permute array dimensions
>>> i.T #Permute array dimensions
```

Changing Array Shape

```
>>> b.ravel() #Flatten the array
>>> g.reshape(3.-2) #Reshape, but don't change data
```

Adding/Removing Elements

```
>>> h.resize((2.6)) #Return a new array with shape (2.6)
>>> np.append(h,q) #Append items to an array
>>> np.insert(a, 1, 5) #Insert items in an array
>>> np.delete(a,[1]) #Delete items from an array
```

Combining Arrays

```
>>> np.concatenate((a,d),axis=0) #Concatenate arrays
array([ 1, 2, 3, 10, 15, 20])
>>> np.vstack((a,b)) #Stack arrays vertically (row-wise)
array([[ 1. , 2. , 3. ],
         1.5, 2. , 3. ]
        [ 4. , 5. , 6. ]])
>>> np.r_[e,f] #Stack arrays vertically (row-wise)
>>> np.hstack((e,f)) #Stack arrays horizontally (column-wise)
array([[ 7., 7., 1., 0.],
       [ 7.. 7.. 0.. 1.11)
>>> np.column stack((a.d)) #Create stacked column-wise arrays
array([[ 1, 10],
>>> np.c_[a,d] #Create stacked column-wise arrays
```

Splitting Arrays

```
>>> np.hsplit(a,3) #Split the array horizontally at the 3rd index
[array([1]),array([2]),array([3])]
>>> np.vsplit(c,2) #Split the array vertically at the 2nd index
[array([[[ 1.5, 2. , 1. ]
[ 4. , 5. , 6. ]]]),
array([[[ 3., 2., 3.],
         [ 4., 5., 6.]]])]
```



Learn Data Skills Online at www.DataCamp.com