

ArXiv Platform, API & Data Collection

Technical Reference for Document Classification Project

March 2026

1. About arXiv

1.1 What is arXiv?

arXiv (pronounced "archive") is a free, open-access repository of electronic preprints and postprints covering physics, mathematics, computer science, quantitative biology, quantitative finance, statistics, electrical engineering, systems science, and economics. Founded in 1991 by Paul Ginsparg at Los Alamos National Laboratory, arXiv is now maintained and operated by Cornell University Library with funding from the Simons Foundation and member institutions worldwide.

As of 2026, arXiv hosts over 2.4 million research papers and receives approximately 20,000 new submissions per month. It is the primary dissemination channel for research in fields such as machine learning, natural language processing, high-energy physics, and mathematics — often making papers publicly available months or years before formal journal publication.

Key facts about arXiv:

Website: <https://arxiv.org> | Founded: 1991 | Operator: Cornell University Library
Total papers (2026): ~2.4 million | Monthly submissions: ~20,000
Subjects: Physics, Mathematics, Computer Science, Statistics, Q-Biology, Q-Finance, Economics, EECS

1.2 arXiv Subject Taxonomy

Papers on arXiv are organised into a two-level subject taxonomy. At the top level, subjects are grouped into broad domains (e.g., Computer Science — "cs", Mathematics — "math", Physics — "physics"). Within each domain, subcategories use a dot-separated notation such as `cs.CL` (Computation and Language), `cs.IR` (Information Retrieval), `cs.AI` (Artificial Intelligence), or `math.ST` (Statistics Theory).

Authors assign one or more category labels at submission time. The primary category determines the paper's primary placement in the repository, while cross-listed categories (secondary classifications) allow a paper to appear in multiple subject listings. This taxonomy forms the ground-truth label structure used by many document classification research projects — including the studies reviewed in this project's accompanying literature review.

Category Code	Full Name	Relevance to This Project
cs.CL	Computation and Language	Core NLP / text classification papers
cs.IR	Information Retrieval	Document retrieval and ranking
cs.AI	Artificial Intelligence	General AI / ML methods
cs.LG	Machine Learning	Classification models, transformers
stat.ML	Machine Learning (Statistics)	Statistical learning theory
cs.DL	Digital Libraries	Bibliographic systems, metadata

1.3 arXiv Metadata Fields

Each paper record on arXiv contains a rich set of structured metadata fields. Understanding these fields is essential for designing an effective data extraction and classification pipeline:

- **arxiv_id** — unique identifier in the format `YYMM.NNNNN` (e.g., `2403.00165`). Persistent across versions.
- **title** — the full paper title as submitted by the authors.
- **authors** — a list of author names. Note: arXiv does not enforce name normalisation, so the same person may appear under multiple name variants.
- **abstract** — the full abstract text, typically 100–300 words. The primary text field for NLP classification tasks.
- **categories** — one or more category codes (e.g., `cs.CL cs.LG`). The first code is the primary category.
- **submitted** — the date and time of initial submission to arXiv.
- **updated** — the date of the most recent version update.
- **doi** — Digital Object Identifier linking to the published version, if available.
- **journal_ref** — journal or conference reference string, if provided by the author (not always present).
- **comment** — optional free-text field used by authors for supplementary information (e.g., "10 pages, 4 figures, submitted to NeurIPS").
- **links** — a list of link objects (PDF, abstract page, HTML version).

2. The arXiv API — Capabilities and Guidelines

2.1 Overview

arXiv provides a public REST API that allows programmatic access to paper metadata. The API is based on the Atom 1.0 syndication format and is accessed via HTTP GET requests to the base endpoint:

```
https://export.arxiv.org/api/query?{parameters}
```

The API supports full-text search across all metadata fields, Boolean query construction, date-range filtering, category filtering, result pagination, and multiple sort orderings. No API key or authentication is required for the standard API. Responses are returned as Atom XML feeds, which can be parsed with standard XML or feed-parsing libraries.

2.2 Search Query Parameters

The API accepts the following key query parameters:

Parameter	Description	Example
search_query	Full-text query with field prefixes and Boolean operators	ti:BERT+AND+cat:cs.CL
id_list	Comma-separated list of specific arXiv IDs to retrieve	2403.00165,2203.05794
start	Index of the first result to return (for pagination)	start=100
max_results	Number of results to return per request (max 2000)	max_results=500
sortBy	Sort field: relevance, lastUpdatedDate, submittedDate	sortBy=submittedDate
sortOrder	Sort direction: ascending or descending	sortOrder=descending

2.3 Field Prefixes for Targeted Search

To search within specific metadata fields, the API uses field prefix notation. Prefixes can be combined with AND, OR, and ANDNOT Boolean operators, and parentheses for grouping:

Prefix	Field Searched
ti:	Title only
au:	Author names
abs:	Abstract text
cat:	Subject category (e.g., cs.CL, cs.LG)
all:	All fields simultaneously (default)
submittedDate:	Submission date range [YYYYMMDD TO YYYYMMDD]
id:	ArXiv ID (prefer id_list parameter instead)

2.4 Rate Limits and Terms of Use

arXiv imposes explicit rate limits on all API consumers. Compliance with these limits is mandatory and violations may result in temporary or permanent access blocks:

Official Rate Limits (arXiv Terms of Use):

- Maximum 1 request every 3 seconds for legacy APIs (arXiv API, OAI-PMH, RSS)
- Single connection at a time — do not parallelise requests
- All machines under your control share the same quota
- Maximum ~2,000 results per page request; up to 300,000 results per query via pagination
- For use cases requiring higher throughput, contact arXiv support

Beyond rate limits, the arXiv Terms of Use permit the following uses of API data: retrieving, storing, transforming, and sharing descriptive metadata about arXiv papers; downloading and using paper content for personal use or research; and building tools and services that help users discover arXiv papers. Commercial redistribution of paper full-text, or any use that threatens normal platform operation, is prohibited.

2.5 The Python arxiv Library

The most widely used client for the arXiv API in Python is the official `arxiv` package (PyPI: <https://pypi.org/project/arxiv/>). As of version 2.4.1 (March 2026), it provides a clean object-oriented interface over the raw HTTP API, handling pagination, rate-limiting sleep, and retry logic automatically.

```
pip install arxiv

# Basic usage
import arxiv

client = arxiv.Client(
    page_size      = 500,          # results fetched per HTTP request (max 2000)
    delay_seconds  = 3,           # seconds between requests — respects rate limit
    num_retries    = 5            # retry failed requests up to 5 times
)
```

The library returns `arxiv.Result` objects with the following attributes: `entry_id`, `title`, `authors`, `summary` (abstract), `categories`, `published`, `updated`, `doi`, `journal_ref`, `comment`,

and `links`. Helper methods `download_pdf()` and `download_source()` are also provided for bulk content retrieval.

3. Extraction Code — How It Works

3.1 High-Level Architecture

The data extraction pipeline is composed of four sequential stages: (1) query construction, (2) paginated API fetching with rate-limit compliance, (3) result parsing and normalisation into a structured record, and (4) persistence to a local data store (CSV or JSON). The diagram below illustrates the pipeline flow:

Pipeline Flow:

[1] Build Query → [2] Paginated Fetch (arxiv.Client) → [3] Parse Result Objects
→ [4] Normalise Fields → [5] Deduplicate → [6] Save to CSV / JSON

3.2 Complete Extraction Script

The following self-contained Python script demonstrates the full extraction pipeline. It queries arXiv for papers matching configurable category and keyword filters, paginates through all available results, normalises metadata, deduplicates records, and writes the output to a CSV file:

```
"""
arxiv_extractor.py
Extracts paper metadata from the arXiv API and saves it to CSV.
"""

import arxiv
import csv
import time
import logging
from datetime import datetime
from pathlib import Path

# — Configuration —
```

```

CATEGORIES = ["cs.CL", "cs.IR", "cs.AI", "cs.LG", "stat.ML"]
KEYWORDS   = ["document classification", "text classification",
              "topic modelling", "keyword extraction"]

DATE_FROM  = "20230101"
DATE_TO    = "20260101"
MAX_RESULTS = 5000      # total records to collect
PAGE_SIZE  = 500        # records per API request (max 2000)
DELAY_SECS = 3          # seconds between requests (arXiv rate limit)
OUTPUT_FILE = "arxiv_papers.csv"

# — Logging setup —————
logging.basicConfig(level=logging.INFO,
                    format="%asctime)s %(levelname)s %(message)s")
log = logging.getLogger(__name__)

# — Query builder —————
def build_query(categories: list[str], keywords: list[str],
               date_from: str, date_to: str) -> str:
    """Construct a Boolean arXiv API query string."""
    cat_clause = " OR ".join(f"cat:{c}" for c in categories)
    kw_clause  = " OR ".join(f"abs:{k}" for k in keywords)
    date_clause = f"submittedDate:[{date_from}0000 TO {date_to}2359]"
    return f"({cat_clause}) AND ({kw_clause}) AND {date_clause}"

# — Normalise a single Result object —————
def normalise(result: arxiv.Result) -> dict:
    """Flatten an arxiv.Result into a plain dictionary."""
    return {
        "arxiv_id" : result.entry_id.split("/abs/")[1],
        "title"    : result.title.strip().replace("\n", " "),
        "authors"  : "; ".join(str(a) for a in result.authors),
        "abstract" : result.summary.strip().replace("\n", " "),
        "categories": " ".join(result.categories),
        "primary_cat": result.primary_category,
        "submitted" : result.published.strftime("%Y-%m-%d") if result.published
    else "",
        "updated"   : result.updated.strftime("%Y-%m-%d")   if result.updated
    else "",
        "doi"       : result.doi or "",
        "journal_ref": result.journal_ref or "",
        "comment"   : result.comment or "",
        "pdf_url"   : next((l.href for l in result.links if l.title == "pdf"),
        ""),
    }

# — Main extraction function —————
def extract(query: str, max_results: int,
           page_size: int, delay: float) -> list[dict]:

```

```

"""Fetch all results matching the query, respecting the rate limit."""
client = arxiv.Client(
    page_size      = page_size,
    delay_seconds  = delay,
    num_retries    = 5
)
search = arxiv.Search(
    query          = query,
    max_results    = max_results,
    sort_by        = arxiv.SortCriterion.SubmittedDate,
    sort_order     = arxiv.SortOrder.Descending
)
records, seen_ids = [], set()
for result in client.results(search):
    rec = normalise(result)
    if rec["arxiv_id"] not in seen_ids:      # deduplicate
        seen_ids.add(rec["arxiv_id"])
        records.append(rec)
    if len(records) % 500 == 0:
        log.info("Collected %d records so far ...", len(records))
log.info("Extraction complete. Total records: %d", len(records))
return records

# — Save to CSV —————
def save_csv(records: list[dict], path: str) -> None:
    if not records:
        log.warning("No records to save.")
        return
    fields = list(records[0].keys())
    with open(path, "w", newline="", encoding="utf-8") as f:
        writer = csv.DictWriter(f, fieldnames=fields)
        writer.writeheader()
        writer.writerows(records)
    log.info("Saved %d records to %s", len(records), path)

# — Entry point —————
if __name__ == "__main__":
    q = build_query(CATEGORIES, KEYWORDS, DATE_FROM, DATE_TO)
    log.info("Query: %s", q)
    data = extract(q, MAX_RESULTS, PAGE_SIZE, DELAY_SECS)
    save_csv(data, OUTPUT_FILE)

```

3.3 Code Walkthrough — Key Sections Explained

3.3.1 Query Construction (build_query)

The `build_query` function assembles a compound Boolean query from three components. The category clause uses the `cat:` field prefix with OR to include papers from multiple relevant arXiv subject areas. The keyword clause uses the `abs:` field prefix with quoted phrases to search within abstract text for exact matches. The date clause uses the `submittedDate:` range syntax `[YYYYMMDD TO YYYYMMDD]` to restrict results to a specific time window, which is essential for managing result set size on popular topics.

For example, the query for this project might resolve to:

```
(cat:cs.CL OR cat:cs.IR OR cat:cs.AI OR cat:cs.LG OR cat:stat.ML)
AND (abs:"document classification" OR abs:"text classification"
     OR abs:"topic modelling" OR abs:"keyword extraction")
AND submittedDate:[202301010000 TO 202601012359]
```

3.3.2 Paginated Fetching (extract)

The `arxiv.Client` object handles all pagination transparently. When `client.results(search)` is iterated, the library automatically issues successive HTTP requests using the `start` offset parameter, waiting `delay_seconds` between each page. The `num_retries` parameter ensures transient network failures are handled gracefully with exponential back-off. The generator pattern (`for result in client.results(search)`) means memory usage remains low regardless of result set size, since results are processed one at a time.

3.3.3 Normalisation (normalise)

The `normalise` function flattens each `arxiv.Result` object into a plain Python dictionary suitable for CSV serialisation. Key transformations include: extracting the bare arXiv ID from the full URI (e.g., `https://arxiv.org/abs/2403.00165v1` → `2403.00165v1`); joining the author list as a semicolon-delimited string; collapsing multi-line abstracts to single-line text; and extracting the PDF link from the list of `Result.Link` objects. Fields that may be absent (`doi`, `journal_ref`, `comment`) are defaulted to empty strings to maintain a consistent schema.

3.3.4 Deduplication and Output

A `seen_ids` set guards against duplicate records, which can occur when a paper is cross-listed in multiple categories that both appear in the query. The final output is written to a UTF-8

encoded CSV with a header row matching the dictionary keys. This format is directly ingestible by pandas (`pd.read_csv()`), which is used in the data processing stages described in Section 4.

3.4 Handling arXiv API Limitations

Several known limitations of the arXiv API must be handled in production extraction pipelines:

1. **The 50,000-record hard limit:** The legacy arXiv API will not return more than approximately 50,000 results for a single query, even with high `max_results` values. To collect larger datasets, queries must be broken into time-windowed slices (e.g., month-by-month) and results concatenated.
2. **Pagination offset limitation:** A known issue (reported in 2024–2025) causes some queries to return empty results when `start > 1000`. The recommended workaround is to reduce `page_size` and use date-based partitioning rather than large offset values.
3. **Author name inconsistency:** arXiv does not normalise author names. The same researcher may appear as "A. Smith", "Alice Smith", or "Alice B. Smith". Downstream author disambiguation requires additional processing (see Section 4.4).
4. **Missing metadata:** The `doi`, `journal_ref`, and `comment` fields are optional and frequently absent. Pipeline code must handle `None` values gracefully.
5. **Version management:** ArXiv IDs include version suffixes (e.g., `2403.00165v2`). The pipeline should decide whether to collect the latest version only or all versions, and deduplicate accordingly.

4. Next Steps: Data Processing and Exploration

Once papers are collected and stored in a CSV or JSON file, the raw data requires substantial processing before it can be used for classification, clustering, or analysis. This section describes the full data processing and exploratory analysis pipeline that the project requires, organised into six stages.

Processing Pipeline Overview:

Stage 1: Loading & Validation → Stage 2: Text Cleaning
→ Stage 3: Feature Engineering → Stage 4: Exploratory Data Analysis (EDA)
→ Stage 5: Embedding & Vectorisation → Stage 6: Label Preparation

4.1 Stage 1: Data Loading and Schema Validation

The first processing step is to load the collected CSV into a pandas DataFrame and validate its schema and completeness. This involves checking for the expected column set, asserting that mandatory fields (`arxiv_id`, `title`, `abstract`, `categories`) are non-null, and profiling missing-value rates for optional fields.

```
import pandas as pd

df = pd.read_csv("arxiv_papers.csv")

# Check shape and missing values
print(df.shape)
print(df.isnull().sum())

# Ensure mandatory fields are populated
assert df["abstract"].isnull().sum() == 0, "Missing abstracts detected"

# Parse date fields
df["submitted"] = pd.to_datetime(df["submitted"])
df["updated"] = pd.to_datetime(df["updated"])

# Parse category list from space-delimited string
df["category_list"] = df["categories"].str.split()
```

Data quality checks at this stage should also include: confirming that `arxiv_id` values are unique (no duplicates passed through the extraction deduplication), verifying that `submitted` dates fall within the intended extraction window, and flagging records where `abstract` is unusually short (fewer than 50 characters), which may indicate a parsing error.

4.2 Stage 2: Text Cleaning

Raw arXiv abstracts contain several noise patterns that must be removed or normalised before NLP processing. The primary cleaning operations are:

- **LaTeX artefact removal:** Abstracts frequently contain inline LaTeX such as `\mathbb{R}^n` or `\textbf{bold}`. These should be stripped using a regex or a dedicated LaTeX-to-text converter such as the `pylatexenc` library.
- **Whitespace and line-break normalisation:** Multi-line abstracts may contain embedded newline characters from the Atom XML. All whitespace sequences should be collapsed to a single space.
- **Unicode normalisation:** Author names and title strings may contain non-ASCII Unicode characters (accented letters, special punctuation). Apply NFC normalisation using `unicodedata.normalize("NFC", text)` for consistent encoding.
- **Case normalisation:** Depending on the downstream model, text should be lowercased for bag-of-words and TF-IDF features, but preserved for transformer-based models (BERT tokenisers are case-sensitive).
- **Stop-word and punctuation removal:** For keyword extraction and TF-IDF features, standard English stop words and punctuation should be removed. For neural embeddings, this step is typically skipped as the model handles these tokens internally.

```
import re, unicodedata

def clean_abstract(text: str) -> str:
    text = unicodedata.normalize("NFC", text)
    text = re.sub(r"\$[\^\\$]+\$", " ", text)      # remove inline LaTeX
    text = re.sub(r"\\[a-zA-Z]+\{[^\}]*\}", " ", text) # remove \cmd{...}
    text = re.sub(r"\s+", " ", text).strip()
    return text

df["abstract_clean"] = df["abstract"].apply(clean_abstract)
df["title_clean"]    = df["title"].apply(clean_abstract)
```

4.3 Stage 3: Feature Engineering

Feature engineering creates derived columns that are useful for analysis and modelling. The following features should be computed from the raw metadata:

- **Primary category extraction:** Parse the first element of the category list as the primary label for single-label classification tasks.
- **Category hierarchy:** Split the primary category code into domain (e.g., "cs") and subdomain (e.g., "CL") for hierarchical classification experiments.
- **Abstract length:** Compute word count and character count of the cleaned abstract. This is useful as an analysis feature and as a quality filter.
- **Author count:** Count the number of semicolon-separated authors per record.
- **Time features:** Extract `year`, `month`, and `day_of_week` from the `submitted` datetime for temporal trend analysis.
- **Has DOI / Has journal ref:** Binary flags indicating whether the paper has been formally published, useful for distinguishing preprints from peer-reviewed papers.
- **Version number:** Parse the version suffix from `arxiv_id` (e.g., `v2`) as an indicator of revision history.

4.4 Stage 4: Exploratory Data Analysis (EDA)

EDA is a critical stage that builds understanding of the dataset before any modelling is attempted. The following analyses should be performed and documented:

4.4.1 Category Distribution

Plot the frequency distribution of primary categories and cross-listed categories. Expect heavy class imbalance: categories like `cs.LG` and `cs.CL` will dominate the collection. This imbalance must be addressed in the modelling stage through stratified sampling, oversampling (SMOTE), or class-weighted loss functions.

```
import matplotlib.pyplot as plt

primary_counts = df["primary_cat"].value_counts()
primary_counts.head(20).plot(kind="bar", figsize=(14, 5))
plt.title("Top 20 Primary Categories")
plt.tight_layout()
plt.savefig("category_distribution.png", dpi=150)
```

4.4.2 Temporal Distribution

Plot submission volume over time (monthly or quarterly). This reveals growth trends, seasonal patterns (e.g., spikes before major conference deadlines), and any gaps or anomalies in the data collection. Papers submitted after a major event (e.g., the release of GPT-4 or a major NeurIPS workshop) may cluster around new sub-topics.

4.4.3 Abstract Length Distribution

Plot histograms of abstract word counts. Most abstracts fall in the 100–250 word range. Outliers — very short abstracts (potentially parsing errors) and very long abstracts (occasionally multi-paper reports) — should be inspected and either cleaned or removed.

4.4.4 Keyword Frequency Analysis

Compute TF-IDF scores across the abstract corpus to identify the most discriminative terms per category. This analysis serves two purposes: it validates that the collected papers are on-topic, and it provides a baseline set of category-discriminating keywords that can be used in the keyword-based clustering stage. Tools:

```
sklearn.feature_extraction.text.TfidfVectorizer with max_features=10000 and min_df=5.
```

4.4.5 Co-authorship and Citation Network Analysis (Optional)

For projects that require understanding research community structure, it is possible to build co-authorship graphs from the authors field, or citation graphs by cross-referencing arXiv IDs mentioned in abstracts or comments. NetworkX is the recommended library for graph construction and analysis.

4.5 Stage 5: Embedding and Vectorisation

The choice of text representation depends on the downstream classification task. The project should prepare multiple representations to enable benchmarking:

- **TF-IDF Bag of Words:** Produces sparse vectors suitable for logistic regression, SVM, and naive Bayes classifiers. Fast to compute, interpretable, and a strong baseline. Use `TfidfVectorizer(ngram_range=(1,2), max_features=50000)` for unigrams and bigrams.

- **Sentence-BERT Embeddings:** Use the `sentence-transformers` library with a pre-trained model such as `all-mpnet-base-v2` to encode each abstract into a 768-dimensional dense vector. These embeddings capture semantic meaning and are suitable for neural classifiers, KNN, and clustering algorithms.
- **SciBERT / SPECTER:** For scientific text, domain-specific models such as SciBERT (trained on scientific literature) or SPECTER (trained on paper citations) may outperform general-purpose sentence embedders. Both are available via HuggingFace `transformers`.
- **BERTopic Topic Vectors:** BERTopic can be used to produce topic-distribution vectors for each document as an additional feature layer, combining embedding-based clustering with c-TF-IDF keyword extraction.

```
from sentence_transformers import SentenceTransformer
import numpy as np

model = SentenceTransformer("all-mpnet-base-v2")

# Encode in batches to manage memory
abstracts = df["abstract_clean"].tolist()
embeddings = model.encode(abstracts, batch_size=64,
                           show_progress_bar=True)

# Save for reuse
np.save("embeddings.npy", embeddings)
```

4.6 Stage 6: Label Preparation and Taxonomy Mapping

Before training any classification model, the target labels must be cleaned, mapped, and split into train/validation/test sets. Key tasks at this stage are:

6. **Label normalisation:** Convert all category codes to lowercase and verify against the official arXiv taxonomy list. Remove any records with unrecognised or malformed category codes.
7. **Hierarchy construction:** Build a two-level label hierarchy mapping each `subdomain` to its parent `domain` (e.g., `cs.CL` → `cs`). This hierarchy is required by hierarchical classification models such as TELEClass.

8. **Class filtering:** Remove categories with fewer than a configurable minimum number of samples (e.g., 50 records). Classes with very few examples cannot be reliably trained on and will degrade model performance.
9. **Multi-label handling:** Papers may be cross-listed in multiple categories. Decide on a strategy: (a) use primary category only for single-label tasks; (b) use the full category list as a multi-label target; or (c) train separate binary classifiers per category.
10. **Train/validation/test split:** Use a stratified split (e.g., 70/15/15) to ensure all categories are represented in each partition. For temporal evaluation, consider a time-based split: train on papers before a cutoff date, test on papers after it.

```
from sklearn.model_selection import train_test_split

# Filter to categories with >= 50 samples
counts = df["primary_cat"].value_counts()
valid_cats = counts[counts >= 50].index
df_filtered = df[df["primary_cat"].isin(valid_cats)].copy()

# Stratified split
train_df, temp_df = train_test_split(
    df_filtered, test_size=0.30,
    stratify=df_filtered["primary_cat"], random_state=42)
val_df, test_df = train_test_split(
    temp_df, test_size=0.50,
    stratify=temp_df["primary_cat"], random_state=42)

print(f"Train: {len(train_df)} | Val: {len(val_df)} | Test: {len(test_df)}")
```

4.7 Recommended Tooling Summary

Task	Recommended Library / Tool
API Extraction	arxiv (PyPI v2.4+)
Data Loading & EDA	pandas, matplotlib, seaborn
Text Cleaning	regex, pylatexenc, unicodedata
TF-IDF Vectorisation	scikit-learn TfidfVectorizer
Dense Embeddings	sentence-transformers (SBERT, SciBERT, SPECTER)
Topic Modelling	BERTopic (Grootendorst 2022)

Dimensionality Reduction	UMAP, PCA (scikit-learn)
Clustering	HDBSCAN, KMeans (scikit-learn)
Classification Models	scikit-learn, HuggingFace Transformers, PyTorch
Train/Test Splitting	scikit-learn train_test_split (stratified)
Experiment Tracking	MLflow or Weights & Biases (wandb)
Graph Analysis (optional)	NetworkX