



VISHAL ENTERPRISE & VRISHAL ENGINEERING PRIVATE LIMITED GROUP OF COMPANIES

DISPATCH NOTE FOR PAINTING

| CLIENT | | SURAJ ROSHNI | | | | LOT NO. | | VE/SURYA-26/STR/DNP/4 | | | | | |
|--------------------------|----------------------------|-----------------------------|-------------------------------|---------------------|----------------------------|-----------------------------|------------------|------------------------------------|----------------------|-------------------------------------|---------------------------|------------------------|-------------------------------|
| PROJECT | | SURYA-26 | | | | DISPATCH DATE | | 16/05/2025 | | | | | |
| WO NO./PO NO. | | 9558569011 | | | | DISPATCH SITE | | SA TECHNOCRATS | | | | | |
| SR NO. | DRAWING NO. | REV.NO. | ASSEMBLY NUMBER | GRID NUMBER | GRID QTY | ASSEMBLY WEIGHT (Kg) | | ASSEMBLY SURFACE AREA (sqm) | PAINT SYSTEM | | REMARKS | | |
| 1 | B10 | 0 | B10 | B10-1 | 2 | 24.102 | | 3.726 | 2 | | -- | | |
| PAINT MANUFACTURE | SURFACE PREPARATION | PROFILE REQUIREMENTS | SALT TEST REQUIREMENTS | PRIMER SHADE | PRIMER APP. METHODE | PRIMER DFT RANGE | MIO SHADE | MIO APP. METHODE | MIO DFT RANGE | FINAL SHADE | FINAL APP. METHODE | FINAL DFT RANGE | TOTAL DFT REQUIREMENTS |
| ASIAN | SA 2 1/2 | 40 - 75 microns | Maximum 50 mg/m ² | SIGMACOVER 620 | SPRAY | 100 Microns | SIGMACOVER 620 | SPRAY | 100 Microns | SIGMADUR 550 / SMOKE GREY (ISC 692) | SPRAY | 50 microns | 250 - 350 microns |
| NOTE | | | | | | | | | | | | | |
| | | PREPARED BY | | | | | | | RECEIVED BY | | | | |
| SIGNATURE | | | | | | | | | | | | | |
| NAME | | HARDIK PRAJAPATI | | | | | | | | | | | |
| DATE | | 16/05/2025 | | | | | | | | | | | |
| VE-DOC-22 REV.00 | | | | | | | | | | | | | |