



Type	Size	Length (mm)	Qty
Gr.8.8	M16	45	2
Gr.8.8	M16	50	1
Gr.8.8	M20	55	2

1. ALL DIMENSIONS ARE IN MILLIMETERS. ELEVATIONS ARE IN METERS UNLESS OTHERWISE NOTED.
2. ALL STRUCTURAL STEEL SHALL CONFORM TO IS : 2062 (GRADE 250BR)
3. ALL CONCRETE GRADE SHALL BE M30.
4. FILLET WELD SHALL BE OF MINIMUM 6MM SIZE FOR SHOP WELD AND 8MM FOR SITE WELD UNLESS NOTED OTHERWISE.
5. COLUMNS SHALL HAVE FULL BEARING ON BASE PLATES U.N.O.
6. WORKING POINTS SHALL BE W.R.T. CG LINES FOR WELDED CONNECTIONS AND W.R.T. GAUGE LINES FOR BOLTED CONSTRUCTION.
7. GRATING THICKNESS TO BE 25 MM



PROJECT NO : PJ-3014
PROJECT NAME : PIN-084 PLANT
DRAWING TITLE : FABRICATION DRAWING OF FIRST FLOOR MEZZANINE

AIL PROJECT NO : PIN-084			
SIZE	DWG NO.	SHEET	REV NO.
A1	PIN-084-TPT-PM4-CS11-004-FAB-B47	1 OF 1	0