

BOLT LIST FOR ONE ASSEMBLY			
Type	Size	Length (mm)	Qty
Gr.8.8	M20	60	6

1. ALL DIMENSIONS ARE IN MILLIMETERS. ELEVATIONS ARE IN METERS UNLESS OTHERWISE NOTED.
2. ALL STRUCTURAL STEEL SHALL CONFORM TO IS : 2062 (GRADE 250BR)
3. ALL CONCRETE GRADE SHALL BE M30.
4. FILLET WELD SHALL BE OF MINIMUM 6MM SIZE FOR SHOP WELD AND 8MM FOR SITE WELD UNLESS NOTED OTHERWISE.
5. COLUMNS SHALL HAVE FULL BEARING ON BASE PLATES U.N.O.
6. WORKING LEVELS SHALL BE AS SHOWN IN THE DRAWING. GRATING FOR WELDED CONSTRUCTION AND W.R.T. GAUGE LINES FOR BOLTED CONSTRUCTION.
7. GRATING THICKNESS TO BE 25 MM
8. FOR GRATING/CHEQUERED PLATE ARRANGEMENT REFER TYP. SKETCH GIVEN BY ALL.

AIL PROJECT NO : PIN-084			
SIZE	DWG NO.	SHEET	REV NO.
A1	PIN-084-TPT-PM1-CS12-002-FAB-1B12	1 OF 1	0