

**STANDARD ANALISA PELUMAS
FYRQUEL OIL EHC UNIT 5,6 DAN 7**

NO	TEST COMPONENT	STANDARD REFERENCE		KETERANGAN
		Mitsubishi	Certificate Of Analysis (COA)	
1	Water content, ppm Vol	1500	-	
2	Total Chloride, ppm Wt	50	19	
3	Total Acid Number, mg KOH/g	0.3	0.01	
4	Kinematic Viscosity 100°F, cSt	43 ± 10%	43.0	
5	Kinematic Viscosity 210°F, cSt	5 ± 10%	5.0	
6	Phosporic Acid, ppm Wt	3.0		
7	Color ASTM	0.3	0.4	
8	Contamination (per ml sample) :			
	> 5 µm	9700	6123	
	> 10 µm	2680	901	
	> 25 µm	380	65	
	> 50 µm	56	9	
9	NAS CLASS 1638			
10	ISO CODE 4406			

STANDARD ANALISA MINYAK SECARA UMUM

NO	TEST COMPONENT	SATUAN	TEST METHODE	REMARK
1	SPECIFIC GRAVITY		D-1298	
2	POUR POINT	°F		
3	FLASH POINT OPEN CUP (CLV)	°C	D-93	
4	FIRE POINT	°C		
5	NEUTRALIZATION NUMBER	mgr KOH/gr	D-974	
6	SAPONIFICATION NUMBER	mgr KOH/gr		
7	SEDIMENT CONTENT	%Wt	D-473	
8	Water content, ppm Vol	ppm	D-4928	
9	Kinematic Viscosity 100°F, cSt	cSt.	D-445	
10	Kinematic Viscosity 210°F, cSt	cSt.	D-445	

**STANDARD ANALISA PELUMAS
PRODUKSI PERTAMINA**

NO	JENIS PELUMAS	BATASAN			REMARK
		VISCOSITAS 40 °C			
		SPEC.	MIN	MAX	
1	Meditran S 10	34.85	31.37	38.34	
2	Meditran S 30	92.88	83.59	102.17	
3	Meditran S 50	236.14	212.53	259.75	
4	Mesran - SAE 40	140.74	126.67	154.81	
5	Turalik 41				
6	Turalik 43				
7	Turalik 48				
8	Turalik 52	68.2	61.38	75.02	

**STANDARD ANALISA PELUMAS
PRODUKSI MOBIL OIL**

NO	JENIS PELUMAS	BATASAN			REMARK
		VISCOSITAS 40 °C			
		SPEC.	MIN	MAX	
1	Mobil DTE Light				
2	Mobil DTE 26	68	61.20	74.80	
3	Mobil DTE BB-220	230	207.00	253.00	
4	Mobil Gear 630	220	198.00	242.00	
5	Mobil Gear 634	460	414.00	506.00	
6	Mobil Gear 636	680	612.00	748.00	Gear box mill

**STANDARD ANALISA PELUMAS
PRODUKSI SHELL**

NO	JENIS PELUMAS	BATASAN			REMARK
		VISCOSITAS 40 °C			
		SPEC.	MIN	MAX	
1	Diala Oil B	8.89			
2	Morlina 10				
3	Morlina C 10				
4	Morlina C 100				
5	Omala 150				
6	Omala 320	320			
7	Omala 460	460	414	506	
8	Omala 468				
9	Omala 680	680			
10	Omala Oil 220				
11	Omala Oil 320	320			
12	Rimula D 40	140			
13	Rored EP 90	182.21			
14	Rored HD-A 140	373.74			
15	Shell Omala Oil 460	460 ± 10 %			
16	Spirax HD 140	559			
17	Spirax EP 90	184			
18	Tellus C-10	10			
19	Tellus Oil 22				
20	Tellus Oil 46	46			
21	Tellus Oil 68	68			
22	Tellus 100				
23	Turbo Oil T-32				
24	Turbo Oil T-46				
25	Turbo Oil T-68				
26	Vitrea 220	220			