

Internally Amplified Vibration Sensors

INDUSTRIAL, GENERAL PURPOSE ACCELEROMETERS

These rugged, general purpose sensors are ideal for machinery monitoring and predictive maintenance applications. They are used on machinery monitoring systems worldwide.

	Sensitivity, mV/g	Acceleration Range, g	Frequency Response, Hz ±5%, ±10%	Temperature Range, °C	Weight, grams	Case Material	Mounting
756 	100	.0007 - 50	3 - 1,000 2 - 5,000	-50 to 90	180	stainless steel	three #8 x 7/8" screws
762 	10	.0015 - 500	3 - 10,000 2 - 12,000	-50 to 120	80	stainless steel	1/4-28 tapped hole
766 	100	.00055 - 50	3 - 10,000 2 - 12,000	-50 to 120	80	stainless steel	1/4-28 tapped hole
768* 	500	.00002 - 10	3 - 4,000 2 - 6,000	-50 to 120	90	stainless steel	1/4-28 tapped hole
776 	100	.0002 - 40	3 - 2,500 2 - 5,000	0 to 85	32	stainless steel	1/4-28 tapped hole
793 	100	.0007 - 50	3 - 5,000 2 - 7,000	-50 to 120	110	stainless steel	1/4-28 tapped hole
793L* 	500	.00001 - 10	0.6 - 700 0.4 - 1,000	-50 to 120	135	stainless steel	1/4-28 tapped hole
793LS 	500	.00001 - 10	0.6 - 700 0.4 - 1,000	-50 to 120	135	stainless steel	1/4-28 tapped hole
793S 	100	.0007 - 50	3 - 5,000 2 - 7,000	-50 to 120	110	stainless steel	1/4-28 tapped hole
796 	100	.0008 - 50	3 - 5,000 2 - 7,000	-50 to 120	100	stainless steel	1/4-28 captive screw

* Ultra low noise sensor.