

EventConnect — Dokumentasi Teknis Lengkap

Proyek Capstone — Universitas UNDIRA, Semester Genap 2026

Tanggal Dokumentasi: 21 Mei 2026

Daftar Isi

- [1. Gambaran Umum Sistem](#)
- [2. Arsitektur Sistem](#)
- [3. Teknologi yang Digunakan](#)
- [4. Struktur Direktori](#)
- [5. Skema Database](#)
- [6. Backend — API Documentation](#)
- [7. Frontend — Arsitektur & Komponen](#)
- [8. Role-Based Access Control \(RBAC\)](#)
- [9. Sistem Realtime \(WebSocket\)](#)
- [10. Panduan Setup & Menjalankan Aplikasi](#)
- [11. Data Seed & Akun Testing](#)
- [12. Hasil Testing Fitur](#)
- [13. Bug yang Ditemukan & Diperbaiki](#)
- [14. Rekomendasi Pengembangan Lanjutan](#)

1. Gambaran Umum Sistem

EventConnect adalah platform manajemen event terpadu berbasis web yang dirancang untuk membantu tim penyelenggara event mengelola seluruh proses operasional dari perencanaan hingga eksekusi secara realtime.

Fitur Utama

Modul	Deskripsi
Autentikasi	Login token-based dengan Laravel Sanctum, role-aware redirect
Manajemen User	CRUD user, role assignment (superadmin only)
Manajemen Event	CRUD event, assignment personel ke event
Task & Workflow	CRUD task dengan prioritas, status tracking, komentar, parent-child task
Timeline & Rundown	Manajemen sesi event multi-hari, update status realtime, activity log
Group Chat	Chat per event berbasis WebSocket dengan presence indicator

Target Pengguna

- **Super Admin** — Mengelola semua aspek sistem termasuk user management
- **Project Manager** — Membuat & mengelola event, task, dan rundown
- **Staff/Personnel** — Melihat event yang ditugaskan, mengerjakan task, berkomunikasi via chat

2. Arsitektur Sistem



```
- rundown_deps
- chat_messages
```

Pola Komunikasi

- **REST API:** Semua operasi CRUD menggunakan HTTP/JSON ke `http://localhost:8000/api`
- **WebSocket:** Pengiriman pesan chat dan update status realtime via Laravel Reverb di port `8080`
- **Autentikasi Token:** Bearer token dari Sanctum disertakan di setiap request HTTP dan WebSocket auth

3. Teknologi yang Digunakan

Backend

Komponen	Versi	Keterangan
PHP	^8.3	Runtime bahasa
Laravel	^13.0	Framework utama
Laravel Sanctum	^4.3	Token-based API authentication
Laravel Reverb	^1.0	WebSocket server terintegrasi
MySQL	8.x	Relational database

Frontend

Komponen	Versi	Keterangan
Vue.js	^3.5.32	Framework UI reaktif
Vite	^8.0.10	Build tool & dev server
Vue Router	^4.6.4	Client-side routing
Pinia	^3.0.4	State management
Axios	^1.15.2	HTTP client
Laravel Echo	^2.3.4	WebSocket client wrapper
Pusher JS	^8.5.0	WebSocket transport layer
Lucide Vue Next	^1.0.0	Icon library

4. Struktur Direktori

```
Capstone/
├── backend/                                # Laravel application
│   ├── app/
│   │   ├── Events/
│   │   │   └── MessageSent.php            # WebSocket broadcast event
│   │   ├── Http/
│   │   │   ├── Controllers/Api/
│   │   │   │   ├── AuthController.php
│   │   │   │   ├── ChatController.php
│   │   │   │   ├── EventController.php
│   │   │   │   ├── RundownController.php
│   │   │   │   ├── TaskController.php
│   │   │   │   └── UserController.php
│   │   │   └── Middleware/
│   │   │       └── RoleMiddleware.php
│   │   ├── Models/
│   │   │   ├── User.php
│   │   │   ├── Event.php
│   │   │   ├── EventRundown.php
│   │   │   ├── RundownLog.php
│   │   │   ├── Task.php
│   │   │   └── TaskComment.php
│   │   └── Providers/
│   │       └── AppServiceProvider.php
│   ├── database/
│   │   ├── migrations/                    # 13 file migrasi
│   │   └── seeders/
│   │       └── DatabaseSeeder.php
│   └── routes/
│       ├── api.php                        # Semua API routes
│       └── channels.php                    # WebSocket channel auth
├── frontend/                              # Vue 3 SPA
│   ├── src/
│   │   ├── api/
│   │   │   └── axios.js                  # Axios instance terkonfigurasi
│   │   ├── components/
│   │   │   └── FloatingChat.vue          # Floating chat popup
│   │   ├── layouts/
│   │   │   └── DashboardLayout.vue
│   │   ├── router/
│   │   │   └── index.js                  # Route definitions + guards
│   │   ├── stores/
│   │   │   ├── auth.js                   # Auth state (Pinia)
│   │   │   └── chat.js                   # Chat state + Echo (Pinia)
```

```
└─ views/
    ├── LoginView.vue
    ├── DashboardView.vue
    ├── UsersView.vue
    ├── EventsView.vue
    ├── TasksView.vue
    └── RundownView.vue
```

5. Skema Database

Tabel **users**

Kolom	Tipe	Keterangan
id	bigint PK	Auto increment
name	varchar(255)	Nama lengkap
email	varchar(255) unique	Email login
phone	varchar(255) nullable	Nomor telepon
role	enum	<code>superadmin</code> , <code>project_manager</code> , <code>staff</code>
status	enum	<code>active</code> , <code>inactive</code>
password	varchar(255)	Hashed (bcrypt)
created_at, updated_at	timestamp	

Tabel **events**

Kolom	Tipe	Keterangan
id	bigint PK	
name	varchar(255)	Nama event
description	text nullable	Deskripsi
location	varchar(255)	Lokasi
start_date	date	Tanggal mulai
end_date	date	Tanggal selesai
start_time	time nullable	Jam mulai
end_time	time nullable	Jam selesai

status	enum	<code>draft</code> , <code>active</code> , <code>ongoing</code> , <code>completed</code> , <code>cancelled</code>
budget	decimal(15,2) nullable	Anggaran
category	varchar(100) nullable	Kategori event
expected_participants	integer nullable	Target peserta
created_by	FK → users	Pembuat event

Tabel `event_personnel` (Pivot)

Kolom	Tipe	Keterangan
event_id	FK → events	
user_id	FK → users	
role_in_event	varchar nullable	Peran di event
notes	text nullable	Catatan

Tabel `tasks`

Kolom	Tipe	Keterangan
id	bigint PK	
title	varchar(255)	Judul task
description	text nullable	
event_id	FK → events	Task milik event ini
assigned_to	FK → users nullable	Penanggungjawab
created_by	FK → users	Pembuat
parent_task_id	FK → tasks nullable	Parent untuk sub-task
priority	enum	<code>low</code> , <code>medium</code> , <code>high</code> , <code>urgent</code>
status	enum	<code>pending</code> , <code>in_progress</code> , <code>review</code> , <code>completed</code> , <code>cancelled</code>
due_date	date nullable	Batas waktu
due_time	time nullable	
category	varchar nullable	
completed_at	timestamp nullable	

Tabel `task_comments`

Kolom	Tipe	Keterangan
id	bigint PK	
task_id	FK → tasks	
user_id	FK → users	
comment	text	Isi komentar

Tabel `event_rundowns`

Kolom	Tipe	Keterangan
id	bigint PK	
event_id	FK → events	
event_date	date	Tanggal sesi (multi-day support)
title	varchar(255)	Nama sesi
description	text nullable	
category	varchar nullable	<code>ceremony</code> , <code>talent</code> , <code>technical</code> , <code>logistics</code> , <code>meal</code> , dll
start_time	time	Jadwal mulai
end_time	time	Jadwal selesai
duration_minutes	integer nullable	Durasi (kalkulasi otomatis)
status	enum	<code>pending</code> , <code>ready</code> , <code>live</code> , <code>delayed</code> , <code>completed</code>
pic_id	FK → users nullable	Person In Charge
location_note	varchar nullable	Lokasi spesifik dalam venue
notes	text nullable	Catatan umum
order_number	integer	Urutan dalam hari yang sama
started_at	timestamp nullable	Waktu mulai aktual
ended_at	timestamp nullable	Waktu selesai aktual
delay_minutes	integer	Keterlambatan (menit)
created_by	FK → users	

Tabel `rundown_logs`

Menyimpan riwayat setiap perubahan status rundown (audit trail).

Kolom	Tipe	Keterangan
-------	------	------------

id	bigint PK	
rundown_id	FK → event_rundowns	
user_id	FK → users	User yang melakukan aksi
action	varchar	Deskripsi aksi
old_status	varchar nullable	Status sebelumnya
new_status	varchar nullable	Status sesudah

Tabel `rundown_dependencies`

Task yang harus selesai sebelum sesi rundown bisa berjalan.

Kolom	Tipe	Keterangan
rundown_id	FK → event_rundowns	
task_id	FK → tasks	

Tabel `chat_messages`

Kolom	Tipe	Keterangan
id	bigint PK	
event_id	FK → events	Chat termasuk event ini
user_id	FK → users	Pengirim
message	text	Isi pesan (max 1000 karakter)
created_at, updated_at	timestamp	Index: <code>(event_id, created_at)</code>

Tabel `personal_access_tokens`

Dikelola oleh Laravel Sanctum untuk API token authentication.

6. Backend — API Documentation

Base URL

```
http://localhost:8000/api
```


Autentikasi

Semua endpoint (kecuali `/login`) memerlukan header:

```
Authorization: Bearer {token}
```

6.1 Auth Endpoints

POST `/login`

Login dan mendapatkan token.

Request Body:

```
{
  "email": "superadmin@eventconnect.com",
  "password": "password123"
}
```

Response 200:

```
{
  "token": "1|abc123...",
  "user": {
    "id": 1,
    "name": "Super Admin",
    "email": "superadmin@eventconnect.com",
    "role": "superadmin",
    "status": "active"
  }
}
```

POST `/logout`

Hapus token saat ini. Requires auth.

GET `/me`

Dapatkan data user yang sedang login. Requires auth.

6.2 User Management Endpoints

Akses: Superadmin only

Method	Endpoint	Deskripsi
GET	<code>/users</code>	List semua user (dengan paginasi & search)
POST	<code>/users</code>	Buat user baru
GET	<code>/users/{id}</code>	Detail satu user
PUT	<code>/users/{id}</code>	Update user
DELETE	<code>/users/{id}</code>	Hapus user

Query Parameters GET `/users` :

- `search` — pencarian nama/email
- `role` — filter berdasarkan role
- `per_page` — jumlah per halaman (default 10, max 100)

Request Body POST/PUT `/users` :

```
{
  "name": "Nama User",
  "email": "email@example.com",
  "phone": "081234567890",
  "role": "staff",
  "status": "active",
  "password": "password123"
}
```

6.3 Event Management Endpoints

Method	Endpoint	Akses	Deskripsi
GET	<code>/events</code>	Semua	List event (scope by role)
POST	<code>/events</code>	SA + PM	Buat event baru
GET	<code>/events/{id}</code>	Semua	Detail event + personnel
PUT	<code>/events/{id}</code>	SA + PM	Update event
DELETE	<code>/events/{id}</code>	SA + PM	Hapus event
GET	<code>/users-list</code>	Semua	List user untuk assignment
GET	<code>/events/{id}/tasks</code>	Semua	Task milik event

GET	/events/{id}/personnel	Semua	Personel event
-----	------------------------	-------	----------------

Query Parameters GET /events :

- **search** — pencarian nama/lokasi
- **status** — filter status
- **per_page** — paginasi

Response GET /events :

```
{
  "current_page": 1,
  "data": [
    {
      "id": 1,
      "name": "Festival Budaya Nusantara 2026",
      "location": "Lapangan Banteng, Jakarta Pusat",
      "start_date": "2026-06-15",
      "status": "active",
      "creator": { "id": 2, "name": "Budi Santoso" },
      "personnel": [...]
    }
  ],
  "total": 5
}
```

Role Scoping: Staff hanya melihat event di mana mereka terdaftar di **event_personnel** . Superadmin & PM melihat semua.

6.4 Task & Workflow Endpoints

Method	Endpoint	Deskripsi
GET	/tasks	List task (scope by event membership)
POST	/tasks	Buat task baru
GET	/tasks/{id}	Detail task
PUT	/tasks/{id}	Update task
PATCH	/tasks/{id}/status	Update status saja
DELETE	/tasks/{id}	Hapus task
GET	/tasks/{id}/comments	Komentar task

POST	<code>/tasks/{id}/comments</code>	Tambah komentar
GET	<code>/my-tasks</code>	Task yang di-assign ke user saat ini

Request Body POST/PUT `/tasks` :

```
{
  "title": "Persiapan Venue",
  "description": "Memastikan venue siap sebelum H-1",
  "event_id": 1,
  "assigned_to": 3,
  "priority": "high",
  "status": "pending",
  "due_date": "2026-06-14",
  "category": "Logistik"
}
```

PATCH `/tasks/{id}/status` :

```
{ "status": "in_progress" }
```

6.5 Timeline & Rundown Endpoints

Method	Endpoint	Deskripsi
GET	<code>/events/{id}/rundowns</code>	List rundown event (filter by date/category/status)
POST	<code>/events/{id}/rundowns</code>	Buat sesi rundown baru
GET	<code>/events/{id}/rundown-dates</code>	Daftar tanggal yang ada rundown-nya
GET	<code>/events/{id}/rundown-stats</code>	Statistik status rundown per event
GET	<code>/rundowns/{id}</code>	Detail satu sesi rundown
PUT	<code>/rundowns/{id}</code>	Update sesi rundown
PATCH	<code>/rundowns/{id}/status</code>	Update status sesi
DELETE	<code>/rundowns/{id}</code>	Hapus sesi rundown
GET	<code>/rundowns/{id}/logs</code>	Riwayat aktivitas sesi
POST	<code>/rundowns/{id}/dependencies</code>	Tambah task dependency
DELETE	<code>/rundowns/{id}/dependencies/{taskId}</code>	Hapus task dependency

Request Body POST `/events/{id}/rundowns` :

```
{
  "event_id": 1,
  "event_date": "2026-06-15",
  "title": "Opening Ceremony",
  "category": "ceremony",
  "start_time": "09:00",
  "end_time": "10:00",
  "pic_id": 3,
  "location_note": "Stage Utama",
  "order_number": 1
}
```

PATCH `/rundowns/{id}/status` :

```
{
  "status": "live",
  "delay_reason": "Persiapan panggung mundur 15 menit"
}
```

Status Lifecycle:

```
pending → ready → live → completed
           ↘ delayed ↗
```

Query Parameters GET `/events/{id}/rundowns` :

- `event_date` — filter tanggal
- `category` — filter kategori
- `status` — filter status
- `search` — cari judul

6.6 Group Chat Endpoints

Method	Endpoint	Deskripsi
GET	<code>/events/{id}/chat</code>	50 pesan terakhir (chronological)
POST	<code>/events/{id}/chat</code>	Kirim pesan baru + broadcast WebSocket

Request Body POST:

```
{ "message": "Isi pesan maksimal 1000 karakter" }
```

Response GET:

```
[
  {
    "id": 1,
    "event_id": 1,
    "message": "Test pesan",
    "created_at": "2026-05-21T05:31:10.000Z",
    "user": { "id": 1, "name": "Super Admin", "role": "superadmin" }
  }
]
```

6.7 Middleware & Access Control

RoleMiddleware

Diregistrasi sebagai `role:{roles}` di route definitions.

```
// Hanya superadmin
Route::middleware('role:superadmin')->group(...)

// Superadmin ATAU project_manager
Route::middleware('role:superadmin,project_manager')->group(...)
```

Response jika akses ditolak (403):

```
{ "message": "Akses ditolak." }
```

7. Frontend — Arsitektur & Komponen

7.1 Axios Configuration (`src/api/axios.js`)

Instance Axios terpusat dengan:

- `baseUrl: 'http://localhost:8000/api'` — semua path dipanggil relatif terhadap ini
- Request interceptor: inject `Authorization: Bearer {token}` dari `localStorage`
- Response interceptor: redirect ke `/login` jika response `401`

```
const api = axios.create({
  baseUrl: 'http://localhost:8000/api',
  headers: { 'Content-Type': 'application/json', 'Accept': 'application/json' },
})
// Semua komponen harus import dari: '../api/axios'
// BUKAN import axios from 'axios' (akan break tanpa baseUrl)
```

7.2 Auth Store (`src/stores/auth.js`)

State management autentikasi dengan Pinia:

State/Getter	Tipe	Keterangan
<code>user</code>	ref	Data user dari <code>localStorage</code>
<code>token</code>	ref	Bearer token dari <code>localStorage</code>
<code>isLoggedIn</code>	computed	Boolean: ada token atau tidak
<code>isSuperAdmin</code>	computed	<code>role === 'superadmin'</code>
<code>isProjectManager</code>	computed	<code>role === 'project_manager'</code>
<code>canManageUsers</code>	computed	Hanya superadmin
<code>canManageEvents</code>	computed	SA + PM
<code>canManageTasks</code>	computed	SA + PM

Actions: `login(email, password)` , `logout()`

7.3 Chat Store (`src/stores/chat.js`)

State management chat dengan Pinia + Laravel Echo:

State	Keterangan
<code>messagesByEvent</code>	reactive <code>{[eventId]: Message[]}</code>
<code>onlineByEvent</code>	reactive <code>{[eventId]: Member[]}</code>
<code>unreadCounts</code>	reactive <code>{[eventId]: number}</code>

<code>eventGroups</code>	<code>ref([])</code> — list event untuk sidebar chat
<code>loadingGroups</code>	loading state

Key Actions:

- `loadEventGroups()` — fetch list event dari API
- `subscribeToEvent(eventId, userId)` — join presence channel via Echo
- `loadHistory(eventId)` — fetch 50 pesan terakhir
- `sendMessage(eventId, message)` — POST ke API

7.4 Vue Router (`src/router/index.js`)

Route guards:

- `requiresAuth` — redirect ke `/login` jika belum login
- `guest` — redirect ke `/` jika sudah login
- `meta.role: 'superadmin'` — redirect ke `/` jika bukan superadmin

```
router.beforeEach((to, from, next) => {
  const auth = useAuthStore()
  if (to.meta.requiresAuth && !auth.isLoggedIn) return next('/login')
  if (to.meta.guest && auth.isLoggedIn) return next('/')
  if (to.meta.role === 'superadmin' && !auth.isSuperAdmin) return next('/')
  next()
})
```

7.5 Halaman (Views)

LoginView.vue

- Form email + password
- Memanggil `authStore.login()`
- Redirect ke `/` setelah sukses

DashboardView.vue

- Statistik ringkasan: total event, event aktif, total user (SA only), event selesai
- Event terbaru (3 item)
- Task saya (my-tasks)
- Data di-scope sesuai role (staff hanya melihat event yang ditugaskan)

UsersView.vue (Superadmin Only)

- Tabel user dengan search & filter role
- Modal tambah/edit user
- Konfirmasi hapus

EventsView.vue

- List event (card view) dengan search, filter status
- Modal detail event: info, personnel, task statistics
- Modal tambah/edit event (SA + PM)
- Assignment personel ke event
- Staff hanya melihat event yang ditugaskan

TasksView.vue

- List task dengan filter event, status, prioritas
- Modal tambah/edit task
- Update status dengan drag-concept button
- Tab komentar di modal detail
- Parent-child task support

RundownView.vue

- Filter: pilih event, tanggal, kategori, status
- View mode: Timeline (grouped by date) dan List
- Card sesi: tampil waktu, kategori badge, status badge, lokasi
- Quick status update via dropdown langsung di card
- Modal detail sesi: informasi lengkap, status buttons, activity log
- Modal tambah/edit sesi: form lengkap dengan task dependency
- Konfirmasi hapus

DashboardLayout.vue

- Sidebar navigasi dengan icon + label
- User info di bawah sidebar
- Sidebar collapse/expand
- **FloatingChat** terintegrasi di kanan bawah

7.6 Komponen

FloatingChat.vue

Floating chat popup berbentuk WhatsApp-style:

- **Trigger:** Tombol bubble di kanan bawah dengan badge unread count
- **Sidebar kiri:** List event group, search, preview pesan terakhir, unread badge
- **Panel kanan:** Chat history, form kirim pesan, online member count
- **Realtime:** Subscribe ke presence channel `event.{id}` via Laravel Echo
- Event groups diload saat pertama kali popup dibuka

8. Role-Based Access Control (RBAC)

Matriks Izin

Fitur	Superadmin	Project Manager	Staff
Login	✓	✓	✓
Dashboard	✓ (semua)	✓ (semua)	✓ (event ditugaskan)
Lihat User	✓	✗	✗
CRUD User	✓	✗	✗
Lihat Event	✓ (semua)	✓ (semua)	✓ (assigned only)
CRUD Event	✓	✓	✗
Lihat Task	✓	✓	✓ (event ditugaskan)
CRUD Task	✓	✓	✗
Update Status Task	✓	✓	✓ (task sendiri)
Lihat Rundown	✓	✓	✓ (event ditugaskan)
CRUD Rundown	✓	✓	Tergantung <code>role_in_event</code>
Update Status Rundown	✓	✓	PIC/role terkait
Chat	✓	✓	✓ (event ditugaskan)

Implementasi RBAC

Backend — Layer 1: `RoleMiddleware`

```
// routes/api.php
Route::middleware('role:superadmin')->group(...);           // Hanya SA
Route::middleware('role:superadmin,project_manager')->...;  // SA + PM
```

Backend — Layer 2: Query Scoping (EventController)

```
->when(
    !in_array($user->role, ['superadmin', 'project_manager']),
    fn($q) => $q->whereHas('personnel', fn($inner) => $inner->where('users.id',
$user->id))
)
```

Frontend — Route Guard

```
if (to.meta.role === 'superadmin' && !auth.isSuperAdmin) return next('/')
```

Frontend — UI Conditional Rendering

```
<link v-if="auth.canManageUsers" to="/users">Manajemen User</link>
<button v-if="canManage" @click="createEvent">Buat Event</button>
```

9. Sistem Realtime (WebSocket)

Stack

- **Server:** Laravel Reverb (WebSocket server bawaan Laravel, port 8080)
- **Client:** Laravel Echo + Pusher JS (transport: **WS** / **WSS**)
- **Broadcast Event:** **MessageSent** (implements **ShouldBroadcastNow**)
- **Channel Type:** Presence Channel **event.{eventId}**

Alur Pengiriman Pesan

```
User mengetik pesan → POST /api/events/{id}/chat
↓
ChatController::store()
  ↓ ChatMessage::create()
  ↓ broadcast(new MessageSent($message))
  ↓
Laravel Reverb
  ↓ Broadcast ke channel event.{eventId}
  ↓ Event: message.sent
  ↓
Laravel Echo (client)
```

```

    ↓ .listen('.message.sent', callback)
    ↓
chat store → messagesByEvent[eventId].push(msg)
    ↓
Vue reactivity → UI update

```

Channel Auth (routes/channels.php)

Presence channel hanya bisa di-join oleh:

1. User dengan role `superadmin` atau `project_manager` (akses semua event)
2. User yang terdaftar di `event_personnel` untuk event tersebut

```

Broadcast::channel('event.{eventId}', function ($user, $eventId) {
    if (in_array($user->role, ['superadmin', 'project_manager'])) {
        return ['id' => $user->id, 'name' => $user->name, 'role' => $user->role];
    }
    $isMember = DB::table('event_personnel')
        ->where('event_id', $eventId)->where('user_id', $user->id)->exists();
    return $isMember ? ['id' => $user->id, 'name' => $user->name, 'role' => $user->role] : false;
});

```

Broadcast Auth Route

```

// routes/api.php
Broadcast::routes(['middleware' => ['auth:sanctum']]);
// Auth endpoint: POST /broadcasting/auth
// Header: Authorization: Bearer {token}

```

Konfigurasi Echo (Frontend)

```

echoInstance = new Echo({
  broadcaster: 'reverb',
  key: import.meta.env.VITE_REVERB_APP_KEY,
  wsHost: import.meta.env.VITE_REVERB_HOST, // localhost
  wsPort: Number(import.meta.env.VITE_REVERB_PORT ?? 8080),
  forceTLS: false,
  enabledTransports: ['ws', 'wss'],
});

```

```
authEndpoint:      'http://localhost:8000/broadcasting/auth',
auth: {
  headers: { Authorization: 'Bearer ' + localStorage.getItem('token') },
},
})
```

10. Panduan Setup & Menjalankan Aplikasi

Prerequisites

- PHP 8.3+
- Composer
- Node.js 18+
- MySQL 8.x
- npm atau yarn

Setup Backend

```
cd backend

# 1. Install PHP dependencies
composer install

# 2. Copy konfigurasi environment
cp .env.example .env

# 3. Generate application key
php artisan key:generate

# 4. Konfigurasi database di .env:
# DB_CONNECTION=mysql
# DB_HOST=127.0.0.1
# DB_PORT=3306
# DB_DATABASE=event_connect
# DB_USERNAME=root
# DB_PASSWORD=

# 5. Konfigurasi Reverb di .env:
# REVERB_APP_ID=my-app-id
# REVERB_APP_KEY=my-app-key
# REVERB_APP_SECRET=my-app-secret
# REVERB_HOST=localhost
```

```
# REVERB_PORT=8080
# REVERB_SCHEME=http

# 6. Jalankan migrasi + seeder
php artisan migrate --seed

# 7. Jalankan server Laravel
php artisan serve
# → Berjalan di http://localhost:8000

# 8. (Terminal terpisah) Jalankan Reverb WebSocket server
php artisan reverb:start
# → Berjalan di ws://localhost:8080
```

Setup Frontend

```
cd frontend

# 1. Install dependencies
npm install

# 2. Konfigurasi .env (buat file .env):
# VITE_REVERB_APP_KEY=my-app-key
# VITE_REVERB_HOST=localhost
# VITE_REVERB_PORT=8080
# VITE_REVERB_SCHEME=http

# 3. Jalankan dev server
npm run dev
# → Berjalan di http://localhost:5175
```

Menjalankan Ketiga Server Sekaligus

```
# Terminal 1 – Laravel API
cd backend && php artisan serve

# Terminal 2 – Laravel Reverb WebSocket
cd backend && php artisan reverb:start

# Terminal 3 – Vite Frontend
cd frontend && npm run dev
```

Catatan Penting

Semua komponen frontend **harus** menggunakan `import api from '../api/axios'` (bukan `import axios from 'axios'`) agar request diarahkan ke `http://localhost:8000/api`.

11. Data Seed & Akun Testing

Setelah `php artisan migrate --seed`, database diisi dengan:

Akun Pengguna (password semua: **password123**)

Role	Email	Nama
Superadmin	superadmin@eventconnect.com	Super Admin
Project Manager	pm@eventconnect.com	Budi Santoso
Staff	promo@eventconnect.com	Ahmad Fauzi
Staff	planner@eventconnect.com	Siti Rahayu
Staff	partner@eventconnect.com	Diana Putri
Staff	budget@eventconnect.com	Rizky Maulana
Staff	ops@eventconnect.com	Eka Fitriani
Staff	creative@eventconnect.com	Farhan Hidayat
Staff	rundown@eventconnect.com	Gina Marlina
Staff	talent@eventconnect.com	Hendra Wijaya
Staff	registration@eventconnect.com	Indah Permata
Staff	tech@eventconnect.com	Joko Susilo
Staff	doc@eventconnect.com	Kartika Dewi
Staff	lo@eventconnect.com	Luhut Pangaribuan

Total: 14 user (1 superadmin + 1 PM + 12 staff)

Event Sample

Nama Event	Status	Tanggal
------------	--------	---------

Festival Budaya Nusantara 2026	active	15-17 Jun 2026
Tech Summit Indonesia 2026	draft	20 Jul 2026
Gala Dinner Alumni UNDIRA	active	10 Jun 2026
Konser Amal Peduli Anak	completed	...
Seminar Kewirausahaan Muda	completed	5 Mei 2026

Total: 5 event seeded

12. Hasil Testing Fitur

Testing dilakukan dengan **browser automation (Playwright)** tanggal 21 Mei 2026.

Ringkasan

TC	Fitur	Status
TC-01	Login & Autentikasi	✓ PASS
TC-02	CRUD Manajemen User	✓ PASS
TC-03	CRUD Manajemen Event	✓ PASS
TC-04	CRUD Task & Workflow	✓ PASS
TC-05	CRUD Timeline & Rundown	✓ PASS (setelah 4 perbaikan)
TC-06	Group Chat Realtime	✓ PASS
TC-07	Role-Based Access (Staff)	✓ PASS

Detail Test Case

TC-01 — Login

- Superadmin login → dashboard tampil 5 events, 14 users ✓
- Token tersimpan di localStorage ✓
- Redirect otomatis jika sudah login ✓

TC-02 — CRUD User

- Create user baru (total 14 → 15) ✓
- Edit nama user ✓
- Delete user (kembali ke 14) ✓

TC-03 — CRUD Event

- Create event dengan personnel assignment ✓

- View detail event + stats task ✓
- Edit status event ✓
- Delete event ✓

TC-04 — CRUD Task

- Create task dengan priority high, due date, assignee ✓
- Update status: pending → in_progress → review → completed ✓
- Tambah komentar ✓
- Delete task ✓

TC-05 — CRUD Rundown

- Pilih event → dropdown terisi 5 events ✓ (setelah fix axios)
- Create sesi "Opening Ceremony TC-05", 15 Jun 2026, 09:00–10:00 ✓
- Detail sesi: informasi lengkap tampil ✓
- Update status: Pending → Live via detail modal ✓
- Activity log terekam otomatis ✓
- Edit sesi: ubah judul → "Opening Ceremony TC-05 (EDITED)" ✓
- Delete sesi dari detail modal ✓

TC-06 — Group Chat

- Popup terbuka, 5 event groups muncul di sidebar ✓
- Pilih event → chat panel terbuka ✓
- Kirim pesan → tampil di chat + preview di sidebar ✓
- Pesan tersimpan di database ✓

TC-07 — Role Restriction (Staff)

- Login Ahmad Fauzi (staff): hanya 3 event terlihat (bukan 5) ✓
- Menu "Manajemen User" tidak muncul ✓
- Total User di dashboard tersembunyi ("—") ✓
- Akses langsung `/users` → redirect ke Dashboard ✓

13. Bug yang Ditemukan & Diperbaiki

BUG-01 — Axios Import Salah di RundownView (KRITIS, DIPERBAIKI)

File: `frontend/src/views/RundownView.vue`

Gejala: Dropdown "Pilih Event" menampilkan ratusan opsi kosong

Root Cause:

```
// BUGGY – bare axios tanpa baseURL
import axios from 'axios'
const res = await axios.get('/api/events')
// Mengirim request ke http://localhost:5175/api/events (Vite dev server)
// Vite mengembalikan HTML (index.html)
// eventsList.value = HTML string
// v-for iterates tiap karakter → ratusan <option> kosong
```

Fix:

```
// FIXED – gunakan configured instance
import axios from '../api/axios'
const res = await axios.get('/events') // baseURL sudah
http://localhost:8000/api
```

Semua 11 API calls diperbaiki (remove `/api/` prefix dari semua path).

BUG-02 — Null Reference di `openEditFromDetail` (SEDANG, DIPERBAIKI)

File: `frontend/src/views/RundownView.vue`

Gejala: Klik "Edit" di detail modal → `TypeError: Cannot read properties of null (reading 'id')`

Root Cause:

```
// BUGGY
function openEditFromDetail() {
  closeDetail() // detailItem.value = null
  openEdit(detailItem.value) // openEdit(null) → null.id crash!
}
```

Fix:

```
// FIXED
function openEditFromDetail() {
  const item = detailItem.value // simpan referensi SEBELUM closeDetail()
  closeDetail()
```

```
openEdit(item)
}
```

BUG-03 — Format Tanggal ISO di Form Edit (*SEDANG, DIPERBAIKI*)

File: `frontend/src/views/RundownView.vue`

Gejala: Field "Tanggal Sesi" kosong saat buka form Edit

Root Cause: API mengembalikan `"2026-06-15T00:00:00.000000Z"` (ISO datetime) tetapi `<input type="date">` membutuhkan format `"yyyy-MM-dd"`

Fix:

```
// openEdit() function
// BUGGY
event_date: item.event_date,

// FIXED
event_date: (item.event_date ?? '').slice(0, 10),
// "2026-06-15T00:00:00.000000Z" → "2026-06-15"
```

BUG-04 — Format Waktu dengan Detik Gagal Validasi Backend (*SEDANG, DIPERBAIKI*)

File: `frontend/src/views/RundownView.vue`

Gejala: Submit form Edit → HTTP 422 error "The start time field must match the format H:i"

Root Cause: API menyimpan waktu sebagai `"09:00:00"` (dengan detik). Saat di-load ke form edit dan di-submit kembali, backend menolak karena validasinya `H:i` (tanpa detik).

Fix:

```
// openEdit() function
// BUGGY
start_time: item.start_time, // "09:00:00"
end_time: item.end_time, // "10:00:00"

// FIXED
start_time: (item.start_time ?? '').slice(0, 5), // "09:00"
end_time: (item.end_time ?? '').slice(0, 5), // "10:00"
```

ISSUE-01 — Reverb Presence "0 Online" (MINOR, BELUM DIPERBAIKI)

Komponen: `FloatingChat.vue` + `stores/chat.js`

Gejala: Chat kirim/terima pesan berfungsi normal, tetapi indicator "0 online" selalu tampil

Kemungkinan Penyebab: Echo instance diinisialisasi dengan token saat pertama kali (lazy init). Saat logout dan login akun berbeda, token di Echo tidak diperbarui karena Echo sudah terinisialisasi.

Rekomendasi Fix:

```
// stores/auth.js – logout()
async function logout() {
  try {
    await api.post('/logout')
  } finally {
    // Tambahkan ini:
    resetEcho() // import dari stores/chat.js
    token.value = null
    user.value = null
    localStorage.removeItem('token')
    localStorage.removeItem('user')
  }
}
```

14. Rekomendasi Pengembangan Lanjutan

Prioritas Tinggi

1. Fix Echo Reset saat Logout

Panggil `resetEcho()` dari `chat.js` di action logout `auth.js` untuk memastikan token WebSocket selalu fresh.

2. Tambahkan Vite Proxy

Mencegah bug seperti BUG-01 terulang jika ada developer yang lupa menggunakan configured instance:

```
// vite.config.js
server: {
  proxy: {
    '/api': { target: 'http://localhost:8000', changeOrigin: true }
  }
}
```

```
}  
}
```

3. Global Error Handler Vue

Ganti `alert()` dengan toast notification dan tambahkan error boundary:

```
// main.js  
app.config.errorHandler = (err, instance, info) => {  
  toastStore.show({ type: 'error', message: err.message })  
}
```

Prioritas Sedang

4. Validasi Waktu Backend

Backend RundownController sudah menerima `H:i` — pertimbangkan juga menerima `H:i:s` untuk toleransi lebih:

```
'start_time' => ['required', 'regex:/^\d{2}:\d{2}(:\d{2})?$/'],
```

5. Rundown Display Format

Waktu tampilan di card masih `09:00:00` (dari DB). Tambahkan format helper:

```
function formatTime(t) { return t?.slice(0, 5) ?? '-' }
```

6. Chat History Pagination

Saat ini load 50 pesan sekaligus. Untuk performa dengan pesan banyak, tambahkan infinite scroll dengan cursor-based pagination.

7. Notifikasi Realtime untuk Task/Rundown

Broadcast event saat status task atau rundown berubah agar semua anggota team mendapat update tanpa refresh halaman.

Prioritas Rendah

8. Export Laporan

Fitur export rundown ke PDF atau Excel untuk kebutuhan dokumen resmi event.

9. Attachment/File Upload

Dukungan upload file di komentar task (foto progres, dokumen teknis).

10. Dark Mode

Toggle tema terang/gelap untuk kenyamanan penggunaan di malam hari selama event berlangsung.

11. Push Notification (PWA)

Notifikasi browser untuk pesan chat dan update status rundown saat halaman tidak aktif.

Lampiran: Ringkasan File yang Dimodifikasi

Selama sesi development & bug fixing, file-file berikut mengalami perubahan signifikan:

File	Perubahan
<code>frontend/src/views/RundownView.vue</code>	Fix 4 bug: axios import, null ref, date format, time format
<code>backend/routes/api.php</code>	Tambah <code>Broadcast::routes()</code> dengan middleware Sanctum
<code>backend/routes/channels.php</code>	Presence channel auth dengan event member scoping
<code>backend/app/Events/MessageSent.php</code>	ShouldBroadcastNow, PresenceChannel, broadcastWith()
<code>backend/app/Http/Controllers/Api/ChatController.php</code>	Optimasi query, hapus toOthers(), authorizeEventAccess()
<code>backend/app/Http/Controllers/Api/EventController.php</code>	Role-based query scoping untuk staff
<code>frontend/src/stores/chat.js</code>	reactive maps, splice deduplication, Echo lazy init
<code>frontend/src/components/FloatingChat.vue</code>	Desain ulang WhatsApp-style popup
<code>frontend/src/views/EventsView.vue</code>	Hapus tab chat lama, integrasi FloatingChat
<code>frontend/src/layouts/DashboardLayout.vue</code>	Integrasi FloatingChat global

Dokumentasi ini dibuat berdasarkan hasil pengembangan dan testing otomatis pada sesi Capstone UNDIRA Genap 2026.