Business answers, in plain language.

A practical guide for managers, stakeholders, and project sponsors.

Data Agent is a local website for asking questions about a PostgreSQL database and downloading results as CSV files. A manager describes the information they need; the application finds the relevant records and presents an answer or export.

The opportunity
Make routine investigations and report preparation easier: fewer manual data lookups, clearer questions, and reusable extracts. The benefit is a pilot hypothesis; time savings and accuracy gains have not yet been measured.

How a request becomes an answer

1. Ask
Enter a business question or request a file.

2. Route and read
The router selects the SQL or extraction analyst, which reads the database.

3. Review and use
Read the final answer or download a CSV for a spreadsheet.

Five tables describe the business

Table	Sample rows	What a record tells you
Users	10,000	Rider or driver profile: name, contact details, location, signup date, and account status.
Vehicles	3,000	A driver's vehicle: make, model, year, plate, color, and active flag.
Rides	20,000	A trip request: rider, driver, times, locations, distance, fare, status, and cancellation reason.
Payments	16,073	A payment: ride, user, amount, method, time, and completed, failed, or refunded status.
Ratings	12,000	Ride feedback: rider, driver, score from 1 to 5, comment, and time.

Counts describe the shared sample CSVs, not the live database. Users include 7,000 riders and 3,000 drivers. Ride, payment, and rating records cover January 2025–July 2026; signup dates begin in January 2023.

Connect the records with care

User and ride IDs connect profiles, trips, payments, and ratings. One ride can have multiple payment or feedback records, so combining them can duplicate totals. Rides do not store a vehicle ID; a driver's vehicle list does not establish which vehicle served a particular trip.

Prepared by Md Tariqul Islam Bhuiyan (Rizvi)

Start with a decision.

Six practical ways to use the project.

Choose a reporting period that exists in the data. Be explicit about dates, filters, row limits, and ordering. The examples below describe intended outputs; important results still need review against the underlying records.

01 Failed payments

Ask "List failed payments in the reporting period, with rider names, amounts, and methods. Export up to 500 rows."

Receive A CSV of payment records for investigation.

Use Assign support cases and check payment-method patterns. A failed record alone does not prove money is still owed.

02 Driver service quality

Ask "Show the 10 lowest-rated drivers in the reporting period, with at least 10 ratings each."

Receive Names, average ratings, and review counts.

Use Prioritize feedback reviews and coaching. Ratings are an investigation signal, not an automatic personnel decision.

03 Ride cancellations

Ask "Show the cancellation rate and a breakdown by reason for rides requested in this period."

Receive Ride counts, the cancellation rate, and recorded reasons.

Use Focus an operational investigation. Define the rate as cancelled rides divided by all rides requested in the period.

04 Payment reporting

Ask "Export payment counts and total amounts by payment method and status for this period."

Receive A compact CSV for the management meeting.

Use Compare payment activity. Keep statuses separate; confirm a common currency before adding amounts.

05 Customer complaints

Ask "For ride ID 123, show the trip details, payments, and ratings as separate lists."

Receive The recorded facts and any missing information.

Use Prepare a support investigation. Replace 123 with a real ride ID; the application does not issue refunds or contact riders.

06 A small data extract

Ask "Export the first 5 ratings, ordered by rating ID ascending, as CSV."

Receive A downloadable file with up to five rows.

Use Demonstrate the workflow or inspect a sample. First by ID is reproducible; it is not a representative or highest-rated sample.

For repeatable reporting, specify a start date (included), an end date (excluded), and the reporting timezone. Use dates for which the database contains records.

From request to review.

A simple demonstration, followed by a measurable pilot.

01
Ask
Enter a question or select a table in the workspace.

02
Run
Click **Run Request**. The application selects an analyst.

03
Review
Read **Your result**; check the meaning, filters, and dates.

04
Download
Open an extracted CSV in Excel for inspection or reporting.

Try this first
"Extract the first 5 rows from ratings, ordered by rating_id ascending, and save them as CSV in data/extract."



A demonstration result: five ratings saved as CSV, with a download link. Results and filenames depend on the connected database.

Know the boundaries

- Local, trusted-user application; no login or shared-team access controls.
- One agent task at a time. Queries and exports default to 1,000 rows, with a maximum of 10,000.
- Prompts and data context may be sent to external AI providers. Local-file transformations execute generated Python.
- No scheduled reports, payment retries, refunds, or customer notifications.

Make the pilot measurable

Choose recurring questions with reference answers verified by the data owner.

- Compare time to a usable result, including corrections and review.
- Check filters, totals, ordering, and exported rows against the database.
- Track completed tasks, retries, AI cost, and human review effort.

Agree on acceptance thresholds before expanding use. Benefits have not yet been measured.

Use the output carefully. A selected-table preview is separate from the agent's query result. Downloaded CSVs are snapshots. The cross icon deletes an extract immediately; **Clear** resets the prompt and result view. Full scenarios and architecture are included in the project resources.