

# Neural Networks


- Perception
- Similarity to human neuron

5

Human neuron  
 x<sub>1</sub> | | | Sndrites (Data)

10

15



$$z = w_1x_1 + w_2x_2 + w_3x_3$$

20

$w$  → weight  
 $x$  → data.

25

$g(z) \rightarrow$  activation function


↳ can be sigmoid

ReLU

↳ rectified linear unit

$$\text{ReLU} \rightarrow f(x) = \begin{cases} x & \text{if } x \geq 0 \\ 0 & \text{if } x < 0 \end{cases}$$

30




$$z = \sum w_i x_i + b$$

→ bias

(decides whether a neuron fires)

## 5 Artificial neuron



## 20 Neuron

- Dendrites
- Synaptic gap
- Soma
- Axon

## Perceptron

- Input
- weight
- $g(z)$
- output.

25

30

Sigmoid  $\rightarrow \sigma(z) = \frac{1}{1+e^{-z}}$

DATE: / /  
PAGE: / /

## Perception

$0 \rightarrow 1$

↳ uses gradient descent  
as a classifier

5

## How to train a perception

- model
- loss


10

↳ cannot use mean squared error

non convex

as it consists of  
a lot of minima

15



↳ use

→ log loss / Binary Cross Entropy

20

$$J(w) = - \sum_{i=1}^m (y^{(i)} \log \hat{y}^{(i)} + (1-y^{(i)}) \log (1-\hat{y}^{(i)}))$$

25

Convex function

Only one global

minimum

30

Updated weight

$$w = w - \eta \frac{\partial J}{\partial w}$$

5



10

15


20

# ANN

## Perception



## 3-layer neural network



&gt; Hidden layer

$$x \rightarrow f(x) \rightarrow g(f(x)) \rightarrow h(g(f(x)))$$


15

Why multilayer perception\* Single Perception model

20


any neural network that performs computation on features you are providing

25



30

works for linearly separable



data

eg AND

	T	F
5	T	F
	F	F

$\rightarrow$  linearly separable

For multi-separable data, we need multi-layer perceptron

10 eg XOR


\* [!AND] AND [OR]  $\rightarrow$  XOR

## 15 Architecture

\* Input layer

\* Hidden layers (n)

20 \* Output layer




No. of rows - m

No. of columns  $\rightarrow n$

## ~~300~~ 2-steps

① Forward Propagation → Backward



$$h_1^{(1)} = \omega_1^{(1)}x + b_1^{(1)}, \quad a_1^{(1)} = \sigma(h_1^{(1)})$$


$$h_2^{(1)} = \omega_2^{(1)}x + b_2^{(1)}, \quad a_2^{(1)} = \sigma(h_2^{(1)})$$

$$h_3^{(1)} = \omega_3^{(1)}x + b_3^{(1)}, \quad a_3^{(1)} = \sigma(h_3^{(1)})$$

## Activation functions

20

\* Sigmoid



30

Tanh fnch

5

10

ReLU

15

20

lesky relu

$$a = \tanh(z)$$

$$= \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

$$a = \max(0, z)$$

$$0 \text{ if } z \geq 0$$

$$z \text{ if } z < 0$$

25

30

derivation of sigmoid

$$g(z) = \frac{1}{1+e^{-z}}$$

5

$$\begin{aligned} g'(z) &= \frac{1}{1+e^{-z}} \left( 1 - \frac{1}{1+e^{-z}} \right) \\ &= g(z) (1 - g(z)) \end{aligned}$$

10

Derivation of Tanh(z)

$$g(z) = \tanh(z)$$

5

$$g'(z) = 1 - (\tanh)^2$$