

Exploratory Data Mining via Search Strategies Lab #5

Ross Jacobucci & Kevin J. Grimm

This presentation will go over the basics of using various multivariate procedures in R. These include:

1. Exploratory Factor Analysis & PCA
2. Structural Equation Models
3. SEM Trees
4. Other Multivariate CART Models

R Packages

EFA & SEM

```
library(psych) # efa & miscellaneous tools  
library(OpenMx) # SEM  
library(lavaan) # SEM
```

SEM Trees

```
# how to install  
#source('http://www.brandmaier.de/semtree/getsemtree.R')  
library(semtree)
```

Other Longitudinal Trees

longRPart package. Not currently maintained on CRAN. Can be accessed from:
<http://cran.r-project.org/src/contrib/Archive/longRPart/>
First Download the 1.0 tar.gz

```
# longRPart is not on CRAN  
# have to install from source  
library(longRPart)  
library(REEMtree)
```

PCA and EFA

To do PCA: `prcomp()` – built-in

To do EFA: `factanal()` – builtin

`fa()` – from **psych**; multiple upgrades

`efaUnrotate()` – from **semTools**; can do FIML for missing data and WLSMV for categorical variables

`GPA()` – from **GPArotation** – one stop shop for factor rotations

nFactors package contains various functions for determining number of factors

CFA: `cfa()` – from **lavaan** package

General SEM: **OpenMx** – can do cfa,sem, mixtures, differential equations... Most general package

lavaan – modeled after Mplus; can do maybe 80% of the things that Mplus can


We will be using the Holzinger Swineford dataset for all of the examples. Data from lavaan package

```
library(lavaan)
library(OpenMx)
# can't get OpenMx from CRAN
#source('http://openmx.psyc.virginia.edu/getOpenMx.R')
HS <- HolzingerSwineford1939
#summary(HS)
#str(HS)
```

PCA, EFA, CFA

PCA

```
pca.out <- prcomp(HS[,7:15])  
#quartz()  
plot(pca.out)
```



PCA continued

The psych package has a PCA function, `principal()`, which uses the same algorithm, but provides much more helpful output.

```
library(psych)
prin1 <- principal(HS[,7:15])
loadings(prin1)
```

```
##
## Loadings:
##      PC1
## x1 0.658
## x2 0.390
## x3 0.477
## x4 0.766
## x5 0.738
## x6 0.772
## x7 0.349
## x8 0.454
## x9 0.591
##
##              PC1
## SS loadings    3.216
## Proportion Var 0.357
```

2 Components

```
prin2 <- principal(HS[,7:15],2)
loadings(prin2)
```

```
##
## Loadings:
##      PC1      PC2
## x1  0.450  0.496
## x2  0.259  0.304
## x3  0.183  0.550
## x4  0.880  0.104
## x5  0.880
## x6  0.875  0.122
## x7           0.610
## x8           0.764
## x9  0.164  0.764
##
##                PC1    PC2
## SS loadings      2.646 2.209
## Proportion Var  0.294 0.245
## Cumulative Var  0.294 0.539
```


3 Components

```
prin3 <- principal(HS[,7:15],3)
loadings(prin3)
```

```
##
## Loadings:
##      PC1      PC3      PC2
## x1  0.321  0.673  0.175
## x2           0.727 -0.102
## x3           0.779  0.155
## x4  0.889  0.124
## x5  0.903
## x6  0.869  0.178
## x7          -0.153  0.830
## x8           0.145  0.818
## x9  0.130  0.435  0.636
##
##
##              PC1      PC3      PC2
## SS loadings    2.501  1.872  1.847
## Proportion Var 0.278  0.208  0.205
## Cumulative Var 0.278  0.486  0.691
```

4 Components

```
prin4 <- principal(HS[,7:15],4)
loadings(prin4)
```


```
##
## Loadings:
##      PC1      PC2      PC3      PC4
## x1  0.306              0.788
## x2  0.105              0.216  0.959
## x3              0.819  0.191
## x4  0.887              0.149
## x5  0.904
## x6  0.869              0.159
## x7              0.832      -0.148
## x8              0.833  0.127  0.108
## x9  0.123  0.603  0.471  0.114
##
##
##      PC1      PC2      PC3      PC4
## SS loadings    2.490  1.783  1.629  1.017
## Proportion Var 0.277  0.198  0.181  0.113
## Cumulative Var 0.277  0.475  0.656  0.769
```

Note, PCA always extracts the same number of components as variables entered. But with `principal()` we have a choice of displaying a specific number of components. In using PCA, 3 components seems to be a little bit cleaner, where we can see “clusters” in the loadings, than others in the factor structure. But still hazy. With 4 components, the last component is really only made up of 1 variable (loading > 0.9). One of the best tools that I know of to determine the number of components (PCA) or factors (EFA) is Horn’s parallel analysis from the `psych` package. Parallel analysis compares the actual eigenvalues to the eigenvalues from a simulated dataset of random noise variables. We are looking for the number of eigenvalues above what would be expected by chance. This makes it look pretty clear, both 3 components and factors

Parallel Analysis

Although called `fa.parallel()` it extracts both components and factors

```
fa.parallel(HS[,7:15])
```



Parallel Analysis With Items

Not Run

```
library(random.polychor.pa)
data(bfi)
bfi.data<-na.exclude(as.matrix(bfi[1:200, 1:5]))
out <- random.polychor.pa(nrep=3, data.matrix=bfi.data, q.eigen=.99)
```

If your variables have 1-5 or 6 categories, then steps need to be taken to change the estimation procedure for a number of methods we will be talking about, including parallel analysis.

R has the built-in `factanal()` which gets the job done in most cases. Defaults to ML estimation and `varimax`(orthogonal rotation)

```
fa.out <- factanal(HS[,7:15],3);loads <- fa.out$loadings
fa.out
```

```
##
## Call:
## factanal(x = HS[, 7:15], factors = 3)
##
## Uniquenesses:
##      x1      x2      x3      x4      x5      x6      x7      x8      x9
## 0.513 0.749 0.543 0.279 0.243 0.305 0.502 0.469 0.543
##
## Loadings:
##      Factor1 Factor2 Factor3
## x1  0.277    0.623    0.151
## x2  0.105    0.489
## x3      0.663    0.130
## x4  0.827    0.165
## x5  0.861
## x6  0.801    0.212
## x7      0.696
## x8      0.162    0.709
## x9  0.132    0.406    0.524
##
##
```

	Factor1	Factor2	Factor3
x1	0.277	0.623	0.151
x2	0.105	0.489	
x3		0.663	0.130
x4	0.827	0.165	
x5	0.861		
x6	0.801	0.212	
x7			0.696
x8		0.162	0.709
x9	0.132	0.406	0.524

```
##
##      Factor1 Factor2 Factor3
```

Rotation

```
# cluster.plot(fa.out)
# extract loadings and feed to rotation program.
library(GPArotation)
gpa.out <- GPFoblq(loads) # oblique rotation
# new loading matrix
round(gpa.out$loadings,2)
```

```
##      Factor1 Factor2 Factor3
## x1      0.19      0.60      0.03
## x2      0.04      0.51     -0.12
## x3     -0.07      0.69      0.02
## x4      0.84      0.02      0.01
## x5      0.89     -0.07      0.01
## x6      0.81      0.08     -0.01
## x7      0.04     -0.15      0.72
## x8     -0.03      0.10      0.70
## x9      0.03      0.37      0.46
```

```
# new factor correlations
gpa.out$Phi
```

```
##           [,1]      [,2]      [,3]
## [1,] 1.0000000 0.3257713 0.2164403
## [2,] 0.3257713 1.0000000 0.2704747
## [3,] 0.2164403 0.2704747 1.0000000
```

Fairly clear factor structure. Not many cross loadings

Factor Scores

Get factor scores:

```
fa.out2 <- fa(HS[,7:15],scores="Bartlett")  
fscor <- fa.out2$scores  
head(fscor)
```

```
##                MR1  
## [1,] -0.22248948  
## [2,] -0.99709195  
## [3,] -2.15390885  
## [4,]  0.02741775  
## [5,] -0.14301155  
## [6,] -1.35498984
```

Not generally advisable to get factor scores as there are a number of inherent problems with them (Grice 2001), but the psych package's `fa()` has multiple options. see "scores=" option.

Confirmatory Factor Analysis

What if we have an idea as to what the structure of a model is?

Great tutorial: <http://lavaan.ugent.be/tutorial/tutorial.pdf>


This means we can specify a simple structure to the model

```
HS.model <- ' visual =~ x1 + x2 + x3
             textual =~ x4 + x5 + x6
             speed =~ x7 + x8 + x9 '
fit <- cfa(HS.model, data=HolzingerSwineford1939)
#summary(fit, fit.measures=TRUE) too much output
coef(fit)
```

##	visual=~x2	visual=~x3	textual=~x5	textual=~x6
##	0.554	0.729	1.113	0.926
##	speed=~x8	speed=~x9	x1~~x1	x2~~x2
##	1.180	1.082	0.549	1.134
##	x3~~x3	x4~~x4	x5~~x5	x6~~x6
##	0.844	0.371	0.446	0.356
##	x7~~x7	x8~~x8	x9~~x9	visual~~visual
##	0.799	0.488	0.566	0.809
##	textual~~textual	speed~~speed	visual~~textual	visual~~speed
##	0.979	0.384	0.408	0.262
##	textual~~speed			
##	0.173			

Plot CFA Model

```
semPlot::semPaths(fit, what="est")
```



Various SEM (CFA) Tools

Get Fit Measures

```
fitMeasures(fit)
```

Modification Indices

```
modindices(fit)
```

Note that lavaan actually has four different functions to run models:

lavaan() - requires you to specify the full model

cfa() - only have to specify part of the model, makes assumptions for CFA models

sem() - makes assumptions typical in more complex sem models

growth() - makes specifying LGM easy, only need intercept and slope specification

Longitudinal Analyses

For this demonstration, we are going to compare the different packages and functions in analyzing longitudinal WISC data. Data is WISC4VPE.DAT.

```
wisc <- read.table("C:/Users/RJacobucci/Documents/GitHub/EDM_Labs/2015/wisc4vpe.DAT")
names(wisc)<- c("V1", "V2", "V4", "V6", "P1", "P2", "P4", "P6", "Moeducat")
# note: V1 refers to verbal scores at grade 1, P is performance
```

Visualization

To use many of the packages in R for longitudinal data (nlme), it is many times required to create a “long” data file, instead of the default wide.

How to do:

```
# get rid of performance variables
```

```
wisc.verb <- wisc[,c(1:4,9)]
```

```
# create subset for plotting
```

```
ntot <- nrow(wisc.verb) # total number of observations
```

```
wisc.verb.sel <- wisc.verb[sample(ntot, 30), ]
```

```
wisc.long <- reshape(wisc.verb, varying = c("V1", "V2", "V4", "V6"), v.names =  
  times = c(1, 2, 4, 6), direction = "long")
```

```
wisc.long.sel <- reshape(wisc.verb.sel, varying = c("V1", "V2", "V4", "V6"),  
  v.names = "verbal", times = c(1, 2, 4, 6),  
  direction = "long")
```

```
head(wisc.long,3)
```

```
##      Moeducat time   verbal id  
## 1.1         0     1 24.41964  1  
## 2.1         0     1 12.44048  2  
## 3.1         2     1 32.42560  3
```


```
names(wisc.long)[2] <- "grade"
```

```
names(wisc.long.sel)[2] <- "grade"
```

Trajectories

Lets take a look at what the trajectories are:
First using lattice package


```
library(lattice)  
xyplot(verbal ~ grade, groups = id, data = wisc.long, type = "o", col = "black"  
       xlab = "Grade of Testing", ylab = "Verbal[t]")
```



Subset Trajectories

This is hard to see, better to use subset

```
xyplot(verbal ~ grade, groups = id, data = wisc.long.sel, type = "o",  
       col = "black", xlab = "Grade of Testing", ylab = "Verbal[t]")
```




on average, scores went up over time

Thats a little better.

GGplot2

But, can we simultaneously view the trajectories over time while seeing the influence that Mother's education may have?

```
library(ggplot2)
qplot(grade, verbal, group=id, data=wisc.long, alpha=I(1/2), colour=factor(Moeducat)
      geom = c("line", "point"), xlab = "Grade of Testing", ylab = "Verbal[t]")
```



It

seems pretty clear that mothers with higher levels of education have children that are consistently higher in verbal performance across time.

So now that we have an idea what we will find if we look at the relationship between mother's education and trajectory, let's test it with statistical models.

SEM Trees

SEM Trees LGCM

Note: SEM Trees can be used with any type of SEM that you can specify in lavaan or OpenMx

Our first example is going to be using a latent growth curve model (lgcm) as our outcome, and attempting to find subgroups based on mother's education and the performance scores

Previous demonstrations using SEM Trees have used OpenMx. In this case, we will use lavaan.

```
linearGCM <- '
  inter =~ 1*V1 + 1*V2 + 1*V4 + 1*V6
  slope =~ 1*V1 + 2*V2 + 4*V4 + 6*V6
  inter ~~ vari*inter; inter ~ meani*1;
  slope ~~ vars*slope; slope ~ means*1;
  inter ~~ cov*slope;
  V1 ~~ residual*V1; V1 ~ 0*1;
  V2 ~~ residual*V2; V2 ~ 0*1;
  V4 ~~ residual*V4; V4 ~ 0*1;
  V6 ~~ residual*V6; V6 ~ 0*1;'
run <- lavaan(linearGCM,wisc) # could also have used growth()
#summary(run)
coef(run)
```

```
##      vari      meani      vars      means      cov residual residual residual
##    15.196    15.151     1.529     4.673     1.565    12.828    12.828    12.828
## residual
##    12.828
```

Same LGM as specified in lavaan

```
resVars <- mxPath( from=c("V1", "V2", "V4", "V6"), arrows=2,
                  free=TRUE, values = c(1,1,1,1),
                  labels=c("residual","residual","residual","residual") )
latVars<- mxPath( from=c("intercept","slope"), arrows=2, connect="unique.pairs"
                  free=TRUE, values=c(1,.4,1), labels=c("vari1","cov1","vars1")
intLoads<- mxPath( from="intercept", to=c("V1", "V2", "V4", "V6"), arrows=1,
                  free=FALSE, values=c(1,1,1,1) )
sloLoads<- mxPath( from="slope", to=c("V1", "V2", "V4", "V6"), arrows=1,
                  free=FALSE, values=c(1,2,4,6) )
manMeans<- mxPath( from="one", to=c("V1", "V2", "V4", "V6"), arrows=1,
                  free=FALSE, values=c(0,0,0,0) )
latMeans<- mxPath( from="one", to=c("intercept","slope"), arrows=1,
                  free=TRUE, values=c(0,1), labels=c("meani1","means1") )
dataRaw<- mxData( observed=wisc[,c(1:4,9)], type="raw" )
lgm.mod<- mxModel("LGM", type="RAM",
                  manifestVars=c("V1", "V2", "V4", "V6"),
                  latentVars=c("intercept","slope"),dataRaw,
                  resVars, latVars, intLoads, sloLoads, manMeans, latMeans)
mod.run <- mxRun(lgm.mod);coef(mod.run)
```

```
## residual      vari1      cov1      vars1      meani1      means1
## 12.827561 15.195543  1.564602  1.528757 15.150807  4.673396
```


Run semtree()

Now use “run” with semtree()

Note: semtree() works better with OpenMx at this time


Just used defaults

```
mytree <- semtree(run,wisc[,c(1:4,9)]) # only moeducat as covariate  
plot(mytree)
```



Plot Trajectories

```
# create expected trajectories from parameters
expected.growth <- matrix(
  rep(t(parameters(mytree))[ , "meani"], each=4) +
  rep(t(parameters(mytree))[ , "means"], each=4)*c(1,2,4,6), nrow=2, byrow=T)
# plot expected trajectories for each leaf
plot(c(1,6), c(10,50), xlab="Grade", ylab="Verbal Score", type="n", main="SEM Tr
lines(c(1,2,4,6), expected.growth[1,], col="red", type="b", lw=3)
lines(c(1,2,4,6), expected.growth[2,], col="blue", type="b", lw=3)
legend("bottomright", c("Mom Ed. = 0", "Mom Ed. = 1 or 2"), col=c("red", "blue"),
```



SEM Trees Results Continued

We should get same results as in the left node of the tree by just subsetting the dataset based on Moeducat = 0

ould get same results as in the left node of the tree by just subsetting the dataset based on Moeducat = 0

```
wisc.sub <- wisc[wisc$Moeducat == 0,]  
run.sub <- lavaan(linearGCM,wisc.sub)  
coef(run.sub)
```

```
##      vari    meani     vars    means      cov residual residual residual  
##  12.016   12.473    1.394    4.085   -0.936    10.950    10.950    10.950  
## residual  
##    10.950
```

Yep, everything checks out. This should make it clear that SEM Trees is really just subsetting the dataset into subgroups based on values of the covariates entered.

SEM Trees Options

Invariance of parameters

```
model <- ' i =~ 1*t1 + 1*t2 + 1*t3 + 1*t4  
          s =~ 0*t1 + l1*t2 + l2*t3 + 3*t4 '  
fit <- growth(model, data=Demo.growth)  
tree.inv = semtree(fit,Demo.growth[,1:5],invariance=c("l1","l2"))
```

This allows parameters to be freely estimated, but forces them to be the same in each group tested

Additional Options

```
##?semtree.control  
control <- semtree.control(method="fair",min.N=20,bonferroni=TRUE)  
tree2 = semtree(mod.run,wisc[,c(1:4,9)],control=control)  
#plot(tree2) Doesn't change results
```

I prefer to set the method="fair" as the default "naive" exhibits a preference for covariates with a large number of response options.

Additionally, I usually set the minimum number per node to be something greater than 20. Remember, each node is an actual SEM model.

Finally, if there are a large number of covariates, setting bonferroni=TRUE corrects for the number of comparisons. Usually doesn't make a difference

SEM Trees 2nd Example

Lavaan Syntax

For the 2nd example we will use a mediation model specified in lavaan

```
# latent variable definition      =~ is measured by
# regression                     ~ is regressed on
# (residual) (co)variance        ~~ is correlated (covariance) with
# intercept (mean)              ~ 1 intercept  # same as regressed, but wit
# mediation parameter definition :=
```


Mediation Example

Based on example from: <http://lavaan.ugent.be/tutorial/mediation.html>

```
set.seed(1234)
X <- rnorm(100)
class <- rbinom(100,1,0.5)
M <- class*0.5*X + rnorm(100)
Y <- class*0.7*M + rnorm(100)
Data <- data.frame(X = X, Y = Y, M = M, class=class)
model <- ' # direct effect
          Y ~ c*X
          # mediator
          M ~ a*X
          Y ~ b*M
          # indirect effect (a*b)
          ab := a*b
          # total effect
          total := c + (a*b)
          '
fit.med <- sem(model, data = Data)
```

Visualize the Model

```
semPlot::semPaths(fit.med)
```



Mediation Continued

```
summary(fit.med)
```

```
## lavaan (0.5-20) converged normally after 12 iterations
```

```
##
```

```
##   Number of observations                      100
```

```
##
```

```
##   Estimator                      ML
```

```
##   Minimum Function Test Statistic          0.000
```

```
##   Degrees of freedom                      0
```

```
##   Minimum Function Value          0.000000000000000
```

```
##
```

```
## Parameter Estimates:
```

```
##
```

```
##   Information                      Expected
```

```
##   Standard Errors                  Standard
```

```
##
```

```
## Regressions:
```

```
##           Estimate  Std.Err  Z-value  P(>|z|)
```

```
##   Y ~
```

```
##     X      (c)    0.101    0.097    1.043    0.297
```

```
##   M ~
```

```
##     X      (a)    0.206    0.110    1.875    0.061
```

```
##   Y ~
```


```
##     M      (b)    0.359    0.087    4.145    0.000
```

```
##
```

```
## Version 2.1-20131122
```

SEM Trees and Mediation

```
tree.med <- semtree(fit.med,Data)  
plot(tree.med)
```



SEM Trees Conclusion

In the mediation example, SEM Trees correctly identified the groups with vastly different parameter estimates.

The semtree package is still under development and bugs pop up occasionally. As an example, semtree currently doesn't work with R 3.3.1, thus why we had you install 3.2.5.

Important Reminder: the models you can run with SEM Trees is not limited to the type of models we presented. Any type of SEM can be used to search for groups.

Mixed Effects Trees

Instead of running the models in a SEM framework, longRPart uses mixed-effects models. This works just as well, as many LGCM can be re-specified as mixed-effects models.

For this we will use the nlme package to run a linear mixed effects model

```
#Linear growth
```

```
mix1 <- lme(fixed = verbal ~ grade, random = ~ grade | id,  
            data = wisc.long, method="ML" )
```

```
summary(mix1) # get same estimates as in LGM, notice SD not VAR
```

```
## Linear mixed-effects model fit by maximum likelihood
```

```
## Data: wisc.long
```

```
##          AIC          BIC      logLik
```

```
##    5050.817 5079.043 -2519.408
```

```
##
```

```
## Random effects:
```

```
## Formula: ~grade | id
```

```
## Structure: General positive-definite, Log-Cholesky parametrization
```

```
##          StdDev      Corr
```

```
## (Intercept) 3.898140 (Intr)
```

```
## grade      1.236429 0.325
```

```
## Residual    3.581559
```

```
##
```

```
## Fixed effects: verbal ~ grade
```

```
##          Value Std.Error DF  t-value p-value
```

```
## (Intercept) 15.150809 0.3681966 611 41.14870      0
```

```
## grade       4.673395 0.1085627 611 43.04789      0
```

```
## Correlation:
```

```
##          (Intr)
```

```
## grade -0.155
```

```
##
```

```
lcart.mod1 <- longRPart(verbal ~ grade, ~ Moeducat, ~ 1 | id, wisc.long)
```


```
summary(lcart.mod1)
```

```
## Call:
## rpart(formula = paste(groupingName, c(rPartFormula)), data = data,
##       method = list(eval = evaluation, split = split, init = initialize),
##       parms = data, control = control)
##      n= 816
##
##              CP nsplit rel error
## 1 0.01981397      0  1.000000
## 2 0.01000000      1  0.980186
##
## Variable importance
## Moeducat
##      100
##
## Node number 1: 816 observations,      complexity param=0.01981397
## deviance (-2logLik) 5220.46 slope 4.7
##   left son=2 (304 obs) right son=3 (512 obs)
##   Primary splits:
##       Moeducat < 0.5 to the left,  improve=2661.947, (0 missing)
##
## Node number 2: 304 observations
```

Plot Tree

```
lrpPlot(lcart.mod1)
```

```
## [[1]]  
## [1] "1"  
##  
## [[1]]  
## [1] "1"
```



```
lrpTreePlot(lcart.mod1,use.n=F)
```

Additional Multivariate Trees

REEMtree

Tree partitioning for longitudinal data where random effects exist. This doesn't really accomplish what we did previously with longRPart or SEM Trees. Interested, see the examples in following links.

<http://pages.stern.nyu.edu/~jsimonof/REEMtree/>

<http://www.r-bloggers.com/a-brief-tour-of-the-trees-and-forests/>

mvpart

Like longRPart, also archived:

<http://cran.r-project.org/src/contrib/Archive/mvpart/>

If we treat the longitudinal data just as a multivariate outcome, we can accomplish a very similar process.

mvtboost

Multivariate boosting

See for example code: <https://github.com/patrickm/mvtboost>