

FARMO DEVELOPER NOTES

Types of User: Inside the system	1
Types of User: Outside the system.....	1
Connection Method: Between Server and User.....	1
Profile Status:.....	1
Possible Activity Types	2
Important Point to Remember:.....	4
Request Handling:.....	5
Login Mechanism: use POST Method.....	7
Signup Mechanism: use both POST and GET Method	11
Forget Password:.....	15

Types of User: Inside the system

1. Admin
2. SuperAdmin
3. Farmer
4. VerifiedFarmer
5. Consumer

Types of User: Outside the system

Means this is for webpage, app which show to user.

- | | |
|-------------|--|
| 1. Admin | Admin = Admin Admin = Super Admin |
| 2. Farmer | Farmer = Farmer Farmer = Verified Farmer |
| 3. Consumer | |

Connection Method: Between Server and User

POST

GET

Profile Status:

profile_status = [

- **PENDING** – the profile is created but not yet reviewed or approved.
 - **ACTIVE** – the profile is verified and currently in use.
 - **SUSPENDED** – the profile is temporarily disabled due to issues or violations.
 - **DELETED** – the profile has been removed or deactivated permanently
-]

Possible Activity Types

THIS ACTIVITIES ARE USED TO TRACK THE USER ACTIVITIES. [USED IN BACKEND]

- **Authentication & Account**
 - LOGIN
 - LOGOUT
 - PASSWORD_CHANGE
 - FORGET_PASSWORD
 - UPDATE_PROFILE_PIC
 - PROFILE_UPDATE
 - VERIFICATION_SUBMITTED
 - VERIFICATION_APPROVED
 - VERIFICATION_REJECTED

- **Wallet & Transactions**
 - WALLET_CREATED
 - WALLET_PIN_CHANGED
 - WALLET_TOPUP
 - WALLET_DEBIT
 - TRANSACTION_INITIATED
 - TRANSACTION_SUCCESS
 - TRANSACTION_FAILED

- **Products**
 - PRODUCT_CREATED
 - PRODUCT_UPDATED
 - PRODUCT_DELETED

- **Orders**

- ORDER_PLACED
 - ORDER_UPDATED
 - ORDER_CANCELLED
 - ORDER_FULFILLED
- **Ratings**
 - RATE_PRODUCT
 - RATE_FARMER
 - FARMER_RATING_UPDATE
 - PRODUCT_RATING_UPDATE
 - FARMER_RATING_DELETE
 - PRODUCT_RATING_DELETE
- **General Activity**
 - SEARCH
 - VIEW_PROFILE
 - ACTIVITY_LOGGED - For other activity.

Important Point to Remember:

Use communication Terms to communicate between backend and Frontend as it is. No change in case. Like do not use **admin**, **farmer**, **pending** and **Login** instead of **Admin**, **Farmer**, **PENDING** and **login**.

Communications Terms: User Types, profile status, Error code, terms inside “...”, etc.

Examples of Terms:

Admin, SuperAdmin, Farmer, VerifiedFarmer, PENDING, ACTIVE, DELETED, login_with_token, login, register, user_id, is_admin, ACCOUNT_INACTIVE, INVALID_CREDENTIALS, login_access.

[**Note:** To separate all terms from others, they are written in “Green Letters” in this doc. But “Green Letters” itself is not a term.]

Request Handling:

Request are generally handled with these HTTP codes. We see some where during browsing 404 is not found like that.

- **100 Continue** → client should continue with request
- **200 OK** → success, existing resource returned. All good
- **201 Created** → success, new resource created like data saved.
- **202 Accepted** → Accepted for further processing but not completed
- **400 Bad Request** → invalid input
- **401 Unauthorized** → unauthorized user
- **403 Forbidden** → authenticated but not allowed.
- **404 User Not Found** → user not found
- **406 Not Acceptable** → data not accepted or acceptable
- **500 Internal Server Error** → server failure.
- And so on.

Suggested Way: eutei thau ekei choti vaya ghari ghari lekhnu pardai na.

Pseudo Code:

File.java

Import errorHandler;

ER = errorHandler(); // creating object

function requestToServer(url, method, data, token):
response = sendRequest(url, method, data, token)

if response.code == 200 or response.code == 201:

// ✓ Success

// handleSuccessful request according to request type

else:

// ✗ Error

ER.error_handler(response)

errorHandler.java

```
class errorHandler{  
    function error_handler(response):  
        switch(response.code):  
            case 400:
```

```
        // or popup dialog box dekhai dinu
        print("Invalid input: " + response.error)
    case 401:
        print("Unauthorized: " + response.error)
    case 403:
        print("Forbidden: " + response.error)
    case 404:
        print("Not Found: " + response.error)
    case 500:
        print("Server Error: " + response.error)
    default:
        print("Unexpected Error: " + response.code + " " + response.error)
}
```

Login Mechanism: use POST Method

Path for “login_with_token” : 'https://...../api/auth/login-with-token/'

Path for “login” : 'https://...../api/auth/login/'

Step in login,

1. takes userID or Phone and Password from **user**.
2. Also collect extra two type of data internally in system i.e. **is_admin** and **device_info**
3. Send to server.
4. Server search user in database, if matches; server create token, refresh_token for login.
5. Server send that token with refresh_token and UserID back to User device.

User uses that token and UserID for any other request like for login, access something.

User to Server: Data flow [request]

First Login:

For Admin [Web]: Admin login every time.

```
{  
    “identifier” = userID or Phone [string]  
    “password” = password [String]  
    “is_admin” = True [Boolean]  
    “device_info” = Windows 11 Brave [String]  
}
```

For Farmer/Comsumer[App]:

```
{  
    “identifier” = userID or Phone [string]  
    “password” = password [String]  
    “is_admin” = False [boolean]  
    “device_info” = Samsung A52 [String]  
}
```


Second Login: Only after “remember me” checked.

For Both:

```
{  
    “user_id” = xxxxxx [String]  
    “token” = xxxxxxxx [String]  
    “refresh_token” = xxxxxxxxx [String]  
    “is_admin” = True or False [boolean]  
    “device_info” = Samsung A52 [String]  
}
```

Server check “token” and “UserID” and give access.

Sever to User: [\[respond\]](#)

Each time “First Login”

For Both:

```
{  
    “token” = xxxxxxx [String]  
    “refresh_token” = xxxxxxxxx [String]  
    “user_id” = xxxxxx [String]  
}
```

Save those data[token, refresh_token and userID] in device.

Error in 400, 401, 403, 404

Second Time Login if user checked remember me.

```
{  
    “token” = token or none  
    “refresh_token” = refresh-token or none
```

```

    "user_id" = userID or none
}

```

Error in 401, 403, 406

If login token is expired:

[For User Expiry time: 40 days && For Admin Expiry time: 12 hrs]

Generally, user send "token" and "userID" for login.

If token is expired. Server uses "refresh_token" to create new "token" and send back to user.

```

{
    "token" = xxxxxx [String]
    "refresh_token" = xxxxxxxx [String]
    "user_id" = xxxxxx [String]
}

```

Error Type:

Type of Error [error_code]:

-  MISSING_CREDENTIALS - Missing identifier or password
-  INVALID_CREDENTIALS - Wrong password
-  ACCOUNT_PENDING - Account awaiting activation
-  ACCOUNT_INACTIVE_OR_SUSPENDED - Account blocked/suspended
-  MISSING_TOKENS_OR_USERID – missing token or refresh token or user_id
-  INVALID_TOKEN - Token expired or invalid

Server to User: For Login failed [\[respond\]](#)

Normal:

```

{

```

```
“error” = Error Message [String]
}
```

Special:

But in 403 HTTP code have little bit different. In 403 Code, it have two possible response, **ACCOUNT_PENDING** and **ACCOUNT_INACTIVE_OR_SUSPENDED**.

```
{
  “error_code” = “ACCOUNT_PENDING”[String]
  “error” = Error Message [String]
}
```

Pseudo Code:

```
If error_code == “ACCOUNT_PENDING”
    transfer to change password:

If error_code == “ACCOUNT_INACTIVE_OR_SUSPENDED”
    //Do nothing just print error msg like other errors.
```

Example: For Wrong Password

```
{
  “error_code” = “INVALID_CREDENTIALS”
}
```

For Account Pending:

It occurs only when Admin creates new user, then admin put any password and make profile Status pending.

To activate account, User [both types of user] have to login with that password given by admin and they have interface to change password with confirm password.

After changing password, account have activated and they again redirected in Login Page.

Then process goes to login.

Signup Mechanism: use both POST and GET Method

Path for “register” : “api/auth/register/

Fields:

1. userID [Required]
2. Password [Required]
3. First Name [Required]
4. Middle Name
5. Last Name [Required]
6. Sex [Required]
7. Date of Birth [Required]
8. User Type [Required]
9. Province [Required]
10. District [Required]
11. Municipal [Required]
12. Ward [Required]
13. Tole [Required]
14. Phone [Required]
15. Secondary Phone
16. Email [Required]
17. Facebook
18. WhatsApp
19. About
20. Profile Picture

Data Send To Server: [request]

```
{  
  "user_id" : userID  
  "password" : Password  
  "f_name" : First Name  
  "m_name" : Middle Name
```

```

    "l_name" : Last Name
    "sex" : Sex
    "dob" : Date of Birth
    "user_type" : User Type
    "province" : Province
    "district" : District
    "municipal" : Municipal
    "ward" : Ward
    "tole" : Tole
    "phone" : Phone
    "phone2" : Secondary Phone
    "email" : Email
    "facebook" : Facebook
    "whatsapp" : WhatsApp
    "about" : About
    "profile_pic" : Profile Picture
    "created_by" : Created_By
}

```

Server Response to Web/App:

For Registration Failed:[error → 400, 403]

```

{
  'error': 'MISSING REQUIRED FIELDS'    [String]
}

```

For Registration Success: [created → 201]

```

{
  'message': 'Successful message'
}

```

```
}
```

For UserID:

Path for 'check_userid_available' : <https://...../api/auth/check-userid/>,

UserID needs to check constantly, entered userID is available or not.

If userID textbox is empty then nothing to worry about.

If a single or more characters are present, then box sent request to server to checked userID is available or not.

Request is to be sent in change in every character in textbox.

Request: App/Web to Server

```
{  
    "user_id": UserID  
}
```

Response: Server to App/Web

```
{  
    "status": 1 or 0 [Integer]  
}
```

Status Int mean:

1 → For Not Available

0 → For Available

For User Type during registration:

Register garne belaa dekhine user_type.

For Web:

user_type = [SuperAdmin, Admin, Farmer, Consumer]

For App:

`user_type = [Farmer, Consumer]`

For Created By: [PRIVILEGES]

Values :

`SuperAdmin` – Access to create super-admin, admin, farmer and consumer [*Web*]

`Admin` – Access to create farmer and consumer [*Web*]

`Itself` – farmer and consumer create their account itself. [*App*]

]

In Web four items for Created By [Super Admin, Admin, Farmer and Consumer]

In App two items for Created By [Farmer and Consumer]

Forget Password:

First ask for phone or userID in 1st step.

path ([api/auth/forgot-password](#))

request: {

 'identifier': userID or phone [String]

}

Response [202 → Accepted]

{

 'user_id' : "userid" [String]

 'half_email' : "email" [String]

}

Response [404 → error]

{

 "error": error_message

}

Second complete email:

show half_email in interface

path : ([api/auth/forget-password-complete-email](#))

half_email is like

email = rmnrjchy@gmail.com → half_email = rmn*****hy@gmail.com

email = chaudharyraman020@outlook.com → half_email = cha*****20@outlook.com

email = rabindangaura@nast.edu.np → half_email = rab*****ra@nast.edu.np

email = hoodrobb33@gmail.com → half_email = hoo*****33@gmail.com

request:

{

 'user_id' : user_id [String]


```

        "email": email [String]
    }
    Response [Accepted → 202]
    {
    } // No data empty json file.
    Response [error → 400 or 500]
    {
        "error": error_message
    }

```

Where error_message = "Email is wrong"

Verify OTP sent in email

OTP expired in 2 minutes.

Path (api/auth/forget-password-verify-otp)

request:

```

{
    'user_id' : user_id [String]
    "otp": otp[Integer]
}
Response [Accepted → 200]
{
}

} // No data empty json file.
Response [error → 400 or 404]
{
    "error": error_message
}

```

Change Password:

Path (`api/auth/forget-password-new-password/`)

request:

```
{  
    'user_id': user_id [String]  
    "new_password": password [String]  
}
```

Response [ok → 200]

```
{
```

```
}// No data empty json file.
```

Response [error → 403 Forbidden]

```
{
```

```
    "error": error_message
```

```
}
```