

Detecting change-points in the structure of a network: Exact Bayesian inference

S. Robin

Joint work with A. Cleylen, E. Lebarbier, G. Rigauill,
L. Schwaller, M. Stumpf



Statistical Analysis of Networks, INI, Dec. 2016, Cambridge

Example: Gene regulatory network along time

Data: [AFI⁺02]

Y_{jt} = expression of j at time t

Example: Gene regulatory network along time

Data: [AFI⁺02]

Y_{jt} = expression of j at time t

'Model':

G_t = gene regulatory network at time t
= graphical model of $(Y_{jt})_j$

Example: Gene regulatory network along time

Data: [AFI⁺02]

Y_{jt} = expression of j at time t

'Model':

G_t = gene regulatory network at time t
= graphical model of $(Y_{jt})_j$

Questions:

- ▶ Is G_t constant along time or is there some 'gene rewiring'?
- ▶ If not, when does it change?
- ▶ And what is the network within each period?


Example of output

Data: $N = 67$ time points, $p = 11$ genes, four expected regions

Example of output

Data: $N = 67$ time points, $p = 11$ genes, four expected regions


Posterior probability of change-points:




Example of output

Data: $N = 67$ time points, $p = 11$ genes, four expected regions

Posterior probability of change-points:



Inferred networks:



Similar problems

Ecology:

Y_{it} = abundance of species i at time t in a given medium

G_t = interaction structure between species at time t .

- Time-evolving species interaction network?

Similar problems

Ecology:

Y_{it} = abundance of species i at time t in a given medium

G_t = interaction structure between species at time t .

- ▶ Time-evolving species interaction network?

Neuroscience:

Y_{it} = activity of brain region i at time t

G_t = connectivity structure between regions at time t .

- ▶ Time-evolving connectivity network?

Outline

Bayesian inference with discrete parameters

Change-point detection

Network inference

Detecting changes in a graphical model

Discussion

Bayesian inference with discrete parameters

Mixed parameter: (θ, T)

$\theta = (\text{means, variances, correlations})$

$\in \Theta = \text{continuous set,}$

$T = (\text{segmentation, graph})$

$\in \mathcal{T} = \text{discrete (finite) set,}$

$$\Rightarrow \quad p(Y) = \sum_{T \in \mathcal{T}} \int_{\Theta} p(Y, \theta, T) \, d\theta = \sum_{T \in \mathcal{T}} p(Y, T)$$

Bayesian inference with discrete parameters

Mixed parameter: (θ, T)

θ = (means, variances, correlations)

$\in \Theta$ = continuous set,

T = (segmentation, graph)

$\in \mathcal{T}$ = discrete (finite) set,

$$\Rightarrow p(Y) = \sum_{T \in \mathcal{T}} \int_{\Theta} p(Y, \theta, T) d\theta = \sum_{T \in \mathcal{T}} p(Y, T)$$

Suppose that the integration wrt θ raise no issue, the summation

$$\sum_{T \in \mathcal{T}}$$

can often not be achieved in a naive way because of the combinatorial complexity.

→ Need to find algorithmic or algebraic shortcuts

Main issue

Size of \mathcal{T} .

- ▶ No big deal if \mathcal{T} is small (e.g. model selection within a small collection).
- ▶ Big issue if $\#\mathcal{T}$ grows (super-)exponentially with the number of observations n or the number of variables p .

Main issue

Size of \mathcal{T} .

- ▶ No big deal if \mathcal{T} is small (e.g. model selection within a small collection).
- ▶ Big issue if $\#\mathcal{T}$ grows (super-)exponentially with the number of observations n or the number of variables p .

Examples.

- ▶ Change-point detection:
- ▶ 'Network inference' = inference of the structure of a graphical model
- ▶ Combination of both

Outline

Bayesian inference with discrete parameters

Change-point detection


Network inference

Detecting changes in a graphical model

Discussion


A change-point detection model

Segmentation \mathcal{T} = set of adjacent segments. $\mathcal{T}^K = \mathcal{T}_{1:n}^K$ set of all possible segmentations.




A change-point detection model

Segmentation \mathcal{T} = set of adjacent segments. $\mathcal{T}^K = \mathcal{T}_{1:n}^K$ set of all possible segmentations.



A change-point detection model

Segmentation T = set of adjacent segments. $\mathcal{T}^K = \mathcal{T}_{1:n}^K$ set of all possible segmentations.



$$\begin{aligned}
 p(Y | T) &= \prod_{r \in T} \underbrace{\int p(\theta_r) \prod_{t \in r} p(Y_t | \theta_r) d\theta_r}_{p(Y^r)}, \\
 &= \prod_{r \in T} p(Y^r), \quad Y^r = (Y_t)_{t \in r}
 \end{aligned}$$

Bayesian inference

Factorability assumptions

- ▶ Independent parameters in each segment:

$$p(\theta \mid T) = \prod_{r \in T} p(\theta_r)$$

- ▶ Data are independent from one segment to another

$$p(Y \mid T, \theta) = \prod_{r \in T} p(Y^r \mid \theta_r)$$

- ▶ Prior distribution for the segmentation:

$$p(T \mid K) = \prod_{r \in T} a_r, \quad \text{e.g. } a_r = n_r^\alpha$$

Some quantities of interest

Marginal likelihood.

$$p(Y|K) = \sum_{T \in \mathcal{T}^K} p(T|K)p(Y|T) \propto \sum_{T \in \mathcal{T}^K} \prod_{r \in T} a_r p(Y^r)$$

where the normalizing constant is

$$\sum_{T \in \mathcal{T}^K} \prod_{r \in T} a_r, \quad \text{where } \#\mathcal{T}_{1:n}^K = \binom{n-1}{K-1}.$$

Some quantities of interest

Marginal likelihood.

$$p(Y | K) = \sum_{T \in \mathcal{T}^K} p(T | K) p(Y | T) \propto \sum_{T \in \mathcal{T}^K} \prod_{r \in T} a_r p(Y^r)$$

where the normalizing constant is

$$\sum_{T \in \mathcal{T}^K} \prod_{r \in T} a_r, \quad \text{where } \#\mathcal{T}_{1:n}^K = \binom{n-1}{K-1}.$$

Posterior distribution of a change-point.

$$\Pr\{\tau_k = t | Y, K\} \propto \left(\sum_{T \in \mathcal{T}_{1:t}^k} \prod_{r \in T} a_r p(Y^r) \right) \left(\sum_{T \in \mathcal{T}_{t+1:n}^{K-k}} \prod_{r \in T} a_r p(Y^r) \right)$$

Some simple algebra

$A = (n + 1) \times (n + 1)$ upper-triangular matrix (with zero diagonal):

$$[A]_{i,j+1} = f_{i,j}, \quad 1 \leq i \leq j \leq n$$

Some simple algebra

$A = (n + 1) \times (n + 1)$ upper-triangular matrix (with zero diagonal):

$$[A]_{i,j+1} = f_{i,j}, \quad 1 \leq i \leq j \leq n$$

$$[A^2]_{1,n+1} = f_{1,1}f_{2,n} + \dots + f_{1,i}f_{i+1,n} + \dots + f_{1,n-1}f_{n,n}$$

$$= \sum_{1 \leq i < n} f_{1,i} f_{i+1,n} = \sum_{T \in \mathcal{T}^2} \prod_{r \in T} f_r$$

Some simple algebra

$A = (n + 1) \times (n + 1)$ upper-triangular matrix (with zero diagonal):

$$[A]_{i,j+1} = f_{i,j}, \quad 1 \leq i \leq j \leq n$$

$$[A^2]_{1,n+1} = f_{1,1}f_{2,n} + \dots + f_{1,i}f_{i+1,n} + \dots + f_{1,n-1}f_{n,n}$$

$$= \sum_{1 \leq i < n} f_{1,i} f_{i+1,n} = \sum_{T \in \mathcal{T}^2} \prod_{r \in T} f_r$$

$$[A^3]_{1,n+1} = f_{1,1}f_{2,2}f_{3,n} + \dots + f_{1,i}f_{i+1,j}f_{j+1,n} + \dots + f_{1,n-2}f_{n-1,n-1}f_{n,n}$$

$$= \sum_{1 \leq i \leq j < n} f_{1,i} f_{i+1,j} f_{j+1,n} = \sum_{T \in \mathcal{T}^3} \prod_{r \in T} f_r$$

Summing over segmentations [RLR11]

Property: Define the upper triangular $(n+1) \times (n+1)$ matrix A :

$$A_{i,j+1} = f_r \quad \text{for } r = \llbracket i, j \rrbracket$$

Summing over segmentations [RLR11]

Property: Define the upper triangular $(n+1) \times (n+1)$ matrix A :

$$A_{i,j+1} = f_r \quad \text{for } r = \llbracket i, j \rrbracket$$

Then

$$[A^K]_{1,n+1} = \sum_{T \in \mathcal{T}_{1:n}^K} \prod_{r \in T} f_r$$

→ all terms are computed in $O(Kn^2)$.

Summing over segmentations [RLR11]

Property: Define the upper triangular $(n+1) \times (n+1)$ matrix A :

$$A_{i,j+1} = f_r \quad \text{for } r = \llbracket i, j \rrbracket$$

Then

$$[A^K]_{1,n+1} = \sum_{T \in \mathcal{T}_{1:n}^K} \prod_{r \in T} f_r$$

→ all terms are computed in $O(Kn^2)$.

► To compute $p(Y | K)$, take $f_r = a_r p(Y^r)$.

Summing over segmentations [RLR11]

Property: Define the upper triangular $(n+1) \times (n+1)$ matrix A :

$$A_{i,j+1} = f_r \quad \text{for } r = \llbracket i, j \rrbracket$$

Then

$$[A^K]_{1,n+1} = \sum_{T \in \mathcal{T}_{1:n}^K} \prod_{r \in T} f_r$$

→ all terms are computed in $O(Kn^2)$.

- ▶ To compute $p(Y | K)$, take $f_r = a_r p(Y^r)$.
- ▶ Similar ideas in [Fea06].

Summing over segmentations [RLR11]

Property: Define the upper triangular $(n+1) \times (n+1)$ matrix A :

$$A_{i,j+1} = f_r \quad \text{for } r = \llbracket i, j \rrbracket$$

Then

$$[A^K]_{1,n+1} = \sum_{T \in \mathcal{T}_{1:n}^K} \prod_{r \in T} f_r$$

→ all terms are computed in $O(Kn^2)$.

- ▶ To compute $p(Y | K)$, take $f_r = a_r p(Y^r)$.
- ▶ Similar ideas in [Fea06].

→ R package EBS (exact Bayesian segmentation) [CR14]

Gene regulatory network

Data: $N = 67$ time points, $p = 11$ genes, four expected regions [AFI⁺02]

Model:

$$t \in r : \quad Y_t | \theta_r = (\mu_r, \Sigma_r) \sim \mathcal{N}(\mu_r, \Sigma_r)$$

→ Saturated graphical model.

Gene regulatory network


Data: $N = 67$ time points, $p = 11$ genes, four expected regions [AFI⁺02]

Model:

$$t \in r : \quad Y_t | \theta_r = (\mu_r, \Sigma_r) \sim \mathcal{N}(\mu_r, \Sigma_r)$$

→ Saturated graphical model.

Posterior probability of change-points: **dotted line**



Outline

Bayesian inference with discrete parameters

Change-point detection

Network inference

Detecting changes in a graphical model

Discussion

Graphical model framework

Property [Hammersley-Clifford]. $p(Y) = p(Y_1, \dots, Y_p)$ is Markov wrt the (decomposable) graph G iff it factorizes wrt the maximal cliques of G :

$$p(Y) \propto \prod_{C \in \mathcal{C}(G)} \psi_C(Y^C), \quad Y^C = (Y_j)_{j \in C}.$$

→ G reveals the structure of conditional independences between the variables Y_1, \dots, Y_p .

Graphical model

Means that

$$p(Y_1, \dots, Y_8) \propto \psi_1(Y_1, Y_2, Y_3) \\ \psi_2(Y_1, Y_4) \psi_3(Y_1, Y_5) \\ \psi_4(Y_2, Y_6) \psi_5(Y_3, Y_8)$$

which implies¹ that


$$Y_4 \perp Y_3 \mid Y_1 \\ (Y_6, Y_7) \perp Y_3 \mid Y_2 \\ \dots$$

¹Under fairly general assumptions on p

Graphical model

Means that

$$p(Y_1, \dots, Y_8) \propto \psi_1(Y_1, Y_2, Y_3) \\ \psi_2(Y_1, Y_4) \psi_3(Y_1, Y_5) \\ \psi_4(Y_2, Y_6) \psi_5(Y_3, Y_8)$$



which implies¹ that



$$Y_4 \perp Y_3 \mid Y_1 \\ (Y_6, Y_7) \perp Y_3 \mid Y_2 \\ \dots$$

'Network inference' problem: Based on $\{(Y_{i1}, \dots, Y_{ip})\}_i$ iid $\sim p$, infer G .

¹Under fairly general assumptions on p



Tree-structures network

Tree assumption: the graph G is a spanning tree T .





Tree-structures network

Tree assumption: the graph G is a spanning tree T .




Tree-structures network

Tree assumption: the graph G is a spanning tree T .



Tree-structures network

Tree assumption: the graph G is a spanning tree T .




- Consistent with the usual assumption that the graph is sparse (although much stronger).
- Not true in general, but may be sufficient for the **inference on local structures**, such as the existence of a given edge.

Hyper-Markov prior

Graphical model:

$p(Y \mid \theta, T)$ factorizes wrt edges of T
(Markov wrt T)




Hyper-Markov prior

Graphical model:

$p(Y | \theta, T)$ factorizes wrt edges of T
(Markov wrt T)

Desirable prior:

$p(\theta | T)$ factorizes wrt edges of T as well
(Hyper-Markov wrt T)



Hyper-Markov prior

Graphical model:


$p(Y | \theta, T)$ factorizes wrt edges of T
(Markov wrt T)

Desirable prior:

$p(\theta | T)$ factorizes wrt edges of T as well
(Hyper-Markov wrt T)

Averaging over T :

This should hold for any tree T



($\theta_4, \theta_5, \theta_{14}, \theta_{15}$ not drawn.)

Hyper-Markov prior

Graphical model:


$p(Y | \theta, T)$ factorizes wrt edges of T
(Markov wrt T)

Desirable prior:

$p(\theta | T)$ factorizes wrt edges of T as well
(Hyper-Markov wrt T)

Averaging over T :

This should hold for any tree T



($\theta_4, \theta_5, \theta_{14}, \theta_{15}$ not drawn.)

Compatible family of strong Markov hyper-dist. [DL93]:

- multinomial-Dirichlet (conjugacy),
- normal-Wishart (conjugacy),
- Gaussian copulas (numerical integration), ...?

Bayesian inference for tree-structured network [SRS15]

$p(Y \mid T)$ Markov wrt T

$$\begin{aligned} p(Y \mid T) &= \prod_j p(Y_j) \prod_{(j,k) \in T} \frac{p(Y_j, Y_k)}{p(Y_j)p(Y_k)} \\ &= \prod_{(j,k) \in T} p(Y_j, Y_k) \Big/ \prod_j p^{d_j-1}(Y_j) \end{aligned}$$

where d_j is the degree (number of neighbors in T) of node j .

Bayesian inference for tree-structured network [SRS15]

$p(Y | T)$ Markov wrt T

$$\begin{aligned} p(Y | T) &= \prod_j p(Y_j) \prod_{(j,k) \in T} \frac{p(Y_j, Y_k)}{p(Y_j)p(Y_k)} \\ &= \prod_{(j,k) \in T} p(Y_j, Y_k) \Big/ \prod_j p^{d_j-1}(Y_j) \end{aligned}$$

where d_j is the degree (number of neighbors in T) of node j .

Prior on T : factorizes over the edges:

$$p(T) \propto \prod_{(j,k) \in T} a_{jk}$$

Quantities of interest

Marginal distribution.

$$p(Y) = \sum_{T \in \mathcal{T}} p(T) p(Y | T) \propto \sum_{T \in \mathcal{T}} \prod_{j,k} \frac{a_{jk} p(Y_j, Y_k)}{p(Y_j) p(Y_k)}$$

where \mathcal{T} stands for the set of all spanning trees.

Quantities of interest

Marginal distribution.

$$p(Y) = \sum_{T \in \mathcal{T}} p(T) p(Y | T) \propto \sum_{T \in \mathcal{T}} \prod_{j,k} \frac{a_{jk} p(Y_j, Y_k)}{p(Y_j) p(Y_k)}$$

where \mathcal{T} stands for the set of all spanning trees.

Posterior probability for an edge to be absent.

$$\Pr\{(j, k) \notin T | Y\} \propto \sum_{T \in \mathcal{T}: (j,k) \notin T} \prod_{j,k} \frac{a_{jk} p(Y_j, Y_k)}{p(Y_j) p(Y_k)}$$

Quantities of interest

Marginal distribution.

$$p(Y) = \sum_{T \in \mathcal{T}} p(T) p(Y | T) \propto \sum_{T \in \mathcal{T}} \prod_{j,k} \frac{a_{jk} p(Y_j, Y_k)}{p(Y_j) p(Y_k)}$$

where \mathcal{T} stands for the set of all spanning trees.

Posterior probability for an edge to be absent.

$$\Pr\{(j, k) \notin T | Y\} \propto \sum_{T \in \mathcal{T}: (j,k) \notin T} \prod_{j,k} \frac{a_{jk} p(Y_j, Y_k)}{p(Y_j) p(Y_k)}$$

Typical form:

$$\sum_{T \in \mathcal{T}} \prod_{(j,k) \in T} f_{jk}, \quad \text{with } \#\mathcal{T} = p^{p-2}.$$

Summing over spanning trees

Matrix-tree theorem. [Cha82]

- ▶ $F = [f_{jk}]$: a symmetric matrix with $f(j, j) = 0, f_{jk} > 0$;
- ▶ $\Delta = [\Delta_{jk}]$ its Laplacian: $\Delta_{jj} = \sum_k f_{jk}, \Delta_{jk} = -f_{jk}$.

Summing over spanning trees

Matrix-tree theorem. [Cha82]

- ▶ $F = [f_{jk}]$: a symmetric matrix with $f(j, j) = 0, f_{jk} > 0$;
- ▶ $\Delta = [\Delta_{jk}]$ its Laplacian: $\Delta_{jj} = \sum_k f_{jk}, \Delta_{jk} = -f_{jk}$.

Then the minors $|\Delta^{uv}|$ of Δ are equal and

$$|\Delta^{uv}| = \sum_{T \in \mathcal{T}} \prod_{(j,k) \in T} f_{jk}.$$

Summing over spanning trees

Matrix-tree theorem. [Cha82]

- ▶ $F = [f_{jk}]$: a symmetric matrix with $f(j, j) = 0, f_{jk} > 0$;
- ▶ $\Delta = [\Delta_{jk}]$ its Laplacian: $\Delta_{jj} = \sum_k f_{jk}, \Delta_{jk} = -f_{jk}$.

Then the minors $|\Delta^{uv}|$ of Δ are equal and

$$|\Delta^{uv}| = \sum_{T \in \mathcal{T}} \prod_{(j,k) \in T} f_{jk}.$$

- ▶ $p(Y)$ and the normalizing constant of $p(T)$, ... can be computed at the cost of computing a $p \times p$ determinant, ie $O(p^3)$.
- ▶ Already used in [MJ06,Kir07] for tree learning.

Posterior probability of an edge

The existence of an edge between variables Y_j and Y_k can be assessed by

$$\Pr\{(j, k) \in T \mid Y\} \propto \sum_{T \ni (j, k)} p(T) p(Y \mid T)$$

which depends on the prior $p(T)$.

The prior probability $\Pr\{(j, k) \in T\}$ can be tuned

- ▶ with the prior coefficient a_{jk}
- ▶ or set to an arbitrary value using an edge-specific probability change.

Posterior probability of an edge

The existence of an edge between variables Y_j and Y_k can be assessed by

$$\Pr\{(j, k) \in T \mid Y\} \propto \sum_{T \ni (j, k)} p(T) p(Y \mid T)$$

which depends on the prior $p(T)$.


The prior probability $\Pr\{(j, k) \in T\}$ can be tuned

- ▶ with the prior coefficient a_{jk}
- ▶ or set to an arbitrary value using an edge-specific probability change.


All posterior probabilities can **still be computed in $O(p^3)$** [Kir07].

→ R package Saturnin (spanning trees used for network inference) [SRS15]


Tree averaging




Tree averaging




Tree averaging



$$P\{T = T_1|Y\}$$




$$P\{T = T_2|Y\}$$




$$P\{T = T_3|Y\}$$


Tree averaging




$$P\{T = T_1|Y\}$$



$$P\{T = T_2|Y\}$$




$$P\{T = T_3|Y\}$$




$$P\{T = T_4|Y\}$$


Tree averaging




$$P\{T = T_1 | Y\}$$



$$P\{T = T_2 | Y\}$$




$$P\{T = T_3 | Y\}$$




$$P\{T = T_4 | Y\}$$

Edge posterior probabilities:




$$P\{(j, k) \in T | Y\}$$


Tree averaging




$$P\{T = T_1|Y\}$$



$$P\{T = T_2|Y\}$$




$$P\{T = T_3|Y\}$$




$$P\{T = T_4|Y\}$$

Edge posterior probabilities:



$$P\{(j, k) \in T|Y\}$$


Thresholding probabilities:



$$P\{(j, k) \in T|Y\}$$

Simulations: ROC curves for edge detection

For various graph topologies ($p = 25$, $n = 25, 50, 200$, $B = 100$ simulations)



Tree


Erdős-Rényi
 $p_c = 2/p$

Erdős-Rényi
 $p_c = 4/p$

Erdős-Rényi
 $p_c = 8/p$

Simulations: Comparison with sampling among DAGs

[NPK11]: MCMC sampling over the directed acyclic graphs (multinomial case)



Tree

Erdős-Rényi
 $p_c = 2/p$

Erdős-Rényi
 $p_c = 4/p$

Erdős-Rényi
 $p_c = 8/p$

Area under the curves: top=ROC, bottom=PR

light grey = multinomial trees (2.2"), dark grey: multinomial DAGs (1393")

Illustration: Raf pathway

Flow cytometry data for $p = 11$ proteins from the Raf signaling pathway [SPP⁺05]



'ground truth'



posterior probabilities



most likely tree



second most likely tree

Outline

Bayesian inference with discrete parameters

Change-point detection

Network inference

Detecting changes in a graphical model


Discussion

Change-point in a graphical model

Change-point in a graphical model

Problem: [SR16]


- Consider p variables observed along time;
- Consider the graph G_t supporting the graphical model at time t ;
- Does the graph G_t remain the same along time?



Change-point in a graphical model

Problem: [SR16]

- ▶ Consider p variables observed along time;
- ▶ Consider the graph G_t supporting the graphical model at time t ;
- ▶ Does the graph G_t remain the same along time?



Examples:

1. Gene regulatory network along the *Drosophila* life cycle?
2. Connections between brain regions along different tasks?

Model

K = number of segments $p(K);$

Model

K = number of segments $p(K);$

$R = (r_k)_k$ = segmentation $p(R|K) \propto \prod_{r \in R} a_r;$

Model

K = number of segments $p(K);$

$R = (r_k)_k$ = segmentation $p(R|K) \propto \prod_{r \in R} a_r;$

$T = (T_r)_r$ = set of trees $p(T|R) = \prod_{r \in R} p(T_r|R),$
 T_r = graphical model in segment r

Model

K	=	number of segments	$p(K);$
$R = (r_k)_k$	=	segmentation	$p(R K) \propto \prod_{r \in R} a_r;$
$T = (T_r)_r$	=	set of trees	$p(T R) = \prod_{r \in R} p(T_r R),$
T_r	=	graphical model in segment r	
$\theta = (\theta_r)_r$	=	parameter in each segment typically: $\text{support}(\Sigma_r^{-1}) = T_r$	$p(\theta T) = \prod_{r \in R} p(\theta_r T_r)$

Model

K	=	number of segments	$p(K);$
$R = (r_k)_k$	=	segmentation	$p(R K) \propto \prod_{r \in R} a_r;$
$T = (T_r)_r$	=	set of trees	$p(T R) = \prod_{r \in R} p(T_r R),$
T_r	=	graphical model in segment r	
$\theta = (\theta_r)_r$	=	parameter in each segment typically: $\text{support}(\Sigma_r^{-1}) = T_r$	$p(\theta T) = \prod_{r \in R} p(\theta_r T_r)$
$Y_t = (Y_{jt})$	=	data collected at time t	$p(Y R, \theta) = \prod_{r \in R} \prod_{t \in r} p(Y_t \theta_r)$

Model

K	= number of segments	$p(K);$
$R = (r_k)_k$	= segmentation	$p(R K) \propto \prod_{r \in R} a_r;$
$T = (T_r)_r$	= set of trees	$p(T R) = \prod_{r \in R} p(T_r R),$
T_r	= graphical model in segment r	
$\theta = (\theta_r)_r$	= parameter in each segment typically: $\text{support}(\Sigma_r^{-1}) = T_r$	$p(\theta T) = \prod_{r \in R} p(\theta_r T_r)$
$Y_t = (Y_{jt})$	= data collected at time t	$p(Y R, \theta) = \prod_{r \in R} \prod_{t \in r} p(Y_t \theta_r)$

Typical issue: Evaluate

$$p(Y|K) = \sum_R \sum_{T=(T_r)_{r \in R}} p(R|K) \prod_{r \in R} p(T_r|R) p(Y^r|T_r)$$

Handling two sums

Double discrete structure:

- ▶ $\approx (N/K)^K$ possible segmentations into K segments;
- ▶ $p^{K(p-2)}$ possible combination of K trees

→ sum over $\approx (N/K)^K p^{K(p-2)}$ terms.

Handling two sums

Double discrete structure:

- ▶ $\approx (N/K)^K$ possible segmentations into K segments;
- ▶ $p^{K(p-2)}$ possible combination of K trees

→ sum over $\approx (N/K)^K p^{K(p-2)}$ terms.

Combining the two preceding tools:

- ▶ Summing of all segmentations in $O(KN^2)$,
- ▶ Summing over all trees in $O(p^3)$ (one tree per possible segment)

→ Global complexity = $O(\max\{K, p^3\}N^2)$

Inference

Quantities of interest can be computed in $O(p^3 N^2)$:

- ▶ $P(\text{change-point at time } t \mid K, Y)$
- ▶ $P(\text{edge } (j, k) \text{ present at time } t \mid K, Y)$
- ▶ $P(\text{edge } (j, k) \text{ present at all } t \mid Y)$
- ▶ $P(K \text{ segments} \mid Y)$.

Inference

Quantities of interest can be computed in $O(p^3 N^2)$:

- ▶ $P(\text{change-point at time } t \mid K, Y)$
- ▶ $P(\text{edge } (j, k) \text{ present at time } t \mid K, Y)$
- ▶ $P(\text{edge } (j, k) \text{ present at all } t \mid Y)$
- ▶ $P(K \text{ segments} \mid Y)$.

+ Network comparison




- ▶ $P(T_1 = T_2 \mid Y_1, Y_2)$
- ▶ $P(\text{edge } (j, k) \text{ present in both } T_1 \text{ and } T_2 \mid Y_1, Y_2)$.

Some simulations

Tree

Erdős ($\pi = 2/p$)

Erdős ($\pi = 4/p$)



Top to bottom: $N = 70, 140, 210$. **Tree-structured** network. **Complete** network.

Gene regulatory network


Gene regulatory network

Data: $N = 67$ time points, $p = 11$ genes, four expected regions

Gene regulatory network

Data: $N = 67$ time points, $p = 11$ genes, four expected regions


Posterior probability of change-points:




Gene regulatory network

Data: $N = 67$ time points, $p = 11$ genes, four expected regions

Posterior probability of change-points:



Inferred networks:




FMRI data [CHA⁺12]

FMRI data collected on
20 patients:
 $p = 5$ brain regions,
 $n = 215$ time-points.

Task changes at $t = 60$
and 120.

Top: 5 patients analyzed
separately.

Bottom: joint analysis of
the same 5 patients



Outline

Bayesian inference with discrete parameters

Change-point detection

Network inference

Detecting changes in a graphical model

Discussion

Summary

To summarize.

- ▶ Exact Bayesian inference can be achieved for some fairly complex models with discrete parameter.
- ▶ Do not have to care about sampling and convergence.
- ▶ No systematic way to check when similar algebraic shortcuts exist
→ ad-hoc developments.

Algebraic properties

Bayesian inference

Maximum likelihood

Algebraic properties

Bayesian inference

Maximum likelihood

Change-point detection

$$\sum_m \prod_{r \in m} p_r$$

→ Matrix power

$$\max_m \sum_{r \in m} \log p_r$$

→ Dynamic programming

Algebraic properties

Bayesian inference

Maximum likelihood

Change-point detection

$$\sum_m \prod_{r \in m} p_r$$

→ Matrix power

$$\max_m \sum_{r \in m} \log p_r$$

→ Dynamic programming

Tree-structured network inference

$$\sum_T \prod_{(jk) \in T} p_{jk}$$

→ Matrix-tree theorem

$$\max_T \sum_{(jk) \in T} \log p_{jk}$$

→ Max. spanning tree

Algebraic properties

	Bayesian inference	Maximum likelihood
Change-point detection	$\sum_m \prod_{r \in m} p_r$ → Matrix power	$\max_m \sum_{r \in m} \log p_r$ → Dynamic programming
Tree-structured network inference	$\sum_T \prod_{(jk) \in T} p_{jk}$ → Matrix-tree theorem	$\max_T \sum_{(jk) \in T} \log p_{jk}$ → Max. spanning tree
Algebra	sum-product	max-sum


Algebraic properties

	Bayesian inference	Maximum likelihood
Change-point detection	$\sum_m \prod_{r \in m} p_r$ \rightarrow Matrix power	$\max_m \sum_{r \in m} \log p_r$ \rightarrow Dynamic programming
Tree-structured network inference	$\sum_T \prod_{(jk) \in T} p_{jk}$ \rightarrow Matrix-tree theorem	$\max_T \sum_{(jk) \in T} \log p_{jk}$ \rightarrow Max. spanning tree
Algebra	sum-product	max-sum

Any other example?









Future works

- Dealing with dependency along time.








- Influence of the prior: $p(T)$ depends on n and/or p .
- Solve numerical issues raised by the exact evaluation of all probabilities.

References I

-  N Arbeitman, E. EM Furlong, F. Imam, E. Johnson, B. H Null, B. S Baker, M. A Krasnow, M. P Scott, R. W Davis, and K. P White. Gene expression during the life cycle of drosophila melanogaster. *Science*, 297(5590):2270–2275, 2002.
-  Chaiken. A combinatorial proof of the all minors matrix tree theorem. *SIAM Journal on Algebraic Discrete Methods*, 3(3):319–329, 1982.
-  Cribben, R. Haraldsdottir, L. Y Atlas, T. D Wager, and M. A Lindquist. Dynamic connectivity regression: determining state-related changes in brain connectivity. *Neuroimage*, 61(4):907–920, 2012.
-  Cleynen and S. Robin. Comparing change-point location in independent series. *Statistics and Computing*, pages 1–14, 2014.
-  P. Dawid and S. L. Lauritzen. Hyper Markov Laws in the Statistical Analysis of Decomposable Graphical Models. *The Annals of Statistics*, 21(3):1272–1317, 1993.
-  Fearnhead. Exact and efficient bayesian inference for multiple changepoint problems. *Statistics and computing*, 16(2):203–213, 2006.
-  Kirshner. Learning with tree-averaged densities and distributions. In *NIPS*, pages 761–768, 2007.
-  Meilă and T. Jaakkola. *Tractable Bayesian learning of tree belief networks*. March 2006.

References II

-  Niinimäki, P. Parviainen, and M. Koivisto. Partial order MCMC for structure discovery in bayesian networks. In Fabio Gagliardi Cozman and Avi Pfeffer, editors, *UAI*, 2011.
-  Rigauill, E. Lebarbier, and S. Robin. Exact posterior distributions over the segmentation space and model selection for multiple change-point detection problem. *Stat. Comp.*, 22:917–29, 2011. DOI: 10.1007/s11222-011-9258-8.
-  Sachs, O. Perez, D. Pe’er, D. A. Lauffenburger, and G. P. N. Causal protein-signaling networks derived from multiparameter single-cell data. *Science (New York, N.Y.)*, 308:523–529, 2005.
-  Schwaller and S. Robin. Exact bayesian inference for off-line change-point detection in tree-structured graphical models. *Statistics and Computing*, pages 1–15, 2016.
-  Schwaller, S. Robin, and M. Stumpf. Bayesian Inference of Graphical Model Structures Using Trees. Technical report, ArXiv:1504.02723, April 2015.