Technical parameters

Model(s):	KHC-08RY3-B
Air-to-water heat pump:	YES
Water-to-water heat pump:	NO
Brine-to-water heat pump:	NO
Low-temperature heat pump:	NO
Equipped with a supplementary heater:	NO
Heat pump combination heater:	NO
Declared climate condition:	WARMER

Parameters are declared for medium-temperature application.

Item	Symbol	Value	Unit
Rated heat output (*)	Prated	7.6	kW
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7℃	Pdh	-	kW
Tj = 2℃	Pdh	7.55	kW
Tj = 7℃	Pdh	4.86	kW
Tj = 12℃	Pdh	2.31	kW
Tj = bivalent temperature	Pdh	4.86	kW
Tj = operating limit	Pdh	7.55	kW
For air-to-water heat pumps: Tj = -15℃	Pdh	-	kW
Bivalent temperature	T_{biv}	7	°C
Cycling interval capacity for heating	P_{cych}	-	kW
Degradation co-efficient (**)	C_{dh}	0.9	--
Power consumption in modes other than active mode			
Off mode	P_{off}	0.014	kW
Standby mode	P_{sb}	0.014	kW
Thermostat-off mode	P_{to}	0.024	kW
Crankcase heater mode	P_{ck}	0.000	kW

Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	175.8	%
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7℃	COPd	-	-
Tj = 2℃	COPd	2.59	-
Tj = 7℃	COPd	3.92	-
Tj = 12℃	COPd	5.55	-
Tj = bivalent temperature	COPd	3.92	-
Tj = operating limit	COPd	2.59	-
For air-to-water heat pumps: Tj = -15℃	COPd	-	-
For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval efficiency	COP_{cyc}	-	-
Heating water operating limit temperature	W_{TOL}	62	°C
Supplementary heater			
Rated heat output (**)	P_{sup}	0	kW
Type of energy input	Electrical		

Other items			
Capacity control	variable		
Sound power level, indoors/outdoors	L_{WA}	-	dB
Annual energy consumption	Q_{HE}	2259	kWh

For air-to-water heat pumps: Rated air flow rate, outdoors	-	4030	m^3/h
For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m^3/h

For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q_{clec}	-	kWh
Annual electricity consumption	AEC	-	kWh

Water heating energy efficiency	η_{wh}	-	%
Daily fuel consumption	Q_{fuel}	-	kWh
Annual fuel consumption	AFC	-	GJ

Contact details	KLIMA-THERM Sp. z o. o. ul. Ostrobramska 101A, 04-041 Warszawa, Polska

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.