

1. dumbvm.
2. 29.
3. LAMEbus.
4. 'int' size varies by machine (16-bit, 32-bit, 64-bit). 'uint32_t' always means exactly 32 bits, making the kernel portable.
5. kill_curthread().
6. 'HZ' times per second; in the default non-'OPT-SYNCHPROBS' build, it is 100 times per second.
7. 31 characters plus the terminating '\0'.
8. 15.
9. 'struct fs(' interface.
To implement a new file system, we must implement four functions: 'fs_sync', 'fs_getvolume', 'fs_getroot', 'fs_unmount'.
10. wchan_sleep()
11. 32 bits wide
12. Operations that can be done are:
 - vop_open
 - vop_close
 - vop_reclaim
 - vop_read
 - vop_readlink
 - vop_getdirentry
 - vop_write
 - vop_ioctl
 - vop_stat
 - vop_gettype
 - vop_tryseek
 - vop_fsync
 - vop_mmap
 - vop_truncate
 - vop_namefile
 - vop_creat
 - vop_symlink
 - vop_mkdir
 - vop_link
 - vop_remove
 - vop_rmdir
 - vop_rename
 - vop_lookup
 - vop_lookupparent
13. 1024 bytes.
14. 119.
15. kern/include/kern/unistd.h

16. It boosts the kernel and then enters the menu system (It calls 'boot()', then 'menu(arguments)'. The boot sequence initializes memory, threads, clocks, VFS, devices, VM, and cpus before handing control to the kernel menu).
17. 'splhigh' disables all interrupts; 'spl0' enables all interrupts.
18. 'splx' returns the previous interrupt state.
19. It is a thread that has been exited but not yet fully deleted.
20. DEVNAME:
21. DEVNAMEraw:
22. vfs_bigclock
23. Non-mountable devices, mountable devices with raw-device names, and hardwired filesystem devices.