

1.3 DIJKSTRA'S 2-STACK DEMO



<http://algs4.cs.princeton.edu>


Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.


Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.



20	*	5	=	100
----	---	---	---	-----





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.



100	+	1	=	101
-----	---	---	---	-----

(1	+	((2	+	3)	*	(4	*	5)))
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---





Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.




Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.



(1	+	((2	+	3)	*	(4	*	5)))
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---



Dijkstra's two-stack algorithm

Value: push onto the value stack.

Operator: push onto the operator stack.

Left parenthesis: ignore.

Right parenthesis: pop operator and two values; push the result of applying that operator to those values onto the operand stack.

101

result

(1	+	((2	+	3)	*	(4	*	5)))
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---