

Homework 5

Robbie McKinsty, Jack McQuown, Cyrus Ramavarapu

12 September 2016

Greedy Problems

Problem 7:

Problem 17:

A greedy algorithm that will determine if there is enough information available to fairly partition the goods is as follows:

Given a set of goods $\mathcal{G} = G_1, G_2, \dots, G_n$, and two orderings on this set, $\mathcal{H} = G_a > G_b > \dots > G_n$ and $\mathcal{W} = G_i > G_k > \dots > G_m$, partition the goods by initially giving \mathcal{W} and \mathcal{H} their maximal elements. Remove the element given to the opposing list from each list. If this is not possible because the maximal elements for both \mathcal{W} and \mathcal{H} are the same, conclude *that there is not enough information guarantee a fair partitioning*.

While there are elements in \mathcal{G} , continue giving \mathcal{W} and \mathcal{H} their second most desired element. Ties are broken arbitrarily. For example, if at a given step both \mathcal{W} and \mathcal{H} want G_c , arbitrarily give G_c to \mathcal{W} and cross it off in the ordering for \mathcal{H} and give \mathcal{H} the next element in the ordering.

After all elements have been assigned, first evenly partition \mathcal{H} and \mathcal{W} into two equal portions. If this is not possible because $|\mathcal{G}|$ is odd, conclude that

there is not enough information available to fairly partition the goods. If the upper half of \mathcal{H} and \mathcal{W} is full, conclude that *there is enough information to fairly partition.*

If the upper half of \mathcal{H} or \mathcal{W} are not full, begin iterating through both orderings and check to see that items given alternate with items not given. If an assignment was reach such that elements from \mathcal{G} can be given to \mathcal{H} and \mathcal{W} such that both pass at least one test, conclude that *there is enough information to fairly partition the goods.* Otherwise, conclude that *there is not enough information available.*

Proof by Exchange:

This algorithm can be

Dynamic Programming

Problem 2:

The longest common subsequence between the three can be initially defined recursively by considering the last letter in common between the three strings and then seeing if this letter is in the longest common subsequence of one letter shorter.

$$S_A = A_1, A_2, A_3, \dots, A_{i-1}, A_i$$

$$S_B = B_1, B_2, B_3, \dots, B_{j-1}, B_j$$

$$S_C = C_1, C_2, C_3, \dots, C_{k-1}, C_k$$

Reading right to left, the first letter common to each string will be the last letter in the longest common subsequence. As a result, once this letter is found, problem can be redefined in terms of the shorter substrings formed by ignoring the first common point and all succeeding letters.

This analysis leads to the following recursive algorithm:

```

Function: LCS
Input: int i, int j, int k
if  $i \equiv j \equiv k \equiv 0$  then
  | return 0
end
if  $A_i \equiv B_j \equiv C_k$  then
  |  $LCS(i-1, j-1, k-1) + A_i$ 
else if  $(A_i \equiv B_j) \neq C_k$  then
  |  $\max(LCS(i-1, j-1, k), LCS(i, j, k-1))$ 
else if  $(A_i \equiv C_k) \neq B_j$  then
  |  $\max(LCS(i-1, j, k-1), LCS(i, j-1, k))$ 
else if  $A_i \neq (B_j \equiv C_k)$  then
  |  $\max(LCS(i, j-1, k-1), LCS(i-1, j, k))$ 
else
  |  $\max(LCS(i, j-1, k-1), LCS(i-1, j, k-1), LCS(i-1, j-1, k))$ 
end

```

Although this algorithm produces the longest common subsequence for three given strings, it runs in exponential time due to the numerous recursive calls that operate on a problem of only 1 letter smaller.

By moving to an array based solution and changing the recursive calls to array look-ups, a polynomial runtime algorithm can be developed.

Function: *Array LCS*

Input: *string A, String B, String C*

Initialization:

Array[][][] *LCS*

for $i \leftarrow 0$ to $\text{len}(A)$ do
 | $LCS[i][0][0] = 0$
end

for $j \leftarrow 0$ to $\text{len}(B)$ do
 | $LCS[0][j][0] = 0$
end

for $k \leftarrow 0$ to $\text{len}(C)$ do
 | $LCS[0][0][k] = 0$
end

Array Calculations:

for $i \leftarrow 0$ to $\text{len}(A)$ do
 for $j \leftarrow 0$ to $\text{len}(B)$ do
 for $k \leftarrow 0$ to $\text{len}(C)$ do
 if $A_i \equiv B_j \equiv C_k$ then
 | $LCS[i][j][k] = LCS[i-1][j-1][k-1] + 1$
 else if $(A_i \equiv B_j) \neq C_k$ then
 | $LCS[i][j][k] = \max(LCS[i-1][j-1][k], LCS[i][j][k-1])$
 else if $(A_i \equiv C_k) \neq B_j$ then
 | $\max(LCS[i][j][k] = LCS[i-1][j][k-1], LCS[i][j-1][k])$
 else if $A_i \neq (B_j \equiv C_k)$ then
 | $LCS[i][j][k] = \max(LCS[i][j-1][k-1], LCS[i-1][j], [k])$
 else
 | $LCS[i][j][k] = \max(LCS[i][j-1][k-1],$
 | $LCS[i-1][j][k-1], LCS[i-1][j-1][k])$
 end
 end
 end
end