

Expectation Maximization

Chapter 5

k-means

T.L. Grobler

Supervised versus Unsupervised

- Supervised Learning:
 - Chapter 4
 - Class label comes with observations
- Unsupervised Learning:
 - Chapter 5
 - Class label inferred from observations

General Expectation Maximization

- Expectation:
 - Chapter 5
 - Current estimate of parameters
 - Estimate class labels
- Maximization (MLE):
 - Chapter 4
 - Current estimate of class labels
 - Estimate parameters
- Alternate E and M step till convergence

Preamble

- Assume we have N -observations
- They belong to one of k -clusters
- The value of k is known

Intuitive Description

- Step 1: Choose initial cluster means
 - Choose k random observations
- Step 2: Assign class labels
 - Assign observations to cluster mean closest to it
- Step 3: Update cluster means
 - Compute cluster means using assigned observations
- Repeat steps until convergence

Objective Function

Label

$$J = \sum_{n=1}^N \sum_{j=1}^k t_{nj} \|\mathbf{x}_n - \mathbf{u}_j\|^2$$

1-of-k coding

$$\mathbf{t}_n = [t_{n1} \ \cdots \ t_{nk}]^T$$

Obs

Cluster Mean
(initialized)

$$t_{nj} = \begin{cases} 1 & \text{if } \mathbf{x}_n \in C_j \\ 0 & \text{otherwise} \end{cases}$$

Min J :
alternate between
fixing and solving for
 \mathbf{t}_n and \mathbf{u}_j

Alternating Estimation Steps

- Determine t_{nj} :
 - \mathbf{x}_n assigned to nearest cluster
 - i.e. $\|\mathbf{x}_n - \mathbf{u}_j\|^2$ smallest
- Determine \mathbf{u}_j :
 - set to mean of newly formed clusters


$$\frac{\partial J}{\partial \mathbf{u}_j} = 0 \implies \mathbf{u}_j = \frac{\sum_{n=1}^N t_{nj} \mathbf{x}_n}{\sum_{n=1}^N t_{nj}}$$

Expectation Maximization


- Expectation Step:
 - class labels hidden
 - \mathbf{t}_n are latent variables
 - given class means
 - calc expected values of \mathbf{t}_n
- Maximization Step:
 - use \mathbf{t}_n
 - compute \sim likelihood
 - maximize likelihood
 - determine \mathbf{u}_j

Example


No Class labels




1-iteration




2-iteration




3-iteration




4-iteration



Another Example



Objective Function Plot



Normalization

- Whitening data
- Normalized data
- Warning
 - Rescales distances
 - Indicative of between cluster separation

Hard versus Soft

- Hard
 - Ambiguity ignored
 - Current strategy
- Soft
 - Reflects uncertainty

Local Minima

- J allows multiple local minima
 - Initialization critical
 - Find good local minima

Binary Split

- Two random cluster means
- k -means (two cluster means)
- Compute scatter of clusters
- Two cluster means from cluster with largest scatter
- k -means (three cluster means)
- Continue until clusters match desired number