Tutorial 8: Support Vector Machine

Rui Zhao

rzhao@ee.cuhk.edu.hk

Mar. 13, 2014

Outline

Support Vector Machine

Support Vector Machine

Programming Toolkits

Lots of packages for SVM are available with interfaces including Matlab, Java, Python, R, Perl, Julia, etc. We list mostly used ones

- LibSVM
 http://www.csie.ntu.edu.tw/~cjlin/libsvm/
- Extensions of LibSVM, e.g., LibLinear, multi-class classification, support large training set, etc.
- SVM^{light} http://svmlight.joachims.org/
- Extensions of SVM^{light}, e.g., SVM^{struct}, SVM^{perf}, SVM^{rank}, etc.

LibSVM

Open source at: https://github.com/cjlin1/libsvm Language: support Matlab/Octave/Python/Java Documentation:

- Setup
- 2 Data format
- 3 Function options
- 4 Example in hand

LibSVM-Matlab/Octave

Setup:

- Environment: Matlab, C/C++ compiler (MSVS in Windows or gcc in Linux/Unix)
- 2 Build mex binaries: type in command window mex -setup to choose a suitable compiler, and then run make.m

Function usage:

- 2 [label_pred, acc, decision/prob] = sympredict(label_test, data_test, model, options); label_test $_{n\times 1}$: testing label (dtype: double) data_test $_{n\times d}$: testing data stacked by row (dtype: double) options: string of training options in LibSVM format.

LibSVM-Matlab/Octave

Function options:

1 svmtrain()

https:

//raw.github.com/cjlin1/libsvm/master/README

```
Usage: sym-train [options] training set file [model file]
options:
-s svm type : set type of SVM (default 0)
        0 -- C-SVC
                              (multi-class classification)
        1 -- nu-SVC
                              (multi-class classification)
        2 -- one-class SVM
        3 -- epsilon-SVR
                                (rearession)
        4 -- nu-SVR
                               (regression)
-t kernel type : set type of kernel function (default 2)
        0 -- linear: u'*v
        1 -- polynomial: (gamma*u'*v + coef0)^degree
        2 -- radial basis function: exp(-gamma*|u-v|^2)
        3 -- sigmoid: tanh(gamma*u'*v + coef0)
        4 -- precomputed kernel (kernel values in training set file)
-d degree : set degree in kernel function (default 3)
-g gamma : set gamma in kernel function (default 1/num features)
-r coef0 : set coef0 in kernel function (default 0)
-c cost : set the parameter C of C-SVC, epsilon-SVR, and nu-SVR (default 1)
-n nu : set the parameter nu of nu-SVC. one-class SVM. and nu-SVR (default 0.5)
-p epsilon : set the epsilon in loss function of epsilon-SVR (default 0.1)
-m cachesize : set cache memory size in MB (default 100)

    e epsilon : set tolerance of termination criterion (default 0.001)

-h shrinking : whether to use the shrinking heuristics, 0 or 1 (default 1)
-b probability estimates : whether to train a SVC or SVR model for probability
estimates. 0 or 1 (default 0)
-wi weight : set the parameter C of class i to weight*C, for C-SVC (default 1)
```

LibSVM-Matlab/Octave

Function options:

2 sympredict()

https:

//raw.github.com/cjlin1/libsvm/master/README Usage: svm-predict [options] test_file model_file output_file options: -b probability_estimates: whether to predict probability estimates, 0 or 1 (default 0); for one-class SVM only 0 is supported

```
% read provided data heart\_scale
[heart_label, heart_data] = libsvmread('../heart_scale');
% SVM training
model = svmtrain(heart_label, heart_data, '-c_1_-g_0.07');
% test the training data
[predict_label, accuracy, dec_values] ...
= svmpredict(heart_label, heart_data, model);
```

LibSVM-Python

Setup:

- Environment: Python, C/C++ compiler (MSVS in Windows or gcc in Linux/Unix).
- 2 Build binaries Type make in terminal if in Linux/Unix, copy ../windows/libsvm.dll to C:/WINDOWS/system32/ if in Windows.
- Use other python interface of LibSVM like scikit-learn http://scikit-learn.org/stable/modules/svm.html

Quick start:

```
# import libsvm packages
>>> from svmutil import *

# Read data in LIBSVM format
>>> y, x = svm_read_problem('../heart_scale')

# SVM training
>>> m = svm_train(y[:200], x[:200], '-c_4')

# SVM testing
>>> p_label, p_acc, p_val = svm_predict(y[200:], x[200:], m)
```