

# **MATERIAL SAFETY DATA SHEET**

# TRIETHYLENETETRAMINE (TETA)

# 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Chemical Name: Triethylenetetramine; TETA

**Manufacturer Information:** 

Delamine B.V.

Barchman Wuytierslaan 10

3818 LH Amersfoort

PO Box 473

3800 AL Amersfoort, The Netherlands

Tel: +31 33 4676897

## FOR EMERGENCIES, CONTACT CHEMTREC 1-800-424-9300 OR 1-703-527-3887

## 2. COMPOSITION/INGREDIENT DESCRIPTION

**OSHA** 

Chemical NameCAS #Hazardous(Y/N)Concentration (%)Triethylenetetramine112-24-3Yapprox. 100

### 3. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW:** CORROSIVE TO EYES, SKIN, AND RESPIRATORY TRACT. HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN. CHEMICALS OF THIS TYPE MAY CAUSE SENSITIZATION BY INHALATION OR SKIN CONTACT.

Physical Appearance and Odor: Pale yellow liquid, ammonia-like odor

#### POTENTIAL HEALTH EFFECTS:

**Acute Eye:** Corrosive to eyes. May cause permanent damage and blindness. Vapors can cause a non-permanent vision problem of seeing "halos" or a "blue haze".

**Acute Skin:** Corrosive. Chemicals of this type may cause sensitization upon prolonged or repeated exposure. Material may be absorbed through the skin.

**Acute Inhalation:** May cause severe irritation to respiratory tract, with coughing, nausea and sore throat. Chemicals of this type may cause sensitization upon prolonged or repeated exposure.

Acute Ingestion: Corrosive to gastrointestinal tract.

Chronic Effects: None known.

#### 4. FIRST AID MEASURES

**Eye Contact:** Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek immediate medical attention.

TRIETHYLENETETRAMINE (TETA) MATERIAL SAFETY DATA SHEET – US Version

Date Prepared: June 30, 2008 Supercedes: None (Page 1 of 6)



#### 4. FIRST AID MEASURES (continued)

**Skin Exposure:** Remove contaminated clothing and shoes. Wash with plenty of soap and water, for at least 15 minutes. Seek immediate medical attention. Launder contaminated clothing and shoes before re-use. **Inhalation:** If respiratory irritation or distress occurs, remove victim to fresh air. Seek medical attention if

respiratory irritation or distress continues.

**Ingestion**: Do not induce vomiting. If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person. Seek immediate medical attention. Do not leave victim unattended.

**Medical Conditions Possibly Aggravated by Exposure:** Skin contact may aggravate existing skin disease.

**Notes to Physician:** All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific antidote available.

### 5. FIRE FIGHTING MEASURES

**Flash point:** 252F (122C)

**Autoignition Temperature:** approx. 640F (337C)

Flammability limits (vol/vol%): Lower: Not determined Upper: Not determined

Extinguishing Media: water spray, fog, dry chemical, foam, CO<sub>2</sub>

Special Fire Fighting Procedures: Firefighters should wear NIOSH/MSHA-approved self-contained

breathing apparatus and full protective clothing. Cool containers exposed to fire with water.

**Unusual Fire and Explosion Hazards:** Closed containers may rupture due to buildup of pressure when exposed to extreme heat. Vapor may travel considerable distance to source of ignition and flash back.

Hazardous Decomposition Materials Under Fire Conditions: Oxides of carbon, oxides of nitrogen, ammonia

# 6. ACCIDENTAL RELEASE MEASURES

**Evacuation Procedures and Safety:** Wear appropriate protective gear for the situation. (See Personal Protection information in Section 8).

Cleanup and Disposal of Spill: Absorb with an inert absorbent. Sweep up, and place in an appropriate closed container for disposal and/or incineration, avoiding contact with spilled material. Clean up residual material by washing area with water. Collect washings for disposal.

**Environmental and Regulatory Reporting:** Do not flush to drain. Spills may be reportable to the National Response Center (800-424-8802) and to state and/or local agencies.

# 7. HANDLING AND STORAGE

**Maximum Storage Temperatures:** Store at <40C (<104F)

**Handling:** Persons with a history of dermal or respiratory sensitization should not work with, or near, this material. Avoid breathing vapors. Avoid direct or prolonged contact with skin and eyes.



### 7. HANDLING AND STORAGE (continued)

**Storage:** Store in tightly-closed, original container. Store in an area that is cool, dry, dark and well-ventilated. Do not re-use container.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Introductory Remarks:** These recommendations provide general guidance for handling this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application.

**Exposure Guidelines:** The following limits apply to components of this material.

Chemical None

**Engineering Controls:** General area dilution/exhaust ventilation.

**Respiratory Protection:** When respirators are required, select NIOSH/MSHA approved equipment based on actual or potential airborne concentrations and in accordance with regulatory standards and/or industrial recommendations. Self-contained or supplied-air respiratory equipment is recommended.

Eye/Face Protection: Safety glasses with side shields, goggles or face shield are recommended.

**Skin Protection:** Skin contact should be minimized through the use of chemical-resistant gloves and boots, and suitable protective clothing.

Work Practice Controls: The following general measures should be taken when working or handling this material: 1) Do not store, use, and/or consume foods, beverages, tobacco products, or cosmetics in areas where this material is stored. 2) Wash hands and face carefully before eating, drinking, using tobacco, applying cosmetics, or using the toilet. 3) Wash exposed skin promptly to remove accidental splashes of contact with this material.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical properties here represent typical properties of this product. Contact the manufacturer for exact specifications.

Physical Appearance: Pale yellow liquid

**Odor:** Ammonia-like odor **pH:** 12 (@ 10% aq, 68F (20C))

**Specific Gravity:** 0.981 **Water Solubility:** Soluble

**Melting Point Range:** -31F (-35C) **Boiling Point Range:** 531F (277C)

Freezing Point Range: Not determined Vapor Pressure: <0.01 mm Hg at 68F (20C)

**Vapor Density:** 5.04 (air = 1) **Viscosity:** 30 mPas (@ 68F, 20C)



### 10. STABILITY AND REACTIVITY

**Chemical Stability:** This material is stable under normal handling and storage conditions described in Section 7.

Conditions to be Avoided: Heat, open flame, sparks.

Materials/Chemicals to be Avoided: Strong oxidizing agents, acids, halogenated organic compounds,

aldehydes, carbon disulfide, vinyl acetate, copper and its alloys, nickel and cobalt.

Hazardous Decomposition Products: Oxides of carbon, oxides of nitrogen, ammonia.

Hazardous Polymerization: Not applicable

#### 11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Severely irritating, rabbit.

Acute Skin Irritation: Severely irritating, rabbit. Positive sensitization (guinea pig).

**Acute Dermal Toxicity:** LD  $_{50}$  = 805 mg/kg, rabbit. **Acute Respiratory Irritation:** No data available

Acute Inhalation Toxicity: No data available. However, this material, like many corrosive substances,

when present in an aerosol form, may present a risk of pulmonary edema, which may be fatal.

Acute Oral Toxicity: LD  $_{50}$  = 2500 mg/kg, rat.

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens. When TETA was administered via drinking water, the NOEL = 276 mg/kg/day (male rat) and 352 mg/kg/day (female rat), 487 mg/kg/day (male mouse) and 551 mg/kg/day (female mouse). No effects on the reproductive organs were noted in these studies. Positive mutagenic activity in the Ames test, the Chinese hamster ovary (CHO) and the sister chromatid exchange (SCE) studies. When triethylenetetramine was administered to pregnant rats and mice, an increase in birth defects was observed in the exposed offspring at maternally-toxic doses in rats of >830 mg/kg/day. However, it is not clear if this effect was due to abnormally low tissue levels of copper in the mother. Reproductive studies in rabbits via dermal administration at maternally-toxic doses of up to 125 mg/kg/day did not produce statistically-significant levels of developmental toxicity. When triethylenetetramine, at a concentration of 35%, was administered to the skin of male mice for their lifetime to determine the carcinogenic potential of the material, no treatment-related tumors were reported. No additional test data found for product.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicological Information:** LC50 = 570 mg/L (guppy). 48hr EC50 = 31.1 mg/L, NOEC = 18 mg/L (daphnia) 72hr IC50 = 20 mg/L, NOEC <2.5 mg/L (algae).

**Chemical Fate Information:** Not readily biodegradable. 20% removal in SCAS test. Activated sludge respiration inhibition test EC50 =800 mg/L. Nitrifying bacteria respiration inhibition test EC50 =15.7 mg/L EC50 = 137 mg/L (Pseudomonas putida)

TRIETHYLENETETRAMINE (TETA) MATERIAL SAFETY DATA SHEET – US Version

Date Prepared: June 30, 2008 Supercedes: None (Page 4 of 6)



### 13. DISPOSAL CONSIDERATIONS

Waste disposal Method: Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Please be advised that state and local requirements for waste disposal may be more restrictive or otherwise different from Federal laws and regulations. Consult state and local regulations regarding the proper disposal of this material.

Container Handling and Disposal: Rinse containers before disposal. Do not allow rinsate to enter the water systems. EPA Hazardous Waste = YES EPA RCRA Hazardous Waste Codes: "C" = Corrosive

#### 14. TRANSPORTATION INFORMATION

**Note:** The listed transportation classification does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors.

### **US Department of Transportation:**

Shipping name: Triethylenetetramine

Hazard Class: 8 ID#: UN2259 Packing Group: II Labels: Corrosive

Emergency Guide#: 153

## 15. REGULATORY INFORMATION

### **Inventory Status:**

US (TSCA): Yes Canada (DSL): Yes

Europe (EINECS/ELINCS): Yes

Australia (AICS): Yes Japan (MITI): Yes Korea (KECL): Yes Philippines (PICCS): Yes

Where: Yes = all ingredients are listed on the inventory, Exempt = All ingredients are either on the inventory or exempt from the requirements of listing, No = Not determined, or one or more ingredients are not on the inventory and are not exempt from listing.

#### **SARA Title III Hazard Classes:**

Fire Hazard: No Reactive Hazard: No Release of Pressure: No Acute Health Hazard: Yes Chronic Health Hazard: Yes

SARA Extremely Hazardous Substances/CERCLA Hazardous Substances: None

**California Proposition 65:** This product does not contain any components that are regulated under Proposition 65.

TRIETHYLENETETRAMINE (TETA) MATERIAL SAFETY DATA SHEET - US Version

Date Prepared: June 30, 2008 Supercedes: None (Page 5 of 6)



#### 16. OTHER INFORMATION

# National Fire Protection Association ("NFPA") Hazard Ratings:

Health: 3 (Severe) Flammability: 1 (Slight) Instability: 0 (Minimal)

### National Paint and Coatings Hazardous Materials Identification System ("HMIS") Hazard Ratings:

Health: 3 (Severe) Flammability: 1 (Slight) Physical Hazard: 0 (Minimal)

Reason for Revision(s): New MSDS

Disclaimer: The information set forth herein has been gathered from standard reference materials and/or Delamine and its related, subsidiary and affiliated companies' test data and is to the best knowledge and belief of Delamine and its related, subsidiary and affiliated companies, accurate and reliable. Such information is offered solely for your consideration, investigation, and verification, and is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones that exist. Delamine and its related, subsidiary and affiliated companies make no warranties, express or implied, and expressly disclaim any and all such warranties with respect to the use of such information or the use of specific material identified herein in combination with any other material or process, and assume no responsibility therefor. Delamine and its related, subsidiary and affiliated companies make no representation or warranty, express or implied, and EXPRESSLY DISCLAIM ANY AND ALL SUCH WARRANTIES, as to the usefulness, sufficiency, MERCHANTABILITY or FITNESS FOR ANY PURPOSE whatsoever of the materials identified herein. The purchaser bears sole responsibility for testing, evaluating and determining the suitability of these materials for whatever use(s), manufacturing and refining processes, and any other such application(s) for which it intends or ultimately makes of these materials. Purchaser bears sole responsibility for obtaining any and all regulatory, legal and governmental approval necessary for such use(s).

END OF MATERIAL SAFETY DATA SHEET