

SAFETY DATA SHEET



Diethylenetriamine, DETA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Diethylenetriamine, DETA**Index number** : 612-058-00-X**EC number** : 203-865-4**REACH Registration number**

Registration number	Legal entity
01-2119473793-27-0001	Delamine BV

CAS number : 111-40-0**Product description** : Not applicable**Product type** : Liquid.

Other means of identification : DIETHYLENETRIAMINE; 2,2'-iminodi(ethylamine); diethylene triamine; 1,2-Ethanediamine, N1-(2-aminoethyl)-; Diethylenetriamine (DETA); Diethylenetriamine-1,2-Ethanediamine, N-(2-aminoethyl)-; 1,2-Ethanediamine, N-(2-aminoethyl)-; 2,2'-Diaminodiethylamine; 1,4,7-Tri-(aza)-heptane; N-(2-Aminoethyl)-1,2-ethanediamine

Chemical formula : C₄H₁₃N₃

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Intermediate.**Area of application** : Industrial applications.

Identified uses
Consumer use as an epoxy and polyurethane curing agent Formulation and (re)packing of substances and mixtures - Industrial Manufacture of substance - Industrial Use as a PU curing agent for rigid foam production - Industrial Use as a PU curing agent for rigid foam production - Professional Use as an epoxy curing agent - Industrial Use as an epoxy curing agent - Professional Use as an intermediate - Industrial

1.3 Details of the supplier of the safety data sheet

DELAMINE B.V.
 Barchman Wuytierslaan 10
 3818 LH Amersfoort
 The Netherlands
 Tel.:31-334676897

e-mail address of person responsible for this SDS : SDS.Delamine@delamine.com

1.4 Emergency telephone number

Supplier

Telephone number : AkzoNobel Chemicals-Deventer-NLT +31 570 679211 (24hours/7days)
 F +31 570 679801

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302
Acute Tox. 4, H312
Acute Tox. 2, H330
Skin Corr. 1B, H314
Eye Dam. 1, H318
Skin Sens. 1, H317
STOT SE 3, H335i

Classification according to Directive 67/548/EEC [DSD]

F+; R26
Xn; R21/22
C; R34
Xi; R37
R43

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Fatal if inhaled.
Harmful if swallowed.
Harmful in contact with skin.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
May cause respiratory irritation.

Precautionary statements

Prevention : Wear protective gloves: >8 hours (breakthrough time): neoprene. Wear eye or face protection. Do not breathe vapour.

Response : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF IN EYES: Immediately call a POISON CENTER or physician.

Storage : Store locked up.

Disposal : Not applicable.

Supplemental label elements : Not applicable.

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII : No.

Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : No.

Diethylenetriamine, DETA

SECTION 2: Hazards identification

Other hazards which do not result in classification : Not applicable.

SECTION 3: Composition/information on ingredients

Substance/mixture : Mono-constituent substance

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
2,2'-iminodiethylamine	REACH #: 01-2119473793-27 EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	100	T+; R26 Xn; R21/22 C; R34 Xi; R37 R43 See section 16 for the full text of the R-phrases declared above	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335i See Section 16 for the full text of the H statements declared above.	[A]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures****Eye contact**

- : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

- : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

- : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

- : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If

SECTION 4: First aid measures

- unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed**Potential acute health effects**

- Eye contact** : Causes serious eye damage.
- Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. Dry sand or other suitable absorbent. Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Halones

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

5.3 Advice for firefighters

- Special precautions for firefighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

SECTION 5: Firefighting measures

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Diethylenetriamine, DETA

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

: Do not store above the following temperature: 40°C (104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : No specific data.

Industrial sector specific solutions : No specific data.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
2,2'-iminodiethylamine	EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin. TWA: 4.3 mg/m ³ 8 hour(s). TWA: 1 ppm 8 hour(s).

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

Derived effect levels

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,2'-iminodiethylamine	DNEL	Short term Inhalation	92.1 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	2.6 mg/m ³	Workers	Local
	DNEL	Short term Dermal	11.4 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	15.4 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1.1 mg/cm ²	Workers	Local
	DNEL	Long term Inhalation	0.87 mg/m ³	Workers	Local
	DNEL	Short term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	27.5 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	4.6 mg/m ³	Consumers	Systemic

Predicted effect concentrations

Product/ingredient name	Type	Compartment Detail	Value	Method Detail

Diethylenetriamine, DETA

SECTION 8: Exposure controls/personal protection

2,2'-iminodiethylamine	PNEC	Fresh water	0.56 mg/l	Assessment Factors
	PNEC	Marine	0.056 mg/l	Assessment Factors
	PNEC	Fresh water sediment	1072 mg/kg dwt	-
	PNEC	Marine water sediment	107.2 mg/kg dwt	-
	PNEC	Soil	214 mg/kg dwt	-
	PNEC	Sewage Treatment Plant	6 mg/l	Assessment Factors

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): neoprene

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: neoprene Boots.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: ammonia filter (Type K) ammonia (Type K) and particulate filter

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. [Viscous liquid.]

Colour : Colourless. Yellow.

Odour : Ammoniacal.

Odour threshold : Not available.

pH : 11.6 [Conc. (% w/w): 1%]

Melting point/freezing point : -39°C

Initial boiling point and boiling range : 207°C

Flash point : Closed cup: 96.7°C

Evaporation rate : Not available.

Diethylenetriamine, DETA**SECTION 9: Physical and chemical properties**

Flammability (solid, gas)	: Not applicable
Burning time	: Not applicable.
Burning rate	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: 0.021 kPa [20°C]
Vapour density	: 3.56 [Air = 1]
Relative density	: 0.9586
Solubility(ies)	: Miscible in water.
Partition coefficient: n-octanol/water	: -1.58
Auto-ignition temperature	: 358°C
Decomposition temperature	: Not available.
Viscosity	: Dynamic: 5.05 mPa·s
Explosive properties	: Not applicable.
Oxidising properties	: None.


9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: Keep away from sources of ignition - No smoking. aerosol or mist formation
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials, metals and acids. Chlorinated hydrocarbon.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
 2,2'-iminodiethylamine	LD50 Dermal	Rabbit	1090 mg/kg	-
	LD50 Oral	Rat	1620 mg/kg	-

Conclusion/Summary : No additional information.Irritation/Corrosion**Conclusion/Summary**

Skin	: Corrosive to the skin.
Eyes	: Highly corrosive.
Respiratory	: May cause respiratory irritation.

Diethylenetriamine, DETA

SECTION 11: Toxicological information

Sensitiser

Product/ingredient name	Route of exposure	Species	Result
2,2'-iminodiethylamine	skin	Guinea pig	Sensitising

Conclusion/Summary

- Skin** : May cause skin sensitisation.
- Respiratory** : Non-sensitiser to lungs. Not classified for respiratory sensitisation.

Mutagenicity

- Conclusion/Summary** : Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

- Conclusion/Summary** : Dermal No carcinogenic effect. Not classified as dangerous NOAEL = 56.3mg/kg bw/day
Oral No data available for this end-point, hence this classification is not considered to be applicable.
Inhalation No data available for this end-point, hence this classification is not considered to be applicable.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
2,2'-iminodiethylamine	-	Equivocal	Equivocal	Rat	Oral	90 days

- Conclusion/Summary** : Fertility NOAEL = 30mg/kg bw/day
Developmental Toxicity: NOAEL = 30mg/kg bw/day
Data inconclusive.
Not fully tested.
Not classified.
Further studies (REACH Annex IX/ X) have been proposed

Teratogenicity

- Conclusion/Summary** : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-iminodiethylamine	Category 3	Inhalation	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

- Information on the likely routes of exposure** : Routes of entry anticipated:Oral, Dermal.
Routes of entry not anticipated:Inhalation.

Potential acute health effects

- Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Ingestion** : Adverse symptoms may include the following:
stomach pains

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

Potential immediate effects : No specific data.

Potential delayed effects : No specific data.

Long term exposure

Potential immediate effects : No specific data.

Potential delayed effects : No specific data.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	Chronic NOAEL Oral Chronic NOAEL Dermal Sub-chronic NOAEL Inhalation Vapour	Rat Rat Rat	70 mg/kg 114 mg/kg 550 mg/m ³	- - 6 hours

- Conclusion/Summary** : Cannot be classified.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Absorption** : Rapidly absorbed.
- Metabolism** : Slowly metabolised.
- Elimination** : Excreted via the faeces. Excreted via the urine.
- Other information** : No specific data.

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
2,2'-iminodiethylamine	EC50 32.7 mg/l NOEC 6 mg/l Acute EC50 1164 mg/l Fresh water Acute EC50 32 mg/l Fresh water Acute LC50 430 mg/l Fresh water Chronic NOEC 5.6 mg/l Fresh water Chronic NOEC 10 mg/l Fresh water	Micro-organism Micro-organism Algae Daphnia Fish Daphnia Fish	3 hours 3 hours 72 hours 48 hours 96 hours 21 days 28 days

- Conclusion/Summary** : Not classified as dangerous
PNEC Intermittent release.= 0.32 mg/l

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,2'-iminodiethylamine	-	87 % - Readily - 21 days	-	-

*Diethylenetriamine, DETA***SECTION 12: Ecological information**

Conclusion/Summary : Readily biodegradable Toxic, not persistent. This substance is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-iminodiethylamine	Fresh water 28 days	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2,2'-iminodiethylamine	-1.58	0.3 to 6.3	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : 19.111

Mobility : No specific data.

12.5 Results of PBT and vPvB assessment

PBT : No.

vPvB : No.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

Packaging





Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Diethylenetriamine, DETA

SECTION 14: Transport information

	ADR/RID	ADN/ADNR	IMDG	IATA
14.1 UN number	UN2079	UN2079	UN2079	UN2079
14.2 UN proper shipping name	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	Diethylenetriamine
14.3 Transport hazard class(es)	8 	8 	8 	8 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.
14.6 Special precautions for user	Not available.	Not available.	Not available.	Not available.
Additional information	Hazard identification number 80 Limited quantity 1 L Tunnel code (E)	-	Emergency schedules (EmS) F-A, S-B	Passenger and Cargo Aircraft Quantity limitation: 1 L Packaging instructions: 851 Cargo Aircraft Only Quantity limitation: 30 L Packaging instructions: 855 Limited Quantities - Passenger Aircraft Quantity limitation: 0.5 L Packaging instructions: Y840

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations

Europe inventory : This material is listed or exempted.

Black List Chemicals : Not listed

Priority List Chemicals : Not listed

Diethylenetriamine, DETA

SECTION 15: Regulatory information

Integrated pollution prevention and control list (IPPC) - Air : Not listed

Integrated pollution prevention and control list (IPPC) - Water : Not listed

International regulations

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

15.2 Chemical Safety Assessment : Complete.

15.3 Registration status : Applicable.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number


Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Expert judgment
Acute Tox. 4, H312	Expert judgment
Acute Tox. 2, H330	Expert judgment
Skin Corr. 1B, H314	Expert judgment
Eye Dam. 1, H318	Expert judgment
Skin Sens. 1, H317	Expert judgment
STOT SE 3, H335i	Expert judgment

Full text of abbreviated H statements : H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H330 Fatal if inhaled.
H335i May cause respiratory irritation.

Full text of classifications [CLP/GHS] : Acute Tox. 2, H330 ACUTE TOXICITY: INHALATION - Category 2
Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4
Acute Tox. 4, H312 ACUTE TOXICITY: SKIN - Category 4
Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B
Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
STOT SE 3, H335i SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): INHALATION [Respiratory tract irritation] - Category 3

SECTION 16: Other information

Full text of abbreviated R phrases :  26- Very toxic by inhalation.
R21/22- Harmful in contact with skin and if swallowed.
R34- Causes burns.
R37- Irritating to respiratory system.
R43- May cause sensitisation by skin contact.

Full text of classifications [DSD/DPD] : + - Very toxic
C - Corrosive
Xn - Harmful
Xi - Irritant

Date of issue/ Date of revision : 29 June 2011

Date of previous issue : 25 February 2011

Version : 6

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors **Identified use name:** Consumer use as an epoxy and polyurethane curing agent
Sector of end use: SU21
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f
Market sector by type of chemical product: PC01
Specific Environmental Release Category: FEICA 11

Processes and activities covered by the exposure scenario Covers the use in consumer application of do-it-yourself glue
Assessment Method See Section 3

Section 2: Operational conditions and risk management measures

Section 2.1: Control of consumer exposure

Contributing exposure scenario controlling consumer exposure for 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Concentration of substance in mixture or article Covers concentrations up to 35%
Physical state: Liquid. Vapour pressure 20.3 Pa*s
Human factors not influenced by risk management: None identified.
Conditions and measures related to information and behavioural advice to consumers Covers use under typical household ventilation.
Contributing scenarios: Operational conditions and risk management measures

Section 2.2: Control of environmental exposure

Contributing exposure scenario controlling environmental exposure for 0:

Product Characteristics: Not available.
Amounts used: 10700 Tonnes/year
Fraction of EU tonnage used in region: 0.1
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day) Not available.
Maximum daily site tonnage (kg/day): Not available.
Frequency and duration of use: Continuous release.
Emission Days (days/year): Not available.
Environmental factors not influenced by risk management:
Local freshwater dilution factor: Not available.
Local marine water dilution factor: Not available.
Other operational conditions of use affecting environmental exposure:
Release fraction to air from process (initial release prior to RMM): Not available.
Release fraction to soil from process (initial release prior to RMM): Not available.
Release fraction to wastewater from process (initial release prior to RMM): Not available.
Conditions and measures related to municipal sewage treatment plant:
Estimated substance removal from wastewater via domestic sewage treatment (%): Not available.
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%): Not available.

Diethylenetriamine, DETA

Identified use name: Consumer use as an epoxy and polyurethane curing agent
Sector of end use: SU21
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f
Market sector by type of chemical product: PC01

Maximum allowable site tonnage (M_{Safe}) based on release Not available.
 following total wastewater treatment removal (kg/d):
 Assumed domestic sewage treatment plant flow (m3/d): Not available.
 Local release to soil: 0
 Local release to air: 0
 Local release to sewage: 5.30E-02

Section 3: Exposure estimation and reference to its source

Section 3.1: Exposure estimation - Consumers

Exposure estimation and reference to its source - Consumers: 2:

	Contributing Scenario:	Frequency (1/Year):	Weight fraction of substance in the article::	Body weight:	Calculation method:
Exposure estimation and reference to its source - Consumers: 0:	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Inhalation :

Mode of release: Not applicable.

Exposure estimation and reference to its source - Consumers: 1:

Exposure (minutes):	Application duration:	Amount/concentration applied (g):	Room volume (m³):	Room volume x ventilation rate: (l/h):
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Release area (cm2):	Temperature (°C):	Mass transfer rate:	Contributing Scenario Molecular weight (g/mole):	Uptake fraction (Update model):	Inhalation rate:
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Dermal:

Application methods: Not applicable.

Surface area (Skin contact area) cm2:	Product amount (g):	Uptake fraction (Update model):	Inhalation event (mg/m³):
Not applicable.	Not applicable.	Not applicable.	Not applicable.
Inhalation mg/m³ (Concentration on day of exposure):	Dermal load (mg/cm2):	Dermal External dose (mg/kg bw):	Dermal (Internal dose) mg/kg bw/day:
Not applicable.	Not applicable.	Not applicable.	Not applicable.
Dermal (External dose) mg/kg bw/day:	Inhalation event/Exposure mg/m³ (Short term exposure):	Dermal systemic exposure (external dose) with gloves (90% efficiency) mg/kg bw/day (Long term exposure):	Inhalation (mg/kg/day) Long term exposure:
Not applicable.	Not applicable.	Not applicable.	Not applicable.

Section 3.2 Exposure estimation-Consumers

Contributing exposure scenario controlling worker exposure for 0:

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Systemic, Inhalable	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Systemic, Oral	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Inhalable		Not applicable.	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
			Not applicable.

Diethylenetriamine, DETA

Identified use name: Consumer use as an epoxy and polyurethane curing agent
 Sector of end use: SU21
 Subsequent service life relevant for that use: No.
 Environmental Release Category: ERC08c, ERC08f
 Market sector by type of chemical product: PC01

Short term exposure, Systemic, Oral	Not applicable.	Not applicable.
-------------------------------------	-----------------	-----------------

Section 3.3 Environment Exposure estimation			
Contributing exposure scenario controlling environmental exposure for 1:			
	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Regional PEC Total: 1.71E-03	Not applicable.
air (direct + STP)	Not applicable.	Regional PEC: 2.06E-05	Not applicable.
Soil (direct releases only)	Not applicable.	Regional PEC natural soil Total: 1.54E-03 Regional PEC industrial soil Total: 1.54E-03	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.00185; Surface water, Dissolved Annual average : 0.00185;	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.00018; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.00018; Regional PEC Total: 1.66E-04	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	During emission :3.55; Regional PEC Total: 5.66E+00	Not applicable.
Marine water sediment mg/kg dwt	Not applicable.	During emission: 0.350; Regional PEC: 4.68E-01	Not applicable.
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.0434, 30 days; 0.0153, 180 days; Regional PEC Total: 4.43E-03	
Grassland averaged mg/kg dwt	Not applicable.	0.007, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 4: Guidance to Downstream User to evaluate if he works inside the boundaries set by the ES	
Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA	
Environment	Not applicable.
Health	Not applicable.
Additional guidance	Not applicable.

Diethylenetriamine, DETA	<p>Identified use name: Consumer use as an epoxy and polyurethane curing agent</p> <p>Sector of end use: SU21</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08c, ERC08f</p> <p>Market sector by type of chemical product: PC01</p>
--------------------------	---

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors **Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02
Specific Environmental Release Category: FEICA 2

Processes and activities covered by the exposure scenario Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. also includes combined formulation/reaction to DETA-adducts

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Continuous process Mixing operations (closed systems) no sampling: No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Continuous process Mixing operations (closed systems) with sample collection: No other specific measures identified.

Respiratory protection: None.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Use in contained batch processes Mixing operations (closed systems) with sample collection: No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Batch process Mixing operations (open systems) with sample collection: Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Mixing operations (open systems): Provide extract ventilation to points where emissions occur. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15****Substance supplied to that use in form of: As such
Sector of end use: SU03****Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02**

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Bulk transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Drum and small package filling Dedicated facility: Ensure operation is undertaken outdoors. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Drum and small package filling Dedicated facility with local exhaust ventilation: Ensure material transfers are under containment or extract ventilation.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15****Substance supplied to that use in form of: As such
Sector of end use: SU03****Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02**

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 8: Use as laboratory reagent****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Physical state:

Covers percentage substance in the product up to 100%

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Contributing exposure scenario controlling environmental exposure for 0: Formulation of preparations*****Amounts used:**

43000 Tonnes/year

Fraction of EU tonnage used in region:

1

Regional use tonnage (tonnes/year):

Not available.

Fraction of Regional tonnage used locally:

Not available.

Annual site tonnage (tonnes/year):

Not available.

Average Local Daily Tonnage (kg/day):

Not available.

Maximum daily site tonnage (kg/day):

30000

Frequency and duration of use:

Continuous release.

Emission Days (days/year):

220

Environmental factors not influenced by risk management:**Local freshwater dilution factor:**

10

Local marine water dilution factor:

100

Other operational conditions of use affecting environmental exposure:**Release fraction to air from process (initial release prior to RMM):**

6.00E-03

Release fraction to soil from process (initial release prior to RMM):

0.00E+00

Release fraction to wastewater from process (initial release prior to RMM):

0.00E+00

Release fraction to air from wide dispersive use (regional only):

Not available.

Release fraction to wastewater from wide dispersive use:

Not available.

Release fraction to soil from wide dispersive use (regional only):

Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**Treat air emission to provide a typical removal efficiency of (%)**

Not available.

Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):

Not applicable.

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):

Not available.

Conditions and measures related to municipal sewage treatment plant:**Estimated substance removal from wastewater via domestic sewage treatment (%):**

92.6%

Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):

92.6%

Maximum allowable site tonnage (M_{safe}) based on release following total wastewater treatment removal (kg/d):

7987900 kg/day

Conditions and measures related to external recovery of waste:

Dispose of waste product or used containers according to local regulations.

Local release to soil, kg/day:

0

Diethylenetriamine, DETA**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15****Substance supplied to that use in form of: As such
Sector of end use: SU03****Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02**

Local release to air, kg/day:	1.80E+02
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.15

Section 3: Exposure estimation

Section 3.1 Workers Exposure estimation

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Section 3.1Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	6.86; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	2.15; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	2.15; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.

Diethylenetriamine, DETA**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15****Substance supplied to that use in form of: As such
Sector of end use: SU03****Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02**

Short term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	1.37; 6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	9.03; 2.15	Not applicable.
Diethylenetriamine, DETA		Identified use name: Formulation and (re)packing of substances and mixtures - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02	

Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 8: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.2 Environment Exposure estimation			
Contributing exposure scenario controlling environmental exposure for 0: Formulation of preparations*			
	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dw	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification

Diethylenetriamine, DETA	Identified use name: Formulation and (re)packing of substances and mixtures - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02
---------------------------------	--

Fresh water sediment mg/kg dwt	Not applicable.	3.2	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.314	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.804, 30 days; 0.269, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.119, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0301	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Processes and activities covered by the exposure scenario Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process with sample collection (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 100%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 100%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 100%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Contributing exposure scenario controlling environmental exposure for 0: Manufacture of substances****Amounts used:****Fraction of EU tonnage used in region:**

1

Regional use tonnage (tonnes/year):

Not available.

Fraction of Regional tonnage used locally:

Not available.

Annual site tonnage (tonnes/year):

Not available.

Average Local Daily Tonnage (kg/day):

Not available.

Maximum daily site tonnage (kg/day):

Not available.

Frequency and duration of use:

Continuous release.

Emission Days (days/year):

300

Environmental factors not influenced by risk management:**Local freshwater dilution factor:**

10

Local marine water dilution factor:

Not available.

Other operational conditions of use affecting environmental exposure:**Release fraction to air from process (initial release prior to RMM):**

Not available.

Release fraction to soil from process (initial release prior to RMM):

Not available.

Release fraction to wastewater from process (initial release prior to RMM):

Not available.

Release fraction to air from wide dispersive use (regional only):

Not available.

Release fraction to wastewater from wide dispersive use:

Not available.

Diethylenetriamine, DETA**Identified use name: Manufacture of substance - Industrial**
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15**Substance supplied to that use in form of: As such**
Sector of end use: SU03**Subsequent service life relevant for that use: No.**
Environmental Release Category: ERC01

Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	Do not apply industrial sludge to natural soils.
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Conditions and measures related to external treatment of waste for disposal:	Store finished products in closed containers (e.g., bulk tanks, drums, cans) Incinerate, absorb, or adsorb vapours stripped from solution whenever necessary
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to sewage, kg/day:	150
Fraction of substance in end-use products:	1
Fraction of main source to local environment:	1

Section 3: Exposure estimation

Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal		Not applicable	
Diethylenetriamine, DETA <div style="text-align: right;"> Identified use name: Manufacture of substance - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC01 </div>			

	General exposures Continuous process with sample collection (closed systems)		Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	6.86	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	2.15	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 0: Manufacture of substances

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.537; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.054; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.044	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	1028.3	During emission
Marine water sediment mg/kg dwt	Not applicable.	102.8	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.002; 30, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.002, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.65E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	5.51	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,
PROC08b, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors	Identified use name: Use as a PU curing agent for rigid foam production - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d Specific Environmental Release Category: FEICA 7
--	--

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.1 Control of worker exposure	
Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)	
Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
Preparation of material for application Mixing operations (closed systems): No other specific measures identified.	
Article formation in mould Batch process (closed systems) Machine Manual: No other specific measures identified.	
Respiratory protection:	
None.	
Section 2.1 Control of worker exposure	
Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises	
Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours.	
Article formation in mould Foaming (open systems) Machine Manual: No other specific measures identified.	
Film formation - air drying (open systems): No other specific measures identified.	
Respiratory protection:	
None.	
Section 2.1 Control of worker exposure	
Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)	
Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.	
Respiratory protection:	
None.	

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Industrial spraying****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 5%.

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 5%.

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Non-dedicated facility: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers percentage substance in the product up to 5%.

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: No other specific measures identified.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name: Use as a PU curing agent for rigid foam production**
- Industrial**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,**
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of: As such****Sector of end use: SU03****Subsequent service life relevant for that use: No.****Environmental Release Category: ERC06c, ERC06d**

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Diethylenetriamine, DETA****Identified use name:** Use as a PU curing agent for rigid foam production
- Industrial**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of:** As such**Sector of end use:** SU03**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC06c, ERC06d

Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environmental factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other operational conditions of use affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day

Conditions and measures related to external recovery of waste:

	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environmental factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Other operational conditions of use affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Section 3: Exposure estimation**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	0.86	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	2.58	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA**Identified use name: Use as a PU curing agent for rigid foam production - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15****Substance supplied to that use in form of: As such****Sector of end use: SU03****Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d**

Section 3.1Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	6.86; Not applicable; 6.86; 6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	2.58; 0.60; 4.30; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	2.58; 0.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.

Diethylenetriamine, DETA**Identified use name: Use as a PU curing agent for rigid foam production - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15****Substance supplied to that use in form of: As such
Sector of end use: SU03****Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d**

Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 5: Industrial spraying			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	4.30; 0.20	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal		Not applicable	
Diethylenetriamine, DETA		Identified use name: Use as a PU curing agent for rigid foam production - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d	

	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers		Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA	Identified use name: Use as a PU curing agent for rigid foam production - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d		
---------------------------------	---	--	--

Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors	Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f Specific Environmental Release Category: FEICA 10
--	---

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
 - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors.

Film formation - air drying: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name: Use as a PU curing agent for rigid foam production**
- Professional**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,**
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**Substance supplied to that use in form of: As such****Sector of end use: SU02a, SU02b****Subsequent service life relevant for that use: No.****Environmental Release Category: ERC08c, ERC08f**

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers: Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name: Use as a PU curing agent for rigid foam production**
- Professional**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,**
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**Substance supplied to that use in form of: As such**
Sector of end use: SU02a, SU02b**Subsequent service life relevant for that use: No.**
Environmental Release Category: ERC08c, ERC08f

Section 2.1 Control of worker exposure Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying Product Characteristics: Concentration of substance in product: Volatility: low Covers percentage substance in the product up to 5%. Physical state: Liquid. Amounts used: Not applicable. Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently). Human factors not influenced by risk management: None identified. Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently). Contributing scenarios: Operational conditions and risk management measures Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.	
Respiratory protection:	None.
Section 2.1 Control of worker exposure Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring Product Characteristics: Concentration of substance in product: Volatility: low Covers percentage substance in the product up to 5%. Physical state: Liquid. Amounts used: Not applicable. Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently). Human factors not influenced by risk management: None identified. Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently). Contributing scenarios: Operational conditions and risk management measures Foaming Manual: Wear suitable gloves tested to EN374.	
Respiratory protection:	None.
Section 2.1 Control of worker exposure Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent Product Characteristics: Concentration of substance in product: Volatility: low Covers percentage substance in the product up to 5%. Physical state: Liquid. Amounts used: Not applicable. Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently). Human factors not influenced by risk management: None identified. Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently). Contributing scenarios: Operational conditions and risk management measures Laboratory activities: No other specific measures identified.	
Respiratory protection:	None.
Section 2.1 Control of worker exposure Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available Product Characteristics: Concentration of substance in product: Volatility: low Covers percentage substance in the product up to 5%. Physical state: Liquid. Amounts used: Not applicable. Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently). Human factors not influenced by risk management: None identified. Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).	
Diethylenetriamine, DETA Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f	

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix**

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365
Environmental factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	0
Release fraction to soil from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production

- Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365
Environmental factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	0
Release fraction to soil from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Section 3: Exposure estimation**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	2.58	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.86; Not applicable; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.02; 0.70; 8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	6.02; 0.70	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	1.37; 2.74	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	12.90; 9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA	Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f		
---------------------------------	---	--	--

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	5.36; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	6.02; 0.28	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Foaming Manual	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA	Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f		
--------------------------	--	--	--

Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	3.01; 0.14	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.2 Environment Exposure estimation			
Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix			
	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PEC_{stp}) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.

Diethylenetriamine, DETA	Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f
---------------------------------	---

Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production
- Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors	Identified use name: Use as an epoxy curing agent - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d Specific Environmental Release Category: FEICA 7
--	--

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Injection moulding of articles (closed systems): No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Film formation - air drying (open systems): Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Industrial spraying****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other operational conditions affecting worker exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Diethylenetriamine, DETA**

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
 PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environmental factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other operational conditions of use affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environmental factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Other operational conditions of use affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Section 3: Exposure estimation**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	0.02	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable; 1.37; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	2.15	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	6.45	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	0.69; Not applicable; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	1.07; 0.25; 10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	0.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	1.07; 0.25	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 5: Industrial spraying**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	10.75; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Short term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA Identified use name: Use as an epoxy curing agent - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d			

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	7.52	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors	Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f Specific Environmental Release Category: FEICA 10
--	---

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (closed systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Or Ensure operation is undertaken outdoors.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour.

Film formation - air drying: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
 PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors.
Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures****Diethylenetriamine, DETA**

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
 PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Respiratory protection: None.

Section 2.2: Control of environmental exposure

Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365
Environmental factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	0.00E+00
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365
Environmental factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	0.00E+00
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Section 3: Exposure estimation**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.02	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	4.51	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	6.86; Not applicable; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	4.30; 0.50; 12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	4.30; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	5.37	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	5.49	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	3.76	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	0.11; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	15.05; 0.70	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	5.37; 0.25	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.2 Environment Exposure estimation**Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix**

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PEC _{stp}) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a
Specific Environmental Release Category: ESVOC 2

Processes and activities covered by the exposure scenario Use of substance as an intermediate (not related to Strictly Controlled Conditions).
 Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

Section 2: Operational conditions and risk management measures

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.1 Control of worker exposure

Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other operational conditions affecting worker exposure: Assumes a good basic standard of occupational hygiene is implemented.
 Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process with sample collection (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:****Concentration of substance in product:**

Volatility: low

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.1 Control of worker exposure**Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent****Product Characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection:

None.

Section 2.2: Control of environmental exposure**Contributing exposure scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)****Amounts used:**

43000 Tonnes/year

Fraction of EU tonnage used in region:

1

Regional use tonnage (tonnes/year):

Not available.

Fraction of Regional tonnage used locally:

Not available.

Annual site tonnage (tonnes/year):

Not available.

Average Local Daily Tonnage (kg/day):

Not available.

Maximum daily site tonnage (kg/day):

14333

Frequency and duration of use:

Continuous release.

Emission Days (days/year):

300

Environmental factors not influenced by risk management:**Local freshwater dilution factor:**

10 Default

Local marine water dilution factor:

100 Default

Other operational conditions of use affecting environmental exposure:**Release fraction to air from process (initial release prior to RMM):**

2.00E-05

Release fraction to soil from process (initial release prior to RMM):

1.00E-003

Release fraction to wastewater from process (initial release prior to RMM):

1.00E-02

Release fraction to air from wide dispersive use (regional only):

Not available.

Release fraction to wastewater from wide dispersive use:

Not available.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Release fraction to soil from wide dispersive use (regional only):	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not applicable.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not available.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	15640 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	14.3
Local release to air, kg/day:	2.86E-01
Local release to sewage, kg/day:	143.3
Fraction of main source to local environment:	0.1

Section 3: Exposure estimation

Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Short term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3.1 Workers Exposure estimation**Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.513; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.051; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.042	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	982.6	During emission
Marine water sediment mg/kg dwt	Not applicable.	98.23	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	114.1, 30 days; 37.5, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	15.0, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	8.6E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	5.262	Not applicable.

Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
 Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,
 PROC08b, PROC15
 Substance supplied to that use in form of: As such
 Sector of end use: SU03
 Subsequent service life relevant for that use: No.
 Environmental Release Category: ERC06a