Material Safety Data Sheet



HEPA-S200

1. Product and company identification

Product name : HEPA-S200

Material uses : Industrial applications: Intermediate. Chemical synthesis.

Supplier : DELAMINE B.V.

Barchman Wuytierslaan 10 3818 LH Amersfoort The Netherlands Tel.:31-334676897

Validation date : ***

In case of emergency : CHEMTREC 1-800-424-9300 OR 1-703-527-3887 (24Hours/7Days)

2. Hazards identification

Physical state : Liquid.

Color : Yellow. [Dark]
Odor : Ammonia.

Emergency overview

Signal word : DANGER!

Hazard statements : CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY CAUSE ALLERGIC

SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN

DAMAGE, BASLID ON AN IN AL DATA

Precautions : Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing.

Use only with adequate ventilation. Keep container tightly closed and sealed until ready

for use. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Potential acute health effects

Inhalation : Corrosive to the respiratory system. Exposure to decomposition products may cause a

health hazard. Serious effects may be delayed following exposure.

Ingestion: Harmful if swallowed. May cause burns to mouth, throat and stomach.

Skin : Corrosive to the skin. Causes burns. Harmful in contact with skin. May cause

sensitization by skin contact.

Eves : Corrosive to eyes. Causes burns.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: mucous

membranes, upper respiratory tract, skin, eyes.

Over-exposure signs/symptoms

2. Hazards identification

Inhalation Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : Adverse symptoms may include the following:

stomach pains

Skin Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

: Adverse symptoms may include the following: **Eyes**

watering redness

Medical conditions aggravated by overexposure

Pre-existing skin disorders and disorders involving any other target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

Composition/information on ingredients 3.

Name	CAS number	%
3,6,9,12-tetra-azatetradecamethylenediamine	4067-16-7	10-30
Amines, polyethylenepoly-	68131-73-7	5-10
Tetraethylenepentamine	112-57-2	1-5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention immediately.

Inhalation Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person. Get medical

attention immediately. **Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is

> suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to

> > 2/9

give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.Dry sand or other suitable absorbent. Use dry chemical, CO₂, water spray (fog) or foam.

Not suitable

: Halones

Special exposure hazards

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Accidental release measures 6.

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up **Small spill**

: Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

7. Handling and storage

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
, ,	AIHA WEEL (United States, 5/2010). Absorbed through skin. Skin sensitizer. TWA: 5 mg/m³ 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: ammonia filter (Type K) ammonia (Type K) and particulate filter

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): neoprene

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Physical and chemical properties 9.

Physical state : Liquid.

Flash point : Closed cup: 184°C (363.2°F)

: >300°C (>572°F) **Auto-ignition temperature** Color : Yellow. [Dark] Odor : Ammonia.

рH : 12

Boiling/condensation point : >350°C (>662°F)

Relative density : 1.015

Vapor pressure : <0.001 kPa (<0.007501 mm Hg) [20°C]

VOC content : 0 lbs/gal (0 g/l)

Dynamic: 600 mPa·s (600 cP) **Viscosity**

Solubility

Miscible in water.

LogKow <0

Stability and reactivity **10**.

Chemical stability : The product is stable.

Conditions to avoid : Keep away from sources of ignition - No smoking. aerosol or mist formation

Incompatible materials Reactive or incompatible with the following materials: oxidizing materials, metals and

acids.

Chlorinated hydrocarbon.

Hazardous decomposition

products

urder normal conditions of storage and use, hazardous decomposition products should not be produced

Possibility of hazardous

reactions

: Under normal conditions of storage and use, lazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

11. **Toxicological information**

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
3,6,9,12-tetra- azatetradecamethylenediamine	LD50 Oral	Rat	1600 mg/kg	-

Conclusion/Summary

Chronic toxicity

Not available.

Conclusion/Summary

Irritation/Corrosion

Not available.

: Mixture: No applicable toxicity data

: Mixture: No applicable toxicity data

Conclusion/Summary

: Not available.

Skin Mixture : No applicable toxicity data **Eyes** : Mixture: No applicable toxicity data : Mixture: No applicable toxicity data Respiratory

Sensitizer

Not available.

Conclusion/Summary : Not available.

*** **United States** 5/9 HEPA-S200

11. Toxicological information

Skin

: Mixture: No applicable toxicity data: Mixture: No applicable toxicity data

Respiratory Carcinogenicity

Conclusion/Summary

Classification

Not available.

: Mixture: No applicable toxicity data

Mutagenicity

Not available.

Conclusion/Summary

Teratogenicity

Not available.

: Mixture: No applicable toxicity data

Conclusion/Summary Reproductive toxicity

Not available.

: Mixture: No applicable toxicity data

Conclusion/Summary : Mixture : No applicable toxicity data

12. Ecological information

Ecotoxicity

: This product shows a low bioaccumulation potential. This material is very toxic to aquatic life with long lasting effects.

Aquatic ecotoxicity

Not available.

: Mixture: No app cab@faxciv da@

Conclusion/Summary

Persistence/degradability

Conclusion/Summary

Not available.

: Mixture: No applicable toxicity data

Partition coefficient: n-

octanol/water

: <0

Bioconcentration factor : Not available.

Mobility : No specific data.

Other adverse effects: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

13. Disposal considerations

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN2735	Polyamines, liquid, corrosive, n.o.s. (Amines, polyethylenepoly-)	8	III	CONTROL N	Limited quantity Yes. Packaging instruction Passenger aircraft Quantity limitation: 5 L Cargo aircraft Quantity limitation: 60 L Special provisions IB3, T7, TP1, TP28, T1
IMDG Class	UN2735	POLYAMINES, LIQUID, CORROSIVE, N.O.S. (Amines, polyethylenepoly-). Marine pollutant (3,6,9,12-tetra- azatetradecamethylenediamine, Amines, polyethylenepoly-)	8	III		Emergency schedules (EmS) F-A, S-B
IATA-DGR Class	UN2735	Polyamin es, li fuir, corrosive, n.o.s. (Amines, polyethylenepoly-)	toni	y.	¥2	Passenger and Cargo AircraftQuantity limitation: 5 L Packaging instructions: 818 Cargo Aircraft OnlyQuantity limitation: 60 L Packaging instructions: 820 Limited Quantities - Passenger Aircraft Quantity limitation: 1 L Packaging instructions: Y818

PG*: Packing group

15. Regulatory information

HCS Classification

: Corrosive material Sensitizing material Target organ effects

U.S. Federal regulations

: TSCA 8(a) IUR: Partial exemption

United States inventory (TSCA 8b): All components are listed or exempted.

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found. SARA 302/304/311/312 hazardous chemicals: Amines, polyethylenepoly-, tetraethylenepentamine fraction; Amines, polyethylenepoly-; 3,6,9,12-tetra-azatetradecamethylenediamine

SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
Amines, polyethylenepoly-, tetraethylenepentamine fraction: Immediate (acute) health hazard; Delayed (chronic) health hazard; Amines, polyethylenepoly-: Immediate (acute)

health hazard, Delayed (chronic) health hazard; 3,6,9,12-tetra-

15. Regulatory information

azatetradecamethylenediamine: Immediate (acute) health hazard, Delayed (chronic)

health hazard

Clean Air Act (CAA) 112 accidental release prevention: No products were found.

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)

: Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals (Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 313

Form R - Reporting requirements

Not applicable.

Supplier notification Not applicable.

State regulations

Massachusetts : The following components are listed: TETRAETHYLENE PENTAMINE

New York : None of the components are listed.

New Jersey : The following or moments are listed: TETF AETHYLENEP ENTAMINE; 1,2-

ETHANEDIĂ VII IE, N°-7, -4 M NO THIN L) N'- [?- [(2-AMINOETHYL)AMINO]ETHYL]-

Pennsylvania : The following components are listed: 1,2-ETHANEDIAMINE, N-(2-AMINOETHYL)-N'-[2-

[(2-AMINOETHYL)AMINO]ETHYL]-

Not available.

United States inventory

(TSCA 8b)

: All components are listed or exempted.

: All components are listed or exempted.

Canada inventory

International regulations

International lists

: Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined. **Korea inventory**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): Not determined.

Chemical Weapons

Convention List Schedule I

Chemicals

: Not listed

Chemical Weapons

Convention List Schedule

II Chemicals

: Not listed

II Cnemicais

Chemical Weapons

Convention List Schedule

III Chemicals

: Not listed


***. United States 8/9

16. Other information

Label requirements

: CAUSES RESPIRATORY TRACT, EYE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NF A 704-2001, Identification of the Hazards of Majorible for Emergency Response Copyright ©1997, National Fire Protection Association, On the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : ***.

Date of previous issue : 13/04/2010

Version : ***

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.