

HEPA

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY/UNDERTAKING

Product label name

Pentaethylenehexamine (75%) / Polyethyleneamines (25%)

Supplier

DELAMINE B.V.

Barchman Wuytierslaan 10

3818 LH Amersfoort

PO Box 473

3800 AL Amersfoort

The Netherlands

Tel.: +31-334676897

E-mail address of person responsible for safety data sheet

SDS.Delamine@delamine.com

Emergency telephone

T +31570679211

F +31570679801

AkzoNobel Chemicals-Deventer-NL

Intended use

Chemical intermediate

Date of last issue / Revision number

2008/10/30 / 1.04

2. HAZARDS IDENTIFICATION

Causes burns.

May be very toxic by inhalation of aerosols.

Harmful in contact with skin and if swallowed.

May cause sensitization by inhalation and skin contact.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is to be considered as a preparation in conformance to EC directives.

Information on hazardous ingredients

Chemical description

Pentaethylenehexamine / Polyethyleneamines

Composition / information on ingredients

Number	% w/w	CAS-number	Chemical name
1	approx. 75	004067-16-7	Pentaethylenehexamine
2	approx. 25	068131-73-7	Polyethylenepolyamines

	Index-No.		Symbol(s) (EU classification)	Risk-phrase(s)
1	612-064-00-2	223-775-9	CN	R34 R43 R50/53
2	612-121-00-1	268-626-9	CN	R21/22 R34 R43 R50/53

4. FIRST AID MEASURES

Symptoms and effects

Product code D3151

Corrosive to eyes, skin and upper respiratory tract.

May be very toxic by inhalation of aerosols. (Do not delay treatment of exposed individuals, death may result.)

First aid



HEPA

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Inhalation

Provide fresh air, rest, half upright position. Seek medical advice after significant exposure.

Skin

Remove immediately all contaminated clothing. Wash off immediately with plenty of soap and water. Take all contaminated clothing off immediately. Seek medical advice if irritation develops. Launder contaminated clothes with plenty of water before reuse. Destroy contaminated shoes if made of leather.

Eve

Rinse immediately and as long as possible with plenty of water (at least 15 minutes), Eyelids should be held away from the eyeball to ensure thorough rinsing. DO NOT remove contact lenses. Always seek medical attention.

Ingestion

Only when conscious, rinse mouth, give plenty of water to drink. DO NOT induce vomiting. Seek medical advice.

Advice to physician

No specific antidote known. Symptomatic treatment is advised. If burn is present treat as any thermal burn after decontamination. If necessary evacuation of the stomach contents should be undertaken by means carrying the least likelihood of aspiration (e.g. gastric lavage in combination with endotracheal intubation).

5. FIRE-FIGHTING MEASURES

Extinguishing media

water, spray, foam, sand, Carbon dioxide, dry powder.

Unsuitable extinguishing media

halones.

Hazardous decomposition / combustion products

Nitrous gases may be produced.

Protective equipment

Wear self contained breathing apparatus. Wear a standard aluminised firefighting suit.

Other information

Cool closed containers with water. Do not direct a solid stream of water or foam into the burning material; this may cause spattering and spread the fire.

Water used to extinguish a fire should not be allowed to enter the drainage system or water courses.

Fire and explosion hazard

Toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see Section 8.

Environmental precautions

Treat using the best available techniques before discharge into drains or the aquatic environment.

Methods for cleaning up

Product code D3151

Absorb with sand, sweep up and put into a container for disposal. Flush remainder with water.

7. HANDLING AND STORAGE

Handling

Persons with a history of sensitization of the skin or the respiratory tract should not be employed in any process in which this product is used. Transfer and handle product only in closed system. When using do not eat, drink or smoke. Avoid contact with skin and eyes. Use only in well-ventilated areas. When workers are facing concentrations above 1 ppm v/v they must use appropriate certified respirators.



HEPA

Fire and explosion prevention

Keep away from sources of ignition - No smoking.

Storage requirements

Store in a dry well ventilated place away from sources of heat and direct sunlight. Store in closed containers preferably under nitrogen.

Avoid contact with atmospheric moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

Take precautionary measures against static discharges. Use only in closed system. Do not use copper, nickel and cobalt containing alloys in process equipment. Ensure good ventilation and local exhaustion of the working area.

Personal protection

Respiratory

When workers are facing concentrations above 1 ppm v/v they must use appropriate certified respirators. Use self-contained or supplied-air respiratory equipment with filter K. When aerosols are present the combined cartridge K/P should be used.

Hand

Protective neoprene gloves. Use self-contained or supplied-air respiratory equipment with filter K. When aerosols are present the combined cartridge K/P should be used.

Eye

Wear tightly fitting safety goggles.

Skin and body

Protective neoprene boots and protective clothing.

Other information

Launder contaminated clothes with plenty of water before reuse.

Contaminated leather items (shoes, belts, watch bands etc.) should be removed and destroyed.

In this country no exposure limit has been established

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
------------	--

liquid

Colour

yellow

Odour

ammonia like

Boiling point/range

> 350 ℃

Melting point/range

not determined

Flash point

174 ℃ (Pensky-Martens, closed cup)

Flammability

not determined

Explosive properties

not determined

Oxidising properties

Product code D3151

not applicable



HEPA

Vapour pressure not determined

Density

approx. 1000 kg/m³ (20 ℃)

Bulk density

not applicable

Solubility in water

Completely miscible

Solubility in other solvents

not available

pH value

approx. 12 (100 g/l water, 20 ℃)

Relative vapour density (air=1)

not determined

Viscosity

not determined

Autoignition temperature

> 300 ℃

Explosion limits

not determined

10. STABILITY AND REACTIVITY

Conditions to avoid

Formation of an aerosol.

Stability

Stable under recommended storage and handling conditions (see section 7).

Incompatibles

acids, chlorinated hydrocarbons, oxidising agents, copper and copper alloys, nickel, cobalt.

Hazardous decomposition products

Nitrous gases may be produced.

11. TOXICOLOGICAL INFORMATION

No experimental toxicological data on the preparation as such available. The following data are applicable to the ingredient(s) listed below:-

Pentaethylenehexamine

Acute toxicity

Oral LD50

rat: 1600 mg/kg.

Inhalation LC50

May be very toxic by inhalation of aerosols.

Irritation

Skin

Corrosive.

Eve

Corrosive.

Respiratory

Highly irritating.



HEPA

Genotoxicity

Positive (Ames test, in presence of S9 mix only)

Polyethylenepolyamines

Acute toxicity

Oral LD50

rat: > 2000 mg/kg (female) 1350-2000 mg/kg (male)

Inhalation LC50

May be very toxic by inhalation of aerosols

Irritation

Skin

Corrosive

Eye

Corrosive

Respiratory

Highly irritating

Sensitization

Causing skin sensitization

Causing sensitization of the respiratory tract

12. ECOLOGICAL INFORMATION

No experimental ecological data are available on the preparation as such. The following data are applicable to the ingredient(s) listed below:-

Pentaethylenehexamine.

Ecotoxicity

fish

Acute toxicity, 96h-LC50: 180 mg/l (Poecilia reticulata).

daphnia

Acute toxicity, 48h-EC50: 18 mg/l (Daphnia magna).

algae

Acute toxicity: 72h-IC50: 0.7 mg/l (Selenastrum capricornutum).

bacteria

Acute toxicity, EC 50: 18 mg/l (Pseudomonas putida). Acute toxicity, EC 50: 164 mg/l (Nitrifying bacteria).

Fate

Degradation Biotic

Not readily biodegradable (Closed bottle test).

Other information

Activated sludge respiration inhibition test EC50: >1600 mg/l.

Polyethylenepolyamines

Ecotoxicity

fish

Acute toxicity, 96h-LC50: 100 mg/l (Poecilia reticulata)

daphnia

Acute toxicity, 48h-EC50: 2 mg/l (Daphnia magna)

algae

Acute toxicity, 72h-IC50: 0.2 mg/l (Selenastrum capricornutum)



HEPA

bacteria

Acute toxicity, EC50: 5 mg/l (Pseudomonas putida) Acute toxicity, EC50: 319 mg/l (Nitrifying bacteria)

Fate

Degradation Biotic

Not Readily biodegradable (Closed bottle test)

Other information

Activated sludge respiration inhibition test EC50: 3200 mg/l

13. DISPOSAL CONSIDERATIONS

Product

Incineration is recommended.

Contaminated packaging

Containers which cannot be cleaned should be disposed of in the same manner as the substance.

Other information

For further advice contact manufacturer.

14. TRANSPORT INFORMATION

Land transport

Class

0

Classification Code

C7

RID class

Packing group

1111

Hazard Identification No.

80

Substance Identification No.

2735

TREM-Card or ERG number

CEFIC TEC(R)-80GC7-II+III

UN number

2735

Proper Shipping Name

POLYAMINES, LIQUID, CORROSIVE, N.O.S. "Pentaethylenehexamine" (Pentaethylenehexamine).

Sea transport (IMO / IMDG-code)

Class

8

Packing group

Ш

UN number

2735

EMS

F-A, S-B



HEPA

Marine pollutant	
no	
Proper Shipping Name	

Polyamines, liquid, corrosive, n.o.s. "Pentaethylenehexamine" (Pentaethylenehexamine).

Air transport (ICAO-TI / IATA-DGR)
UN number 2735
Class 8
Packing group
Proper Shipping Name Polyamines, liquid, corrosive, n.o.s. "Pentaethylenehexamine" (Pentaethylenehexamine).

15. REGULATORY INFORMATION	
Product label name Pentaethylenehexamine (75%) / Polyethyleneamines (25%)	
Labelling according to EC directives	
EC-number See section 3	
Classification based on Annex-VI	

R(isk) phrase(s) (EU classification)		
Code	Description	
R21/22.	Harmful in contact with skin and if swallowed.	
R34.	Causes burns.	
R43.	May cause sensitization by skin contact.	
R50/53.	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	

S(afety) phrase(s) (EU classification)		
Code	Description	
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice	
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection	
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)	
S60	This material and its container must be disposed of as hazardous waste	
S61	Avoid release to the environment. Refer to special instructions/Safety data sheets	



HEPA

Symbol(s) (EU classification)





CORROSIVE

DANGEROUS FOR THE ENVIRONMENT

Other information

TSCA Inventory (USA): yes

DSL (Canada): yes

Substance and/or product listed in Directive 96/82/EC.

German Water Hazard Class (WGK)

3

16. OTHER INFORMATION

R-phrase information		
Chemical name	R(isk) phrase(s) (EU classification)	
Pentaethylenehexamine	R34 R43 R50/53	Causes burns May cause sensitization by skin contact Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Polyethylenepolyamines	R21/22 R34 R43 R50/53	Harmful in contact with skin and if swallowed Causes burns May cause sensitization by skin contact Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

History Date of printing/ pdf file generated 2009/07/10

Revision

1.04

Composed by

M. Gyimesi

J. Bos

Changes were made in section

Composers

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.