

Polyethyleneamines, HEPA

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND THE COMPANY/UNDERTAKING

Product label name

Polyethyleneamines

Supplier

DELAMINE B.V.

Barchman Wuytierslaan 10

3818 LH Amersfoort

PO Box 473

3800 AL Amersfoort

The Netherlands

Tel.: +31-334676897

E-mail address of person responsible for safety data sheet

SDS.Delamine@delamine.com

Emergency telephone

AkzoNobel Chemicals-Deventer-NLT +31 570 679211

F +31 570 679801

Intended use

Chemical intermediate

Date of last issue / Revision number

2009/06/18 / 3.11

2. HAZARDS IDENTIFICATION

Causes burns.

Harmful in contact with skin and if swallowed.

May be very toxic by inhalation of aerosols

May cause sensitization by inhalation and skin contact.

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is to be considered as a preparation in conformance to EC directives.

Information on hazardous ingredients

Chemical description

Polyethyleneamines

Composition / information on ingredients

Number	% w/w	CAS-number	Chemical name	
1	approx. 30	004067-16-7	Pentaethylenehexamine	
2	approx. 70	068131-73-7	Polyethylenepolyamines	

	Index-No.		Symbol(s) (EU classification)	Risk-phrase(s)
1	612-064-00-2	223-775-9	CN	R34 R43 R50/53
2	612-121-00-1	268-626-9	CN	R21/22 R34 R43 R50/53

4. FIRST AID MEASURES

Symptoms and effects

Corrosive to eyes, skin and upper respiratory tract.

May be very toxic by inhalation of aerosols (Do not delay treatment of exposed individuals, death may result).

First aid



Polyethyleneamines, HEPA

General

In all cases of doubt, or when symptoms persist, seek medical attention.

Inhalation

Provide fresh air, rest, half upright position. Seek medical advice after significant exposure.

Skin

Remove immediately all contaminated clothing. Wash off with soap and water. Seek medical advice if irritation develops. Launder contaminated clothes with plenty of water before reuse. Destroy contaminated shoes if made of leather.

Eve

Rinse immediately and as long as possible with plenty of water (at least 15 minutes). Eyelids should be held away from the eyeball to ensure thorough rinsing: DO NOT remove contact lenses.

Ingestion

Only when conscious, rinse mouth, give plenty of water to drink. DO NOT induce vomiting. Seek medical advice.

Advice to physician

No specific antidote known. Symptomatic treatment is advised. If burn is present treat as any thermal burn after decontamination. If necessary evacuation of the stomach contents should be undertaken by means carrying the least likelihood of aspiration (e.g. gastric lavage in combination with endotracheal intubation).

5. FIRE-FIGHTING MEASURES

Extinguishing media

water, spray, foam, sand, Carbon dioxide, dry powder.

Unsuitable extinguishing media

halones.

Hazardous decomposition / combustion products

Nitrous gases may be produced.

Protective equipment

Wear self contained breathing apparatus. Wear a standard aluminised firefighting suit.

Other information

Cool closed containers with water. Do not direct a solid stream of water or foam into the burning material; this may cause spattering and spread the fire. Water used to extinguish a fire should not be allowed to enter the drainage system or water courses.

Fire and explosion hazard

Toxic fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see Section 8.

Environmental precautions

Treat using the best available techniques before discharge into drains or the aquatic environment.

Methods for cleaning up

Absorb with sand, sweep up and put into a container for disposal. Flush remainder with water.

7. HANDLING AND STORAGE

Handling

Persons with a history of sensitization of the skin or the respiratory tract should not be employed in any process in which this product is used. Transfer and handle product only in closed system. When using do not eat, drink or smoke. Avoid contact with skin and eyes. Use only in well-ventilated areas.

When workers are facing concentrations above 1 ppm v/v they must use appropriate certified respirators.

Fire and explosion prevention

Keep away from sources of ignition - No smoking.



Polyethyleneamines, HEPA

Storage requirements

Store in a dry well ventilated place away from sources of heat and direct sunlight. Store in closed containers preferably under nitrogen. Avoid contact with atmospheric moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls

Take precautionary measures against static discharges. Use only in closed system. Do not use copper, nickel and cobalt containing alloys in process equipment. Ensure good ventilation and local exhaustion of the working area.

Personal protection

Respiratory

When workers are facing concentrations above 1 ppm v/v they must use appropriate certified respirators. Use self-contained or supplied-air respiratory equipment or respirator with Filter K. When aerosols are present the combined cartridge K/P should be used.

Hand

Protective neoprene gloves.

Eve

Wear tightly fitting safety goggles.

Skin and body

Protective neoprene boots, and protective clothing.

Other information

Launder contaminated clothes with plenty of water before reuse. Contaminated leather items (shoes, belts, watch bands etc.) should be removed and destroyed.

In this country no exposure limit has been established

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour

yellow

Odour

ammonia like

Boiling point/range

> 350 ℃

Melting point/range

not determined

Flash point

184 ℃ (Pensky-Martens, closed cup)

Flammability

not determined

Explosive properties

not determined

Oxidising properties

not applicable

Vapour pressure

< 0.001 kPa (20 ℃)

Density

1015 kg/m³ (20 ℃)

Product code 308371



Polyethyleneamines, HEPA

Bulk	dens	it	ty

not applicable

Solubility in water

Completely miscible

Solubility in other solvents

not available

pH value

approx. 12 (100 g/l water, 20 ℃)

Partition coefficient n-octanol/water

Log Pow: < 0

Relative vapour density (air=1)

not determined

Viscosity

600 mPa.s (20 ℃)

Autoignition temperature

> 300 ℃

Explosion limits

not determined

10. STABILITY AND REACTIVITY

Conditions to avoid

Formation of an aerosol.

Stability

Stable under recommended storage and handling conditions (see section 7).

Incompatibles

acids, chlorinated hydrocarbons, oxidising agents, copper and copper alloys, nickel, cobalt.

Hazardous decomposition products

Nitrous gases may be produced.

11. TOXICOLOGICAL INFORMATION

Polyethylenepolyamines

Acute toxicity

Oral LD50

rat: > 2000 mg/kg (female) 1350-2000 mg/kg (male)

Inhalation LC50

May be very toxic by inhalation of aerosols

Irritation

Skin

Corrosive

Eye

Corrosive

Product code 308371

Respiratory

Highly irritating

Sensitization

Causing skin sensitization

Causing sensitization of the respiratory tract

12. ECOLOGICAL INFORMATION



Polyethyleneamines, HEPA

Polyethylenepolyamines

Ecotoxicity

fish

Acute toxicity, 96h-LC50: 100 mg/l (Poecilia reticulata)

Acute toxicity, 48h-EC50: 2 mg/l (Daphnia magna)

Acute toxicity, 72h-IC50: 0.2 mg/l (Selenastrum capricornutum)

bacteria

Acute toxicity, EC50: 5 mg/l (Pseudomonas putida) Acute toxicity, EC50: 319 mg/l (Nitrifying bacteria)

Degradation Biotic

Not Readily biodegradable (Closed bottle test)

Other information

Activated sludge respiration inhibition test EC50: 3200 mg/l

13. DISPOSAL CONSIDERATIONS

Product

Incineration is recommended.

Contaminated packaging

Containers which cannot be cleaned should be disposed of in the same manner as the substance.

Other information

For further advice contact manufacturer.

14. TRANSPORT INFORMATION

Land transport

Class

Classification Code

C7

RID class

Packing group

Hazard Identification No.

Substance Identification No.

2735

UN number

2735

Proper Shipping Name

POLYAMINES, LIQUID, CORROSIVE, N.O.S. HIGHER ETHYLENE POLYAMINES HEPA.

Other information

Transport label(s): 8 ADR Tunnel code: E



Polyethyleneamines HFPA

1 olyethyleneamines, the A
Sea transport (IMO / IMDG-code)
Class 8
Packing group
UN number

2735

EMS

F-A, S-B Marine pollutant

no

Proper Shipping Name

Polyamines, liquid, corrosive, n.o.s. HIGHER ETHYLENE POLYAMINES HEPA.

Other information Transport label(s): 8

Air transport (ICAO-TI / IATA-DGR)
UN number 2735
Class 8
Packing group
Proper Shipping Name Polyamines, liquid, corrosive, n.o.s. HIGHER ETHYLENE POLYAMINES HEPA.

15. REGULATORY INFORMATION
Product label name Polyethyleneamines
Labelling according to EC directives
EC-number See section 3
Classification based on Annex-VI

R(isk) phrase(s) (EU classification)		
Code	Description	
R21/22.	Harmful in contact with skin and if swallowed.	
R34.	Causes burns.	
R43.	May cause sensitization by skin contact.	
R50/53.	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	


S(afety) phrase(s) (EU classification)	
--	--



Polyethyleneamines, HEPA

Description	
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
Wear suitable protective clothing, gloves and eye/face protection.	
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).	
This material and its container must be disposed of as hazardous waste.	
Avoid release to the environment. Refer to special instructions/Safety data sheets.	
-	

Symbol(s) (EU classification)



Other information

TSCA Inventory (USA): yes.

Substance and/or product listed in Directive 96/82/EC.

German Water Hazard Class (WGK)

|2

16. OTHER INFORMATION

Product code 308371

R-phrase information		
Chemical name	R(isk) phrase(s) (EU classification)	
Pentaethylenehexamine	R34 R43 R50/53	Causes burns May cause sensitization by skin contact Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Polyethylenepolyamines	R21/22 R34 R43 R50/53	Harmful in contact with skin and if swallowed Causes burns May cause sensitization by skin contact Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

History
Date of printing/ pdf file generated 2010/07/23
Revision 3.11
Composed by M. Gyimesi J. Bos



Polyethyleneamines, HEPA

Changes were made in section

сh

This information only concerns the above mentioned product and does not need to be valid if used with other product(s) or in any process. The information is to our best present knowledge correct and complete and is given in good faith but without warranty. It remains the user's own responsibility to make sure that the information is appropriate and complete for his special use of this product.