

SAFETY DATA SHEET



Diethylenetriamine, DETA

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Diethylenetriamine, DETA
Index number : 612-058-00-X
EC number : 203-865-4

REACH Registration number

Registration number	Legal entity
01-2119473793-27-0001	Delamine BV

CAS number : 111-40-0
Product description : Not applicable
Product type : Liquid.
Other means of identification : DIETHYLENETRIAMINE; 2,2'-iminodi(ethylamine); diethylene triamine; 1, 2-Ethanediamine, N1-(2-aminoethyl)-; Diethylenetriamine (DETA); Diethylenetriamine-1,2-Ethanediamine, N-(2-aminoethyl)-; 1,2-Ethanediamine, N-(2-aminoethyl)-; 2,2'-Diaminodiethylamine; 1,4,7-Tri-(aza)-heptane; N-(2-Aminoethyl)-1,2-ethanediamine
Chemical formula : C4-H13-N3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Intermediate.
Area of application : Industrial applications.

Identified uses
<input checked="" type="checkbox"/> Consumer use as an epoxy and polyurethane curing agent Formulation and (re)packing of substances and mixtures - Industrial Manufacture of substance - Industrial Use as a PU curing agent for rigid foam production - Industrial Use as a PU curing agent for rigid foam production - Professional Use as an epoxy curing agent - Industrial Use as an epoxy curing agent - Professional Use as an intermediate - Industrial

1.3 Details of the supplier of the safety data sheet

DELAMINE B.V.
Barchman Wuytierslaan 10
3818 LH Amersfoort
Netherlands
Telephone number: +31-334676897
e-mail address of person responsible for this SDS : SDS.Delamine@delamine.com

1.4 Emergency telephone number

Supplier

Telephone number : GBK/Infotrac ID 104075 : International (001) 352 323 3500 (24 hours per day)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mono-constituent substance

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302
 Acute Tox. 4, H312
 Acute Tox. 2, H330
 Skin Corr. 1B, H314
 Eye Dam. 1, H318
 Skin Sens. 1, H317
 STOT SE 3, H335 (Respiratory tract irritation)

Classification according to Directive 67/548/EEC [DSD]

T+; R26
 Xn; R21/22
 C; R34
 Xi; R37
 R43

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Fatal if inhaled.
 Harmful if swallowed or in contact with skin.
 Causes severe skin burns and eye damage.
 May cause an allergic skin reaction.
 May cause respiratory irritation.

Precautionary statements

Prevention : Wear protective gloves: > 8 hours (breakthrough time): neoprene. Wear eye or face protection. Do not breathe vapour.

Response : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF IN EYES: Immediately call a POISON CENTER or physician.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients : 2,2'-iminodiethylamine

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

SECTION 2: Hazards identification

Containers to be fitted with child-resistant fastenings : Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII : No.

Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : No.

Other hazards which do not result in classification : Not applicable.

SECTION 3: Composition/information on ingredients

Substance/mixture : Mono-constituent substance

Product/ingredient name	Identifiers	%	<u>Classification</u>		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
2,2'-iminodiethylamine	EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	100	T+; R26 Xn; R21/22 C; R34 Xi; R37 R43 See Section 16 for the full text of the R-phrases declared above.	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 (Respiratory tract irritation) See Section 16 for the full text of the H statements declared above.	[A]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

Eye contact : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

SECTION 4: First aid measures

- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed**Potential acute health effects**

- Eye contact** : Causes serious eye damage.
- Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 4: First aid measures

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. Dry sand or other suitable absorbent. Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Halones

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides

5.3 Advice for firefighters

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 6: Accidental release measures

Large spill : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 40°C (104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Seveso II Directive - Reporting thresholds (in tonnes)**Danger criteria**

Category	Notification and MAPP threshold	Safety report threshold
H2: Acute toxicity 2 any route of entry or Acute toxicity 3 Inhalation/Dermal route of entry	50	200
C1: Very toxic	5	20

7.3 Specific end use(s)

Recommendations : No specific data.

Industrial sector specific solutions : No specific data.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

8.1 Control parameters**Occupational exposure limits**

Product/ingredient name	Exposure limit values
2,2'-iminodiethylamine	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. TWA: 4.3 mg/m ³ 8 hours. TWA: 1 ppm 8 hours.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,2'-iminodiethylamine	DNEL	Short term Inhalation	92.1 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	2.6 mg/m ³	Workers	Local
	DNEL	Short term Dermal	11.4 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	15.4 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	1.1 mg/cm ²	Workers	Local
	DNEL	Long term Inhalation	0.87 mg/m ³	Workers	Local
	DNEL	Short term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	27.5 mg/m ³	Consumers	Systemic
	DNEL	Long term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	4.6 mg/m ³	Consumers	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2'-iminodiethylamine	Fresh water	0.56 mg/l	Assessment Factors
	Marine	0.056 mg/l	Assessment Factors
	Fresh water sediment	1072 mg/kg dwt	-
	Marine water sediment	107.2 mg/kg dwt	-
	Soil	214 mg/kg dwt	-
	Sewage Treatment Plant	6 mg/l	Assessment Factors

8.2 Exposure controls

SECTION 8: Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): neoprene
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: neoprene Boots.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: ammonia filter (Type K) ammonia (Type K) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Appearance**

- Physical state** : Liquid. [Viscous liquid.]
- Colour** : Colourless. Yellow.
- Odour** : Ammoniacal.
- Odour threshold** : Not available.
- pH** : 11.6 [Conc. (% w/w): 1%]
- Melting point/freezing point** : -39°C
- Initial boiling point and boiling range** : 207°C
- Flash point** : Closed cup: 96.7°C
- Evaporation rate** : Not available.

SECTION 9: Physical and chemical properties

Flammability (solid, gas)	: Not applicable.
Burning time	: Not applicable.
Burning rate	: Not applicable.
Upper/lower flammability or explosive limits	: Not available.
Vapour pressure	: 0.021 kPa [room temperature]
Vapour density	: 3.56 [Air = 1]
Relative density	: Not available.
Solubility(ies)	: Not available.
Solubility in water	: Miscible in water.
Partition coefficient: n-octanol/ water	: -1.58
Auto-ignition temperature	: 358°C
Decomposition temperature	: Not available.
Viscosity	: Dynamic (room temperature): 5.05 mPa·s
Explosive properties	: Not applicable.
Oxidising properties	: None.

9.2 Other information

Density	: 0.959 g/cm ³ [20°C]
Physical/chemical properties comments	: No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: The product is stable.
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	: Keep away from sources of ignition - No smoking. aerosol or mist formation
10.5 Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials, metals and acids. Chlorinated hydrocarbon.
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	LD50 Dermal LD50 Oral	Rabbit Rat	1045 mg/kg 1620 mg/kg	- -

Conclusion/Summary : Inhalation (Aerosol. Rat, 8 hours) : LD0= 0.07 mg/l; LD100= 0.30 mg/l

SECTION 11: Toxicological information**Irritation/Corrosion****Conclusion/Summary**

- Skin** : Corrosive to the skin.
- Eyes** : Highly corrosive.
- Respiratory** : May cause respiratory irritation.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
2,2'-iminodiethylamine	skin	Guinea pig	Sensitising

Conclusion/Summary

- Skin** : May cause skin sensitisation.
- Respiratory** : Non-sensitiser to lungs. Not classified for respiratory sensitisation.

Mutagenicity

- Conclusion/Summary** : Not mutagenic in a standard battery of genetic toxicological tests.

Carcinogenicity

- Conclusion/Summary** : Dermal No carcinogenic effect. Not classified as dangerous NOAEL = 56.3mg/kg bw/day
 Oral No data available for this end-point, hence this classification is not considered to be applicable.
 Inhalation No data available for this end-point, hence this classification is not considered to be applicable.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
2,2'-iminodiethylamine	-	Equivocal	Equivocal	Rat	Oral	90 days

- Conclusion/Summary** : Fertility NOAEL = 30mg/kg bw/day
 Developmental Toxicity: NOAEL = 30mg/kg bw/day
 Data inconclusive.
 Not fully tested.
 Not classified.
 Further studies (REACH Annex IX/ X) have been proposed

Teratogenicity

- Conclusion/Summary** : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-iminodiethylamine	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

- Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal.
 Routes of entry not anticipated: Inhalation.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

SECTION 11: Toxicological information

- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure**Short term exposure**

- Potential immediate effects** : No specific data.
- Potential delayed effects** : No specific data.

Long term exposure

- Potential immediate effects** : No specific data.
- Potential delayed effects** : No specific data.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	Chronic NOAEL Oral Chronic NOAEL Dermal Sub-chronic NOAEL Inhalation Vapour	Rat Rat Rat	70 mg/kg 114 mg/kg 550 mg/m ³	- - 6 hours

- Conclusion/Summary** : Cannot be classified.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Absorption** : Rapidly absorbed.
- Metabolism** : Slowly metabolised.
- Elimination** : Excreted via the faeces. Excreted via the urine.
- Other information** : No specific data.

SECTION 12: Ecological information**12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
2,2'-iminodiethylamine	EC50 32.7 mg/l	Micro-organism	3 hours
	NOEC 6 mg/l	Micro-organism	3 hours
	Acute EC50 1164 mg/l Fresh water	Algae	72 hours
	Acute EC50 32 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 430 mg/l Fresh water	Fish	96 hours
	Acute NOEC 10 mg/l Fresh water	Algae	72 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia	21 days
	Chronic NOEC 10 mg/l Fresh water	Fish	28 days

Conclusion/Summary : Not classified as dangerous
PNEC Intermittent release.= 0.32 mg/l

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,2'-iminodiethylamine	-	87 % - Readily - 21 days	-	-

Conclusion/Summary : Readily biodegradable. Toxic, not persistent. This substance is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-iminodiethylamine	Fresh water 28 days	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2,2'-iminodiethylamine	-1.58	0.3 to 6.3	low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : 19.111

Mobility : No specific data.

12.5 Results of PBT and vPvB assessment

PBT : No.

vPvB : No.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations






The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

SECTION 13: Disposal considerations

- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.
- Packaging**
- Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	UN2079	UN2079	UN2079	UN2079
14.2 UN proper shipping name	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	Diethylenetriamine
14.3 Transport hazard class(es)	8 	8 	8 	8 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	Yes.	No.	No.
Additional information	Hazard identification number 80 Limited quantity 1 L Tunnel code (E)	 The product is only regulated as an environmentally hazardous substance when transported in tank vessels.	Emergency schedules (EmS) F-A, S-B	Passenger and Cargo Aircraft Quantity limitation: 1 L Packaging instructions: 851 Cargo Aircraft Only Quantity limitation: 30 L Packaging instructions: 855 Limited Quantities - Passenger Aircraft Quantity limitation: 0.5 L Packaging instructions: Y840

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Diethylenetriamine, DETA

SECTION 14: Transport information

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern


None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Other EU regulations


Europe inventory : All components are listed or exempted.

Seveso II Directive

 This product is controlled under the Seveso II Directive.

Danger criteria

Category

 H2: Acute toxicity 2 any route of entry or Acute toxicity 3 Inhalation/Dermal route of entry
C1: Very toxic

15.2 Chemical Safety Assessment : Complete.

15.3 Registration status : Applicable.

SECTION 16: Other information

 Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EUH statement = CLP-specific Hazard statement
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RRN = REACH Registration Number
vPvB = Very Persistent and Very Bioaccumulative

Key literature references and sources for data : Regulation (EC) No. 1272/2008 [CLP]; European convention concerning international road transport of dangerous goods (ADR) done in Geneva on September 30, 1957 (Dz. U. no. 35/1975, pos. 189) plus amendments; Regulation for the transport of dangerous materials on the Rhine (ADN); Occupational exposure limits; International regulations

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

SECTION 16: Other information

Classification	Justification
Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335 (Respiratory tract irritation)	Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment

Full text of abbreviated H statements :

- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation. (Respiratory tract irritation)

Full text of classifications [CLP/GHS] :

- Acute Tox. 2, H330 ACUTE TOXICITY (inhalation) - Category 2
- Acute Tox. 4, H302 ACUTE TOXICITY (oral) - Category 4
- Acute Tox. 4, H312 ACUTE TOXICITY (dermal) - Category 4
- Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
- Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B
- Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1
- STOT SE 3, H335 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3

Full text of abbreviated R phrases :

- R26- Very toxic by inhalation.
- R21/22- Harmful in contact with skin and if swallowed.
- R34- Causes burns.
- R37- Irritating to respiratory system.
- R43- May cause sensitisation by skin contact.

Full text of classifications [DSD/DPD] :

- T+ - Very toxic
- C - Corrosive
- Xn - Harmful
- Xi - Irritant

Training advice : Ensure operatives are trained to minimise exposures. Training staff on good practice.

Date of issue/ Date of revision : 15/04/2014

Date of previous issue : 07/09/2012

Version : 9

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Consumer

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1: Title

Short title of the exposure scenario/List of use descriptors **Identified use name:** Consumer use as an epoxy and polyurethane curing agent
Sector of end use: SU21
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f
Market sector by type of chemical product: PC01
Specific Environmental Release Category: FEICA 11

Processes and activities covered by the exposure scenario Covers the use in consumer application of do-it-yourself glue

Assessment Method See Section 3

Section 2: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0:

Consumer use

Product characteristics: Physical form of product : Liquid.
Concentration of substance in mixture or article: Covers concentrations up to 35%
Amounts used: 10700 Tonnes/year
Fraction of EU tonnage used in region: 0.1
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day) Not available.
Maximum daily site tonnage (kg/day): Not available.
Frequency and duration of use: Continuous release.
Emission Days (days/year): 365

Environment factors not influenced by risk management:

Local freshwater dilution factor: 10 Default
Local marine water dilution factor: 100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): 0
Release fraction to soil from process (initial release prior to RMM): 0
Release fraction to wastewater from process (initial release prior to RMM): 9.00E-03

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment (%): 92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%): Not available.
Maximum allowable site tonnage (M_{safe}) based on release following total wastewater treatment removal (kg/d): Not available.
Assumed on-site sewage treatment plant flow (m^3/d): Not available.

Local release to soil: 0
Local release to air: 0
Local release to sewage: 5.30E-02
Fraction of substance in end-use products: Not applicable
Fraction of main source to local environment: 0.002

Diethylenetriamine, DETA

Identified use name: Consumer use as an epoxy and polyurethane curing agent

Sector of end use: SU21

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Market sector by type of chemical product: PC01

Section 2.2: Control of consumer exposure**Contributing scenario controlling consumer exposure for 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

Consumer use	
Product characteristics:	Physical form of product : Liquid.
Concentration of substance in mixture or article	Covers concentrations up to 35%
Physical state:	Liquid. Vapour pressure 20.3 Pa*s
Human factors not influenced by risk management:	None identified.
Conditions and measures related to information and behavioural advice to consumers	Covers use under typical household ventilation.
Contributing scenarios: Operational conditions and risk management measures	

Section 3: Exposure estimation and reference to its source**Section 3.1 Environment - Exposure estimation****Contributing scenario controlling environmental exposure for 0:**

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Regional PEC : 1.71E-03	Not applicable.
air (direct + STP)	Not applicable.	Regional PEC: 2.06E-05	Not applicable.
Soil (direct releases only)	Not applicable.	Regional PEC natural soil [Total]: 1.54E-03 Regional PEC industrial soil [Total]: 1.54E-03	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.00185; Surface water, Dissolved Annual average : 0.00185;	Not applicable.
Marine water mg/l	Not applicable.	Local/During emission/Dissolved: 0.00018; Annual average, Local/ Dissolved, 0.00018; Regional PEC [Total]: 1.66E-04	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	During emission :3.55; Regional PEC : 5.66E+00	Not applicable.
Marine water sediment mg/kg dwt	Not applicable.	During emission: 0.350; Regional PEC: 4.68E-01	Not applicable.
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.0434, 30 days; 0.0153, 180 days; Regional PEC: 4.43E-03	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.007, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Diethylenetriamine, DETA**Identified use name:** Consumer use as an epoxy and polyurethane curing agent**Sector of end use:** SU21**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC08c, ERC08f**Market sector by type of chemical product:** PC01

Section 3:2 Exposure estimation - Consumers**Exposure estimation and reference to its source - Consumers: 3: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

	Contributing Scenario:	Frequency (1/Year):	Weight fraction of substance in the article::	Body weight:	Calculation method:
Exposure estimation and reference to its source - Consumers: 1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Inhalation :

Mode of release: Not applicable.

Exposure estimation and reference to its source - Consumers: 2: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Exposure (minutes):	Application duration:	Amount/concentration applied (g):	Room volume (m³):	Room volume x ventilation rate: (l/h):	
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.	
Release area (cm2):	Temperature (°C):	Mass transfer rate:	Contributing Scenario Molecular weight (g/mole):	Uptake fraction (Update model):	Inhalation rate:
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

Dermal:

Application methods: Not applicable.

Surface area (Skin contact area) cm2:	Product amount (g):	Uptake fraction (Update model):	Inhalation event (mg/m³):
Not applicable.	Not applicable.	Not applicable.	Dermal : Not applicable , Inhalation :0.227 mg/m³
Inhalation mg/m³ (Concentration on day of exposure):	Dermal load (mg/cm2):	Dermal External dose (mg/kg bw):	Dermal (Internal dose) mg/kg bw/day:
Not applicable.	Not applicable.	Not applicable.	0.538
Dermal (External dose) mg/kg bw/day:	Inhalation event/Exposure mg/m³ (Short term exposure):	Dermal systemic exposure (external dose) with gloves (90% efficiency) mg/kg bw/day (Long term exposure):	Inhalation (mg/kg/day) Long term exposure:
Acute :0.538 mg/kg bw/day	0.227	0.0044 mg/kg bw/day	1.4E-5 mg/kg/day

Section 3:3 Exposure estimation- Consumers**Contributing scenario controlling consumer exposure for 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Not applicable.	0.0044	Not applicable.
Long term exposure, Systemic, Inhalable	Not applicable.	1.4E-5	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Systemic, Oral	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Not applicable.	0.538	Not applicable.
Short term exposure, Systemic, Inhalable		0.227	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Oral	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA**Identified use name:** Consumer use as an epoxy and polyurethane curing agent**Sector of end use:** SU21**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC08c, ERC08f**Market sector by type of chemical product:** PC01

Section 4:: Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional guidance	Not applicable.

Diethylenetriamine, DETA**Identified use name:** Consumer use as an epoxy and polyurethane curing agent**Sector of end use:** SU21**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC08c, ERC08f**Market sector by type of chemical product:** PC01

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02
Specific Environmental Release Category: FEICA 2

Processes and activities covered by the exposure scenario Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. also includes combined formulation/reaction to DETA-adducts

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Formulation of preparations*

Amounts used: 43000 Tonnes/year
Fraction of EU tonnage used in region: 1
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day): Not available.
Maximum daily site tonnage (kg/day): 30000
Frequency and duration of use: Continuous release.
Emission Days (days/year): 220

Environment factors not influenced by risk management:

Local freshwater dilution factor: 10
Local marine water dilution factor: 100

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): 6.00E-03
Release fraction to soil from process (initial release prior to RMM): 0.00E+00
Release fraction to wastewater from process (initial release prior to RMM): 0.00E+00
Release fraction to air from wide dispersive use (regional only): Not available.
Release fraction to soil from wide dispersive use (regional only): Not available.
Release fraction to wastewater from wide dispersive use: Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%): Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%): Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%): Not available.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment (%): 92.6%

Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%): 92.6%

Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/d): 7987900 kg/day

Conditions and measures related to external recovery of waste: Dispose of waste product or used containers according to local regulations.

Local release to soil, kg/day: 0

Local release to air, kg/day: 1.80E+02

Local release to sewage, kg/day: 0

Fraction of main source to local environment: 0.15

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics: Volatility: low

Concentration of substance in product: Covers percentage substance in the product up to 100%

Physical state: Liquid.

Amounts used: Not applicable.

Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management: None identified.

Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Continuous process Mixing operations (closed systems) no sampling: No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics: Volatility: low

Concentration of substance in product: Covers percentage substance in the product up to 100%

Physical state: Liquid.

Amounts used: Not applicable.

Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management: None identified.

Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Continuous process Mixing operations (closed systems) with sample collection: No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Product characteristics: Volatility: low

Concentration of substance in product: Covers percentage substance in the product up to 100%

Physical state: Liquid.

Amounts used: Not applicable.

Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management: None identified.

Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

Substance supplied to that use in form of: As such

Sector of end use: SU03

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC02

Contributing scenarios: Operational conditions and risk management measures

Use in contained batch processes Mixing operations (closed systems) with sample collection: No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Batch process Mixing operations (open systems) with sample collection: Provide extract ventilation to points where emissions occur.

Respiratory protection: None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Mixing operations (open systems): Provide extract ventilation to points where emissions occur. Wear suitable gloves tested to EN374.

Respiratory protection: None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Bulk transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Drum and small package filling Dedicated facility: Ensure operation is undertaken outdoors. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Drum and small package filling Dedicated facility with local exhaust ventilation: Ensure material transfers are under containment or extract ventilation.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 8: Use as laboratory reagent

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection:

None.

Section 3:: Exposure estimation

Section 3:1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Formulation of preparations*

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.2	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.314	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.804, 30 days; 0.269, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.119, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0301	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Short term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	6.86; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	2.15; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	2.15; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	1.37; 6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	9.03; 2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 8: Use as laboratory reagent

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Processes and activities covered by the exposure scenario Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Manufacture of substances

Amounts used:

Fraction of EU tonnage used in region: Not available.
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day): Not available.
Maximum daily site tonnage (kg/day): Not available.

Frequency and duration of use: Continuous release.
Emission Days (days/year): 300

Environment factors not influenced by risk management:

Local freshwater dilution factor: 4462
Local marine water dilution factor: Not available.

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): Not available.
Release fraction to soil from process (initial release prior to RMM): Not available.
Release fraction to wastewater from process (initial release prior to RMM): Not available.
Release fraction to air from wide dispersive use (regional only): Not available.
Release fraction to soil from wide dispersive use (regional only): Not available.
Release fraction to wastewater from wide dispersive use: Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%) Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%) Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%) Not available.

Conditions and measures related to municipal sewage treatment plant: Sewage sludge incineration

Estimated substance removal from wastewater via on-site sewage treatment (%) 60%

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	60%
Conditions and measures related to external treatment of waste for disposal:	Store finished products in closed containers (e.g., bulk tanks, drums, cans) Incinerate, absorb, or adsorb vapours stripped from solution whenever necessary
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Fraction of substance in end-use products:	1
Fraction of main source to local environment:	1

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process with sample collection (closed systems): No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Use as laboratory reagent

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection: None.

Section 3:: Exposure estimation

Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Manufacture of substances

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.537; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): Not applicable; Annual average, Dissolved, Resulting PEC local, water (mg/l): Not applicable	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	1028.3	During emission
Marine water sediment mg/kg dwt	Not applicable.	Not applicable	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.002; 30, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.002, 180 days	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	2.65E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.019	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 6: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC01

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: *Manufacture of substance - Industrial*
Process Category: *PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15*
Substance supplied to that use in form of: *As such*
Sector of end use: *SU03*
Subsequent service life relevant for that use: *No.*
Environmental Release Category: *ERC01*

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d
Specific Environmental Release Category: FEICA 7

Processes and activities covered by the exposure scenario Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

Amounts used: 10700 Tonnes/year
Fraction of EU tonnage used in region: 1
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day): Not available.
Maximum daily site tonnage (kg/day): 800
Frequency and duration of use: Continuous release.
Emission Days (days/year): 220

Environment factors not influenced by risk management:

Local freshwater dilution factor: 10 Default
Local marine water dilution factor: 100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): 1.70E-02
Release fraction to soil from process (initial release prior to RMM): 0.00E+00
Release fraction to wastewater from process (initial release prior to RMM): 0.00E+00
Release fraction to air from wide dispersive use (regional only): Not available.
Release fraction to soil from wide dispersive use (regional only): Not available.
Release fraction to wastewater from wide dispersive use: Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%): Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%): Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%): Not available.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800

Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environment factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Fraction of main source to local environment:

0.016

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Article formation in mould Batch process (closed systems) Machine Manual: No other specific measures identified.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

Substance supplied to that use in form of: As such
Sector of end use: SU03

Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours.

Article formation in mould Foaming (open systems) Machine Manual: No other specific measures identified.

Film formation - air drying (open systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 5: Industrial spraying****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

Respiratory protection:

None.

Diethylenetriamine, DETA**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of:** As such**Sector of end use:** SU03**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC06c, ERC06d

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Product characteristics:

Concentration of substance in product:

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Non-dedicated facility: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics:

Concentration of substance in product:

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 8: Roller application or brushing

Product characteristics:

Concentration of substance in product:

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Roller, spreader, flow application: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

Substance supplied to that use in form of: As such

Sector of end use: SU03

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Dipping, immersion and pouring: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 10: Use as laboratory reagent****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

Section 3:: Exposure estimation**Section 3.1 Environment - Exposure estimation****Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics**

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dw	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production -
Industrial

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

Substance supplied to that use in form of: As such

Sector of end use: SU03

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC06c, ERC06d

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PEC _{stp}) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	0.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	2.58	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	6.86; Not applicable; 6.86; 6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	2.58; 0.60; 4.30; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	2.58; 0.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 5: Industrial spraying

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	4.30; 0.20	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 8: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 10: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

Substance supplied to that use in form of: As such

Sector of end use: SU03

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC06c, ERC06d

Short term exposure, Local,
Inhalable

Not applicable.

Not applicable.

Not applicable.

Section 4:: Guidance to check compliance with the exposure scenario

Environment

Not available.

Health

Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment

Not applicable.

Health

Not applicable.

Additional Good Practices

Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production -
Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors	<p>Identified use name: Use as a PU curing agent for rigid foam production - Professional</p> <p>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19</p> <p>Substance supplied to that use in form of: As such</p> <p>Sector of end use: SU02a, SU02b</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08c, ERC08f</p> <p>Specific Environmental Release Category: FEICA 10</p>
--	--

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365

Environment factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	0
Release fraction to soil from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365

Environment factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	0
Release fraction to soil from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M_{Safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Fraction of main source to local environment:

0.002

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors.

Film formation - air drying: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers: Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics:

Concentration of substance in product:

Volatility: low

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 7: Roller application or brushing

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 8: Non industrial spraying

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Foaming Manual: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 10: Use as laboratory reagent****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production -
Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA	<p>Identified use name: Use as a PU curing agent for rigid foam production - Professional</p> <p>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19</p> <p>Substance supplied to that use in form of: As such</p> <p>Sector of end use: SU02a, SU02b</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08c, ERC08f</p>
---------------------------------	--

Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	2.58	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.86; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.02; 0.70; 8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA		Identified use name: Use as a PU curing agent for rigid foam production - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f	

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	6.02; 0.70	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	1.37; 2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	12.90; 9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3:.2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:.2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 7: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:.2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 8: Non industrial spraying**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	5.36; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	6.02; 0.28	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Foaming Manual	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 10: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3:2 Workers - Exposure estimation**Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	3.01; 0.14	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional

Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

Substance supplied to that use in form of: As such

Sector of end use: SU02a, SU02b

Subsequent service life relevant for that use: No.

Environmental Release Category: ERC08c, ERC08f

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors
Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d
Specific Environmental Release Category: FEICA 7

Processes and activities covered by the exposure scenario Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

Amounts used: 10700 Tonnes/year
Fraction of EU tonnage used in region: 1
Regional use tonnage (tonnes/year): Not available.
Fraction of Regional tonnage used locally: Not available.
Annual site tonnage (tonnes/year): Not available.
Average Local Daily Tonnage (kg/day): Not available.
Maximum daily site tonnage (kg/day): 800
Frequency and duration of use: Continuous release.
Emission Days (days/year): 220

Environment factors not influenced by risk management:

Local freshwater dilution factor: 10 Default
Local marine water dilution factor: 100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): 1.70E-02
Release fraction to soil from process (initial release prior to RMM): 0.00E+00
Release fraction to wastewater from process (initial release prior to RMM): 0.00E+00
Release fraction to air from wide dispersive use (regional only): Not available.
Release fraction to soil from wide dispersive use (regional only): Not available.
Release fraction to wastewater from wide dispersive use: Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%): Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%): Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%): Not available.

Conditions and measures related to municipal sewage treatment plant:

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220

Environment factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Injection moulding of articles (closed systems): No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Film formation - air drying (open systems): Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 5: Industrial spraying****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other given operational conditions affecting workers exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other given operational conditions affecting workers exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 8: Roller application or brushing****Product characteristics:****Concentration of substance in product:****Physical state:****Amounts used:****Frequency and duration of use:****Human factors not influenced by risk management:****Other given operational conditions affecting workers exposure:**

Volatility: low

Covers concentrations up to 50%

Liquid.

Not applicable.

Covers daily exposures up to 8 hours (unless stated differently).

None identified.

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 10: Use as laboratory reagent

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Respiratory protection:

None.

Section 3:: Exposure estimation

Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dw	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	0.02	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	6.45	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	0.69; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	1.07; 0.25; 10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	0.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	1.07; 0.25	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 5: Industrial spraying			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	10.75; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA <div> Identified use name: Use as an epoxy curing agent - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d </div>			

Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 8: Roller application or brushing			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Diethylenetriamine, DETA <div> Identified use name: Use as an epoxy curing agent - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 Substance supplied to that use in form of: As such Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC06c, ERC06d </div>			

Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 10: Use as laboratory reagent

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	7.52	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06c, ERC06d

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors	<p>Identified use name: Use as an epoxy curing agent - Professional</p> <p>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19</p> <p>Substance supplied to that use in form of: As such</p> <p>Sector of end use: SU02a, SU02b</p> <p>Subsequent service life relevant for that use: No.</p> <p>Environmental Release Category: ERC08c, ERC08f</p> <p>Specific Environmental Release Category: FEICA 10</p>
--	--

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365

Environment factors not influenced by risk management:

Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM):	0.00E+00
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.

Conditions and measures related to municipal sewage treatment plant:

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	Not available.
Fraction of Regional tonnage used locally:	Not available.
Annual site tonnage (tonnes/year):	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage (kg/day):	5.8
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	365
Environment factors not influenced by risk management:	
Local freshwater dilution factor:	10 Default
Local marine water dilution factor:	100 Default
Other given operational conditions affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	0.00E+00
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Release fraction to air from wide dispersive use (regional only):	Not available.
Release fraction to soil from wide dispersive use (regional only):	Not available.
Release fraction to wastewater from wide dispersive use:	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of (%):	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%):	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%):	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems) with sample collection: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour.

Film formation - air drying: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics:

Concentration of substance in product:

Volatility: low

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 7: Roller application or brushing

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Respiratory protection:

None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 8: Non industrial spraying

Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 10: Use as laboratory reagent****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

Section 2.2: Control of worker exposure**Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available****Product characteristics:**

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Wear a respirator conforming to EN140 with Type A filter or better. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dw	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dw	Not applicable.	3.678	During emission
Marine water sediment mg/kg dw	Not applicable.	0.374	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dw	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3:.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dw	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,
 PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.02	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:.2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	4.51	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:.2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	6.86; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	4.30; 0.50; 12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA <div> Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f </div>			

Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	4.30; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	5.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Diethylenetriamine, DETA			
Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f			

Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:.2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:.2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 7: Roller application or brushing			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	5.49	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	3.76	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:.2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 8: Non industrial spraying			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	0.11; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	15.05; 0.70	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA			
Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f			

Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 10: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	5.37; 0.25	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Diethylenetriamine, DETA			
Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 Substance supplied to that use in form of: As such Sector of end use: SU02a, SU02b Subsequent service life relevant for that use: No. Environmental Release Category: ERC08c, ERC08f			

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19
Substance supplied to that use in form of: As such
Sector of end use: SU02a, SU02b
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC08c, ERC08f

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition Mono-constituent substance
Product name Diethylenetriamine, DETA

Section 1:: Title

Short title of the exposure scenario/List of use descriptors **Identified use name:** Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a
Specific Environmental Release Category: ESVOC 2

Processes and activities covered by the exposure scenario Use of substance as an intermediate (not related to Strictly Controlled Conditions).
Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

Section 2:: Operational conditions and risk management measures

Section 2.1: Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)

Amounts used: 43000 Tonnes/year

Fraction of EU tonnage used in region: 1

Regional use tonnage (tonnes/year): Not available.

Fraction of Regional tonnage used locally: Not available.

Annual site tonnage (tonnes/year): Not available.

Average Local Daily Tonnage (kg/day): Not available.

Maximum daily site tonnage (kg/day): 14333

Frequency and duration of use: Continuous release.

Emission Days (days/year): 300

Environment factors not influenced by risk management:

Local freshwater dilution factor: 10 Default

Local marine water dilution factor: 100 Default

Other given operational conditions affecting environmental exposure:

Release fraction to air from process (initial release prior to RMM): 2.00E-05

Release fraction to soil from process (initial release prior to RMM): 1.00E-003

Release fraction to wastewater from process (initial release prior to RMM): 1.00E-02

Release fraction to air from wide dispersive use (regional only): Not available.

Release fraction to soil from wide dispersive use (regional only): Not available.

Release fraction to wastewater from wide dispersive use: Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Treat air emission to provide a typical removal efficiency of (%): Not applicable.

Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of ³ (%): Not available.

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of ³ (%): Not available.

Conditions and measures related to municipal sewage treatment plant:

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Estimated substance removal from wastewater via on-site sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M _{Safe}) based on release following total wastewater treatment removal (kg/d):	15640 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	14.3
Local release to air, kg/day:	2.86E-01
Local release to sewage, kg/day:	143.3
Fraction of main source to local environment:	0.1

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
General exposures Continuous process (closed systems):	No other specific measures identified.
Bulk product storage (closed systems):	No other specific measures identified.
Respiratory protection:	None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
General exposures Continuous process with sample collection (closed systems):	No other specific measures identified.
Respiratory protection:	None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Product characteristics: Volatility: low
Concentration of substance in product: Covers percentage substance in the product up to 100%
Physical state: Liquid.
Amounts used: Not applicable.
Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management: None identified.
Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented.
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Respiratory protection: None.

Section 2.2: Control of worker exposure

Contributing scenario controlling worker exposure for 6: Use as laboratory reagent

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

Respiratory protection: None.

Section 3:: Exposure estimation

Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.513; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.051; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.042	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	982.6	During emission
Marine water sediment mg/kg dwt	Not applicable.	98.23	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	114.1, 30 days; 37.5, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	15.0, 180 days	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,
 PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m ³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m ³	Not applicable.	8.6E-05	Not applicable.
Annual deposition mg/m ² /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	5.262	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Section 3:2 Workers - Exposure estimation

Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3:2 Workers - Exposure estimation			
Contributing scenario controlling worker exposure for 6: Use as laboratory reagent			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a

Section 4:: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional Good Practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,
PROC08b, PROC15
Substance supplied to that use in form of: As such
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC06a