

# SAFETY DATA SHEET



Diethylenetriamine, DETA

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Diethylenetriamine, DETA**Index number** : 612-058-00-X**EC number** : 203-865-4**REACH Registration number**

Registration number	Legal entity
01-2119473793-27-0001	Delamine BV

**CAS number** : 111-40-0**Product description** : Not applicable**Product type** : Liquid.

**Other means of identification** : DIETHYLENETRIAMINE; 2,2'-iminodi(ethylamine); diethylene triamine; 1,2-Ethanediamine, N1-(2-aminoethyl)-; Diethylenetriamine (DETA); Diethylenetriamine-1,2-Ethanediamine, N-(2-aminoethyl)-; 1,2-Ethanediamine, N-(2-aminoethyl)-; 2,2'-Diaminodiethylamine; 1,4,7-Tri-(aza)-heptane; N-(2-Aminoethyl)-1,2-ethanediamine

**Chemical formula** : C<sub>4</sub>-H<sub>13</sub>-N<sub>3</sub>

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Intermediate.**Area of application** : Industrial applications.

Identified uses
Consumer use as an epoxy and polyurethane curing agent Formulation and (re)packing of substances and mixtures - Industrial Manufacture of substance - Industrial Use as a PU curing agent for rigid foam production - Industrial Use as a PU curing agent for rigid foam production - Professional Use as an epoxy curing agent - Industrial Use as an epoxy curing agent - Professional Use as an intermediate - Industrial

### 1.3 Details of the supplier of the safety data sheet

DELAMINE B.V.  
 Barchman Wuytierslaan 10  
 3818 LH Amersfoort  
 The Netherlands  
 Tel.: 31-334676897

**e-mail address of person responsible for this SDS** : SDS.Delamine@delamine.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : AkzoNobel Chemicals-Deventer-NLT +31 570 679211 (24hours/7days)  
 F +31 570 679801

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mono-constituent substance

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302  
Acute Tox. 3, H311  
Acute Tox. 2, H330  
Skin Corr. 1B, H314  
Eye Dam. 1, H318  
Skin Sens. 1, H317  
STOT SE 3, H335i

#### Classification according to Directive 67/548/EEC [DSD]

T+; R26  
T; R24  
Xn; R22  
C; R34  
R43

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Fatal if inhaled.  
Toxic in contact with skin.  
Harmful if swallowed.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

#### Precautionary statements

**Prevention** : Wear protective gloves: >8 hours (breakthrough time): neoprene. Wear eye or face protection. Do not breathe vapour.

**Response** : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Immediately call a POISON CENTER or physician. IF IN EYES: Immediately call a POISON CENTER or physician.

**Storage** : Store locked up.

**Disposal** : Not applicable.

**Supplemental label elements** : Not applicable.

### 2.3 Other hazards

**Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII** : No.

**Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : No.

Diethylenetriamine, DETA

**SECTION 2: Hazards identification**

Other hazards which do : Not applicable.  
not result in classification

**SECTION 3: Composition/information on ingredients**

Substance/mixture : Mono-constituent substance

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
2,2'-iminodiethylamine	REACH #: 01-2119473793-27 EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	100	T+; R26  T; R24 Xn; R22 C; R34 R43  <b>See section 16 for the full text of the R-phrases declared above</b>	Acute Tox. 4, H302  Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335i  <b>See Section 16 for the full text of the H statements declared above.</b>	[A]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

Type

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If

## SECTION 4: First aid measures

unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye damage.

**Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

**Skin contact** : Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.

**Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness

**Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing

**Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. Dry sand or other suitable absorbent. Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Halones

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides

### 5.3 Advice for firefighters

## SECTION 5: Firefighting measures

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Diethylenetriamine, DETA****SECTION 7: Handling and storage****Advice on general occupational hygiene**

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**7.2 Conditions for safe storage, including any incompatibilities**

: Do not store above the following temperature: 40°C (104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

**7.3 Specific end use(s)****Recommendations**

: No specific data.

**Industrial sector specific solutions**

: No specific data.

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**8.1 Control parameters****Occupational exposure limits**

Product/ingredient name	Exposure limit values
2,2'-iminodiethylamine	<b>EH40/2005 WELs (United Kingdom (UK), 8/2007). Absorbed through skin.</b> TWA: 4.3 mg/m <sup>3</sup> 8 hour(s). TWA: 1 ppm 8 hour(s).

**Recommended monitoring procedures**

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances.

**Derived effect levels**

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,2'-iminodiethylamine	DNEL	Short term Inhalation	92.1 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	2.6 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Dermal	11.4 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	15.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1.1 mg/cm <sup>2</sup>	Workers	Local
	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	27.5 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	4.6 mg/m <sup>3</sup>	Consumers	Systemic



**SECTION 8: Exposure controls/personal protection****Predicted effect concentrations**

Product/ingredient name	Type	Compartment Detail	Value	Method Detail
2,2'-iminodiethylamine	PNEC	Fresh water	0.56 mg/l	Assessment Factors
	PNEC	Marine	0.056 mg/l	Assessment Factors
	PNEC	Fresh water sediment	1072 mg/kg dwt	-
	PNEC	Marine water sediment	107.2 mg/kg dwt	-
	PNEC	Soil	214 mg/kg dwt	-
	PNEC	Sewage Treatment Plant	6 mg/l	Assessment Factors

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. >8 hours (breakthrough time): neoprene

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: neoprene Boots.

**Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: ammonia filter (Type K) ammonia (Type K) and particulate filter

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

**Physical state** : Liquid. [Viscous liquid.]

**Colour** : Colourless. Yellow.

**Odour** : Ammoniacal.

**Odour threshold** : Not available.

**pH** : 11.6 [Conc. (% w/w): 1%]

**Melting point/freezing point** : -39°C

**Initial boiling point and boiling range** : 207°C

**Diethylenetriamine, DETA****SECTION 9: Physical and chemical properties**

<b>Flash point</b>	: Closed cup: 96.7°C
<b>Evaporation rate</b>	: Not available.
<b>Flammability (solid, gas)</b>	: Not applicable
<b>Burning time</b>	: Not applicable.
<b>Burning rate</b>	: Not applicable.
<b>Upper/lower flammability or explosive limits</b>	: Not available.
<b>Vapour pressure</b>	: 0.021 kPa [20°C]
<b>Vapour density</b>	: 3.56 [Air = 1]
<b>Relative density</b>	: 0.9586
<b>Solubility(ies)</b>	: Miscible in water.
<b>Partition coefficient: n-octanol/water</b>	: -1.58
<b>Auto-ignition temperature</b>	: 358°C
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Dynamic: 5.05 mPa·s
<b>Explosive properties</b>	: Not applicable.
<b>Oxidising properties</b>	: None.

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: The product is stable.
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: Keep away from sources of ignition - No smoking. aerosol or mist formation
<b>10.5 Incompatible materials</b>	: Reactive or incompatible with the following materials: oxidizing materials, metals and acids. Chlorinated hydrocarbon.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	LD50 Dermal	Rabbit	707 mg/kg	-
	LD50 Oral	Rat	1620 mg/kg	-

**Conclusion/Summary** : No additional information.**Irritation/Corrosion****Conclusion/Summary**



**Diethylenetriamine, DETA****SECTION 11: Toxicological information**

- Skin** : Corrosive to the skin.
- Eyes** : Highly corrosive.
- Respiratory** : May cause respiratory irritation.

**Sensitiser**

Product/ingredient name	Route of exposure	Species	Result
2,2'-iminodiethylamine	skin	Guinea pig	Sensitising

**Conclusion/Summary**

- Skin** : May cause skin sensitisation.
- Respiratory** : Non-sensitiser to lungs. Not classified for respiratory sensitisation.

**Mutagenicity**

- Conclusion/Summary** : Not mutagenic in a standard battery of genetic toxicological tests.

**Carcinogenicity**

- Conclusion/Summary** : Dermal No carcinogenic effect. Not classified as dangerous NOAEL = 56.3mg/kg bw/day  
Oral No data available for this end-point, hence this classification is not considered to be applicable.  
Inhalation No data available for this end-point, hence this classification is not considered to be applicable.

**Reproductive toxicity**

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
2,2'-iminodiethylamine	-	Equivocal	Equivocal	Rat	Oral	90 days

- Conclusion/Summary** : Fertility NOAEL = 30mg/kg bw/day  
Developmental Toxicity: NOAEL = 30mg/kg bw/day  
Data inconclusive.  
Not fully tested.  
Not classified.  
Further studies (REACH Annex IX/ X) have been proposed

**Teratogenicity**

- Conclusion/Summary** : No known significant effects or critical hazards.

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-iminodiethylamine	Category 3	Inhalation	Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Not available.

- Information on the likely routes of exposure** : Routes of entry anticipated:Oral, Dermal.  
Routes of entry not anticipated:Inhalation.

**Potential acute health effects**

- Inhalation** : Fatal if inhaled. May cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Ingestion** : Harmful if swallowed. May cause burns to mouth, throat and stomach.
- Skin contact** : Causes severe burns. Toxic in contact with skin. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye damage.

**Symptoms related to the physical, chemical and toxicological characteristics**

**Diethylenetriamine, DETA****SECTION 11: Toxicological information**

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Ingestion** : Adverse symptoms may include the following:  
stomach pains
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness

**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure**

**Potential immediate effects** : No specific data.

**Potential delayed effects** : No specific data.

**Long term exposure**

**Potential immediate effects** : No specific data.

**Potential delayed effects** : No specific data.

**Potential chronic health effects**

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	Chronic NOAEL Oral Chronic NOAEL Dermal Sub-chronic NOAEL Inhalation Vapour	Rat Rat Rat	70 mg/kg 114 mg/kg 550 mg/m <sup>3</sup>	- - 6 hours

- Conclusion/Summary** : Cannot be classified.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.
- Absorption** : Rapidly absorbed.
- Metabolism** : Slowly metabolised.
- Elimination** : Excreted via the faeces. Excreted via the urine.
- Other information** : No specific data.

**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
2,2'-iminodiethylamine	EC50 32.7 mg/l NOEC 6 mg/l Acute EC50 1164 mg/l Fresh water Acute EC50 32 mg/l Fresh water Acute LC50 430 mg/l Fresh water Chronic NOEC 5.6 mg/l Fresh water Chronic NOEC 10 mg/l Fresh water	Micro-organism Micro-organism Algae Daphnia Fish Daphnia Fish	3 hours 3 hours 72 hours 48 hours 96 hours 21 days 28 days

- Conclusion/Summary** : Not classified as dangerous  
PNEC Intermittent release.= 0.32 mg/l

**Diethylenetriamine, DETA****SECTION 12: Ecological information****12.2 Persistence and degradability**

Product/ingredient name	Test	Result	Dose	Inoculum
2,2'-iminodiethylamine	-	87 % - Readily - 21 days	-	-

**Conclusion/Summary** : Readily biodegradable Toxic, not persistent. This substance is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-iminodiethylamine	Fresh water 28 days	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2,2'-iminodiethylamine	-1.58	0.3 to 6.3	low

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : 19.111

**Mobility** : No specific data.

**12.5 Results of PBT and vPvB assessment**

**PBT** : No.

**vPvB** : No.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.





**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN/ADNR	IMDG	IATA
14.1 UN number	UN2079	UN2079	UN2079	UN2079
14.2 UN proper shipping name	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	Diethylenetriamine
14.3 Transport hazard class(es)	8 	8 	8 	8 
14.4 Packing group	II	II	II	II
14.5 Environmental hazards	No.	No.	No.	No.
14.6 Special precautions for user	Not available.	Not available.	Not available.	Not available.
Additional information	<b>Hazard identification number</b> 80  <b>Limited quantity</b> 1 L  <b>Tunnel code</b> (E)	-	<b>Emergency schedules (EmS)</b> F-A, S-B	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 1 L Packaging instructions: 851 <b>Cargo Aircraft Only</b> Quantity limitation: 30 L Packaging instructions: 855 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 0.5 L Packaging instructions: Y840

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

## SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

Other EU regulations

**Europe inventory** : This material is listed or exempted.

**Diethylenetriamine, DETA**

## SECTION 15: Regulatory information

**Black List Chemicals** : Not listed  
**Priority List Chemicals** : Not listed  
**Integrated pollution prevention and control list (IPPC) - Air** : Not listed  
**Integrated pollution prevention and control list (IPPC) - Water** : Not listed

### International regulations

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed  
**Chemical Weapons Convention List Schedule II Chemicals** : Not listed  
**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

**15.2 Chemical Safety Assessment** : Complete.

**15.3 Registration status** : Applicable.

## SECTION 16: Other information

🔍 Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335i	Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment Expert judgment

**Full text of abbreviated H statements** : H302 Harmful if swallowed.  
 H311 Toxic in contact with skin.  
 H314 Causes severe skin burns and eye damage.  
 H317 May cause an allergic skin reaction.  
 H318 Causes serious eye damage.  
 H330 Fatal if inhaled.  
 H335i May cause respiratory irritation.

**Full text of classifications [CLP/GHS]** : Acute Tox. 2, H330 ACUTE TOXICITY: INHALATION - Category 2  
 Acute Tox. 3, H311 ACUTE TOXICITY: SKIN - Category 3  
 Acute Tox. 4, H302 ACUTE TOXICITY: ORAL - Category 4  
 Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
 Skin Corr. 1B, H314 SKIN CORROSION/IRRITATION - Category 1B  
 Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1  
 STOT SE 3, H335i SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE): INHALATION [Respiratory tract irritation] -

**SECTION 16: Other information**

Category 3

**Full text of abbreviated R phrases** : R26- Very toxic by inhalation.  
R24- Toxic in contact with skin.  
R22- Harmful if swallowed.  
R34- Causes burns.  
R43- May cause sensitisation by skin contact.

**Full text of classifications [DSD/DPD]** : T+ - Very toxic  
T - Toxic  
C - Corrosive  
Xn - Harmful

**Date of issue/ Date of revision** : 25 February 2011

**Date of previous issue** : 02/12/2010

**Version** : 5

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



## Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

## Section 1: Title

Short title of the exposure scenario	<b>Identified use name:</b> Consumer use as an epoxy and polyurethane curing agent <b>Sector of end use:</b> SU21 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f <b>Market sector by type of chemical product:</b> PC01
--------------------------------------	--

List of use descriptors	<b>Identified use name:</b> Consumer use as an epoxy and polyurethane curing agent <b>Sector of end use:</b> SU21 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f <b>Market sector by type of chemical product:</b> PC01 <b>Specific Environmental Release Category:</b> FEICA 11
-------------------------	--

**Processes and activities covered by the exposure scenario** Covers the use in consumer application of do-it-yourself glue

**Assessment Method** See Section 3

## Section 2: Operational conditions and risk management measures

## Section 2.1: Control of consumer exposure

Concentration of substance in mixture or article	Covers concentrations up to 35%
Physical state:	Liquid. Vapour pressure 20.3 Pa*s
Human factors not influenced by risk management:	None identified.
Conditions and measures related to information and behavioural advice to consumers	Covers use under typical household ventilation.
Contributing scenarios: Operational conditions and risk management measures	

## Section 2.2: Control of environmental exposure

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	0.1
Frequency and duration of use:	Continuous release.
Local release to soil:	0
Local release to air:	0
Local release to sewage:	5.30E-02

## Section 3: Exposure estimation and reference to its source

## Section 3.1: Exposure estimation - Consumers

Contributing Scenario:	Frequency (1/Year):	Weight fraction of substance in the article::	Body weight:	Calculation method:
Exposure estimation and reference to its source - Consumers: 0: Inhalation : Mode of release: Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.
Exposure estimation and reference to its source - Consumers: 1:				
Exposure (minutes):	Application duration:	Amount/concentration applied (g):	Room volume (m³):	Room volume x ventilation rate: (l/h):
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.
Release area (cm²):	Temperature (°C):	Mass transfer rate:	Contributing Scenario Molecular weight (g/mole):	Uptake fraction (Update model): Inhalation rate:

Diethylenetriamine, DETA

**Identified use name:** Consumer use as an epoxy and polyurethane curing agent  
**Sector of end use:** SU21  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f  
**Market sector by type of chemical product:** PC01

Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.
<b>Dermal:</b>					
<b>Application methods:</b> Not applicable.					
<b>Surface area (Skin contact area) cm2:</b>	<b>Product amount (g):</b>	<b>Uptake fraction (Update model):</b>	<b>Inhalation event (mg/m³):</b>		
Not applicable.	Not applicable.	Not applicable.	Not applicable.		
<b>Inhalation mg/m³ (Concentration on day of exposure):</b>	<b>Dermal load (mg/cm2):</b>	<b>Dermal External dose (mg/kg bw):</b>	<b>Dermal (Internal dose) mg/kg bw/day:</b>		
Not applicable.	Not applicable.	Not applicable.	Not applicable.		
<b>Dermal (External dose) mg/kg bw/day:</b>	<b>Inhalation event/Exposure mg/m³ (Short term exposure):</b>	<b>Dermal systemic exposure (external dose) with gloves (90% efficiency) mg/kg bw/day (Long term exposure):</b>	<b>Inhalation (mg/kg/day) Long term exposure:</b>		
Not applicable.	Not applicable.	Not applicable.	Not applicable.		

<b>Section 3.2 Exposure estimation-Consumers</b>			
<b>Contributing exposure scenario controlling worker exposure for 0:</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Systemic, Oral</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>		Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Oral</b>	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.3 Environment Exposure estimation</b>			
<b>Contributing exposure scenario controlling environmental exposure for 1:</b>			
	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Regional PEC Total: 1.71E-03	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Regional PEC: 2.06E-05	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Regional PEC natural soil Total: 1.54E-03 Regional PEC industrial soil Total: 1.54E-03	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PECstp) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.00185; Surface water, Dissolved Annual average : 0.00185;	Not applicable.

<b>Diethylenetriamine, DETA</b>	<b>Identified use name: Consumer use as an epoxy and polyurethane curing agent</b> <b>Sector of end use: SU21</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC08c, ERC08f</b> <b>Market sector by type of chemical product: PC01</b>
---------------------------------	--

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.00018; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.00018; Regional PEC Total: 1.66E-04	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	During emission :3.55; Regional PEC Total: 5.66E+00	Not applicable.
Marine water sediment mg/kg dwt	Not applicable.	During emission: 0.350; Regional PEC: 4.68E-01	Not applicable.
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.0434, 30 days; 0.0153, 180 days; Regional PEC Total: 4.43E-03	
Grassland averaged mg/kg dwt	Not applicable.	0.007, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06-05	Not applicable.
Annual deposition mg/m2/d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

#### Section 4: Guidance to Downstream User to evaluate if he works inside the boundaries set by the ES

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional guidance	Not applicable.

## Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

## Section 1: Title

**Short title of the exposure scenario** **Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

**List of use descriptors** **Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02  
**Specific Environmental Release Category:** FEICA 2

**Processes and activities covered by the exposure scenario** Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. also includes combined formulation/reaction to DETA-adducts

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
 Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Continuous process Mixing operations (closed systems) no sampling: No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

**Respiratory protection:** None.

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
 Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

Continuous process Mixing operations (closed systems) with sample collection: No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Use in contained batch processes Mixing operations (closed systems) with sample collection: No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Batch process Mixing operations (open systems) with sample collection: Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Mixing operations (open systems): Provide extract ventilation to points where emissions occur. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Bulk transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Drum and small package filling Dedicated facility: Ensure operation is undertaken outdoors. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Drum and small package filling Dedicated facility with local exhaust ventilation: Ensure material transfers are under containment or extract ventilation.

**Respiratory protection:**

None.



**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 8: Use as laboratory reagent****Product Characteristics:****Concentration of substance in product:**

Volatility: low

**Physical state:**

Covers percentage substance in the product up to 100%

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:**

None.

**Section 2.2: Control of environmental exposure****Contributing exposure scenario controlling environmental exposure for 0: Formulation of preparations\*****Product Characteristics:****Concentration of substance in mixture or article:****Amounts used:**

43000 Tonnes/year

**Fraction of EU tonnage used in region:**

1

**Maximum daily site tonnage (kg/day):**

30000

**Frequency and duration of use:**

Continuous release.

**Emission Days (days/year):**

220

**Environmental factors not influenced by risk management:****Local marine water dilution factor:**

100

**Other operational conditions of use affecting environmental exposure:****Release fraction to air from process (initial release prior to RMM):** 6.00E-03**Release fraction to soil from process (initial release prior to RMM):** 0.00E+00**Release fraction to wastewater from process (initial release prior to RMM):** 0.00E+00**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:****Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):** Not applicable.**Conditions and measures related to municipal sewage treatment plant:****Estimated substance removal from wastewater via domestic sewage treatment (%):** 92.6%**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):** 92.6%**Maximum allowable site tonnage (M<sub>Safe</sub>) based on release following total wastewater treatment removal (kg/d):** 7987900 kg/day**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.**Local release to soil, kg/day:**

0

**Local release to air, kg/day:**

1.80E+02

**Local release to sewage, kg/day:**

0

**Fraction of main source to local environment:**

0.15

**Diethylenetriamine, DETA****Identified use name: Formulation and (re)packing of substances and mixtures - Industrial****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15****Substance supplied to that use in form of: As such  
Sector of end use: SU03****Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC02**

### Section 3: Exposure estimation

#### Section 3.1 Workers Exposure estimation

##### Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) no sampling; Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

#### Section 3.1 Workers Exposure estimation

##### Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Continuous process Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial  
 Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
 Substance supplied to that use in form of: As such  
 Sector of end use: SU03  
 Subsequent service life relevant for that use: No.  
 Environmental Release Category: ERC02

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Use in contained batch processes Mixing operations (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	6.86; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	2.15; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Batch process Mixing operations (open systems) with sample collection; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	2.15; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC02**

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC02**

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	1.37; 6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	9.03; 2.15	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility with local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 8: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Environment Exposure estimation****Contributing exposure scenario controlling environmental exposure for 0: Formulation of preparations\***

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	

**Diethylenetriamine, DETA**

**Identified use name: Formulation and (re)packing of substances and mixtures - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC02**

Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.2	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.314	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.804, 30 days; 0.269, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.119, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0301	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Formulation and (re)packing of substances and mixtures - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC02



## Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

## Section 1: Title

**Short title of the exposure scenario** **Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**List of use descriptors** **Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**Processes and activities covered by the exposure scenario** Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

**Respiratory protection:** None.

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process with sample collection (closed systems): No other specific measures identified.

Diethylenetriamine, DETA

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

###### Product Characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

###### Contributing scenarios: Operational conditions and risk management measures

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

Respiratory protection:

None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

###### Product Characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

###### Contributing scenarios: Operational conditions and risk management measures

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

Respiratory protection:

None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

###### Product Characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently).

Human factors not influenced by risk management:

None identified.

Other operational conditions affecting worker exposure:

Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

###### Contributing scenarios: Operational conditions and risk management measures

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Respiratory protection:

None.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,  
PROC08b, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC01

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:**

None.

**Section 2.2: Control of environmental exposure****Contributing exposure scenario controlling environmental exposure for 0: Manufacture of substances****Product Characteristics:****Concentration of substance in mixture or article:****Amounts used:****Fraction of EU tonnage used in region:**

1

**Frequency and duration of use:**

Continuous release.

**Emission Days (days/year):**

300

**Environmental factors not influenced by risk management:****Other operational conditions of use affecting environmental exposure:****Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:****Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):**

Not applicable.

**Conditions and measures related to municipal sewage treatment plant:**

Do not apply industrial sludge to natural soils.

**Estimated substance removal from wastewater via domestic sewage treatment (%):**

92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):**

92.6%

**Conditions and measures related to external treatment of waste for disposal:**Store finished products in closed containers (e.g., bulk tanks, drums, cans)  
Incinerate, absorb, or adsorb vapours stripped from solution whenever necessary**Conditions and measures related to external recovery of waste:**

Dispose of waste product or used containers according to local regulations.

**Local release to sewage, kg/day:**

150

**Fraction of substance in end-use products:**

1

**Diethylenetriamine, DETA****Identified use name: Manufacture of substance - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15****Substance supplied to that use in form of: As such**  
**Sector of end use: SU03****Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC01**

## Section 3: Exposure estimation

## Section 3.1 Workers Exposure estimation

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

## Section 3.1 Workers Exposure estimation

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

## Section 3.1 Workers Exposure estimation

## Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial  
 Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
 Substance supplied to that use in form of: As such  
 Sector of end use: SU03  
 Subsequent service life relevant for that use: No.  
 Environmental Release Category: ERC01

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	6.86	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	2.15	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Environment Exposure estimation****Contributing exposure scenario controlling environmental exposure for 0: Manufacture of substances**

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.537; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.054; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.044	Not applicable.

**Diethylenetriamine, DETA****Identified use name: Manufacture of substance - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15****Substance supplied to that use in form of: As such  
Sector of end use: SU03****Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC01**



Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	1028.3	During emission
Marine water sediment mg/kg dwt	Not applicable.	102.8	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.002; 30, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.002, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.65E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	5.51	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Manufacture of substance - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a,  
PROC08b, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC01

## Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

## Section 1: Title

Short title of the exposure scenario	<b>Identified use name:</b> Use as a PU curing agent for rigid foam production - Industrial <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU03 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC06c, ERC06d
List of use descriptors	<b>Identified use name:</b> Use as a PU curing agent for rigid foam production - Industrial <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU03 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC06c, ERC06d <b>Specific Environmental Release Category:</b> FEICA 7

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
---	--

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

General exposures (closed systems) with sample collection: No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Article formation in mould Batch process (closed systems) Machine Manual: No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours.

Article formation in mould Foaming (open systems) Machine Manual: No other specific measures identified.

Film formation - air drying (open systems): No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours.  
Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Industrial spraying****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of &gt;20.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Non-dedicated facility: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: No other specific measures identified.

**Respiratory protection:**

None.

**Diethylenetriamine, DETA****Identified use name:** Use as a PU curing agent for rigid foam production - Industrial**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

**Respiratory protection:**

None.

**Section 2.2: Control of environmental exposure****Diethylenetriamine, DETA****Identified use name:** Use as a PU curing agent for rigid foam production - Industrial**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics****Product Characteristics:****Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region:** 1  
**Maximum daily site tonnage (kg/day):** 800

**Frequency and duration of use:** Continuous release.  
**Emission Days (days/year):** 220

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Release fraction to air from process (initial release prior to RMM):** 1.70E-02  
**Release fraction to soil from process (initial release prior to RMM):** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM):** 0.00E+00

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):** Not applicable.

**Conditions and measures related to municipal sewage treatment plant:**

**Estimated substance removal from wastewater via domestic sewage treatment (%):** 92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):** 92.6%

**Maximum allowable site tonnage (M<sub>safe</sub>) based on release following total wastewater treatment removal (kg/d):** 214560 kg/day

**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.

**Local release to soil, kg/day:** 0

**Local release to air, kg/day:** 14

**Local release to sewage, kg/day:** 0

**Fraction of main source to local environment:** 0.016

**Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers****Product Characteristics:****Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region:** 1  
**Maximum daily site tonnage (kg/day):** 800

**Frequency and duration of use:** Continuous release.  
**Emission Days (days/year):** 220

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Release fraction to air from process (initial release prior to RMM):** 1.70E-02  
**Release fraction to soil from process (initial release prior to RMM):** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM):** 0.00E+00

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):** Not applicable.

**Conditions and measures related to municipal sewage treatment plant:****Diethylenetriamine, DETA****Identified use name:** Use as a PU curing agent for rigid foam production - Industrial**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

### Section 3: Exposure estimation

<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	0.86	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
<b>Diethylenetriamine, DETA</b> <b>Identified use name: Use as a PU curing agent for rigid foam production - Industrial</b> <b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15</b> <b>Substance supplied to that use in form of: As such</b> <b>Sector of end use: SU03</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC06c, ERC06d</b>			



Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	2.58	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process (closed systems) Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	6.86; Not applicable; 6.86; 6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	2.58; 0.60; 4.30; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
<b>Diethylenetriamine, DETA</b> <b>Identified use name: Use as a PU curing agent for rigid foam production - Industrial</b> <b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15</b> <b>Substance supplied to that use in form of: As such</b> <b>Sector of end use: SU03</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC06c, ERC06d</b>			

Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming (open systems) Machine Manual ; Film formation - air drying (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations* and articles (multistage and/or significant contact)</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	2.58; 0.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 5: Industrial spraying</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	4.30; 0.20	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	6.86	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.1 Workers Exposure estimation

#### Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.1 Workers Exposure estimation

#### Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

## Section 3.2 Environment Exposure estimation

### Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

## Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC06c, ERC06d

## Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

## Section 1: Title

Short title of the exposure scenario	<b>Identified use name:</b> Use as a PU curing agent for rigid foam production - Professional <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU02a, SU02b <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f
--------------------------------------	---

List of use descriptors	<b>Identified use name:</b> Use as a PU curing agent for rigid foam production - Professional <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU02a, SU02b <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f <b>Specific Environmental Release Category:</b> FEICA 10
-------------------------	---

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 5%.
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



General exposures (closed systems) with sample collection: No other specific measures identified.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors.

Film formation - air drying: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers: Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Foaming Manual: Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Diethylenetriamine, DETA****Identified use name: Use as a PU curing agent for rigid foam production - Professional****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19****Substance supplied to that use in form of: As such  
Sector of end use: SU02a, SU02b****Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC08c, ERC08f**

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Respiratory protection:

None.

**Section 2.2: Control of environmental exposure**

**Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix**

**Product Characteristics:**

**Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year

**Fraction of EU tonnage used in region:** 0.1

**Maximum daily site tonnage (kg/day):** 5.8

**Frequency and duration of use:** Continuous release.

**Emission Days (days/year):** 365

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Release fraction to air from process (initial release prior to RMM):** 0

**Release fraction to soil from process (initial release prior to RMM):** 0

**Release fraction to wastewater from process (initial release prior to RMM):** 1.50E-02

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):** Not applicable.

**Conditions and measures related to municipal sewage treatment plant:**

**Estimated substance removal from wastewater via domestic sewage treatment (%):** 92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):** 92.6%

**Maximum allowable site tonnage ( $M_{\text{safe}}$ ) based on release following total wastewater treatment removal (kg/d):** 1730 kg/day

**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.

**Local release to soil, kg/day:** 0

**Local release to air, kg/day:** 0

**Local release to sewage, kg/day:** 8.80E-02

**Fraction of main source to local environment:** 0.002

**Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix**

**Product Characteristics:**

**Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year

**Fraction of EU tonnage used in region:** 0.1

**Maximum daily site tonnage (kg/day):** 5.8

**Frequency and duration of use:** Continuous release.

**Emission Days (days/year):** 365

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

Release fraction to air from process (initial release prior to RMM):	0
Release fraction to soil from process (initial release prior to RMM):	0
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):	Not applicable.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

### Section 3: Exposure estimation

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.01	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Diethylenetriamine, DETA</b> <div> Identified use name: Use as a PU curing agent for rigid foam production - Professional  Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  Substance supplied to that use in form of: As such  Sector of end use: SU02a, SU02b  Subsequent service life relevant for that use: No.  Environmental Release Category: ERC08c, ERC08f </div>			

<b>Short term exposure, Systemic, Dermal</b>	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	0.34	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	2.58	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.86; Not applicable; 1.37	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.02; 0.70; 8.60	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Diethylenetriamine, DETA</b>	<b>Identified use name: Use as a PU curing agent for rigid foam production - Professional</b>
	<b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19</b>
	<b>Substance supplied to that use in form of: As such</b>
	<b>Sector of end use: SU02a, SU02b</b>
	<b>Subsequent service life relevant for that use: No.</b>
	<b>Environmental Release Category: ERC08c, ERC08f</b>



**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	6.02; 0.70	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	1.37; 2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	12.90; 9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA****Identified use name: Use as a PU curing agent for rigid foam production - Professional****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19****Substance supplied to that use in form of: As such****Sector of end use: SU02a, SU02b****Subsequent service life relevant for that use: No.****Environmental Release Category: ERC08c, ERC08f**



**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	5.36; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	6.02; 0.28	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.

**Diethylenetriamine, DETA****Identified use name: Use as a PU curing agent for rigid foam production - Professional****Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19****Substance supplied to that use in form of: As such  
Sector of end use: SU02a, SU02b****Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC08c, ERC08f**

Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring</b>			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Foaming Manual	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	8.60	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent</b>			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b> <b>Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available</b>			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	3.01; 0.14	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Diethylenetriamine, DETA</b>			
<b>Identified use name: Use as a PU curing agent for rigid foam production - Professional</b> <b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19</b> <b>Substance supplied to that use in form of: As such</b> <b>Sector of end use: SU02a, SU02b</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC08c, ERC08f</b>			

Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

## Section 3.2 Environment Exposure estimation

### Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

## Section 3.2 Environment Exposure estimation

### Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	

Diethylenetriamine, DETA

Identified use name: Use as a PU curing agent for rigid foam production - Professional  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
Substance supplied to that use in form of: As such  
Sector of end use: SU02a, SU02b  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC08c, ERC08f

Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

## Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

## Section 1: Title

Short title of the exposure scenario	<b>Identified use name:</b> Use as an epoxy curing agent - Industrial <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU03 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC06c, ERC06d
--------------------------------------	---

List of use descriptors	<b>Identified use name:</b> Use as an epoxy curing agent - Industrial <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU03 <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC06c, ERC06d <b>Specific Environmental Release Category:</b> FEICA 7
-------------------------	--

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.
---	--

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

General exposures (closed systems) with sample collection: No other specific measures identified.

Injection moulding of articles (closed systems): No other specific measures identified.

Film formation - air drying (closed systems): No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Film formation - air drying (open systems): Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Section 2.1 Control of worker exposure</b>	
<b>Contributing exposure scenario controlling worker exposure for 5: Industrial spraying</b>	
<b>Product Characteristics:</b>	Volatility: low
<b>Concentration of substance in product:</b>	Covers concentrations up to 50%
<b>Physical state:</b>	Liquid.
<b>Amounts used:</b>	Not applicable.
<b>Frequency and duration of use:</b>	Covers daily exposures up to 8 hours (unless stated differently).
<b>Human factors not influenced by risk management:</b>	None identified.
<b>Other operational conditions affecting worker exposure:</b>	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	
Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.	
<b>Respiratory protection:</b>	None.
<b>Section 2.1 Control of worker exposure</b>	
<b>Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</b>	
<b>Product Characteristics:</b>	Volatility: low
<b>Concentration of substance in product:</b>	Covers concentrations up to 50%
<b>Physical state:</b>	Liquid.
<b>Amounts used:</b>	Not applicable.
<b>Frequency and duration of use:</b>	Covers daily exposures up to 8 hours (unless stated differently).
<b>Human factors not influenced by risk management:</b>	None identified.
<b>Other operational conditions affecting worker exposure:</b>	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	
Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.	
Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.	
<b>Respiratory protection:</b>	None.
<b>Section 2.1 Control of worker exposure</b>	
<b>Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</b>	
<b>Product Characteristics:</b>	Volatility: low
<b>Concentration of substance in product:</b>	Covers concentrations up to 50%
<b>Physical state:</b>	Liquid.
<b>Amounts used:</b>	Not applicable.
<b>Frequency and duration of use:</b>	Covers daily exposures up to 8 hours (unless stated differently).
<b>Human factors not influenced by risk management:</b>	None identified.
<b>Other operational conditions affecting worker exposure:</b>	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	
Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Wear suitable gloves tested to EN374.	
<b>Respiratory protection:</b>	None.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,**  
**PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC06c, ERC06d**



**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Respiratory protection:**

None.

**Section 2.2: Control of environmental exposure****Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics****Product Characteristics:****Concentration of substance in mixture or article:****Amounts used:**

10700 Tonnes/year

**Fraction of EU tonnage used in region:**

1

**Maximum daily site tonnage (kg/day):**

800

**Frequency and duration of use:**

Continuous release.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Emission Days (days/year):	220
Environmental factors not influenced by risk management:	
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):	Not applicable.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016
Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers	
Product Characteristics:	
Concentration of substance in mixture or article:	
Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region:	1
Maximum daily site tonnage (kg/day):	800
Frequency and duration of use:	Continuous release.
Emission Days (days/year):	220
Environmental factors not influenced by risk management:	
Local marine water dilution factor:	100 Default
Other operational conditions of use affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM):	1.70E-02
Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	0.00E+00
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):	Not applicable.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal (kg/d):	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
<b>Diethylenetriamine, DETA</b> <div> Identified use name: Use as an epoxy curing agent - Industrial  Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  Substance supplied to that use in form of: As such  Sector of end use: SU03  Subsequent service life relevant for that use: No.  Environmental Release Category: ERC06c, ERC06d </div>	

## Section 3: Exposure estimation

## Section 3.1 Workers Exposure estimation

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	0.02	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

## Section 3.1 Workers Exposure estimation

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable; 1.37; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	2.15	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) with sample collection; Injection moulding of articles (closed systems); Film formation - air drying (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial  
 Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,  
 PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
 Substance supplied to that use in form of: As such  
 Sector of end use: SU03  
 Subsequent service life relevant for that use: No.  
 Environmental Release Category: ERC06c, ERC06d

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	6.45	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	0.69; Not applicable; 1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	1.07; 0.25; 10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	0.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	1.07; 0.25	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC06c, ERC06d**

<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 5: Industrial spraying</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	10.75; 0.50	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	9.03	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

<b>Diethylenetriamine, DETA</b>	<b>Identified use name: Use as an epoxy curing agent - Industrial</b> <b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15</b> <b>Substance supplied to that use in form of: As such</b> <b>Sector of end use: SU03</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC06c, ERC06d</b>
---------------------------------	---

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 8: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC06c, ERC06d**



**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	7.52	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Environment Exposure estimation****Contributing exposure scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics**

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	Local concentration	PEC aquatic (local+regional)	Justification
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC06c, ERC06d**



## Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC06c, ERC06d

## Identification of the substance or mixture

Product definition	Mono-constituent substance
Product name	Diethylenetriamine, DETA

## Section 1: Title

Short title of the exposure scenario	<b>Identified use name:</b> Use as an epoxy curing agent - Professional <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU02a, SU02b <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f
--------------------------------------	---

List of use descriptors	<b>Identified use name:</b> Use as an epoxy curing agent - Professional <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19 <b>Substance supplied to that use in form of:</b> As such <b>Sector of end use:</b> SU02a, SU02b <b>Subsequent service life relevant for that use:</b> No. <b>Environmental Release Category:</b> ERC08c, ERC08f <b>Specific Environmental Release Category:</b> FEICA 10
-------------------------	---

Processes and activities covered by the exposure scenario	Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.
---	--

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage (closed systems): No other specific measures identified.

Respiratory protection:	None.
-------------------------	-------

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product Characteristics:	Volatility: low
Concentration of substance in product:	Covers concentrations up to 50%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently).
Human factors not influenced by risk management:	None identified.
Other operational conditions affecting worker exposure:	Assumes a good basic standard of occupational hygiene is implemented. Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
 Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
 Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour.

Film formation - air drying: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

#### Section 2.1 Control of worker exposure

##### Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
 Assumes activities are at ambient temperature (unless stated differently).

##### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:**

None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with Type A filter or better.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: No other specific measures identified.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**

Assumes a good basic standard of occupational hygiene is implemented.

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures****Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,**  
**PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**

**Respiratory protection:** None.

## Section 2.2: Control of environmental exposure

**Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix**

### Product Characteristics:

**Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year

**Fraction of EU tonnage used in region:** 0.1

**Maximum daily site tonnage (kg/day):** 5.8

**Frequency and duration of use:** Continuous release.

**Emission Days (days/year):** 365

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Release fraction to air from process (initial release prior to RMM):** 0.00E+00

**Release fraction to soil from process (initial release prior to RMM):** 0.00E+00

**Release fraction to wastewater from process (initial release prior to RMM):** 1.50E-02

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):** Not applicable.

**Conditions and measures related to municipal sewage treatment plant:**

**Estimated substance removal from wastewater via domestic sewage treatment (%):** 92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):** 92.6%

**Maximum allowable site tonnage ( $M_{safe}$ ) based on release following total wastewater treatment removal (kg/d):** 1730 kg/day

**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.

**Local release to soil, kg/day:** 0

**Local release to air, kg/day:** 0

**Local release to sewage, kg/day:** 8.80E-02

**Fraction of main source to local environment:** 0.002

**Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix**

### Product Characteristics:

**Concentration of substance in mixture or article:**

**Amounts used:** 10700 Tonnes/year

**Fraction of EU tonnage used in region:** 0.1

**Maximum daily site tonnage (kg/day):** 5.8

**Frequency and duration of use:** Continuous release.

**Emission Days (days/year):** 365

**Environmental factors not influenced by risk management:**

**Local marine water dilution factor:** 100 Default

**Other operational conditions of use affecting environmental exposure:**

**Release fraction to air from process (initial release prior to RMM):** 0.00E+00

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

Release fraction to soil from process (initial release prior to RMM):	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM):	1.50E-02
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of <sup>3</sup> (%):	Not applicable.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal (kg/d):	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

### Section 3: Exposure estimation

#### Section 3.1 Workers Exposure estimation

##### Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	0.02	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

#### Section 3.1 Workers Exposure estimation

##### Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) with sample collection	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**



<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures (closed systems) with sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	0.34	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	4.51	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	6.86; Not applicable; 1.37	Not applicable.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	4.30; 0.50; 12.90	Not applicable.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	4.30; 0.50	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	5.37	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems); Storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 7: Roller application or brushing**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Roller, spreader, flow application	5.49	Not applicable.
Long term exposure, Systemic, Inhalable	Roller, spreader, flow application	3.76	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Roller, spreader, flow application	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 8: Non industrial spraying**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Spraying Manual; Aerosols	0.11; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	15.05; 0.70	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Dipping, immersion and pouring	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Dipping, immersion and pouring	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Dipping, immersion and pouring	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 10: Use as laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	10.75	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1 Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	Not applicable.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	5.37; 0.25	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an epoxy curing agent - Professional**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19**  
**Substance supplied to that use in form of: As such**  
**Sector of end use: SU02a, SU02b**  
**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC08c, ERC08f**

## Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

## Section 3.2 Environment Exposure estimation

Contributing exposure scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
Substance supplied to that use in form of: As such  
Sector of end use: SU02a, SU02b  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC08c, ERC08f

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC sediment (local+regional)	Justification
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
	Local concentration	PEC soil (local+regional)	Justification
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC air (local+regional)	Justification
During emission mg/m³	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m³	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m²/d	Not applicable.	Not applicable.	Not applicable.
	Local concentration	PEC aquatic (local+regional)	Justification
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an epoxy curing agent - Professional  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
Substance supplied to that use in form of: As such  
Sector of end use: SU02a, SU02b  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC08c, ERC08f

## Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

## Section 1: Title

**Short title of the exposure scenario** **Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

**List of use descriptors** **Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a  
**Specific Environmental Release Category:** ESVOC 2

**Processes and activities covered by the exposure scenario** Use of substance as an intermediate (not related to Strictly Controlled Conditions).  
Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

## Section 2: Operational conditions and risk management measures

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

General exposures Continuous process (closed systems): No other specific measures identified.

Bulk product storage (closed systems): No other specific measures identified.

**Respiratory protection:** None.

## Section 2.1 Control of worker exposure

## Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

## Contributing scenarios: Operational conditions and risk management measures

Diethylenetriamine, DETA

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a



General exposures Continuous process with sample collection (closed systems): No other specific measures identified.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

General exposures Use in contained batch processes with sample collection: No other specific measures identified.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

General exposures Batch process with sample collection (open systems): Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

**Section 2.1 Control of worker exposure**

**Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

**Product Characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently).  
**Human factors not influenced by risk management:** None identified.  
**Other operational conditions affecting worker exposure:** Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with Type A filter or better.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.1 Control of worker exposure****Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent****Product Characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently).

**Human factors not influenced by risk management:**

None identified.

**Other operational conditions affecting worker exposure:**Assumes a good basic standard of occupational hygiene is implemented.  
Assumes activities are at ambient temperature (unless stated differently).**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:**

None.

**Section 2.2: Control of environmental exposure****Contributing exposure scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)****Product Characteristics:****Concentration of substance in mixture or article:****Amounts used:**

43000 Tonnes/year

**Fraction of EU tonnage used in region:**

1

**Maximum daily site tonnage (kg/day):**

14333

**Frequency and duration of use:**

Continuous release.

**Emission Days (days/year):**

300

**Environmental factors not influenced by risk management:****Local marine water dilution factor:**

100 Default

**Other operational conditions of use affecting environmental exposure:****Release fraction to air from process (initial release prior to RMM):**

2.00E-05

**Release fraction to soil from process (initial release prior to RMM):**

1.00E-003

**Release fraction to wastewater from process (initial release prior to RMM):**

1.00E-02

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:****Treat air emission to provide a typical removal efficiency of (%):**

Not applicable.

**Conditions and measures related to municipal sewage treatment plant:****Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

Estimated substance removal from wastewater via domestic sewage treatment (%):	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs (%):	92.6%
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal (kg/d):	15640 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	14.3
Local release to air, kg/day:	2.86E-01
Local release to sewage, kg/day:	143.3
Fraction of main source to local environment:	0.1

### Section 3: Exposure estimation

Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process (closed systems); Bulk product storage (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Section 3.1 Workers Exposure estimation			
Contributing exposure scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure			
Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process with sample collection (closed systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC06a

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	12.90	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Use in contained batch processes with sample collection	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	0.04	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Batch process with sample collection (open systems)	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.1Workers Exposure estimation****Contributing exposure scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Equipment cleaning and maintenance	2.74	Not applicable.
Long term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	6.02; 4.30	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Equipment cleaning and maintenance	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name: Use as an intermediate - Industrial**  
**Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15**

**Substance supplied to that use in form of: As such**  
**Sector of end use: SU03**

**Subsequent service life relevant for that use: No.**  
**Environmental Release Category: ERC06a**

Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	1.37	Not applicable.
Long term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.1 Workers Exposure estimation</b>			
<b>Contributing exposure scenario controlling worker exposure for 6: Use as laboratory reagent</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	Not applicable.
Long term exposure, Systemic, Inhalable	Laboratory activities	9.03	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

<b>Section 3.2 Environment Exposure estimation</b>			
<b>Contributing exposure scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)</b>			
	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>

<b>Diethylenetriamine, DETA</b>	<b>Identified use name: Use as an intermediate - Industrial</b> <b>Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15</b> <b>Substance supplied to that use in form of: As such</b> <b>Sector of end use: SU03</b> <b>Subsequent service life relevant for that use: No.</b> <b>Environmental Release Category: ERC06a</b>
---------------------------------	---

Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.513; Surface water, Dissolved Annual average : 0.442	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.051; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.042	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	982.6	During emission
Marine water sediment mg/kg dwt	Not applicable.	98.23	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	114.1, 30 days; 37.5, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	15.0, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	8.6E-05	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	5.262	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

Environment	Not available.
Health	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

Environment	Not applicable.
Health	Not applicable.
Additional good practices	Not applicable.

Diethylenetriamine, DETA

Identified use name: Use as an intermediate - Industrial  
Process Category: PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
Substance supplied to that use in form of: As such  
Sector of end use: SU03  
Subsequent service life relevant for that use: No.  
Environmental Release Category: ERC06a