


Text Analytics

David Li


Regular expressions

State machine examples

- Example 1: $ac^+ | bd$



- Example 2: $a(b^* | c)d$



Matching example

- Graph:
-
- A graph with six nodes: 1, 2, 3, 4, 5, and 6. Node 1 is the start node, indicated by an incoming arrow. Node 6 is the final node, indicated by a double circle. Edges are labeled with characters: from node 1 to node 1 on 'b' (self-loop); from node 1 to node 2 on 'a'; from node 2 to node 5 on 'a'; from node 2 to node 3 on 'b'; from node 3 to node 4 on 'c'; from node 4 to node 1 on 'd' (curved edge); and from node 5 to node 6 on 'b'. Node 6 has a self-loop on 'c'. Nodes 4 and 6 are shaded gray.
- Matching
 - abc
 - bbabc
 - baab
 - baabcc
 - abcd bbbabc
 - abcd
 - e

Regular expressions

- Regular expressions can be thought of as a combination of literals and *metacharacters*
- To draw an analogy with natural language, think of literal text forming the words of this language, and the metacharacters defining its grammar
- Regular expressions have a rich set of metacharacters

Literals

Simplest pattern consists only of literals. The literal "nuclear" would match to the following lines:

```
Ooh. I just learned that to keep myself alive after a
nuclear blast! All I have to do is milk some rats
then drink the milk. Aweosme. :}
```

Laozi says nuclear weapons are mas macho

Chaos in a country that has nuclear weapons -- not good.

my nephew is trying to teach me nuclear physics, or
possibly just trying to show me how smart he is
so I'll be proud of him [which I am].

lol if you ever say "nuclear" people immediately think
DEATH by radiation LOL

Literals

The literal "Obama" would match to the following lines

Politics r dum. Not 2 long ago Clinton was sayin Obama
was crap n now she sez vote 4 him n unite? WTF?
Screw em both + McCain. Go Ron Paul!

Clinton concedes to Obama but will her followers listen??

Are we sure Chelsea didn't vote for Obama?

thinking ... Michelle Obama is terrific!

jetlag..no sleep...early mornig to starbux..Ms. Obama
was moving

Regular Expressions

- Simplest pattern consists only of literals; a match occurs if the sequence of literals occurs anywhere in the text being tested
- What if we only want the word "Obama"? or sentences that end in the word "Clinton", or "clinton" or "clinto"?

Regular Expressions

We need a way to express

- whitespace word boundaries
- sets of literals
- the beginning and end of a line
- alternatives ("war" or "peace")

Metacharacters to the rescue!

Metacharacters

Some metacharacters represent the start of a line

```
^i think
```

will match the lines

```
i think we all rule for participating  
i think i have been outed  
i think this will be quite fun actually  
i think i need to go to work  
i think i first saw zombo in 1999.
```


Metacharacters

\$ represents the end of a line

morning\$

will match the lines

well they had something this morning
then had to catch a tram home in the morning
dog obedience school in the morning
and yes happy birthday i forgot to say it earlier this morning
I walked in the rain this morning
good morning

Character Classes with []

We can list a set of characters we will accept at a given point in the match

[Bb] [Uu] [Ss] [Hh]

will match the lines

The democrats are playing, "Name the worst thing about **Bush**!"

I smelled the desert creosote **bush**, brownies, BBQ chicken

BBQ and **bush**walking at Molonglo Gorge

Bush TOLD you that North Korea is part of the Axis of Evil

I'm listening to **Bush** - Hurricane (Album Version)

Character Classes with []

`^[Ii] am`

will match

`i am` so angry at my boyfriend i can't even bear to
look at him

`i am` boycotting the apple store

`I am` twittering from iPhone

`I am` a very vengeful person when you ruin my sweetheart.

`I am` so over this. I need food. Mmmm bacon...

Character Classes with []

Similarly, you can specify a range of letters [a-z] or [a-zA-Z]; notice that the order doesn't matter

```
^[0-9] [a-zA-Z]
```

will match the lines

7th inning stretch

2nd half soon to begin. OSU did just win something

3am - cant sleep - too hot still.. :(

5ft 7 sent from heaven

1st sign of starvagtion

Character Classes with []

When used at the beginning of a character class, the “^” is also a metacharacter and indicates matching characters NOT in the indicated class

```
[^?.]$
```

will match the lines

i like basketballs

6 and 9

dont worry... we all die anyway!

Not in Baghdad

helicopter under water? hmmm

More Metacharacters

"." is used to refer to any character. So

9.11

will match the lines

its stupid the post 9-11 rules

if any 1 of us did 9/11 we would have been caught in days.

NetBios: scanning ip 203.169.114.66

Front Door 9:11:46 AM

Sings: 0118999881999119725...3 !

More Metacharacters: |

This does not mean “pipe” in the context of regular expressions; instead it translates to “or”; we can use it to combine two expressions, the subexpressions being called alternatives

```
flood|fire
```

will match the lines

is **fire**wire like usb on none macs?

the global **flood** makes sense within the context of the bible

yeah ive had the **fire** on tonight

... and the **floods**, hurricanes, killer heatwaves, rednecks, gun nuts, etc.

More Metacharacters: |

We can include any number of alternatives...

`flood|earthquake|hurricane|coldfire`

will match the lines

Not a whole lot of **hurricanes** in the Arctic.

We do have **earthquakes** nearly every day somewhere in our State

hurricanes swirl in the other direction

coldfire is STRAIGHT!

'cause we keep getting **earthquakes**

More Metacharacters: |

The alternatives can be real expressions and not just literals

```
^[Gg]ood|[Bb]ad
```

will match the lines

good to hear some good news from someone here

Good afternoon fellow american infidels!

good on you-what do you drive?

Katie... guess they had bad experiences...

my middle name is trouble, Miss Bad News

More Metacharacters: (and)

Subexpressions are often contained in parentheses to constrain the alternatives

```
~([Gg]ood|[Bb]ad)
```

will match the lines

bad habbit

bad coordination today

good, becuae there is nothing worse than a man in kinky underwear

Badcop, its because people want to use drugs

Good Monday Holiday

Good riddance to Limey

More Metacharacters: ?

The question mark indicates that the indicated expression is optional

```
[Gg]eorge( [Ww]\.)? [Bb]ush
```

will match the lines

```
i bet i can spell better than you and george bush combined
BBC reported that President George W. Bush claimed God told him to invade
a bird in the hand is worth two george bushes
```

One thing to note...

In the following

```
[Gg]eorge( [Ww]\.)? [Bb]ush
```

we wanted to match a "." as a literal period; to do that, we had to "escape" the metacharacter, preceding it with a backslash In general, we have to do this for any metacharacter we want to include in our match

More metacharacters: * and +

The * and + signs are metacharacters used to indicate repetition; * means “any number, including none, of the item” and + means “at least one of the item”

`\(.*\)`

will match the lines

anyone wanna chat? `(24, m, germany)`

hello, 20.m here... `(east area + drives + webcam)`

`(he means older men)`

`()`

More metacharacters: * and +

The * and + signs are metacharacters used to indicate repetition; * means “any number, including none, of the item” and + means “at least one of the item”

`[0-9]+ (.*) [0-9]+`

will match the lines

working as MP here 720 MP battallion, 42nd birgade
so say 2 or 3 years at colleage and 4 at uni makes us 23 when and if we fir
it went down on several occasions for like, 3 or 4 *days*
Mmmm its time 4 me 2 go 2 bed

More metacharacters: { and }

{ and } are referred to as interval quantifiers; they let us specify the minimum and maximum number of matches of an expression

`[Bb]ush(+[^\s]+){1,5} debate`

will match the lines

Bush has historically won all major debates he's done.

in my view, Bush doesn't need these debates..

bush doesn't need the debates? maybe you are right

That's what Bush supporters are doing about the debate.

Felix, I don't disagree that Bush was poorly prepared for the debate.

indeed, but still, Bush should have taken the debate more seriously.

Keep repeating that Bush smirked and scowled during the debate

More metacharacters: **m** and **n**

{m, n}

- **m,n** means at least **m** but not more than **n** matches
- **m** means exactly **m** matches
- **m,** means at least **m** matches

More metacharacters: (and) revisited

- In most implementations of regular expressions, the parentheses not only limit the scope of alternatives divided by a "|", but also can be used to "remember" text matched by the subexpression enclosed
- We refer to the matched text with \1, \2, etc.

More metacharacters: (and) revisited

So the expression

```
+[a-zA-Z]+\1 +
```

will match the lines

time for bed, night night twitter!

blah blah blah blah

my tattoo is so so itchy today

i was standing all all alone against the world outside...

hi anybody anybody at home

estudiando css css css css.... que desastritoooo

More metacharacters: (and) revisited

The * is “greedy” so it always matches the *longest* possible string that satisfies the regular expression. So

`^s(.*)s`

matches

sitting at starbucks

setting up mysql and rails

studying stuff for the exams

spaghetti with marshmallows

stop fighting with crackers

sore shoulders, stupid ergonomics

More metacharacters: (and) revisited

The greediness of * can be turned off with the ?, as in

`^s(.*)s$`

Summary

- Regular expressions are used in many different languages;
- Regular expressions are composed of literals and metacharacters that represent sets or classes of characters/words
- Text processing via regular expressions is a very powerful way to extract data from “unfriendly” sources (not all data comes as a CSV file)

(Thanks to Mark Hansen for some material in this lecture.)

Regular Expression Functions

The primary R functions for dealing with regular expressions are

- `grep`, `grep1`: Search for matches of a regular expression/pattern in a character vector; either return the indices into the character vector that match, the strings that happen to match, or a TRUE/FALSE vector indicating which elements match
- `regexpr`, `gregexpr`: Search a character vector for regular expression matches and return the indices of the string where the match begins and the length of the match
- `sub`, `gsub`: Search a character vector for regular expression matches and replace that match with another string
- `regexec`: Easier to explain through demonstration.

grep

Here is an excerpt of the Baltimore City homicides dataset:

```
> homicides <- readLines("homicides.txt")
> homicides[1]
[1] "39.311024, -76.674227, iconHomicideShooting, 'p2', '<dl><dt>Leon
Nelson</dt><dd class=\"address\">3400 Clifton Ave.<br />Baltimore, MD
21216</dd><dd>black male, 17 years old</dd>
<dd>Found on January 1, 2007</dd><dd>Victim died at Shock
Trauma</dd><dd>Cause: shooting</dd></dl>'"

> homicides[1000]
[1] "39.33626300000, -76.55553990000, icon_homicide_shooting, 'p1200',...
```

How can I find the records for all the victims of shootings (as opposed to other causes)?

grep

```
> length(grep("iconHomicideShooting", homicides))  
[1] 228  
> length(grep("iconHomicideShooting|icon_homicide_shooting", homicides))  
[1] 1003  
> length(grep("Cause: shooting", homicides))  
[1] 228  
> length(grep("Cause: [Ss]hooting", homicides))  
[1] 1003  
> length(grep("[Ss]hooting", homicides))  
[1] 1005
```


grep

```
> i <- grep("[cC]ause: [Ss]hooting", homicides)
> j <- grep("[Ss]hooting", homicides)
> str(i)
  int [1:1003] 1 2 6 7 8 9 10 11 12 13 ...
> str(j)
  int [1:1005] 1 2 6 7 8 9 10 11 12 13 ...
> setdiff(i, j)
integer(0)
> setdiff(j, i)
[1] 318 859
```

```
> homicides[859]
[1] "39.33743900000, -76.66316500000, icon_homicide_bluntforce,
'p914', '<dl><dt><a href=\"http://essentials.baltimoresun.com/
micro_sun/homicides/victim/914/steven-harris\">Steven Harris</a>
</dt><dd class=\"address\">4200 Pimlico Road<br />Baltimore, MD 21215
</dd><dd>Race: Black<br />Gender: male<br />Age: 38 years old</dd>
<dd>Found on July 29, 2010</dd><dd>Victim died at Scene</dd>
<dd>Cause: Blunt Force</dd><dd class=\"popup-note\"><p>Harris was
found dead July 22 and ruled a shooting victim; an autopsy
subsequently showed that he had not been shot,...</dd></dl>'"
```

grep

By default, `grep` returns the indices into the character vector where the regex pattern matches.

```
> grep("^New", state.name)
[1] 29 30 31 32
```

Setting `value = TRUE` returns the actual elements of the character vector that match.

```
> grep("^New", state.name, value = TRUE)
[1] "New Hampshire" "New Jersey"      "New Mexico"      "New York"
```

`grepl` returns a logical vector indicating which element matches.

```
> grepl("^New", state.name)
[1] FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
[13] FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
[25] FALSE FALSE FALSE FALSE TRUE TRUE TRUE TRUE FALSE FALSE FALSE FALSE
[37] FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE FALSE
[49] FALSE FALSE
```

Some limitations of grep

- The grep function tells you which strings in a character vector match a certain pattern but it doesn't tell you exactly where the match occurs or what the match is (for a more complicated regex).
- The regexpr function gives you the index into each string where the match begins and the length of the match for that string.
- regexpr only gives you the first match of the string (reading left to right).
gregexpr will give you all of the matches in a given string.

"g" means global

How can we find the date of the homicide?

```
> homicides[1]
[1] "39.311024, -76.674227, iconHomicideShooting, 'p2', '<dl><dt>Leon
Nelson</dt><dd class=\"address\">3400 Clifton Ave.<br />Baltimore,
MD 21216</dd><dd>black male, 17 years old</dd>
<dd>Found on January 1, 2007</dd><dd>Victim died at Shock
Trauma</dd><dd>Cause: shooting</dd></dl>'"
```

Can we just 'grep' on "Found"?

The word 'found' may be found elsewhere in the entry.

```
> homicides[954]
[1] "39.30677400000, -76.59891100000, icon_homicide_shooting, 'p816',
'<dl><dd class=\"address\">1400 N Caroline St<br />Baltimore, MD 21213</dd>
<dd>Race: Black<br />Gender: male<br />Age: 29 years old</dd>
<dd>Found on March 3, 2010</dd><dd>Victim died at Scene</dd>
<dd>Cause: Shooting</dd><dd class=\"popup-note\"><p>Wheeler\\'s body
was&nbsp;found on the grounds of Dr. Bernard Harris Sr.&nbsp;Elementary
School</p></dd></dl>'"
```

regexpr

Let's use the pattern

```
<dd>[F|f]ound(.*)</dd>
```

What does this look for?

```
> regexpr("<dd>[F|f]ound(.*)</dd>", homicides[1:10])  
[1] 177 178 188 189 178 182 178 187 182 183  
attr("match.length")  
[1] 93 86 89 90 89 84 85 84 88 84  
attr("useBytes")  
[1] TRUE  
> substr(homicides[1], 177, 177 + 93 - 1)  
[1] "<dd>Found on January 1, 2007</dd><dd>Victim died at Shock  
Trauma</dd><dd>Cause: shooting</dd>"
```

* Is greedy, so it matches the furthest </dd>

The previous pattern was too greedy and matched too much of the string. We need to use the ? metacharacter to make the regex "lazy".

```
> regexpr("<dd>[F|f]ound(.*)</dd>", homicides[1:10])  
[1] 177 178 188 189 178 182 178 187 182 183  
attr(,"match.length")  
[1] 33 33 33 33 33 33 33 33 33 33  
attr(,"useBytes")  
[1] TRUE
```

The indices of beginnings stay the same

The lengths of matches are much shorter

```
> substr(homicides[1], 177, 177 + 33 - 1)  
[1] "<dd>Found on January 1, 2007</dd>"
```


regmatches

One handy function is `regmatches` which extracts the matches in the strings for you without you having to use `substr`.

```
> r <- regexpr("<dd>[F|f]ound(.*)</dd>", homicides[1:5])
> regmatches(homicides[1:5], r)
[1] "<dd>Found on January 1, 2007</dd>" "<dd>Found on January 2, 2007</dd>"
[3] "<dd>Found on January 2, 2007</dd>" "<dd>Found on January 3, 2007</dd>"
[5] "<dd>Found on January 5, 2007</dd>"
```

- `regexpr` finds the locations of matches
- `regmatches` gets the content from the found locations

sub/gsub

Sometimes we need to clean things up or modify strings by matching a pattern and replacing it with something else. For example, how can we extract the data from this string?

```
> x <- substr(homicides[1], 177, 177 + 33 - 1)
> x
[1] "<dd>Found on January 1, 2007</dd>"
```

We want to strip out the stuff surrounding the "January 1, 2007" piece.

```
> sub("<dd>[F|f]ound on |</dd>", "", x)
[1] "January 1, 2007</dd>"
```

Tips:

sub -- substitute the first

gsub -- global substitute

```
> gsub("<dd>[F|f]ound on |</dd>", "", x)
[1] "January 1, 2007"
```

sub/gsub

sub/gsub can take vector arguments

```
> r <- regexpr("<dd>[F|f]ound(.*)</dd>", homicides[1:5])
> m <- regmatches(homicides[1:5], r)
> m
[1] "<dd>Found on January 1, 2007</dd>" "<dd>Found on January 2, 2007</dd>"
[3] "<dd>Found on January 2, 2007</dd>" "<dd>Found on January 3, 2007</dd>"
[5] "<dd>Found on January 5, 2007</dd>"
> gsub("<dd>[F|f]ound on |</dd>", "", m)
[1] "January 1, 2007" "January 2, 2007" "January 2, 2007" "January 3, 2007"
[5] "January 5, 2007"
> as.Date(d, "%B %d, %Y")
[1] "2007-01-01" "2007-01-02" "2007-01-02" "2007-01-03" "2007-01-05"
```

regexec

The `regexec` function works like `regexr` except it gives you the indices for parenthesized sub-expressions.

```
> regexec("<dd>[F|f]ound on (.*?)</dd>", homicides[1])
```


```
[[1]]
```

```
[1] 177 190
```

```
attr(,"match.length")
```

```
[1] 33 15
```

[1] "39.311024, -76.674227, iconHomicideShooting, p2" "<dl><dt>Leon
Nelson</dt><dd class=\"address\">3400 Clifton Ave.
Baltimore, MD
21216</dd><dd>black male, 17 years old</dd><dd>Found on January 1,
2007</dd><dd>Victim died at Shock Trauma</dd><dd>Cause: shooting</
dd></dl>"



```
> regexec("<dd>[F|f]ound on .*?</dd>", homicides[1])
```

```
[[1]]
```

```
[1] 177
```

```
attr(,"match.length")
```

```
[1] 33
```

Now we can extract the string in the parenthesized sub-expression.

```
> regexec("<dd>[F|f]ound on (.*?)</dd>", homicides[1])  
[[1]]  
[1] 177 190  
attr(,"match.length")  
[1] 33 15  
  
> substr(homicides[1], 177, 177 + 33 - 1)  
[1] "<dd>Found on January 1, 2007</dd>"  
  
> substr(homicides[1], 190, 190 + 15 - 1)  
[1] "January 1, 2007"
```

Even easier with the `regmatches` function.


```
> r <- regexec("<dd>[F|f]ound on (.*?)</dd>", homicides[1:2])
> regmatches(homicides[1:2], r)
[[1]]
[1] "<dd>Found on January 1, 2007</dd>" "January 1, 2007"

[[2]]
[1] "<dd>Found on January 2, 2007</dd>" "January 2, 2007"
```

Let's make a plot of monthly homicide counts

```
> r <- regexec("<dd>[F|f]ound on (.*?)</dd>", homicides)
> m <- regmatches(homicides, r)
> dates <- sapply(m, function(x) x[2])
> dates <- as.Date(dates, "%B %d, %Y")
> hist(dates, "month", freq = TRUE)
```

Histogram of dates



Summary

The primary R functions for dealing with regular expressions are

- `grep`, `grep1`: Search for matches of a regular expression/pattern in a character vector
- `regexpr`, `gregexpr`: Search a character vector for regular expression matches and return the indices where the match begins; useful in conjunction with `regmatches`
- `sub`, `gsub`: Search a character vector for regular expression matches and replace that match with another string
- `regexec`: Gives you indices of parenthesized sub-expressions.

stringr package

- R provides a solid set of string operations, but because they have grown organically over time, they can be inconsistent and a little hard to learn.
- **stringr**: written by Hadley Wickham
 - Basic string operations
 - Pattern matching

Basic string operations

- `str_c` is equivalent to `paste`, but it uses the empty string (`""`) as the default separator and silently removes zero length arguments.
- `str_length` is equivalent to `nchar`, but it preserves `NA`'s (rather than giving them length 2) and converts factors to characters (not integers).
- `str_sub` is equivalent to `substr` but it returns a zero length vector if any of its inputs are zero length, and otherwise expands each argument to match the longest. It also accepts negative positions, which are calculated from the left of the last character. The end position defaults to -1, which corresponds to the last character.
- `str_sub<-` is equivalent to `substr<-`, but like `str_sub` it understands negative indices, and replacement strings not do need to be the same length as the string they are replacing.

Basic string operations

- `str_dup` to duplicate the characters within a string.
- `str_trim` to remove leading and trailing whitespace.
- `str_pad` to pad a string with extra whitespace on the left, right, or both sides.

Pattern matching

- `str_detect` detects the presence or absence of a pattern and returns a logical vector. Based on `grepl`.
- `str_locate` locates the first position of a pattern and returns a numeric matrix with columns `start` and `end`. `str_locate_all` locates all matches, returning a list of numeric matrices. Based on `regexpr` and `gregexpr`.
- `str_extract` extracts text corresponding to the first match, returning a character vector.
- `str_extract_all` extracts all matches and returns a list of character vectors.

Pattern matching

- `str_match` extracts capture groups formed by `()` from the first match. It returns a character matrix with one column for the complete match and one column for each group.
- `str_match_all` extracts capture groups from all matches and returns a list of character matrices.
- `str_replace` replaces the first matched pattern and returns a character vector.
- `str_replace_all` replaces all matches. Based on `sub` and `gsub`.
- `str_split_fixed` splits the string into a fixed number of pieces based on a pattern and returns a character matrix. `str_split` splits a string into a variable number of pieces and returns a list of character vectors.

Pattern Match

- **Arguments:** Each pattern matching function has the same first two arguments, a character vector of strings to process and a single pattern (regular expression) to match.
 - The replace functions have an additional argument specifying the replacement string,
 - The split functions have an argument to specify the number of pieces.
- “When writing regular expressions, I strongly recommend generating a list of positive (pattern should match) and negative (pattern shouldn’t match) test cases to ensure that you are matching the correct components.” -- Hadley Wickham

Other resources

- A good reference sheet
 - <http://www.regular-expressions.info/reference.html>
- A tool that allows you to interactively test what a regular expression will match
 - <https://regex101.com/>
 - <http://regexpr.com/>