

# Low Level Layered Language

## L-LANGUAGE

(Draft 1b)

Robert L. Walton

March 31, 2024

### Table of Contents

1	Introduction . . . . .	4
2	Overview . . . . .	4
3	Lexemes . . . . .	15
4	Logical Lines, Blocks, and Statements . . . . .	20
5	Expressions . . . . .	23
6	Primaries . . . . .	30
6.1	Names . . . . .	30
6.2	Constants . . . . .	34
6.2.1	Rational Constants . . . . .	35
6.2.2	Map Constants . . . . .	36
6.3	Reference Expressions . . . . .	38
6.4	Function Calls . . . . .	42
6.5	Bracketed Expressions . . . . .	43
7	Assignment Statements . . . . .	44
7.1	Expression Assignment Statements . . . . .	48
7.2	Call Assignment Statements . . . . .	49
7.3	Block Assignment Statements . . . . .	50
7.4	Deferred Assignment Statements . . . . .	52
7.5	Loop Assignment Statements . . . . .	53
8	Conditional Statements . . . . .	56
9	Trace Statements . . . . .	57
10	Declarations . . . . .	57
10.1	Type Declarations . . . . .	58
10.1.1	Defined Type Expansions . . . . .	60
10.1.2	Type Fields . . . . .	62
10.1.3	Type Subfields . . . . .	64
10.1.4	Type Dimensions . . . . .	65

10.1.5	Type Conversions . . . . .	66
10.2	Pointer Type Declarations . . . . .	67
10.2.1	Pointer Type Conversions . . . . .	71
10.3	Inline Function Declarations . . . . .	72
10.3.1	Inline Call-Declaration Matching . . . . .	79
10.4	Reference Function Declarations . . . . .	88
10.4.1	Reference Call-Declaration Matching . . . . .	90
10.5	Inclusions . . . . .	93
10.6	Out-of-Line Function Declarations . . . . .	95
10.6.1	Function Type Declarations . . . . .	97
10.7	Module and Body Declarations . . . . .	98
10.7.1	Program Initialization . . . . .	99
11	Parser Output . . . . .	100
12	Scope . . . . .	101
13	Lifetimes . . . . .	106
14	Memory Management . . . . .	113
14.1	Copying Garbage Collection . . . . .	114
14.2	Marking Garbage Collection . . . . .	116
14.3	Counting Garbage Collection . . . . .	116
14.4	Locating Global and Local Heap Pointers . . . . .	117
15	Non-Function Operators . . . . .	118
16	Builtin Abbreviations . . . . .	120
17	Constant Functions and Compiler Constants . . . . .	122
17.1	Compile Time General Functions . . . . .	122
17.2	Compile Time Numeric Functions . . . . .	122
17.3	Compile Time String Functions . . . . .	124
17.4	Compile Time Map Functions . . . . .	126
17.5	Type, Field, Subfield, and Pointer Type Maps . . . . .	129
17.5.1	Type Maps . . . . .	130
17.5.2	Field Maps . . . . .	132
17.5.3	Subfield Maps . . . . .	133
17.5.4	Pointer Type Maps . . . . .	134
17.6	Compile Time Compilation Functions . . . . .	134
17.7	Compile Time Exception and Trace Support . . . . .	135
17.8	Compile Time Machine Parameters . . . . .	136
18	Builtin Run-Time Functions and Constants . . . . .	136
18.1	Builtin Run-Time Constants . . . . .	136
18.2	Builtin Implicit Conversions . . . . .	136

18.2.1	Numeric Implicit Conversions . . . . .	137
18.2.2	Pointer Implicit Conversions . . . . .	138
18.2.3	Qualifier Implicit Conversions . . . . .	138
18.3	Builtin Explicit Conversions . . . . .	138
18.3.1	Numeric Explicit Conversions . . . . .	139
18.3.2	Pointer Explicit Conversions . . . . .	140
18.4	Builtin Floating Point Operations . . . . .	140
18.5	Builtin Integer Operations . . . . .	142
18.6	Builtin Pointer Operations . . . . .	144
18.7	Builtin Exception and Trace Support Operations . . . . .	145
19	Atomic Operations . . . . .	146

# 1 Introduction

This document describes **L-Language**, the Layered Language System Low Level Language.

The L-Language is a system programming language built on the following two main ideas:

**Type Checking Segregation Hypothesis** A strongly typed-checked general-purpose computer-efficient language is impossible. What is possible is to segregate non-type-checkable code into small inline library functions and into macro functions, with code that uses these sublanguages being strongly type-checked.

**Fully Capable Macro Sublanguage Hypothesis** It is better for a programming language to have a builtin macro language that is a general purpose interpreted language than it is for the programming language to build into itself many more limited and specialized type declaration and flow control features.

The author of this document does not plan to implement the L-Language. However, a parser for the L-Language is being built on top of the ‘layered’ system for lexical analysis and parsing, and is being used to debug the design of the ‘layered’ system.

# 2 Overview

A typical L-Language statement is:

```
int X = Y - C#"0"
```

This allocates a new variable `X` of type `int` and sets its value to the value of the variable `Y` minus the constant `C#"0"` (which is the character code of the character 0). The ‘variable’ `X` is readable, but after it is initialized it is not writable.

The following is another example:

```
av *READ-WRITE* uns8 @bp @= local[81]
av uns8 @cp = "Hello!"
int i = 0
while i < cp.upper:
    bp[i] = cp[i]
    next i = i + 1
bp[cp.upper] = 0
```

Here ‘`local[81]`’ creates an aligned vector of 81 `uns8` (8-bit unsigned) numbers in the current function frame and returns an aligned vector pointer, or `av`, to the vector, marking the vector elements as `*READ-WRITE*`. “Hello!” is a constant vector of `uns8` numbers and is similar except that it marks the vector elements `co`, for ‘constant’, which is the implied default qualifier for `@cp`, and therefore is not explicitly given. Vector pointers can be used with indices to reference elements of their vectors, and have `upper` and `lower` bounds on

these indices. Here the `lower` bounds are their defaults, which are 0.

Here `@bp` is a variable whose name begins with ‘@’ and whose value is therefore a pointer. Such a variable has an associated indirect variable `bp` whose name is missing the initial ‘@’. The expression `@bp[i]` designates a pointer to the  $i+1$ ’st element of the vector pointed at by `@bp`, but the expression `bp[i]` designates the value of the element. Similarly for `@cp[i]` and `cp[i]`.<sup>1</sup>

The qualifier `*READ-WRITE*` says that a value can be read or written, the default qualifier `co`, or ‘constant’, says a value can be read but will never be written no matter what, the qualifier `ro`, or read-only, says that the value can be read but cannot be written using the variable name given, though it might be written by some other piece of code that accesses the value under another name. The qualifier `*WRITE-ONLY*` says that the value cannot be read but can be written using the variable name given, but might be read by some other piece of code or other device.

There are also two qualifiers that specify the lifetime of the target of a pointer: `*GLOBAL*`, and `*HEAP*`. The default is no lifetime qualifier (a.k.a., undeclared pointer) which means, roughly, that the pointer is valid only until the code block in which the pointer was first calculated is no longer executing. Typically pointer variables are default-undeclared, as in the example. The “Hello!” constant in the example is a `*GLOBAL*` pointer, meaning that the pointer is valid during the entire program execution, but such pointers are implicitly convertible to undeclared pointers, as in the example. `*HEAP*` pointers point at garbage collectable values and obey special rules that we shall not discuss here.

Variables in function frames and module memory have names, like `X`, `Y`, and `Z`, and values that are constants. These values most frequently have a size equal to the natural word size of the computer (typically 32 or 64 bits), or several times that size: `intd` is a two word (double) integer and `intq` is a four word (quad) integer. Although the value of a variable is constant, the value may point at a memory location that is read-write.

An aligned vector pointer `av` is a quad integer (`intq`) containing:

- A ‘base pointer’ `int` holding the byte address of an `int` in memory that contains the ‘base (byte) address’ of the vector. Note that the `av` value does not contain the base address, but contains instead this pointer to where the base address is stored in memory. This scheme allows the base address to be changed without changing the `av` value.
- An ‘offset’ `int` that is added to the base address to form the byte address of the vector element that has index 0 in the vector (this element does not exist if 0 is not an allowed index).
- A ‘lower bound’ `int` which is the minimum allowed value of the index `int`.

---

<sup>1</sup>‘@’ is analogous to C++ ‘&’ used in a variable declaration, but here ‘@’ can be used with different types of pointers, can be used without restrictions for structure members, and can be used with mutable pointers.

- An ‘upper bound’ `int` which is the maximum allowed value of the index `int` plus 1.

There are other types of pointer. An `fv`, or ‘field vector’, is like an `av` aligned vector except that the offset `int` has a bit address in its high order part and a field size in bits in its low order part. The `ap` (‘aligned pointer’) and `fp` (‘field pointer’) types are similar but do not have the bounds and cannot be indexed. Lastly there is the direct pointer, `dp`, that is just a single `int` containing a byte address; this is most useful for calling C language functions. New pointer types may be defined by the user.

Variables whose names begin with ‘@’ take pointer values, and the variable’s name with the initial ‘@’ removed is called the associated target variable and names the value pointed at. Thus `@V` is a pointer valued variable and `V` is the value `@V` points at. For example:

```
int X = 5
ap *READ-WRITE* int @Y    // `@= local' is implied
Y = X + 2                  // Now Y == 7
Y = Y - 4                  // Now Y == 3
X = X + 1                  // Illegal! X is co
ap ro int @Z = @Y          // Copies pointer value @Y.
                           // Pointer conversion from *READ-WRITE*
                           // to ro is legal.
```

Here the implied ‘@= local’ allocates an `int` to the current function frame, zeros it, and returns an ‘`ap *READ-WRITE* int`’ pointer to its location.

Instead of making a variable point at a `*READ-WRITE*` location you can update the constant variable using the `next` construct:

```
int X = 5
int Y = X + 2              // Now Y == 7; Y is co
next Y = Y - 4             // Now Y == 3; Y is co
Y = Y + 1                  // Illegal! Y is co
```

Here ‘`next Y`’ is a new variable, distinct from `Y`, but with the same type, pointer type, qualifiers, and name ‘`Y`’, which hides the previous variable of the same name. The advantage of doing this is that it makes compilation more efficient by keeping variables constant (i.e., `co`), and it improves debuggability by retaining the different values of the variable for inspection by a debugger.

Loops use the ‘`next ...`’ construct. For example:

```
// Compute sum of 4, 5, and 6.
//
int sum = 0
int i = 4
next sum, next i = while i <= 6:
    next sum = sum + i
```

```
next i = i + 1
```

which is semantically equal to:

```
int sum = 0
int i = 4
next sum, next i:
    next sum = sum + i
    next i = i + 1
next sum, next i:
    next sum = sum + i
    next i = i + 1
next sum, next i:
    next sum = sum + i
    next i = i + 1
```

The ‘`next sum`’ and ‘`next i`’ before the ‘`:`’, which are the output variables for the block of code containing the two ‘`+`’ statements, can also be implied as they appear as output variables of the ‘`+`’ statements, so the above loop can be written as:

```
int sum = 0
int i = 4
while i <= 6:
    next sum = sum + i
    next i = i + 1
```

L-Language has a full set of number types: `int8`, `uns8`, `int16`, `uns16`, `flt16`, `...`, `int128`, `uns128`, `flt128`; for signed integer, unsigned integer, and floating point respectively. The types `int`, `uns`, `flt` are just these types for the target machine word size. The types `intd`, `intq`, `unsd`, `unsq` are just integer types for twice (double) or four times (quad) the target machine word size. The `bool` type is a single bit interpreted as true if 1 and false if 0: it is in essence a 1-bit unsigned integer, but it is not considered to be a number type.

User defined types have values that consist of a sequence of bytes containing fields. Fields in turn can contain subfields. An example is:

```
type my_type:
    uns32                                // Container for:
    [31-24]  uns8 op code                // Operation
    [31]      bool has constant          // Format indicator
    [23-0]    int constant                // Constant
    [23-16]   uns8 src1                   // Source Register
    [15-8]    uns8 src2                   // Source Register
    [7-0]     uns8 des                    // Destination Register
```

```

my type X:
    X.op code = 5          // This is an initialization block
    X.src1 = 2             // for X in which X is *INIT*.
    X.src2 = 3
    X.des = 3
uns op = X.op code        // Now op == 5
int d = X.des             // Now d == 3
ap *READ-WRITE* my type @Y // '@= local' is implied
Y.op code = 129
fp *READ-WRITE* int @C = @Y.constant
ap *READ-WRITE* uns8 @OP = @Y.op code
next op = OP              // Now op == 129
bool B = Y.has constant // Now B == 1
C = -1234                 // Now Y.constant = -1234

```

In this example there is one field in a `my type` value, an unlabeled `uns32` integer. Inside this unlabeled field there are 6 subfields, the first of which is an `uns8` integer occupying the highest order 8 bits of the unlabeled field, bits 31-24, where bits are numbered 0, 1, 2, ... from low to high order. The second subfield is a 1-bit `bool` value that occupies the high order bit, bit 31, of the unlabeled field. Note that subfields can overlap.

Defined type values are aligned on byte boundaries when they are stored in memory. Therefore the ‘`op code`’ subfield is on a byte boundary, and the location of `OP` is an `ap` aligned pointer. Although the `constant` subfield is on a byte boundary, it is shorter than an `int`, and therefore the location of `C` must be an `fp` field pointer. If ‘`op code`’ were in bits 30-23 instead of 31-24, it would not be on a byte boundary and the location of `OP` would also have to be an `fp` field pointer.

Note that ‘`Y.op code`’ is a `*READ-WRITE* uns8` while ‘`@Y.op code`’ is a `co` pointer to a `*READ-WRITE* uns8`.

Names in L-Language can have multiple lexemes, as in the type name ‘`my type`’, the subfield name ‘`op code`’, and what L-Language calls the associated member name ‘`.op code`’ which can be used to access the field.

Another example is:

```

type my type:
    pack
    uns8    kind          // Object Kind
    [7] bool animal      // True if Animal
    [6] bool vegetable    // True if Vegetable
    flt64   weight       // Object Weight
    align   64
    *LABEL* extension

```



```

***                                // Enables type extension.

type my type:
  *OFFSET*  extension
  flt64    height           // Object Height
  flt64    width            // Object Width
  ***                                // Enables type extension.

type my type:
  *OFFSET*  extension
  flt64    volume           // Object Volume; overlays height.
                                // No further type extension allowed.

type your type:
  *INCLUDE* my type // Copy sub-declarations of my type
  *OFFSET* *SIZE*   // *SIZE* is max origin seen so far.
  av uns8 @name     // Aligned vector pointer to name
                    // character string

. . . . .

my type X:
  X.kind = BOX
  X.weight = 55
  X.height = 1023
  X.width = 572

your type Y:
  Y.kind = BEER
  Y.weight = 0.45
  Y.volume = 48
  Y.@name = "John Doe's Lager"

```

Here `my type` and `your type` are defined by statements called *type-declarations*. Each of these *type-declarations* contains a sequence of sub-declarations, e.g., for `my type` the first two sub-declarations are ‘`pack`’ and ‘`uns8 kind`’. There is a current offset in bits that starts at 0 and is updated by each sub-declaration. A sub-declaration such as ‘`uns8 kind`’ allocates a field (i.e., `kind`) at the current offset and adds the size of the field to the current offset.

In the example the fields are `kind`, `weight`, `height`, etc. Fields can be packed or aligned; aligned is the default. An aligned number has an offset that is a multiple of the length of the number. Here fields are initially packed so that since `kind` has offset 0 bytes and size 1 byte, `weight` has offset 1 byte. Subfields `animal` and `vegetable` are 1-bit values inside `kind`.

The `align 64` sub-declaration moves the current offset forward to a 64-bit boundary and causes fields beyond it to be aligned and not packed. A number is aligned if its offset is a multiple of its length. Alignments must be powers of two. A defined type has an alignment equal to the least common multiple (in this case just the largest) of the alignments of its aligned fields.

A `*LABEL*` is like a zero length field that has no value and is used to associate an origin-label with the current offset. Here `extension` has the offset value of 128 bits (16 bytes). The `*OFFSET*` sub-declaration resets the current offset to the offset of a given origin-label, or to `*SIZE*`, which denotes the current size of the type in bits (which may increase with later sub-declarations).

The `***` sub-declaration at the end of a *type-declaration* defining a user defined type indicates that the definition may be continued by a later *type-declaration*, as is done for `my type` above. The sub-declarations of the later *type-declaration* are simply appended to those of previous *type-declarations*.

The `*INCLUDE*` sub-declaration copies all the sub-declarations from another user defined type. If the user defined type is defined by multiple *type-declarations*, only sub-declarations from the *type-declarations* in the current scope (see 12<sup>p101</sup>) are copied.

Defined types can be extended (as per the example), and fields can overlay each other. A defined type value has a size in bytes just large enough to accommodate all its fields. If a defined type has multiple *type-declarations*, this size may not be known until load time.

Values of defined types are strictly run-time values. In contrast, values of `const` type are compile-time values, and are not available at run-time. Number lexemes consisting of digits and optional signs, decimal points, and exponents, are converted to IEEE 64-bit floating point `const` values, as are special numeric-word lexemes such as `inf`, `+inf`, `-inf`, and `nan`. Other number constants represent rational `const` values with unbounded integral numerators and denominators; for example, `D#"1/3"` represents the precise rational one-third. Number constants can be converted to run-time numbers during compilation. However it is a compile error if the result will not fit into the runtime number. This happens, for example, if `1.1`, `1e20`, or `D#"1/3"` is converted to an `int32`.

Quoted strings denote string `const` values that can be converted during compilation to run-time vectors with `co` unsigned integer elements that encode the string in UTF-8, UTF-16, or UTF-32.

Lastly there are map `const` values that can hold lists and dictionaries. Map values can be mutable at compile-time, but cannot be converted to run-time values.

Expressions, statements, and functions that use only `const` values execute at compile-time and can be used to compute compile-time `const` values including maps that represent code.

By default, functions in L-Language are inline. For example,

```
function int r = max ( int x, int y ):
```

```

    if x < y:
        r = y
    else:
        r = x

int x = ...
int y = ...
int z = max ( x, y )

```

L-Language does not support implicit conversions of run-time function results<sup>2</sup>, but does support implicit conversion of variables<sup>3</sup> and constants. Any number constant or rational constant may be converted implicitly to any run-time number type as long as the constant value can be stored exactly in a variable of the run-time type or the run-time type is floating point (in which case there may be loss of precision or conversion to an infinity). Any run-time numeric variable value may be implicitly converted at run-time to a number type that will hold all the possible values of the variable, or to any floating point type (in which case the run-time conversion result may be less precise or an infinity).

Language expressions have **target types**. For a function call, the function result cannot be implicitly converted to the target type. However a function call that returns a **const** result is replaced by its value at compile time, and this value can be implicitly converted to the target type. Also, variable values may be implicitly converted to a target type.

Most builtin operators, such as '+', have operands of the same type as their result.

An example of all this is:

```

flt w = 1.1           // flt is target type of 1.1
int x = 123           // int is target type of 123
int y = 2e5           // int is target type of 2e5
int z = 1e100         // illegal; int is target type of 1e100
                      // which is too large to fit
flt r1 = x            // implicit conversion is legal as x is a
                      // variable name and not a function call
int r2 = 5 + max ( x, y ) // int is target type of +, 5, max, x, y
int r3 = max ( y, w )   // illegal; int is target type of w and
                      // flt cannot implicitly convert to int
int r4 = max ( x, 123 ) // int is target type of max, x, 123
int r5 = max ( x, 123.4 ) // illegal; int is target type of 123.4
                      // which cannot be stored in a int

const c1 = 100
const c2 = 1000
int r6 = max ( x, c1 + c2 ) // legal; c1 + c2 is replaced by 1100

```

---

<sup>2</sup>In this matter L-Language follows ADA.

<sup>3</sup>Unlike ADA.

```
// which has int target type
```

For each type  $T$ , a function:

```
function T r = T ( T v );
r = v
```

is provided. Such an ‘identity’ function might seem useless, but in fact it can be used in an expression ‘ $T(e)$ ’ to force the target type of  $e$  to be  $T$ . As an example consider the following, where there are builtin functions:

```
function N r = N ( N v1 )
function N r = ( N v1 ) "+" ( N v2 )
function bool r = ( N v1 ) "<" ( N v2 )
```

for every number type  $N$ :

```
int x = ...
bool b1 = ( x + 3 < 5 )
    // Illegal: any target type N to which int is implicitly
    // convertible can be used as the target type of "+", so
    // this is ambiguous.
bool b2 = ( flt ( x + 3 ) < 5 )
    // Legal: the argument of flt must have type flt, so that
    // becomes the target type of "+". Because flt (...) is
    // an explicit type conversion, flt is also the target
    // type of 5.
bool b3 = ( x + 3 < int ( 5 ) )
    // Legal: the argument of int must have type int, so that
    // becomes the target type of "5". Because int (...) is
    // an explicit type conversion, int is also the target
    // type of x + 5.
//
```

Integer arithmetic ignores overflows (as in C and C++); for example, if integer  $+$  produces a value too large for its target, the result is undefined and may or may not cause program termination.

There are conversion functions from a floating point type  $F$  to any integer type  $I$  with prototypes:

```
function I r = floor ( F v )
function I r = ceiling ( F v )
function I r = truncate ( F v )
function I r = round ( F v )
```

that take a floating point value and round it toward negative infinity (`floor`), positive infinity (`ceiling`), zero (`truncate`), or nearest (`round`). If the value is too large to be stored in `I`, the result is undefined and may or may not cause program termination.

The `ro` qualifier name can be used by itself as a conversion function name to convert `co` or `*READ-WRITE*` qualifiers to `ro` qualifiers. This can handle cases where a function returns a `*READ-WRITE*` pointer to set an `ro` pointer.

```
function ap *READ-WRITE* int r = foo ( ... )
ap ro int @p = ro ( foo ( ... ) )
```

Although function results cannot be implicitly converted, variables can be, and implicit conversion of `co` or `*READ-WRITE*` to `ro` is defined for pointer-valued variables.

In addition to using target types to select which overloaded function is being called, the types of implicitly convertible arguments, that is, variables and constants, can be used. Essentially function definitions that require fewer implicit conversions are preferred. For example,

```
int x = ...
bool b1 = ( x < 6 )
    // There is a separate "<" operator for every number type,
    // so x and 6 could both be converted to, say, flt. But this
    // is two implicit conversions, whereas using the "<" operator
    // for int requires only one conversion, so this is used.
bool b2 = ( x < 6.5 )
    // Again int is chosen for "<", but this time 6.5 produces a
    // compiler error when converted to an int. Inconvertibility
    // of particular constant values is NOT considered in selecting
    // among overloaded function definitions.
bool b3 = ( x <= floor ( 6.5 ) )
    // Again int is chosen for "<", but this time 6.5 is replaced
    // by 6.0 by the compile-time execution of the floor function.
```

It is possible to define compile-time functions:

```
function const r = max ( const x, const y ):
    if x < y: r = y
    else:    r = x

const x = 2e5
const y = 3e6
const z = 9e4
const w = max ( x, max( y, z ) )
```

Such functions are not available at run-time, and are not really inline, as there is no distinction between inline and out-of-line for compile-time functions.

Inline function definitions may make use of type wildcards. A name that is a single word beginning with `T$` is a type wildcard that denotes an arbitrary type. Thus the example:

```
function T$r r = max ( T$r x, T$r y ):
    if x < y: r = y
    else:     r = x

const x = 2e5
int y = 27e4
int z = max ( x, y )      // T$r is int, x converts to int.
const u = 34e4
const v = max ( x, u )    // T$r is const, all values are const.
const w = max ( x, y )    // Illegal: T$r is const, y is not.
```

A wildcard type of a result variable gets its value from the target type of a function call. A wildcard type of an argument can get its value from the argument type, but only if the later is a variable, or more generally, a reference expression (e.g., `x[i]`). Typing is mostly done top-down using target types, but reference expressions get types bottom up from the variable explicitly named in the reference expression.

Pointer types can be wildcards which must have names that are single words beginning with `P$`. A list of qualifiers can also be a wild card named by a single word beginning with `Q$`. An example is:

```
function uns r = strlen ( P$s Q$s uns8 @s ):
    dp ro uns8 @sdp = *UNCHECKED* ( @s )
    r = call "strlen" ( @sdp )
```

which converts the pointer of type `P$s` to a pointer of type `dp` (direct pointer) and calls the ‘foreign’ C programming language subroutine `strlen` with the direct pointer. The `*UNCHECKED*` function is needed to produce a direct pointer from other pointer types, though this function is undefined for some argument pointer types (e.g., field pointer types).

A pointer type has two places where a qualifier may appear, as in

```
type my control block:
    *READ-WRITE* ap *GLOBAL* ro uns32 @cr
    ....
```

in which `@cr` is a read-write pointer variable pointing at a global read-only `uns32` location `cr`.

Pointer types cannot be cascaded, but there are a work-arounds.

Any inline function can create new code that is inserted after the statement containing a call to the function. The code is expressed as a `const` map value in the format output by the code parser. As a simple example, if the inline function contains:

```

const T = `my number`      // == {"my", "number"}
const V = `my variable`    // == {"my", "variable"}
*INCLUDE* (T, V):
    T V = x + y
    T z = max ( V, 1000 )

```

then a statement calling the inline function will be followed by the code:

```

my number my variable = x + y
my number z = max ( my variable, 1000 )

```

which the parser renders as the `const` map value:

```

{ { { "my", "number", "my", "variable" }, "=",
    { { "x" }, "+", { "y" } } },
  { { "my", "number", "z" }, "=",
    { "max", { { "my", "variable" }, { "1000" },
      ".initiator" => "(",
      ".separator" => ",",
      ".terminator" => ")" } } } }

```

Code to be inserted can also be computed directly as a `const` map value without using ‘`*INCLUDE*`’ statements.

### 3 Lexemes

An L-Language source file is a sequence of bytes that is a UTF-8 encoding of a sequence of UNICODE characters. This is scanned into a sequence of **lexemes**.<sup>4</sup>

Unless otherwise specified, the term ‘**character**’ in this document means a 32-bit UNICODE character.

Lexemes are defined in terms of the following character classes:

```

horizontal-space-character ::= characters in UNICODE category Zs
                                (includes ASCII-single-space)
                                | horizontal-tab-character
vertical-space-character ::= line-feed | carriage-return
                                | form-feed | vertical-tab
space-character ::= horizontal-space-character | vertical-space-character
graphic-character ::= characters in UNICODE categories L, M, N, P, and S
control-character ::= characters in UNICODE categories C and Z
isolated-separating-character ::=

```

---

<sup>4</sup>L-Language lexemes are layered system standard lexemes, which are a compromise between the needs of programming languages and the needs of natural languages.

characters in UNICODE categories **Ps**, **Pi**, **Pe**, and **Pf**;  
 includes { ( [ « » ] ) }  
*separating-character* ::= | | *isolated-separating-character*  
*leading-separator-character* ::= ‘ | ¡ | ¸  
*trailing-separator-character* ::= ’ | ! | ? | . | : | , | ;  
*quoting-character* ::= "  
*letter* ::= characters in UNICODE category **L**  
*ASCII-digit* ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9  
*digit* ::= characters in UNICODE category **Nd** (includes *ASCII-digits*)  
*lexical-item-character* ::= *graphic-character* other than  
*separating-character* or "

Comments may be placed at the ends of lines:

*comment* ::= // *comment-character*\*  
*comment-character* ::= *graphic-character* | *horizontal-space-character*

Lexemes may be separated by *white-space*, which is a sequence of *space-characters*, but, with some exceptions mentioned just below, is not itself a lexeme:

*white-space* ::= *space-character*<sup>+</sup>  
*horizontal-space* ::= *horizontal-space-character*<sup>+</sup>  
*vertical-space* ::= *vertical-space-character*<sup>+</sup>

The following is a special virtual lexeme:

*indent* ::= virtual lexeme inserted just before the first *graphic-character* on a line

**Indent lexemes** have no characters, but do have an **indent**, which is the indent of the graphic character after the indent lexeme. The **indent** of a character is the number of columns that precede the character in the character's physical line. *Control-characters* other than *horizontal-space-characters* take zero columns, as do characters of classes **Mn** (combining-marks) and **Me** (ending marks). All other characters take one column, except for tabs, that are set every 8 columns. Indent lexemes are used to form logical lines and blocks (4<sup>p20</sup>).

One kind of *vertical-space* is given special distinction:

*line-break* ::= *vertical-space* containing exactly one *line-feed*

This is the *line-break* lexeme.

Non-*indent*, non-*line-break white-space*, such as occurs in the middle of text or code outside comments, is discarded and not treated as a lexeme. Such *white-space* may be used to separate lexemes.

*Horizontal-space-characters* other than single space are illegal inside *quoted-string* lexemes (defined below). *Vertical-space* that has no *line-feeds* is illegal (see below). *Control-characters* not in *white-space* are illegal. Characters that have no UNICODE category are *unrecognized-*



*characters* and are illegal:

***misplaced-horizontal-space-character*** ::= *horizontal-space-character*, other than ASCII-single-space  
***misplaced-vertical-space-character*** ::= *vertical-space-character* other than *line-feed*  
***illegal-control-character*** ::= *control-character*, but not a *horizontal-space-character* or *vertical-space-character*  
***unrecognized-character*** ::= character with no UNICODE category or with a category other than **L**, **M**, **N**, **P**, **S**, **C**, or **Z**

Sequences of these characters generate warning messages, but are otherwise like *horizontal-space*:

***misplaced-horizontal*** ::= *misplaced-horizontal-space-character*<sup>+</sup>  
***misplaced-vertical*** ::= *misplaced-vertical-space-character*<sup>+</sup>  
***illegal-control*** ::= *illegal-control-character*<sup>+</sup>  
***unrecognized*** ::= *unrecognized-character*<sup>+</sup>

*Misplaced-horizontal* only exists inside a *quoted-string*, but the other three sequences can appear anywhere. When they occur, these sequences generate warning messages, but otherwise they behave like *horizontal-space*. Specifically, outside *quoted-strings* and *comments* these sequences can be used to separate other lexemes, just as *horizontal-space* can be used, whereas inside *quoted-strings* and *comments* these sequences do nothing aside from generating warning messages.

The lexemes in a L-Language program are specified in Figure 1<sup>p18</sup>. This specification assumes there are no illegal characters in the input; see text above to account for such characters.

The symbol ‘::=’ is used in syntax equations that define lexemes or parts of lexemes whose syntactic elements are character sequences that must not be separated by *white-space*. The symbol ‘:=’ is used in syntax equations that define sequences of lexemes that may and sometimes must be separated by *white-space*.

There is a special ***end-of-file*** lexeme that occurs only at the end of a file.

Files are scanned into sequences of lexemes which are then divided into logical lines as per 4<sup>p20</sup>. After each logical line is formed, *indent*, *comment*, *line-break*, and *end-of-file* lexemes are deleted from the logical line.

A ***special-character-representative*** can consist of a UNICODE character name surrounded by angle brackets. Examples are **<NUL>**, **<LF>**, **<SP>**, **<NBSP>**. There are three other cases: **<Q>** represents the doublequote “”, **<NL>** (new line) represents a line feed (same as **<LF>**), and **<UUC>** represents the ‘**unknown UNICODE character**’ which in turn is used to represent illegal UTF-8 character encodings.

**lexeme** ::= *numeric-word* | *word* | *natural* | *number* | *numeric*  
           | *mark* | *separator* | *quoted-string*  
           | *indent* | *line-break* | *comment* | *end-of-file*  
**strict-separator** ::= *isolated-separating-character* | |<sup>+</sup>  
**leading-separator** ::= ' <sup>+</sup> | ¡ <sup>+</sup> | ¸ <sup>+</sup>  
**trailing-separator** ::= ' <sup>+</sup> | ! <sup>+</sup> | ? <sup>+</sup> | . <sup>+</sup> | : <sup>+</sup> | ; | ,  
**separator** ::= *strict-separator* | *leading-separator* | *trailing-separator*  
**quoted-string** ::= " *character-representative*<sup>\*</sup> "  
**character-representative** ::= *graphic-character* other than "  
                                   | *ASCII-single-space-character*  
                                   | *special-character-representative*  
**special-character-representative** ::= < { *upper-case-letter* | *digit* }<sup>+</sup> >  
**lexical-item** ::= *lexical-item-character*<sup>+</sup> not beginning with //  
**lexical-item** ::= *leading-separator*<sup>\*</sup> *middle-lexeme*<sup>?</sup> *trailing-separator*<sup>\*</sup>  
**middle-lexeme** ::= *lexical-item* not beginning with a *leading-separator-character*  
                                   or ending with a *trailing-separator-character*  
**numeric-word** ::= *sign*<sup>?</sup> **nan** | *sign*<sup>?</sup> **inf**      [where *letters* are case insensitive]  
**word** ::= *middle-lexeme* that contains a *letter* before any *digit*  
                                   and is not a *numeric-word*  
**natural** ::= *decimal-digit*<sup>+</sup> not beginning with 0 | 0  
                                   [but lexical type may be changed; see p20]  
**number** ::= *sign*<sup>?</sup> *integer-part* *exponent-part*<sup>?</sup> that is not a *natural*  
                                   | *sign*<sup>?</sup> *integer-part*<sup>?</sup> *fraction-part* *exponent-part*<sup>?</sup>  
                                   [but lexical type may be changed; see p20]  
**integer-part** ::= *decimal-digit*<sup>+</sup>      **fraction-part** ::= . *decimal-digit*<sup>+</sup>  
**exponent-part** ::= *exponent-indicator* *sign*<sup>?</sup> *decimal-digit*<sup>+</sup>  
**sign** ::= + | -      **exponent-indicator** ::= e | E  
**numeric** ::= *middle-lexeme* that contains a *digit* before any *letter*  
                                   and is not a *natural* or *number*  
**mark** ::= *middle-lexeme* not containing a *letter* or a *digit*  
**indent** ::= see p16      *line-break* ::= see p16  
**comment** ::= see p16      *end-of-file* ::= see p17

Figure 1: L Language Program Lexemes

A *special-character-representative* can also consist of a hexadecimal UNICODE character code, which must begin with a digit. Thus `<OFF>` represents `ÿ` whereas `<FF>` represents a form feed.

**Quoted string lexemes** separated by the `#` mark are glued together if they are in the same logical line. Thus

```
"This is a longer sentence" #
  " than we would like."
"And this is a second sentence."
```

is equivalent to

```
"This is a longer sentence than we would like."
"And this is a second sentence."
```

This is useful for breaking long quoted string lexemes across line continuations. But there is an important case where there is not an exact equivalence between the glued and unglued versions. `"<" # "LF" # ">"` is not equivalent to `"<LF>"`. The former is a 4-character quoted string, the characters being `<`, `L`, `F`, and `>`. The latter is a 1-character quoted string, the character being a line feed.

The definition of a **middle-lexeme** is unusual: it is what is left over after removing *leading-separators* and *trailing-separators* from a *lexical-item*. The lexical scan first scans a *lexical-item*, and then removes *leading-separators* and *trailing-separators* from it. Also *trailing-separators* are removed from the end of a *lexical-item* by a right-to-left scan, and not the usual left-to-right scan which is used for everything else. Thus the *lexical-item* `'¿4,987?,,::'` yields the *leading-separator* `'¿'`, the *middle-lexeme* `'4,987'`, and the four *trailing-separators* `'?'`, `'.'`, `'.'` and `'::'`.

*Words*, *numerics*, and *marks* in the same logical line are glued together if the first ends with `#` and the second begins with `#`. Thus

```
This is a continued-#
      #middle# #-lexeme.
```

is equivalent to

```
This is a continued-middle-lexeme.
```

For compatibility, two consecutive `#` marks may be used to glue together two quoted strings, as in

```
"This is a continued-"#
      #"quoted"# #-string".
```

which is equivalent to

```
"This is a continued-quoted-string".
```

A *numeric-word*, *natural*, or *number* lexeme is a C/C++ constant, and conversely a C/C++ decimal constant that does not end in a *decimal-point* is a *numeric-word*, *natural*, or *number*

lexeme. All these lexemes are given an IEEE double precision number value after the manner of C/C++, and then their lexical type is changed as follows:

- If the value is not a finite number, the new type is *numeric-word*. For example, this applies to `1e500` which converts to the same value as `+inf`.
- If the value is an integer in the range  $[0, 10^{15})$  the new type is *natural*. For example, this applies to `1e3` which converts to the same value as `1000`.
- Otherwise the new type is *number*. For example, this applies to `1e20` or `1.1`.

In contrast, a *numeric*, like `02/28/2022`, represents a character string and in this is like a *word*. The lexeme `2/3` is also a *numeric* and is not used to represent a number; instead the lexeme pair `D# "2/3"` is used to represent a rational number constant (value of `const` type).

## 4 Logical Lines, Blocks, and Statements

Each non-blank physical line begins with an *indent* lexeme that is followed by a lexeme that cannot be an *indent*, *line-break*, or *end-of-file*.

Lexemes are organized into **logical lines**.<sup>5</sup> A logical line begins immediately after an *indent* lexeme, and the **indent** of the logical line is the indent of this *indent* lexeme (i.e., the indent of the first graphic character of the logical line).

A logical line ends with the next *indent* lexeme whose indent is not greater than the indent of the logical line, or with an *end-of-file*. Thus physical lines with indent greater than that of the current logical line are **continuation lines** for that logical line.

A code file is a sequence of ‘**top level**’ logical lines that are required to have indent 0.

A logical line may end with a **block** that is itself a sequence of logical lines that have indents greater than the indent of the logical line containing the block. The block is introduced by a ‘:’ at the end of a physical line, provided the ‘:’ is not inside brackets or quotes (e.g., not inside ( ) or ‘ ’). If the first *indent* lexeme after the ‘:’ has an indent that is not greater than the indent of the logical line containing the ‘:’, the block is empty. Otherwise the indent of this *indent* lexeme becomes the **indent** of the block and the indent of all the logical lines in the block. The first logical line of the block starts immediately after this *indent* lexeme. The block ends just before the first logical line with lesser indent than the block indent, or the end of file. More specifically, the last logical line of the block ends with an *indent* whose indent is less than the block indent, or with an *end-of-file*.

Examples are:

---

<sup>5</sup>L-Language lexemes logical lines and indented paragraphs are layered system bracketed subexpression recognition pass logical lines and paragraphs.

```

this is a top level logical line ending with a block:
  this is the first line of the block
  this is the
    second line of the block
  this is the third line of the block:
    this is the first line of a subblock
    this is the second line
      of the subblock:
        this is the only line of a sub-subblock
    this is the third line of the subblock
  this is the fourth line
    of the block:
      this is the only line of the second subblock
  this is the fifth line of the block
    and it ends with an empty subblock:
this is the second top level
  logical line

```

A warning message is output if two indents that are being compared differ by more than 0 and less than 2 columns, in order to better detect indentation mistakes.

*Line-break* lexemes are effectively ignored. A sequence of *line-break* lexemes is followed by an *indent* or *end-of-file* which is not ignored. Blank physical lines are represented by sequences of more than one *line-break* lexeme, and are effectively ignored.

A logical line that contains *comments*, but no lexemes other than *comments*, *line-breaks*, *indents* and a possible *end-of-file*, is a ‘**comment line**’.

It is an error to begin non-comment logical lines with a *comment*. *Comments* can be used freely in the middle of or at the end of any logical line, or at the beginning of a comment line.

It is an error for the first logical line of a file to have an indent that is greater than 0, the top level indent.

It is an error for a block to be in the middle of a logical line. This means that the first *indent* following the block must have an indent no greater than that of the logical line containing the block.

Examples are:

```

// this is a logical line that is a single comment

// this is a logical line that has two
  // comments

this is a logical line // with a comment

```

```
// and another comment
with three comments // and a last comment

this is a logical line ending with a block:
    First line of the block
    Second line of the block
// Comment that ends block
// Comment that is in error because
    it begins a logical line that this continues

this is a logical line with a block:
    First line of the block
    Second line of the block
    but the block is in error because it is before
    this continuation of the logical line that contains
    the block

this is a logical line ending with a block:
    First line of the block
    Second line of the block
    // comments that end the block, but are in error,
    // because they continue the logical line
    // containing the block
```

After a logical line has been formed, any *indent*, *comment*, *line-break*, and *end-of-file* lexemes in the logical line are removed from the logical line. If the result is empty, e.g., the logical line is a comment line, it is discarded. Otherwise the modified logical line becomes a L-Language ‘*statement*’.

Therefore a file is a sequence of top-level statements.

Since a logical line can end with a block that itself consists of a sequence of logical lines, a statement can end with a block that itself consists of a sequence of statements.

## 5 Expressions

Expressions<sup>6</sup> are built from operators, such as **+** and **\***, and primaries, such as variable names and function calls.

Operators are characterized by fixity, precedence, and format. The L-Language operators are listed in Figures 2<sup>p25</sup>, 3<sup>p26</sup>, and 4<sup>p27</sup>.

Given this, expressions have the following syntax, where an *P-expression* is an expression all of whose operators that are outside brackets have precedence equal to or greater than P:

$$\begin{aligned}
 \textit{expression} &::= (L-1)\text{-expression} \\
 \textit{P-expression} &::= P\text{-initial-operators}^? \\
 &\quad \{ (P+1)\text{-expression} \mid P\text{-middle-operator} \}^+ \\
 &\quad P\text{-final-operators}^? \\
 \textit{P-basic-expression} &::= P\text{-initial-operator}^? \\
 &\quad \{ (P+1)\text{-expression} \mid P\text{-middle-operator} \}^+ \\
 &\quad P\text{-final-operator}^? \\
 \textit{P-initial-operators} &::= P\text{-prefix-operator}^* P\text{-initial-operator} \\
 \textit{P-final-operators} &::= P\text{-final-operator} P\text{-postfix-operator}^* \\
 (H+1)\text{-expression} &::= \textit{non-operator}^+ \\
 \textit{P-operator} &::= \text{operator of precedence P} \\
 \textit{P-initial-operator} &::= P\text{-operator with } \mathbf{initial} \text{ flag} \\
 \textit{P-final-operator} &::= P\text{-operator with } \mathbf{final} \text{ flag} \\
 \textit{P-middle-operator} &::= P\text{-operator with } \underline{\text{neither}} \text{ } \mathbf{initial} \text{ nor } \mathbf{final} \text{ flag} \\
 \textit{P-prefix-operator} &::= P\text{-operator with } \underline{\text{both}} \text{ the } \mathbf{initial} \text{ and } \mathbf{right} \text{ flags} \\
 \textit{P-postfix-operator} &::= P\text{-operator with } \underline{\text{both}} \text{ the } \mathbf{final} \text{ and } \mathbf{left} \text{ flags}
 \end{aligned}$$

where in a *P-expression*:

---

<sup>6</sup>L-Language expressions are layered system standard operator parsing pass expressions with the addition of some operators.

$P$  is any precedence in the range  $[L-1, H]$ ;  
 no two  $(P+1)$ -expressions may be adjacent;  
 each  $P$ -operator with a **left** flag must be preceded by a  $(P+1)$ -expression;  
 each  $P$ -operator with a **right** flag must be followed by a  $(P+1)$ -expression;  
 any operator with an **afix** flag must not be the first  $P$ -operator  
     in a  $P$ -expression;  
 no operator may have both a **initial** and a **left** flag;  
 no operator may have both a **right** and a **final** flag;  
 no operator may have both a **initial** and an **afix** flag;  
 if there is more than one operator in a  $P$ -expression-initial-operators,  
     implicit ‘(’ left parentheses are inserted between operators;  
 if there is more than one operator in a  $P$ -expression-final-operators,  
     implicit ‘)’ right parentheses are inserted between operators;  
 if the implicit parentheses are not balanced, implicit parentheses  
     are inserted at the beginning or end to balance the implicit parentheses;

Essentially the expression being parsed is organized into  $P$ -expressions where  $P$  is the precedence of the  $P$ -expression. Generally a  $P$ -expression consists of a sequence of  $(P+1)$ -expressions and operators of precedence  $P$ . If a  $P$ -expression is not a  $P$ -basic-expression, implicit parentheses are inserted to make the  $P$ -expression into a  $P$ -basic-expression that contains a subexpression that is also a  $P$ -basic-expression. As an example of this, if ‘-’ is a prefix operator, ‘- - x’ is converted to the equivalent of ‘- (- x)’.

The operators can have any combination of the following **base fixities**:

<b>initial</b>	$P$ -operator must be the first thing in its $P$ -expression.
<b>final</b>	$P$ -operator must be the last thing in its $P$ -expression.
<b>left</b>	$P$ -operator must be immediately preceded by a $(P+1)$ -expression in its $P$ -expression.
<b>right</b>	$P$ -operator must be immediately followed by a $(P+1)$ -expression in its $P$ -expression.
<b>afix</b>	$P$ -operator must be after a (not necessarily immediately) preceding $P$ -operator in its $P$ -expression.

The following **combination fixities** are defined:

<b>prefix</b>	<b>initial</b> + <b>right</b>
<b>infix</b>	<b>left</b> + <b>right</b>
<b>postfix</b>	<b>left</b> + <b>final</b>
<b>nofix</b>	none of <b>initial</b> , <b>final</b> , <b>left</b> , or <b>right</b>

All of these but **initial** and **prefix** can be combined with **afix**.



Line Level Operators				
Must Occur Outside Parentheses and Brackets				
At Top Level or Inside { * ... * }				
Operator	Meaning	Fixity	Format	Precedence
if	conditional	prefix	conditional	0000
else if				
else	terminating conditional	initial	terminating conditional	
:	conditional completion	afix right	(none)	
subblock	conditional or declaration completion	afix		
	assignment or loop	postfix	postfix	
type	declaration	prefix	declaration	
pointer type				
function				
reference function				
out-of-line function				
is type		afix infix	(none)	
is function				
--->	abbreviate	infix	binary	
=	assignment	left	assignment	1000
+=	increment	infix	binary	
-=	decrement			
*=	multiply by			
/=	divide by			
=	include			
&=	mask			
^=	flip			
<<=	shift left			
>>=	shift right			
@=	pointer assignment	infix	binary	

Figure 2: L-Language Line Operators

Non-Line Level Operators: Part I  
May Occur Inside or Outside Parentheses and Brackets

Operator	Meaning	Fixity	Format	Precedence
,	separator	nofix	separator	2000
loop	iterator	prefix	unary	3000
while				
until			iteration	
exactly				
at most				
times			iteration modifier	
if	selector	infix	selector	10000
else		infix afix	(none)	
BUT NOT	logical and not	infix	binary	11000
AND	logical and	infix	n-ary	11100
OR	logical or			
NOT	logical not	prefix	unary	11200
==	is equal	infix	infix	12000
!=	is not equal			
<	is less than			
<=	is less than or equal			
>	is greater than			
>=	is greater than or equal			
+	addition	infix	sum	13000
-	subtraction		n-ary	
	bitwise or			
&	bitwise and			
^	bitwise xor			
/	division	infix	binary	13100
*	multiplication		n-ary	13200
**	exponentiation		binary	13300
<<	left shift			
>>	right shift			

Figure 3: L-Language Non-Line Operators

Non-Line Level Operators: Part II  
May Occur Inside or Outside Parentheses and Brackets

Operator	Meaning	Fixity	Format	Precedence
+	no-op	prefix	unary	H-1
-	negation			
~	bitwise complement			
#	length			
D#	decimal rational			
B#	binary rational			
X#	hexadecimal rational			
C#	character rational			

Figure 4: L-Language Non-Line Operators

The operators in Figures 2<sup>p25</sup>, 3<sup>p26</sup>, and 4<sup>p27</sup> have precedences in the range  $[L, H]$ . Precedence  $(L-1)$  is reserved for the ‘error operator’ which is a nofix operator inserted by the parser to ‘fix up’ parsing errors so parsing can continue. Precedence  $(H-1)$  is reserved for prefix operators and precedence  $H$  is reserved for postfix operators (although not all prefix and postfix operators have these precedences).

The first *P-operator* in a *P-expression* determines the *P-expression*’s **format**, which is one of the following, where in describing expression formats we use:

‘expression’ to mean *P-expression*,  
‘operator’ to mean *P-operator*,  
and ‘operand’ to mean  $(P+1)$ -*expression*:

<b>conditional</b>	The expression must consist of the operator followed by an operand followed by either a : operator and an operand or by just a subblock operator (: indented paragraph, which can be an operator).
<b>terminating conditional</b>	The expression must consist of the operator followed by either a : operator and an operand or by just a subblock operator.
<b>postfix</b>	The expression must consist of an operand followed by the operator.
<b>declaration</b>	The expression must consist of an operator followed by an operand (that may contain = and ,) followed sometimes by a subblock operator.
<b>binary</b>	The expression must consist of an operand followed by the operator followed by an operand. There must be only one operator in the expression.
<b>assignment</b>	The expression must consist of an operand followed by the operator followed by an <u>optional</u> operand.

<b>selector</b>	The expression operators must all be either <b>if</b> or <b>else</b> . The expression must consist of alternating operands and operators and begin and end with an operand. The two possible operators alternate, with <b>if</b> first and <b>else</b> last.
<b>separator</b>	All operators in the expression must be identical. There are no other constraints on the expression. An implied empty operand is inserted between two consecutive operators, at the beginning if the expression begins with an operator, and at the end if the expression ends with an operator. Then the operators are deleted from the expression and the expression operator is attached to the expression as its <b>.separator</b> attribute.
<b>infix</b>	The expression must consist of alternating operands and operators and begin and end with an operand.
<b>n-ary</b>	All operators in the expression must be identical. The expression must consist of alternating operands and operators and begin and end with an operand.
<b>unary</b>	The expression must consist of the operator followed by an operand.
<b>iteration</b>	The expression must consist of the operator followed by an operand optionally followed by the afix operator ' <b>times</b> ',
<b>sum</b>	The expression operators must all be either <b>+</b> or <b>-</b> . The expression must consist of alternating operands and operators and begin and end with an operand.

There is an additional special syntactic rule:

1. Non-line bitwise operators (**|**, **&**, **^**, **<<**, **>>**, and **~**) cannot be mixed with non-line arithmetic operators (**+**, **-**, **/**, **\***, and **\*\***) outside parentheses in a subexpression. E.g., '**x + (y \* ~ z)**' is illegal but '**x + (y \* (~ z))**' is legal.

Full semantics of operators and expressions is described later, but the following examples give an idea of some of this semantics:

**T v = x + y \* z**

Here **T** is the **target type** of the expression '**x + y \* z**' and thus must be the result type of the prototype of the **+** function, since function results cannot be implicitly converted. Because it is the result type of **+** and arithmetic operators (with a few exceptions) have operands that are of the same type as their result, **T** is also the target type of **x** and **\***, and since it is the target type of **\*** it will be the target type of **y** and **z**. Implicit conversions of variables are allowed, so **x**, **y**, and **z** will all be converted to type **T** before any computation is done.

**T v = x if y else z**

If **y** is not a **const**, it is evaluated with target type **bool**. If that value is **true**, **x** is

evaluated and returned; otherwise **z** is evaluated and returned. Both **x** and **z**, have target type **T**.

However if **y** is a **const** value, the right-side of the statement is replaced by **x** or **z**, whichever is discarded is also not compiled, and if it would be in error were it compiled, the error is not detected (unless it is a parsing error).

**bool v = x AND y**

If either operand evaluates to **FALSE**, compile-time evaluation stops and the statement is replaced by '**bool v = FALSE**'.

Otherwise same as '**bool v = y if x else FALSE**'.

The **const** values **TRUE** and **FALSE** are implicitly convertible to run-time **bool true** (1) and **false** (0), respectively.

**x < y < z**

This is logically equivalent to '**x < y AND y < z**', except that **y** is evaluated at most once.

If any comparison evaluates to **FALSE** at compile-time, compile-time evaluation stops and the entire expression is replaced by '**FALSE**'.

If a single comparison evaluates to **TRUE** at compile-time, that comparison is removed from the **AND**-containing version of the expression.

If run-time evaluation is necessary, some operands need to be evaluated at run-time, and a target type **T** needs to be found for these operands. A single target type **T** must work as the target type of all the run-time operands. If several target types **T** work and one is the type of a reference expression operand, that is used. Otherwise if several work, it is a compile error.

Changing the expression to '**T(x) < y < z**' will force the target type to be **T** if that works, or a compile error otherwise.

**v[x+5] = y**

The target type of subscript expressions such as '**x + 5**' is **int**.

**~ x**

The '**~**' operator evaluates on signed integers as if they were represented in two's complement by binary values of unbounded size, and similarly for other bitwise operators.

**x \*\* y**

Requires that **y** be a **const** integer; **x \*\* 0 == 1**, **x \*\* 1 == x**, **x \*\* -1 == 1/x** for all **x**.

**x += y**

Means '**x = x + y**', where **x** must be **\*READ-WRITE\***.

**next x += y**

Means '**next x = x + y**'. '**next x**' must be defined.

## 6 Primaries

A **primary** is an *expression* that has no operators outside parentheses or brackets:

```
primary ::=  constant-primary
           |  reference-expression  [p38]
           |  function-call          [p42]
           |  bracketed-expression  [p43]

constant-primary ::= constant other than rational-constant
constant ::= see p34
rational-constant ::= see p35
```

Note that a *rational-constant* is an operator (e.g. **D#**) followed by a *string-constant*, and therefore contains an operator and is not a *primary*.

### 6.1 Names

A **name** is a sequence of lexemes used to name things like variables and functions. Names are building blocks of primaries.

```
name ::= initial-name-item continuing-name-item★
initial-name-item ::= name-item other than natural
continuing-name-item ::= name-item not containing ‘.’
name-item ::=  word containing no ‘.’ that follows a character that is not a ‘.’
                [see text about splitting words with embedded ‘.’s]
                |  natural [see p20]
                |  quoted-word containing no ‘.’ that follows a character
                    that is not the beginning " or another ‘.’
                |  quoted-mark containing no ‘.’ that follows a character
                    that is not the beginning " or another ‘.’
                |  quoted-separator not containing ‘.’s
quoted-word ::= " word "
quoted-mark ::= " mark "
quoted-separator ::= " separator "
```

- ‘.’s must appear at the beginning of *words* and **marks** (examples: ‘**..size**’ and ‘**.\***’). See text about splitting *words* and *marks* with embedded ‘.’s.

*Words* and *marks* containing embedded ‘.’s are split into parts which contain ‘.’s only at their beginning. Thus:

<b>bill.1.weight..size</b>	splits into	<b>bill</b>	<b>.1</b>	<b>.weight</b>	<b>..size</b>
<b>p.@.*</b>	splits into	<b>p</b>	<b>@</b>	<b>.*</b>	
<b>.*.*</b>	splits into	<b>@</b>	<b>.*</b>		
<b>.,.*</b>	splits into	<b>.,</b>	<b>.*</b>		
<b>.*.p</b>	splits into	<b>.*</b>	<b>.p</b>		

However it is a compile error if one of the parts is not a *word* or *mark*, as in the examples where **.1** is a *number* and **.,** is not a legal lexeme.

*Quoted-words* and *quoted-marks* are not split.

A function may be defined with a *name* that is a *quoted-word* or *quoted-mark*, such as "AND" or "+". It may then be called by an expression in which the quotes are omitted, such as **x AND y** or **x + y**. Similarly a function may be defined with a function-term **".\*"** and called by the expression **p.\*** which is split into **p @.\***.

Name items beginning with more than one **'.'** are reserved for use by systems and compilers (e.g., **..size** in the examples). Name items that are words containing **'\$'** or that both begin and end with **'\*'** are similarly reserved. For example, words of the form **'T\$...'** are reserved for use as type wildcards.

A name may begin with a *word* that is a *module-abbreviation* that designates a code module: see 10.7<sup>p98</sup>. For example **std** abbreviates the builtin standard module.

L-Language uses many kinds of names (the numbers in brackets refer to rules below):

**simple-name** ::= *word* not containing any **'.'**s or **'@'**s [2, 3, 6]

**module-abbreviation** ::= *simple-name*

**ma** ::= *module-abbreviation*

**pointer-type-name** ::= *ma*<sup>?</sup> *simple-name* [5]

**basic-name** ::= *name* not containing a **'.'**, *quoted-mark*, or *quoted-separator*  
[1, 2, 3, 6]

**type-name** ::= *ma*<sup>?</sup> *basic-name* not containing **'@'**s [4]

**variable-name** ::= *ma*<sup>?</sup> *basic-name*

**function-variable-name** ::= *variable-name*

**pointer-variable** ::= *variable-name* whose *basic-name* begins with an **@**

**target-variable** ::= *variable-name* whose *basic-name* does not begin with an **@**

**statement-label** ::= *basic-name* not containing **'@'**s

**member-name** ::= *name* beginning with a *word* or *quoted-mark* containing a **'.'**,  
but not containing a *quoted-separator* [2, 3, 6]

(note: all **'.'**s in a *name* must be at the beginning of the *name*)

**pointer-member-name** ::= *member-name* with **@** following the initial **'.'**s

**target-member-name** ::= *member-name* that is not a *pointer-member-name*

**data-label** ::= *basic-name* | *member-name*

$$function-term-name ::= name \text{ not containing a `.` } [1, 2, 3, 6]$$
$$\textit{qualifier-name} ::= \text{co} \mid \text{ro} \mid \text{*READ-WRITE*} \mid \text{*WRITE-ONLY*} \\ \mid \text{*GLOBAL*} \mid \text{*HEAP*}$$

co abbreviates ‘constant’ meaning ‘never changes’

`ro` abbreviates ‘read-only’ meaning ‘other code may change’

\*GLOBAL\* has global (forever) lifetime

\*HEAP\* has lifetime managed by a garbage collector

$$\textit{operator-word} ::= \text{if} \mid \text{else} \mid \text{while} \mid \text{until} \mid \text{AND} \mid \text{OR} \mid \text{NOT} \mid \text{BUT}$$
$$\begin{array}{lcl} \textit{function-keyword} & ::= & \text{no} \mid \text{not} \mid \text{function} \\ & & \mid \text{"="} \mid \text{" ,"} \mid \text{"("} \mid \text{")"} \mid \text{"["} \mid \text{"]"} \end{array}$$

*wild-card* ::= *simple-name* beginning with *wild-card-prefix*

*wild-card-prefix* ::= one of:

**T\$** name is assigned a *type-name*

**P\$** name is assigned a *pointer-type-name*

**Q...\$** *qualifier-wild-card*; name is assigned a list of *qualifier-names* subject to *qualifier-wild-card-flags* ‘...’

$$\textit{qualifier-wild-card} ::= \mathbf{Q} \textit{ qualifier-wild-card-flag}^{\star} \mathbf{\$}$$

*qualifier-wild-card-flag* ::= one of:

**R** readable, excludes **\*WRITE-ONLY\***

**W** writable, excludes ro and co

**U** allows undeclared (i.e., neither **\*GLOBAL\*** or **\*HEAP\***) [7]

**G** allows **\*GLOBAL\*** [7]

H allows **\*HEAP\***

The name resolver treats a sequence of names in certain contexts as having the form:

$$\{ \textit{qualifier-name}^{\star} \quad \textit{pointer-type-name} \}^?$$

$$\textit{qualifier-name}^{\star} \quad \textit{type-name} \quad \textit{variable-name}$$

where any *pointer-type-name*, *type-name*, or *variable-name* may begin with a *module-abbreviation*. While scanning this sequence from left to right, the name resolver does not back up after identifying a *qualifier-name*, *module-abbreviation*, *pointer-type-name* or *type-name* in the sequence. As a consequence, the following rules should be followed, least there be various confusing syntax or semantic errors (some violations of these rules will be detected as compilation errors, but some will not be):

1. *Basic-names* and *function-term-names* should not begin with a *module-abbreviation*.
2. *Names* should not contain *function-keywords*.



3. *Names* that are not themselves operator names should not begin with *initial-operators*, end with *final-operators*, or contain *middle-operators*.
4. A *type-name* should not begin with a *pointer-type-name*.
5. A *pointer-type-name* should not begin with a *type-name*.
6. *Names* that are not *qualifier-names* should not contain *qualifier-names*, with the exception that a *qualifier-name* by itself can be a *function-term-name*.
7. If any of L, G, or H are used as a *qualifier-wild-card-flags*, those not used indicate that their corresponding lifetime types are not allowed. If none of L, G, or H are used, all lifetime types are allowed (as if LGH has been used).

*Variable-names*, *type-names*, and *pointer-type-names* that begin with a *module-abbreviation* are called **external**. Non-external names are called **internal**.

A name can abbreviate another name, using the statement:

***abbreviation-statement*** ::= *abbreviating-name* ---> *abbreviated-name*

For example:

bool ---> std bool

Note that it is whole names that are abbreviated, and not parts of names.

The ---> operator executes at compile time. The *abbreviation-statement* must be within the scope<sup>p101</sup> of a definition of the *abbreviated-name*, which must be one of the following kinds:

*pointer-type-name*  
*type-name*  
*qualifier-name*  
*pointer-variable*  
*target-variable*  
*statement-label*  
*pointer-member-name*  
*target-member-name*

The *abbreviating-name* will be of the same kind as the *abbreviated-name*, and must follow the syntax rules of that kind. For example, if the *abbreviated-name* is a *target-name*, the *abbreviating-name* cannot begin with ‘@’.

Note that *function-term-names* used in *function-calls* cannot be abbreviated.

## 6.2 Constants

A **constant** is a value of type **const** computed at compile-time. One type of constant, the map constant, is not actually constant and can be changed.

There are five of types of constants:

```

constant ::=  special-constant
              |  string-constant
              |  number-constant
              |  rational-constant
              |  map-constant
special-constant ::=  TRUE | FALSE | UNDEF | NONE
                      |  *LOGICAL-LINE* | *INDENTED-PARAGRAPH*
string-constant ::=  quoted-string

```

The meanings of the *special-constants* are:

**TRUE** The boolean value true. Convertible to **bool** ( 1 ).

**FALSE** The boolean value false. Convertible to **bool** ( 0 ).

**UNDEF** The value exists but is undefined (unknown).

**NONE** The value does not exist.

**\*LOGICAL-LINE\*** see Section 11 <sup>p100</sup>

**\*INDENTED-PARAGRAPH\*** see Section 11 <sup>p100</sup>

A special constant is not equal to any other constant. The constant **TRUE** can be implicitly converted to the run-time **bool** value 1. The constant **FALSE** can be implicitly converted to the run-time **bool** value 0.

A **string-constant** is just a *quoted-string* lexeme that denotes a character string: see p18 and p19.

String constants can be used to load run-time vectors with **uns8**, **uns16**, or **uns32** type elements. UTF-8, UTF-16, or UTF-32 encodings are used according to element size.

A **number-constant** is an *natural*, *number*, or *numeric-word* lexeme converted to an IEEE 64-bit floating point number.

A number constant may be converted to a run-time number type such as **int32** or **flt64**. It is a compile error to convert to an integer type that cannot hold the exact value of the number. Conversion to a run-time floating type is however never a compile error. If necessary the converted value is **+Inf** or **-Inf** or loses precision.

*Rational-constants* and *map-constants* are described in the following sections.

### 6.2.1 Rational Constants

A **rational constant** is a rational number with unbounded numerators and denominators, where the denominator is at least 1 and the numerator and denominator have no common factors (other than 1). If the denominator is 1, the rational is called a **rational integer**.

Rational constants are computed at compile-time by the operators:

Operator	Argument String
<b>D#</b>	<i>decimal-constant-string</i>
<b>B#</b>	<i>binary-constant-string</i>
<b>X#</b>	<i>hexadecimal-constant-string</i>
<b>C#</b>	<i>character-constant-string</i>

Each of these operators takes a **const** string as its sole argument. The syntax of the argument strings is:

```

sign ::= + | -
exponent ::= { e | E } sign? dit+
decimal-constant-string
    ::= " decimal-natural decimal-fraction? exponent? "
       | " decimal-natural / decimal-natural "
decimal-natural ::= dit+ { , dit dit dit }*
decimal-fraction ::= . { dit dit dit , }* dit+
dit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
binary-constant-string
    ::= " binary-natural binary-fraction? exponent? "
       | " binary-natural / binary-natural "
binary-natural ::= bit+ { , bit bit bit bit }*
binary-fraction ::= . { bit bit bit bit , }* bit+
bit ::= 0 | 1
hexadecimal-constant-string
    ::= " hexadecimal-natural hexadecimal-fraction? exponent? "
       | " hexadecimal-natural / hexadecimal-natural "
hexadecimal-natural ::= hit+ { , hit hit }*
hexadecimal-fraction ::= . { hit hit , }* hit+
hit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | a | b | c | d | e | f | A | B | C | D | E | F
character-constant-string ::= " character-representative "
character-representative ::= see p18

```

where

1. Denominators in fractions must not be zero.

Decimal naturals may have commas every 3 digits from the end and decimal fractions may have commas every 3 digits from the decimal point. Similarly for binary naturals and fractions with commas every 4 binary digits, and with hexa-decimal naturals and fractions with commas every 2 hexa-decimal digits. If there is a decimal point, there must be at least one integer digit and one fraction digit.

For decimal constants without / the denominator is specified by the exponent and is a power of **10**; for binary constants, a power of **2**; and for hexadecimal constants, a power of **16**.

The value of a character constant is the integral UNICODE code point of the *character-representative*.

A rational constant may be converted to a run-time number type such as `int32` or `flt64`. It is a compile error to convert to an integer type that cannot hold the exact value of the rational constant. Conversion of a rational constant to a run-time floating type is however never a compile error. If necessary the converted value is `+Inf` or `-Inf` or precision is lost.

There are also run-time `D#`, `B#`, and `X#` operators (see p139), but rationals cannot be stored at run-time.

### 6.2.2 Map Constants

A **map constant** has two parts, a list (a.k.a, a vector) and a dictionary. Either or both can be empty.

A map constant is computed by an *expression* whose syntax is:

```

map-constant ::= { }
                | { map-list }
                | { map-dictionary }
                | { map-list, map-dictionary }
                | phrase-constant
                | expression-constant
                | type-constant
                | pointer-type-constant

map-list ::= list-element { , list-element }*
map-dictionary ::= dictionary-entry { , dictionary-entry }*
dictionary-entry ::= dictionary-label => dictionary-value
list-element ::= constant-expression
dictionary-label ::= constant-expression evaluating to a string
dictionary-value ::= constant-expression
constant-expression ::= a const valued expression as defined on p78
expression ::= see p23
phrase-constant ::= ‘ expression ’

```

*expression-constant* ::= { \* *expression* \* }  
*type-constant* ::= *type-name*  
*pointer-type-constant* ::= *pointer-type-name*  
*type-name* ::= see p31  
*pointer-type-name* ::= see p31

Maps cannot be represented at run-time.

By abuse of language, **list** is used to refer to a map whose dominant mode of usage is to go through the map list elements sequentially. Similarly **vector** is used to refer to a map whose dominant mode of usage is to access the map list elements randomly using subscripts. And **dictionary** is used to refer to a map whose dominant mode of usage is to access the map's dictionary elements.

Dictionary entries are also called **attributes**. For lists and vectors, they are also called **annotations**.

Each *map-expression* creates a distinct map: no two such maps are `==`. A map created by a *map-expression* is initially set so that it and all its dictionary entries are read-only. This can be changed: see p126.

An ***expression-constant*** is shorthand for the *map-constant* produced when the *expression* is parsed: see p100. Generally, parsing an expression groups expression elements into sublists and moves bracket and separator punctuation to annotations (dictionary entries). Some examples are:

The expression:	Is equivalent to:
{* X = ( Y + 1 ) *}	{ { "X" }, "=", { { "Y" }, "+", { 1 }, ".initiator" =>"(", ".terminator" =>")" } }
{* X, Y = Y, X *}	{ { "X", "Y", ".separator" => ",," }, "=", { "Y", "X", ".separator" => ",," } }
{* X + Y * Z *}	{ { "X" }, "+", { { "Y" }, "*", { "Z" } } }
{* X 3 = Y Z + 1 *}	{ { "X", 3 } "=", { { "Y", "Z" } "+", { 1 } } }

In an  $\{ * \textit{expression} * \}$  constant, line level operators (those in Figure 2<sup>p25</sup>) are recognized if and only if they are outside parentheses in the *expression*.

**Phrase-constants** are like *expression-constants* except that operators (including separators, e.g. ‘,’) are not recognized. Brackets are recognized and create sublists. Some examples contrasting with *expression-constants* are:

The Expression:	Is Equivalent To:
<code>'X = Y + 1'</code>	<code>{ "X", "=", "Y", "+", 1 }</code>
<code>{* X = Y + 1 *}</code>	<code>{ { "X" }, "=", { { "Y" } "+" { 1 } } }</code>
<code>'X = ( Y + 1 )'</code>	<code>{ "X", "=", { "Y", "+", 1,</code> <code>          ".initiator" =&gt; "(",</code> <code>          ".terminator" =&gt; ")" } }</code>
<code>{* X = ( Y + 1 ) *}</code>	<code>{ { "X" }, "=", { { "Y" }, "+", { 1 },</code> <code>          ".initiator" =&gt; "(",</code> <code>          ".terminator" =&gt; ")" } }</code>

Map constants containing parsed code can be computed by *include-assignment-statements*: see p94.

*Type-names* and *pointer-type-names* can be used at compile-time as if they were variables of type `const` with map values. These map values are partly read-only, with the read-only part including elements with labels like `.size` for the size in bits of run-time values of the type. Users can add their own elements if these do not conflict with the names of the read-only elements. See p130.

### 6.3 Reference Expressions

A *reference-expression* computes a **reference pointer** to a location. In some cases the *reference-expression* computes a **real reference pointer** that can be stored in a variable. In other cases a **virtual reference pointer** is computed that can only be used by the *reference-expression* to read a value from the location or write a value into the location.

*Reference-expressions* are simple or compound. A **simple reference-expression** is a *variable-name*, `'next variable-name'`, or *function-variable-name*. A **compound reference-expression** consists of two parts: a **base** that is a smaller *reference-expression*, and an **offset** that follows the base with a `[` or *member-name* (which begins with `'.'`: see p31).

Every *reference-expression* begins with a simple *reference-expression* called the **root** of the *reference-expression*. The root is then followed by zero or more offsets.

The full syntax of a *reference-expression* is:

```

reference-expression ::= simple-reference-expression
                        | reference-base reference-offset
simple-reference-expression ::= variable-name
                                | next variable-name
                                | function-variable-name
reference-base ::= reference-expression

```

```

reference-offset ::=  member-name
                      |  index-list
                      |  member-name index-list

```

```

index-list ::= [ index { , index }* ]

```

```

index ::= expression

```

```

variable-name ::= see p31

```

```

function-variable-name ::= see p31

```

```

member-name ::= see p31

```

1. An *expression* with no operators that begins with a *(function-)variable-name* is a *reference-expression*.

Otherwise an *expression* with no operators is one of:

- (a) a *constant*<sup>p34</sup>, or
  - (b) a (non-reference) *function-call*<sup>p42</sup>, or
  - (c) an explicitly or implicitly parenthesized subexpression preceded by a *module-abbreviation* (see p44 for more information about this last case)
2. If a *reference-expression* begins with a *module-abbreviation*, the *module-abbreviation* is part of the *(function-)variable-name* that is the root of the *reference-expression*. Note that removing the *module-abbreviation* that begins an external *(function-)variable-name* creates a different *(function-)variable-name* that names a different variable.
  3. One dimensional indexing can be used with **av** and **fv** pointers. Multi-dimensional indexing can be used with *member-names* of multi-dimensional fields and sub-fields. Multi-dimensional indexing can also be used with user defined pointers that are the equivalent of multi-dimensional **av** or **fv**, plus reference functions defining *reference-offsets* that use such pointers: see Reference Function Declarations, 10.4<sup>p88</sup>.

Examples of reference pointers are:

```

type my type:
  int X;
  ap mytype @Y

my type Z:      // A virtual pointer is computed to the variable Z.
  Z.X = 5       // A virtual pointer to Z.X is computed.
  Z.@Y = null   // A virtual pointer to Z.@Y is computed.
                // This is virtual both because it points into the
                // local stack where Z is, and also because it points
                // at a location whose type is a pointer type.

ap my type @W:  // A real pointer @W is computed to the variable W.

```

```

W.X = 5      // A real pointer to W.X (denotable by @W.X) is computed.
W.@Y = null  // A virtual pointer to W.@Y is computed.
              // The pointer is virtual because it points at a pointer.
W.@Y = @W    // A virtual pointer to @W is computed and dereferenced
              // to make a real pointer that is the value of `@W'.
              // W.@Y now points at W.

```

Generally a run-time reference pointer is virtual if and only if it points into a local or global stack or it points at a location containing a value of pointer type. Compile time reference pointers (involving `const` values) are always virtual, and consist of either a pointer into a compile-time local or global stack, or a map/index pair.

A virtual reference pointer is replaced by the value it points at in the following situations:

- It was computed by a *reference-base* in a compound *reference-expression* and it points at a run-time pointer value or a compile-time map `const` value.
- It was computed by an entire run-time *reference-expression* with a *pointer-variable* root, it points at a pointer value, and the *reference-expression* is being used to produce a real reference pointer value and not to store a value.

If the root of a *reference-expression* is a *pointer-variable* (beginning with `@`), the reference pointer computed by the entire *reference-expression* is not dereferenced, and it is an error if the reference pointer is not real. If the root is a *target-variable*, the reference pointer is dereferenced, and the pointer may be virtual.

*Reference-expressions* can call *reference-functions* to perform all or some of their computations. There are two kinds of *reference-functions*:

- **Function Variables:** These functions are invoked by *function-variable-names* that are syntactically like *variable-names* which are *simple-reference-expressions* and possibly the roots of compound *reference-expressions*.
- **Function Offsets:** These functions are invoked by *reference-offsets* in compound *reference-expressions* that act like postfix operators on real reference pointers produced by the bases of the compound *reference-expressions*.

For details on calls to *reference-functions* see Reference Functions<sup>p88</sup>. The rest of this section applies to *reference-expressions* that do not make these calls.

A *member-name* of the form ‘`.data-label`’ may be used to select a field or subfield of a user defined type<sup>p58</sup> value or a dictionary entry of a *map-dictionary*.

An *index* may be used to select an element of a vector or array in a user defined type value, or the element of a vector pointed at by a pointer, or an element of a *map*. An *index* can be a *const* string. In general, if “*S*” is a `const` string, “[*S*”] is equivalent to ‘*S*’. This can be



Reference Expression Result Pointer Target or Value Qualifiers Given Base and Field Qualifiers					
Base Access Qualifier	Field Access Qualifier				
	(none)	co	ro	*READ-WRITE*	*WRITE-ONLY*
co	co	co	co	co	(illegal)
ro	ro	co	ro	ro	(illegal)
*READ-WRITE*	*READ-WRITE*	co	ro	*READ-WRITE*	*WRITE-ONLY*
*WRITE-ONLY*	*WRITE-ONLY*	(illegal)	(illegal)	*WRITE-ONLY*	*WRITE-ONLY*
*INIT*	*INIT*	*INIT*	*INIT*	*INIT*	*INIT*

1. Here *\*INIT\** is a pseudo-qualifier used for bases that are being initialized. It has the same effect as *\*WRITE-ONLY\** except that it forces fields/subfields of the base to be *\*INIT\** even if they are *co* or *ro*.
2. The *reference-expression* has the same lifetime qualifier (*\*GLOBAL\**, *\*HEAP\**, or undeclared ) and lifetime depth as the base (see 13<sup>p106</sup>).

Figure 5: Reference Expression Qualifier Computation

used with a run-time *reference-expression* as a field or subfield label, or with a compile-time *reference-expression* to select a map *dictionary-entry*.

Otherwise the *index* must be a positive or negative integer. Bounds imposed by user defined types or stored in a pointer are used to check that the *index* is within range. The target type of a run-time *index* is **int**.

The type of a run-time *reference-expression* is computed bottom up starting with the type of the root. Run-time virtual reference pointers are just like real reference pointers of **ap** or **fp** type, except that a virtual pointer may point into the run-time local or global stack or may point at a pointer datum. The reference pointer for a *variable-name* root of the reference expression is in essence an **ap** pointer with *co* or *\*INIT\** qualifier pointing into the local or global stack. *Reference-offsets* modify this as the *reference-expression* is computed. At some point the virtual reference pointer may point at a real pointer datum and be replaced by that real pointer datum according to the rules above.

When a *member-name reference-offset* specifying a field in a user defined type modifies a virtual or real reference pointer, the qualifiers of the resulting reference pointer are determined according to Figure 5. The target type of the modified pointer is provided by the *member-name reference-offset*, which may also change the (effective) pointer type of the modified reference pointer from **ap** to **fp**. Note that if the qualifiers of the unmodified reference pointer are *co* or *\*INIT\**, these remain the qualifiers of the modified reference pointer.

Computing types of reference pointers is a bottom-up process, and is different from computing types of general sub-*expressions*, which are top-down using a target type provided by the *statement* containing the sub-*expression*. Since the type of a *reference-expression* does not depend on its containing *statement*, implicit conversion of a *reference-expression* value to a *statement* provided target type is allowed, whereas implicit conversion of a sub-*expression* that is a *function-call* is not allowed.

Reference pointers at compile-time either point into the compile-time local or global stacks or consist of a map/index pair of **const** value. These pointers always point at a **const** value, and are always virtual – there are no real compile-time reference pointers. A *reference-offset* always dereferences the current reference point to a **const** value that must be a map, and then forms a map/index pair for the new reference pointer.

Map **const** values are represented internally by pointers to where the map is stored, so that if **X** is a variable equal to, i.e., pointing at, a map, then **Y = X** copies the pointer to the map to the variable **Y**. By default map constants are read-only and cannot be changed, but it is possible to mark a whole map as read-write, and to independently mark dictionary members as either read-only or read-write. Dictionary members are marked read-only when they are initially created.

The following example illustrates computation with map constants:

```
const U = {"A", "B"}[0] // Illegal: {"A". "B"} is not a simple
                        // reference expression.

const X = {"A", "B"}
const V = X[0]          // Legal, == "A".
X[0] = "C"              // Illegal, X is read-only.
read-write ( X )
X[0] = "C"              // Now X is {"C", "B"}.
const Y = X              // Now X and Y are both {"C", "B"}.
Y[1] = "D"              // Now X and Y are both {"C", "D"}.
const Z = { Y, "M" }    // Now Z is {{ "C", "D" }, "M" }.
Z[0].W = "N"            // Now Z is {{ "C", "D", "W" => "N" }, "M" },
                        // X and Y are both {"C", "D", "W" => "N"}.

X.W = "P"               // Illegal, X.W is read-only.
read-write ( X, "W" )
X.W = "P"               // X and Y are both {"C", "D", "W" => "P"}.
                        // Now Z is {{ "C", "D", "W" => "P" }, "M" },
```

## 6.4 Function Calls

The syntax of function calls is:

**function-call** ::=  
*module-abbreviation*? *parenthesized-call-argument-list*<sup>\*</sup> *call-term*<sup>+</sup>

$\text{call-term} ::= \text{call-term-name call-argument-list}^*$   
 $\quad \quad \quad | \text{no call-term-name}$   
 $\quad \quad \quad | \text{not call-term-name}$   
 $\text{call-term-name} ::= \text{function-term-name with quotes optionally removed from}$   
 $\quad \quad \quad \text{quoted-words, quoted-marks, and quoted-separators}$   
 $\text{function-term-name} ::= \text{see p32}$   
 $\text{call-argument-list} ::= (\text{actual-argument } \{ , \text{actual-argument} \}^* )$   
 $\quad \quad \quad | [ \text{actual-argument } \{ , \text{actual-argument} \}^* ]$   
 $\quad \quad \quad | ( ) | [ ]$   
 $\text{parenthesized-call-argument-list} ::=$   
 $\quad \quad \text{call-argument-list with parentheses } ( ) \text{ (and not square brackets } [ ])$   
 $\text{actual-argument} ::= \text{expression}$   
 $\text{expression} ::= \text{see p23}$

1. *Call-term-names* cannot be abbreviated.
2. *Call-terms* of the form ‘no x’ and ‘not x’ are equivalent to ‘x(FALSE)’.
3. *Parenthesized-call-argument-lists* may have implicit parentheses.
4. There must be at least one explicit or implicit *parenthesized-call-argument-list* just before or just after the first *call-term-name* (to distinguish *function-calls* from *reference-expressions*).

Thus a *function-call* is an optional *module-abbreviation* followed by a sequence of *function-term-names* and *call-argument-lists*. Note that *Function-term-names* cannot contain ‘.’s and therefore cannot be *member-names*, which are reserved for *reference-calls*<sup>p88</sup>. Also any [ ] bracketed *call-argument-lists* must be preceded by a *parenthesized-call-argument-list*, a syntactic distinction to their use in *reference-calls*.

*Function-calls* are matched to *function-prototypes* in *function-declarations*. The *call-term-names* in a match are identical to the *function-term-names* taken from the prototype being matched, except that quotes (") in a prototype *quoted-word*, *quoted-mark*, or *quoted-separator* may (or may not) be omitted in the *function-call*. The first step in matching is to scan the *function-call* to identify the *call-term-names*. There is no parser backing up after this is done: if the results of this initial scan do not lead to a satisfying match, the entire call-declaration match fails.

## 6.5 Bracketed Expressions

The syntax of a *bracketed-expression* is:

$$\begin{aligned}
\textit{bracketed-expression} &::= \textit{ma}^? ( \textit{expression} ) \\
&| [ \textit{expression} ] \\
&| \{ \textit{expression} \} \\
&| ' \textit{expression} ' \\
&| \{ * \textit{expression} * \} \\
\textit{ma} &::= \textit{module-abbreviation} \quad [\text{see p31}]
\end{aligned}$$

Arithmetic subexpressions and some function argument lists are bracketed with  $()$  brackets. Reference expression index lists and some function argument lists are bracketed with  $[]$  brackets. Expressions that compute map constants are bracketed with  $\{ \}$ ,  $' '$ , or  $\{ * * \}$ , brackets (see 6.2.2<sup>p36</sup>).

An expression of the form  $'\textit{ma} ( \textit{expression} )'$  is just syntactic sugar for  $'( \textit{ma} \textit{expression} )'$ , except that the *expression* is parsed before the *ma* is moved inside the  $()$ 's. Thus if *mom* is a *module-abbreviation*,  $'\textit{mom} ( \textit{x} + \textit{y} * \textit{z} )'$  is syntactic sugar for

$$( \textit{mom} \textit{x} "+" ( \textit{y} "*" \textit{z} ) )$$

in which the parenthesis pair surrounding  $'\textit{y} "*" \textit{z}'$  is implied. This allows the *module-abbreviation* to be applied to the outermost operator in the *expression*.

## 7 Assignment Statements

*Assignment-statements* have a list of variables on the left side of an  $"="$  operator which receive values from a list of expressions or a block of code on the right side of the operator. The left-side variables and the  $"="$  may be omitted if the right side produces no values, or if all left-side variables have the form of  $'\textit{next variable-name}'$  and are implied by the right side.

The forms of an *assignment-statement* are:

$$\begin{aligned}
\textit{assignment-statement} &::= \textit{expression-assignment-statement} \\
&| \textit{call-assignment-statement} \\
&| \textit{block-assignment-statement} \\
&| \textit{deferred-assignment-statement} \\
&| \textit{loop-assignment-statement} \\
&| \textit{isolated-declaration-statement}
\end{aligned}$$

$$\begin{aligned}
\textit{expression-assignment-statement} &::= \\
&\textit{assignment-result} \{ , \textit{assignment-result} \}^* = \textit{expression-list}
\end{aligned}$$

*expression-list* ::= see p48

*call-assignment-statement*

$$\begin{aligned}
&::= \textit{assignment-result} \{ , \textit{assignment-result} \}^* = \textit{assignment-call} \\
&| \textit{assignment-call}
\end{aligned}$$

*assignment-call* ::= *function-call* | *call-expression*

*function-call* ::= see p42

*call-expression* ::= see p98

**block-assignment-statement** ::=

*block-variable-declaration* { , *block-variable-declaration* }<sup>\*</sup>  
     { = { **do** *block-label* }<sup>?</sup> }<sup>?</sup> :  
         *statement*<sup>\*</sup>  
         *exit-subblock*<sup>\*</sup>  
 | **do** *block-label*<sup>?</sup> :  
     *statement*<sup>\*</sup>  
     *exit-subblock*<sup>\*</sup>

**deferred-assignment-statement** ::=

*result-variable-declaration* { , *result-variable-declaration* }<sup>\*</sup> = \*DEFERRED\*

**loop-assignment-statement** ::=

*block-variable-declaration* { , *block-variable-declaration* }<sup>\*</sup> =  
     *iteration-control* :  
         *statement*<sup>\*</sup>  
         *exit-subblock*<sup>\*</sup>  
 | *iteration-control* :  
     *statement*<sup>\*</sup>  
     *exit-subblock*<sup>\*</sup>

**isolated-declaration-statement** ::= *result-variable-declaration*

**exit-subblock** ::= *exit-label* **exit** :  
                     *statement*<sup>\*</sup>

*iteration-control* ::= see p54

**block-label** ::= *statement-label*

**exit-label** ::= *statement-label*

*statement-label* ::= see p31

**assignment-result** ::= *block-variable-declaration*  
                             | *reference-expression*

*reference-expression* ::= see p38

**block-variable-declaration** ::= *result-variable-declaration*  
                                     | *next-variable-declaration*

**result-variable-declaration** ::=  
     *type-name* *target-variable*  
 | *pointer-type-name* *qualifier-name*<sup>\*</sup> *type-name*  
     *pointer-variable* { @= *allocation-call* }<sup>?</sup>

**next-variable-declaration**

::= **next** *target-variable-name*  
     | **next** *pointer-variable-name* { @= *allocation-call* }<sup>?</sup>

*qualifier-name* ::= see p32  
*pointer-type-name* ::= see p31  
*type-name* ::= see p31  
*variable-name* ::= see p31  
*target-variable* ::= see p31  
*pointer-variable* ::= see p31  
***allocation-call*** ::= *function-call*

where

1. For a *pointer-variable* with an *allocation-call*, the *allocation-call* allocates and zeros memory for the associated *target-variable*, and returns a pointer to the allocated memory that is stored in the *pointer-variable*. For such a *pointer-variable* it is the associated *target-variable* that is set by the *assignment-statement*.
2. For an *isolated-declaration-statement* declaring a *pointer-variable* with no *allocation-call*, ‘@= local’ is implied if the *pointer-variable* has no lifetime qualifier (is undeclared), and ‘@= global’ is implied if the *pointer-variable* has the \*GLOBAL\* qualifier.
3. For an *isolated-declaration-statement* ‘= \*DEFERRED\*’ is implied unless the declaration is of a \*READ-WRITE\* *pointer-variable*.
4. An *isolated-declaration-statement* declaring a \*READ-WRITE\* *pointer-variable* (for which ‘= \*DEFERRED\*’ is not implied) is equivalent to a *block-assignment-statement* with an empty subblock.

Associated with *block-assignment-statements* and *loop-assignment-statements* there are *control-statements* to control the flow of execution within the more complex *assignment-statement*:

***control-statement*** ::= *block-control-statement* [p50]  
                                   | *loop-control-statement* [p54]

A ...-*variable-declaration* allocates memory for its variables in the frame of the currently executing out-of-line function. The sizes of these variables must be known at compile time. For a *pointer-variable* it is the pointer itself that is allocated to the currently executing out-of-line function; the memory pointed at can be allocated elsewhere. For sizes not known at compile time, a pointer to the variable can be allocated by an *allocation-call* that is given the variable size at run-time.

*Expression-assignment-statements* set the values of their result variables to the values of the *expressions* in the *expression-list*. *Call-assignment-statements* set the values of their result variables to the values returned by the *function-call*.

A *block-variable-declaration* initializes its variables according to the declaration syntax as follows:

Non-**next** variable declaration with no *allocation-call*:

The memory is zeroed.

**Next** variable declaration with no *allocation-call*:

Previous value of the named variable.

Variable declaration with *allocation-call*:

Value returned by the *allocation-call* (the allocated memory is zeroed).

Zeroed numbers are zero, while zeroed pointers typically cause segmentation faults when de-referenced.

In a *block-assignment-statement*, variables declared by *block-variable-declarations* without *allocation-calls* are given the qualifier **\*INIT\*** in *statements* of the *block-assignment-statement* and **co** after the *block-assignment-statement*. The **\*INIT\*** qualifer is equivalent to **\*WRITE-ONLY\*** except that it forces fields and elements of the value to also be **\*INIT\***<sup>p41</sup>.

In a *block-assignment-statement*, *pointer-variables* declared by *block-variable-declarations* with *allocation-calls* are initialized by the *allocation-call* (see p51) and are thereafter **co**, but the memory pointed at is zeroed initially, **\*INIT\*** in *statements* of the *block-assignment-statement*, and subject to the *pointer-variable qualifiers* after the *block-assignment-statement*.

A *loop-assignment-statement* is similar to a *block-assignment-statement* except that variables declared by *next-variable-declarations* are reallocated for each iteration of the loop, and the value given by the previous iteration can be read by the current iteration using the *variable-name* (without a preceding '**next**'). Non-**next** variables are allocated only at the start of the *loop-assignment-statement*, and are **\*INIT\*** (and not readable) throughout all iterations.

If a *declaration* declares a *pointer-variable*, an associated *target-variable* is implicitly declared at the same time whose name is the *pointer-name* with the initial '@' removed. The *target-variable* is not itself allocated to memory, but instead references the value the *pointer-variable* points at.

Note that a variable declaration does not allow qualifiers on anything but the target of a pointer. The implicit qualifier of a declared variable is **co** after the *assignment-statements* meaning that the value of the variable once initially set is never changed. The qualifiers of a *target-variable* associated with a *pointer-variable* are **\*INIT\*** in the subblock *statements* of a *block/loop-assignment-statement* and those of the target of its associated pointer after the *block/loop-assignment-statement*.

A *next-variable-declaration* for a variable **v** must occur in the scope of either a non-*next-variable-declaration* for **v** or another *next-variable-declaration* for **v**. Furthermore, **v** cannot be a *target-variable* associated with a *pointer-variable*. The *next-variable-declaration* re-declares **v** making a new variable that hides the previously declared **v**. The new variable has the same types and qualifiers as the previous variable named **v**.

A *next-variable-declaration* for a variable **v** enables '**next v**' to be used as an *assignment-result* within the subblock *statements* of a *block/loop assignment-statement*. Use of **v** within these statements without the '**next**' refers to the value of **v** just before a *block-assignment-*

*statement* or current *loop-assignment-statement* iteration was executed.

Under some circumstances ‘**next v**’ will be implicitly added to the *assignment-result* list of a *call-statement* (see p49), the *block-variable-declaration* list of a *block-assignment-statement* (see p52), or the *block-variable-declaration* list of a *loop-assignment-statement* (see p55).

A *deferred-assignment-statement* behaves like a *block-assignment-statement* with an empty block, but in addition allows each of its variables to be redeclared in a subsequent ‘companion’ *block-variable-declaration* which does not reallocate the variable (there may be separate companions for different variables).

For loops, 4 copies of the variables allocated by an iteration are allocated to the out-of-line function frame when the function is called, and the loop cycles among these copies. A call to ‘**local**’ inside a loop stores a pointer value in one of these 4 copies. If such a pointer is already allocated by a previous loop iteration, its memory is reused, or doubled in size and reallocated. This means that the total memory allocated to a pointer inside a loop copy by ‘**local**’ will never be more than 4 times the size of the maximum memory needed for any single loop iteration. As there can be 4 copies of the iteration variables, a call to ‘**local**’ inside a loop may allocate to the stack at most  $4 \times 4 = 16$  times as much memory as any single iteration call to ‘**local**’.

## 7.1 Expression Assignment Statements

The syntax of an *expression-assignment-statement* is:

***expression-assignment-statement*** ::=  
     *assignment-result* { , *assignment-result* }<sup>\*</sup> = *expression-list*  
***expression-list*** ::= *expression* { , *expression* }<sup>\*</sup>  
*assignment-result* ::= see p45  
*expression* ::= see p23

where

1. The number of *expressions* must equal the number of *assignment-results*.
2. The *expression-list* must not consist of a single *expression* which is a *function-call* (else the *statement* is a *call-assignment-statement* as described in 7.2<sup>p49</sup>). However the *expression-list* may consist of a single *reference-call*.

Sub-*expressions* computable at compile-time are evaluated in bottom-to-top left-to-right order and replaced by their **const** values before the *statement* is compiled into run-time code. At run-time *expressions* are evaluated in bottom-to-top left-to-right order and then the *expression* values are stored in the *assignment-results*.

Variable names declared by *result-variable-declarations* that are *assignment-results* are not visible to the *expressions*. In particular, if ‘**next V**’ is an *assignment-result*, the name ‘**V**’ in an



*expression* will refer to the variable that exists before the *expression-assignment-statement*.

The type of an *assignment-result* becomes the **target type** of its corresponding *expression*. If the *expression* is a *function-call*, the type of the first result of the *function-prototype* must match the target type of the *expression*, and the types of the prototype arguments become the target types of the *actual-argument* sub-expressions.

If an *expression* is a *reference-expression* or a *constant-expression* (which is replaced by a constant), it will be implicitly converted to its target type if possible.

An example is:

```
int x = 5           // target type of 5 is int
flt y = 6           // target type of 6 is flt
flt z = 7           // target type of 7 is flt
flt r1 = x + y       // target type of +, x, y is flt
flt r2 = x + y * z   // target type of +, x, *, y, z is flt
next x = z           // illegal; target type of z is int
```

Here the + and \* operator functions are only defined for cases where their operand types are the same as their result type, and **int** variables may be implicitly converted to **flt** but not vice-versa.

## 7.2 Call Assignment Statements

The syntax of a *call-assignment-statement* is:

***call-assignment-statement***

$::= \text{assignment-result } \{ , \text{assignment-result} \}^* = \text{assignment-call}$   
 $\quad \mid \text{assignment-call}$

***assignment-call***  $::= \text{function-call} \mid \text{call-expression}$

*assignment-result*  $::=$  see p45

*function-call*  $::=$  see p42

*call-expression*  $::=$  see p98

A *call-assignment-statement* with *assignment-results* follows the same general rules as *expression-assignment-statements* except that its right side is a single *function-call* or the functionally similar *call-expression* and the result values of the call are stored in the *assignment-results* proceeding left-to-right. Excess call results are discarded. There must be at least as many call results as there are *assignment-results*.

The types of the function prototype results cannot be implicitly converted to the types of the *assignment-results*.

The right side of a *call-assignment-statement* may have an implied '**next** *v*' if the *function-prototype* has a '**next** *w*' *prototype-result-declaration* and a *prototype-argument-declaration* of the form ' $\dots$  *type-name w*', and *v* is a *variable-name* that by itself is the actual argument

matched to  $w$  (see p74). An example is:

```
function next w = inc ( int w ):
    next w = w + 1
int v = 5
inc ( v )    // Equivalent to `next v = v + 1'.
```

### 7.3 Block Assignment Statements

The syntax of *block-assignment-statements* is:

```
block-assignment-statement ::=
    block-variable-declaration { , block-variable-declaration }*
    { = { do block-label }? }? :
        statement*
        exit-subblock*
| do block-label? :
    statement*
    exit-subblock*
block-variable-declaration ::= see p45
exit-subblock ::= exit-label exit:
    statement*
exit-label ::= statement-label
statement-label ::= see p31
statement ::= see p22
exception-subblock ::= exit-subblock whose exit-label is *EXCEPTION*
block-control-statement ::= goto-exit-statement | throw-statement
go-to-exit-statement ::= see p51
throw-statement ::= see p51
```

where

1. The exit-label **\*EXCEPTION\*** is special and any *exception-subblock* must be the last *exit-subblock* in the *block-assignment-statement*.

The *block-assignment-statement* first allocates and initializes memory in the current function frame for the variables declared by the *block-variable-declarations*.

Then any *statements* and *exit-subblocks* are executed. During this execution block variables not set by an *allocation-call* are **\*INIT\***<sup>p41</sup>, and after this execution, these variables become **co**. During this execution pointer variables set by an *allocation-call* are **co**, but their target type is changed to **\*INIT\***, and after execution the target type qualifiers become whatever the pointer variable declarations specify.

When a declaration has an *allocation-call*, its variable must have pointer type, and the *allocation-call* is executed to set the pointer before any *statements* in the *block-assignment-statement* are executed. The *allocation-call* is executed with a pre-pended argument list consisting of two **uns** values in () parentheses. The first value is the number of bytes to be allocated, and the second value is the byte alignment of the memory to be allocated. The *prototype-pattern* of the called function's prototype<sup>p73</sup> must begin with '( **uns** **length**, **uns** **alignment** )', although the argument names may be different. The called function must allocate a block of memory with the required number of bytes and alignment and zero that block. The prototype must have exactly one result variable whose type is identical to the the pointer type of the *pointer-variable* being set (but the prototype result type may contain wildcards).

As a general rule, allocator functions that return a value of type **av** or **fv** or a user defined vector pointer have a [] argument list with a single argument giving a vector size **N**. The allocator allocates not a single block of the given length and alignment, but instead a vector of **N** such blocks, with zero padding between the blocks if necessary to obtain proper alignment for each block. However, this is by convention and is not a builtin requirement of the L-Language. The convention is followed by the builtin allocators (e.g., **local**).

A *go-to-exit-statement* within a block may exit the block or enter an *exit-subblock* of the block:

**go-to-exit-statement** ::= **go to** *go-to-label* **exit**  
**go-to-label** ::= *block-label* | *exit-label* other than \*EXCEPTION\*

Unless a *go-to-exit-statement* is executed, a block exits after the last *statement* in the block, and an *exit-subblock* exits its containing block after the last *statement* in the *exit-subblock*.

A *go-to-exit-statement* in an *exit-subblock* may only enter a subsequent *exit-subblock* or exit any of its containing *block-assignment-statements* by using that block's *block-label*.

An *exception-subblock* is entered if any preceding *statement* in the *block-assignment-statement* executes a:

**throw-statement** ::= **throw** *throw-ID*?  
**throw-ID** ::= *expression* evaluating to an **uns** integer

If a **throw-statement** is executed in an *exception-subblock*, it behaves as if the containing *block-assignment-statement* were replaced by the **throw-statement**. If a *block-assignment-statement* has no *exception-subblock*, it behaves as if it did have an *exception-subblock* whose only statement was a '**throw**' statement (without *throw-ID*).

A *throw-statement* with *throw-ID* stores the *throw-ID* and statement program counter in the **std current exception data**: see section 18.7<sup>p145</sup>. A *throw-statement* without a *throw-ID* leaves the **std current exception data** untouched.

A statement that has a fault, such as a memory fault or an integer divide-by-zero fault, executes as a *throw-statement* with one of the builtin *throw-IDs* of section 18.7<sup>p145</sup>.

*Go-to-exit-statements* define various possible execution paths through a *block-assignment-statement* (these are paths in an acyclic graph). It is a compile error if a *statement* within the *block-assignment-statement* uses a declaration and the statement can be reached by a path that does not contain the declaration. Note that declarations not in *exit-subblocks* have scope that includes the *exit-subblocks*, but declarations within an *exit-subblock* have scope that ends with the end of the *exit-subblock*. A *function declaration* is ‘used’ if and only if its prototype matches a *function-call*.<sup>7</sup>

There is an exception to the last paragraph for *exception-subblocks*. In these any `co` variable allocated in the *block-assignment-statement* may be read, but the value will be zero or `null` if the variable’s declaration has not been executed. The ‘`is set`’ function<sup>p145</sup> should be used to test a variable in this case.

If ‘`next variable-name`’ is used as an *assignment-result* of some *statement* within a *block-assignment-statement* that is not within the scope of a *result-variable-declaration* for the *variable-name* that is also within some *statement* of the *block-assignment-statement*, then ‘`next variable-name`’ will be automatically added to the *block-variable-declarations* of the *block-assignment-statement*, if it is not already there. For example:

```
int x = 5
do:
    next x = x + 1
```

is equivalent to:

```
int x = 5
next x = do:
    next x = x + 1
```

## 7.4 Deferred Assignment Statements

The syntax of *deferred-assignment-statements* is:

***deferred-assignment-statement* ::=**  
*result-variable-declaration* { , *result-variable-declaration* }<sup>\*</sup> = **\*DEFERRED\***  
*result-variable-declaration* ::= see p45

Each variable declared by a *result-variable-declaration* of a *deferred-assignment-statement* must be declared identically, except for addition or subtraction of an *allocation-call*, as a *block-variable-declaration* of a *block-assignment-statement* that is within the scope<sup>p101</sup> of the *deferred-assignment-statement*. The *block-assignment-statement*, known as the **companion** of the *result-variable-declaration*, computes the value of the declared variable, except in the case of a pointer variable whose value is set by an *allocation-call* in the *deferred-assignment-*

---

<sup>7</sup>Stack space for every stack variable that might be used by an out-of-line function is allocated when the out-of-line function is called. Space allocated by the `local` function is treated differently: see p117.

*statement*. If a *deferred-assignment-statement* is in a module (10.7<sup>p98</sup>), companions of its *result-variable-declarations* must be in that module or its bodies.

A pointer variable may have an *allocation-call* in either its *deferred-assignment-statement* or in its companion, but not both.

*Deferred-assignment-statements* and their companions must be top-level.

*Deferred-assignment-statement* variable initialization is the same as *block-assignment-statement* variable initialization, except that after the statement the variables are made *ro* and not *co* if they are not set by an *allocation-call* in the *deferred-assignment-statement*. Code that reads such *ro* variables before companions compute their values will read zero. For pointers this will typically reference undefined memory which will cause a memory fault if accessed. For code after a companion in the same file as the companion the variable qualifier will be changed to *co*.

For pointers allocated by a *deferred-assignment-statement*, the target value will be zeroed and the the pointer target will be given the *ro* qualifier, except for code after the pointer's companion in the same file as the companion, for which the pointer target will be given its declared qualifiers. In particular, function bodies after the companion in the companion's file will see these declared qualifiers.<sup>8</sup>

The variables declared in a *deferred-assignment-statement* are treated as normal *block-variable-declaration* variables inside their companions. In particular, inside their companions the *ro* variables are *\*INIT\**<sup>p41</sup>, and the *co* pointer variables set by an *allocation-call* in their *deferred-assignment-statement* have their target type changed to *\*INIT\** inside their companions.

## 7.5 Loop Assignment Statements

A *loop-assignment-statement* has the syntax:

$$\begin{aligned}
 \textbf{loop-assignment-statement} ::= & \\
 & \textit{block-variable-declaration} \{ \textit{ , block-variable-declaration} \}^* = \\
 & \quad \textit{iteration-control-list} : \\
 & \quad \textit{statement}^* \\
 & \quad \textit{exit-subblock}^* \\
 & | \textit{iteration-control-list} : \\
 & \quad \textit{statement}^* \\
 & \quad \textit{exit-subblock}^* \\
 \textbf{iteration-control-list} ::= & \textit{iteration-control} \{ \textit{ , iteration-control} \}^*
 \end{aligned}$$


---

<sup>8</sup>If the companion is in a body, that body may not be initialized (thereby executing the companion) until after code that imports the body's module is initialized: see 10.7.1<sup>p99</sup>.

**iteration-control** ::= **loop** *loop-label*?  
                           | **exactly** *int-expression times*  
                           | **at most** *int-expression times*  
                           | **while** *bool-expression*  
                           | **until** *bool-expression*

**loop-label** ::= *statement-label*

*statement-label* ::= see p31

**int-expression** ::= *expression* evaluating to an int

**bool-expression** ::= *expression* evaluating to a bool

**loop-control-statement** ::= *break-statement* | *continue-statement*

**break-statement** ::= **break** *loop-label*?

**continue-statement** ::= **continue** *loop-label*?

A *loop-assignment-statement* that has no *result-variable-declarations* (as opposed to *next-variable-declarations*) is the semantic equivalent of a sequence of zero or more copies of the statement with its *iteration-controls* deleted, making these copies into *block-assignment-statements*. Each copy is called an **iteration** of the *loop-assignment-statement*. The number of iterations is determined at run-time by the *iteration-controls* and *loop-control-statements*.

A simple example is:

```
int sum = 0
int i = 1
next sum, next i = while i < 4:
    next sum = sum + i
    next i = i + 1
```

which is semantically equivalent to:

```
int sum = 0
int i = 1
next sum, next i =:
    next sum = sum + i
    next i = i + 1
next sum, next i =:
    next sum = sum + i
    next i = i + 1
next sum, next i =:
    next sum = sum + i
    next i = i + 1
// Now sum == 6 and i == 4
```

However at run-time the variable values of all but the last 4 iterations of the *loop-assignment-statement* are discarded, which would not be the case if the compiler actually inserted iter-

ations in the source code. This only affects debugging.

If instead there are *result-variable-declarations*, these are treated as if they had been moved to an immediately outer *block-assignment-statement*. For example:

```
int sum = 0
int i = 1
int result, next sum, next i = loop:
    next sum = sum + i
    next i = i + 1
    if i + 1 >= 4:
        result = sum
        break // terminate loop
```

is semantically equivalent to:

```
int sum = 0
int i = 1
int result:
    next sum, next i = loop:
        next sum = sum + i
        next i = i + 1
        if i + 1 >= 4:
            result = sum
            break // terminate loop
```

Another way of putting this is that the variables of *next-variable-declarations* get allocated anew each iteration, but the variables of *result-variable-declarations* are only allocated once before the first iteration. As they have the *\*INIT\** qualifier throughout the *loop-assignment-statement*, they can only be written inside that *statement*.

The *iteration-controls* are independent of each other: *loop x* just provides a *loop-label*, exactly *x times* and at most *x times* both terminate the loop after *x* iterations (both do the same thing), *while x* terminates the loop if *x* is *false* at the start of an iteration, and *until x* terminates the loop if *x* is *true* at the start of an iteration. There can be at most one *loop x*, but there can be multiple variants of the other *iteration-controls*.

The *break-statement* exits the current iteration of the *loop-assignment-statement* and prevents further iterations. A *continue-statement* exits the current iteration of the *loop-assignment-statement* but lets the *iteration-control* determine whether there will be any more iterations. If there are nested loops, a *loop-label* may be used with these statements to designate which nested iteration is being exited.

As in *block-assignment-statements*, if ‘*next V*’ occurs as an *assignment-result* within the loop *statements* but is not within the scope of a *result-variable-declaration* for *V* that is also within the loop *statements*, ‘*next V*’ will be added to the *next-variable-declaration* list of the *loop-assignment-statement*. Therefore the above example could be written as:

```

int sum = 0
int i = 1
next sum = while i < 4:
    next sum = sum + i
    next i = i + 1

```

or

```

int sum = 0
int i = 1
while i < 4:
    next sum = sum + i
    next i = i + 1

```

## 8 Conditional Statements

A *conditional-statement* executes another *statement* or block of *statements* according to what a *bool-expression* evaluates to. *Conditional-statements* have the syntax:

```

conditional-statement ::=
    if bool-expression :
        statement*
    | else if bool-expression :
        statement*
    | else :
        statement*
    | if bool-expression : restricted-statement
    | else if bool-expression : restricted-statement
    | else : restricted-statement

```

*bool-expression* ::= see p54

*restricted-statement* ::=

*expression* with no operator of precedence equal to or less than 0  
(the precedence of the ‘:’ operator)

where

1. An ‘else if’ or ‘else’ *statement* must be immediately preceded by an ‘if’ or ‘else if’ *statement*.

An example is:

```

int x = 5
int y = 6
int z:

```



```

    int sum = x + y          // Sets sum = 11
    int product = x * y      // Sets product = 30
    if sum < product:
        z = sum              // Sets z = 11
    else: z = product        // Is NOT executed
// Now z = 11

```

## 9 Trace Statements

A *trace-statement* optionally writes an information record into a trace file:

***trace-statement*** ::= **trace** *trace-ID* , *trace-description* { , *trace-value* }<sup>\*</sup>  
***trace-ID*** ::= *expression* with an **uns** integer value in the range [0,63]  
***trace-description*** ::= *expression* with a **const** string value  
***trace-value*** ::= *reference-expression* with a value of any run time type

A *trace-statement* with *trace-ID* X is executed if bit 1 << X of the **std current trace mask**<sup>p145</sup> is on. Otherwise the *trace-statement* is a no-operation.

When a *trace-statement* is executed it outputs a trace record into a trace file (not specified by this document) that contains the program counter (as a **dp uns8 @pc** value) followed by the *trace-values*. The program counter, when used with debugging information files output by the compiler and loader (not specified by this document), identifies the particular *trace-statement*, its *trace-description*, and the data types of the *trace-values*. This information allows the trace record to be printed in a human readable form (in a manner not specified by this document).

## 10 Declarations

The following is a complete list of declarations:

***declaration*** ::= *result-variable-declaration* [p45]  
                   | *next-variable-declaration* [p45]  
                   | *block-variable-declaration* [p45]  
                   | *prototype-result-declaration* [p72]  
                   | *prototype-argument-declaration* [p73]  
                   | *declaration-statement*

<b>declaration-statement</b> ::=	<i>type-declaration</i>	[p58]
	<i>field-declaration</i>	[p58]
	<i>subfield-declaration</i>	[p59]
	<i>pointer-type-declaration</i>	[p67]
	<i>function-declaration</i>	[p72]
	<i>reference-function-declaration</i>	[p88]
	<i>out-of-line-function-declaration</i>	[p95]
	<i>function-type-declaration</i>	[p97]
	<i>function-constant-declaration</i>	[p97]
	<i>module-declaration</i>	[p98]
	<i>body-declaration</i>	[p99]

## 10.1 Type Declarations

The syntax of a type declaration is:

**type-declaration** ::= **type** *defined-type-name* :  
   *type-subdeclaration*<sup>\*</sup>  
                                   | **type** *defined-type-name* : **\*DEFERRED\***  
**defined-type-name** ::= *type-name*  
*type-name* ::= see p31

**type-subdeclaration** ::=

::=	<i>field-declaration</i>
	<b>align</b> <i>alignment</i> <sup>?</sup>
	<b>pack</b>
	<b>*INCLUDE*</b> <i>defined-type-name</i>
	<b>*LABEL*</b> <i>origin-label</i>
	<b>*OFFSET*</b> <i>origin-label</i> { {+ -} <i>integer-constant-expression</i> } <sup>?</sup>
	<b>*OFFSET*</b> {+ -} <sup>?</sup> <i>integer-constant-expression</i>
	<b>*OFFSET*</b> <b>*SIZE*</b>
	<b>***</b>
	<b>*EXTERNAL*</b>
	<b>*OFFSET*</b> <b>*SIZE*</b>

**field-declaration** ::= *field-without-subfields-declaration*  
                           | *field-with-subfields-declaration*

**field-without-subfields-declaration** ::=

	<i>qualifier-name</i> <sup>*</sup> <i>field-type-name</i> <i>target-label</i> <i>field-dimension</i> <sup>*</sup>
	<i>qualifier-name</i> <sup>*</sup> <i>pointer-type-name</i>
	<i>qualifier-name</i> <sup>*</sup> <i>field-type-name</i> <i>pointer-label</i> <i>field-dimension</i> <sup>*</sup>

**field-with-subfields-declaration** ::=  
     *qualifier-name*<sup>\*</sup> **std**? *number-type-name* *target-label*? *field-dimension*<sup>\*</sup>  
     *subfield-declaration*<sup>+</sup>

**field-type-name** ::= *type-name* that is not **const**

*type-name* ::= see p31

**number-type-name** ::=   **int** | **int8** | **int16** | **int32** | **int64** | **int128**  
                               |   **uns** | **uns8** | **uns16** | **uns32** | **uns64** | **uns128**  
                               |   **flt** | **flt16** | **flt32** | **flt64** | **flt128**

*pointer-type-name* ::= see p31

**field-label** ::= *data-label*

**pointer-label** ::= *field-label* beginning with zero or more ‘.’s followed by an ‘@’

**target-label** ::= *field-label* that is not a *pointer-label*

**origin-label** ::= *basic-name* not beginning with @

**data-label** ::= see p31

**basic-name** ::= see p31

**field-dimension** ::= [ *dimension-size* ]

**dimension-size** ::= *constant-expression* with non-negative integer value

*constant-expression* ::= a **const** valued expression as defined on p78

**subfield-declaration** ::=

*bit-range* *subfield-type-name* *subfield-label* *subfield-dimension*<sup>\*</sup>

**subfield-type-name** ::= *number-type-name* | **bool**

**subfield-label** ::= *target-label*

**subfield-dimension** ::= [ *dimension-size* ]

**bit-range** ::=   [ *onlybit* ]  
                   | [ *highlowbits* ]  
                   | [ *highbit - lowbit* ]

**onlybit** ::= *constant-expression* with non-negative integer value

**highlowbits** ::= *dit*+ - *dit*+      [this is a single lexeme]

**highbit** ::= *constant-expression* with non-negative integer value

**lowbit** ::= *constant-expression* with non-negative integer value

*dit* ::= see p35

**alignment** ::= *constant-expression* with power of 2 integer value

The *type-subdeclarations* are processed in order. At the beginning of each, there is a align/pack switch value and an offset-in-bits integer. These determine the offset in bits of the next *field-declaration* field encountered relative to the beginning of each datum of the defined type being declared. There may be several *type-declarations* for the same defined

type (see 10.1.1<sup>p60</sup>), and at the beginning of the first the align/pack switch is set to align and the offset is set to zero.

If the align/pack switch is in the **align** position and the next *type-subdeclaration* is a *field-declaration*, the current offset will be incremented before becoming the offset of the field being declared. The increment will be just enough to make the offset an exact multiple of the field's type's alignment. The alignment of a number type is its size in bits. The alignment of a defined type is the least common multiple of the alignment of any of its fields, which, since all alignments are powers of two, is the same as the largest alignment of any of the fields.

A value of **bool** type has a size of 1 bit and an alignment of 8 bits. When it is stored in 8 bits, the value is encoded like a signed integer equal to -1 for **true** and 0 for **false**.

An '**align** *N*' sub-declaration behaves like an unnamed field of alignment *N* bits and zero length, and in addition sets the align/pack switch to 'align'. An '**align**' sub-declaration just sets the align/pack switch to 'align'.

A **pack** sub-declaration sets the align/pack switch to 'pack'.

An **\*INCLUDE\*** sub-declaration copies all the *type-subdeclarations* of the given defined type into the current sequence of *type-subdeclarations*.

A **\*DEFERRED\*** *type-declaration* declares a *defined-type-name* without declaring the definition of the named type. Such a *type-declaration* is typically used allow the *defined-type-name* to be used as the target type of a pointer before its fields are declared.

The *defined-type-name* in a *type-declaration* is declared before the *type-declaration*'s sub-declarations are processed, so these sub-declarations may use the *defined-type-name* as a pointer target type.

A **\*LABEL\*** sub-declaration assigns the current offset to the given *origin-label* and provides the *origin-label* for use by subsequent **\*OFFSET\*** sub-declarations. Each *origin-label* may be defined only once for a given defined type.

An **\*OFFSET\*** sub-declaration changes the current offset to the value of a given *origin-label*, or to that value plus or minus an integer, or to a given integer. '**\*OFFSET\*** **\*SIZE\***' is special: see p62.

### 10.1.1 Defined Type Expansions

A defined type can have just one or several *type-declarations*. The set of all its *type-declarations* is called the **expansion tree** of the defined type.

The set of fields and subfields of the defined type is the union of those defined by any *type-declaration* in the defined type's expansion tree. However these may not have unique names, as long as each name is unique in the scope of the *type-declaration* that defines the name (because two *type-declarations* in the expansion tree can have disjoint scopes).

All but one of the *type-declarations* in an expansion tree must be within the scope<sup>p101</sup> of another *type-declaration* in the expansion tree, and the expansion tree is a tree-graph in which each *type-declaration* X is the root of a subtree containing all *type-declarations* Y in the tree that are within the scope of X (or equivalently, that have a scope that is a subset of the scope of X). Thus the **parent** of a non-root Y is the *type-declaration* X in the expansion tree with the smallest scope that contains Y.

Non-root *type-declarations* in the expansion tree are called *expansions*, and the root *type-declaration* is called just the **root**.

A *defined-type-name* must be inside the scope of the root of its expansion tree to be visible, and hence usable.

A **leaf** in an expansion tree is a *type-declaration* that is not the parent of any other *type-declaration* in the expansion tree (equivalently, a leaf is a tree node with no children). An expansion tree is **linear** if it has only one leaf (equivalently, no tree node has more than one child). The sole leaf of a linear expansion tree is called a **linear leaf**.

Expansion trees are either internal or external.

Each *type-declaration* in an **internal expansion tree** that is not a linear leaf must end with the **\*\*\*** sub-declaration, and all *type-declarations* in the tree must be in the same module or its bodies. However the *defined-type-name* may be external. If the tree has a linear leaf that does not have a **\*\*\*** sub-declaration, the *defined-type-name* is **non-expandable** within the scope of the linear leaf *type-declaration*. Outside that scope, but within the scope of the tree root, the *defined-type-name* is said to be expandable.

Each *type-declaration* in an **external expansion tree** must end with the **\*EXTERNAL\*** sub-declaration. The *defined-type-name* is expandable wherever it is defined (i.e., within the scope of the tree root).

The final size and alignment of an expandable *defined-type-name* are not known until load time. Allocators use the load time size and alignment to allocate memory for a value of the type and then zero that memory. Thus the ‘**local**’ allocator can allocate a datum of an expandable *defined-type-name* and return a pointer to the datum.

A *defined-type-name* must be non-expandable if it is used as a *type-name* in a variable declaration, or as a *field-type-name* in a *type-subdeclaration*, or as a *defined-type-name* in an **\*INCLUDE\*** *type-subdeclaration*. However an expandable *defined-type-name* can be used as the target of a pointer type used as a variable type or field type.

A *field-label* or *subfield-label* declared within a *type-declaration* may only be used within the scope of the *type-declaration* in which the *field-label* or *subfield-label* is declared, and may not be re-declared within this scope.

Similarly an *origin-label* may only be used only after its definition in its defining *type-declaration* X and within other *type-declarations* in the same expansion tree that are within the scope of X, and may not be re-declared in the places it can be used.

Because it is possible for different *type-declarations* in an expansion tree to have disjoint scopes, a given label may refer to different things in these disjoint scopes: e.g., it might be a *field-label* in one scope and an *origin-label* in the other, or it might name completely different fields in the two scopes.

At the beginning of each *type-declaration* the align/pack switch is set to align, the offset is set to zero if the *type-declaration* is the root of its expansion tree, and the offset is undefined and must be set by an *\*OFFSET\** statement before it is used if the *type-declaration* is a non-root.

*\*LABEL\** and *\*OFFSET\** sub-declarations are typically used to overlay sections of a defined type's value, and create what in other languages are union types. Care must be taken in using union values as both type-violations and unexpected field allocations can result.

An '*\*OFFSET\* \*SIZE\**' sub-declaration changes the current offset to the size of values of the type being defined, as it is computed at the point where the *\*OFFSET\* \*SIZE\** sub-declaration is encountered. This is just the maximum of all offset values previously computed in the current *type-declaration* and its ancestors in the expansion tree. The '*\*OFFSET\* \*SIZE\**' sub-declaration is not allowed in a *type-declaration* if any of the ancestors of the *type-declaration* in its expansion tree has more than one child.

### 10.1.2 Type Fields

A field of a value of a user defined type is accessed by prepending '.' to the *field-label* to form a *member-name* in a *reference-expression* (see p40). An example is:

```
type my type:
    uns8    kind          // Object Kind
    flt     weight

my type X:
    // Within this block X is *INIT*.
    X.kind = HIPPOPOTAMUS
    X.weight = 152.34
uns8 kind = X.kind
flt weight = X.weight
```

If a *field-label* is a *pointer-label*, an associated *target-label* is declared consisting of the *pointer-label* minus its first '@'. The *target-label* references a virtual field consisting of the target value stored at the location pointed at by the *pointer-label* field's pointer value. An example<sup>9</sup> is:

```
type list element:
    int value
    ap list element @successor
```

---

<sup>9</sup>As 'next' is a keyword, we use 'successor' here.

```

// Make circular list.
//
ap list element @Y      // `@= local = *DEFERRED*' is implied
ap list element @X:     // `@= local' is implied
    X.value = 1
    X.@successor = @Y
ap list element @Y:
    Y.value = 2
    Y.@successor = @X
//
// Now X.value == 1 and X.successor.value == 2 and
// similarly Y.value == 2 and Y.successor.value == 1,
// while X.@successor == @Y and Y.@successor == @X are
// pointers to local memory.

```

A field of the defined type can only be accessed by code in the scope of a *type-declaration* declaring the field.

An example is:

```

type my type: *DEFERRED*
ap *READ-WRITE* my type @X    // `@= local' is implied
                                // Legal, my type members need not be declared.
                                // Size and alignment of my type values is
                                // computed at load time. The allocated value
                                // will be zeroed.
ap ro my type @Y = @X // Legal, only ap copied.
ap my type @Z:         // Legal, `@= local' is implied
    Z = X              // Legal, the value at @X is copied to
                        // the value at @Z. However in this
                        // case the value is completely zero.

type my type:           // Definition of my type that was *DEFERRED*.
    *LABEL* origin     // `origin' is set to offset 0
    int I              // Offset of I is 0.
    ***
X.I = 55                // Legal, .I has been declared. X is
                        // *READ-WRITE*.

type my type:           // Expansion of my type
    *OFFSET* *SIZE*
    int J              // Now X.J == 0
    ***
X.J = 66                // Legal, .J has been declared.

```

```

type my type:          // Expansion of my type
    *OFFSET* origin
    int K1
    int K2

// Now X.K1 == X.I == 55; X.K2 == X.J == 66; but you must know
// how offsets are assigned to believe this.

```

### 10.1.3 Type Subfields

Subfields are parts of the previously declared number type field. The bits occupied by a subfield are given by its *bit-range*, where bits are numbered 0, 1, ... from the low order end of numbers.

A subfield value may have fewer bits than the number-type of the subfield. For integer types, the value is the low order bits of the integer, with the high order bits added when the value is read by adding 0 bits for unsigned integers or copies of the highest order bit for signed integers. For floating types, the value is missing low order mantissa bits, which are added as zeros. If a value outside the representable range is stored, it is not an error. Unsigned and two's complement integer values are truncated, and IEEE floating values have low order mantissa bits dropped (there is no rounding). However, it is a compile error to have a floating type whose sign and exponent parts plus 1 mantissa bit cannot be stored in the subfield value.

*Subfield-labels* and *field-labels* have the same standing within *reference-expressions*. Both have associated *member-names* made by adding a single '.' to the beginning of the *field-label* or *subfield-label*. For example:

```

type my type:
    uns8    kind          // Object Kind
    [0] bool animal      // True if Animal
    [1] bool vegetable    // True if Vegetable
    flt      weight

my type X:
    // Within this block X is *INIT*.
    X.kind = HIPPOPOTAMUS
    // Also sets animal bit and clears vegetable bit.
    X.weight = 152.34
uns8 kind = X.kind
bool animal = X.animal
bool vegetable = X.vegetable
flt weight = X.weight

```



### 10.1.4 Type Dimensions

If a *field-declaration* with *field-label*  $F$  contains a single *field-dimension*  $[n]$  then  $n$  fields are allocated to ascending offsets, using zero padding if necessary to align all  $n$  fields. The labels of these fields are  $F[i]$  for  $0 \leq i < n$ . If there is a subfield labeled  $S$  of the field,  $S[i]$  refers to the subfield in  $F[i]$ . For example:

```
type character attributes:
    uns8 [128]
    [0] bool is graphic

character attributes X:
    int i = 0
    while i < 128:
        X.is graphic[i] = 32 < i && i < 127
        next i = i + 1
    bool line feed is graphic = X.is graphic [C#<LF>"]
    bool A is graphic = X.is graphic [C#"A"]
```

In a *field-declaration* two *field-dimensions*  $[n1] [n2]$  is treated as syntactic sugar for  $[n1*n2]$  with  $F[i1] [i2]$  being syntactic sugar for  $F[i1*n2+i2]$ .<sup>10</sup> Similarly  $[n1] [n2] [n3]$  is syntactic sugar for  $[n1*n2*n3]$  with  $F[i1] [i2] [i3]$  being syntactic sugar for  $F[i1*n2*n3+i2*n2+i3]$ . And so forth for any number of *field-dimensions*.

If a *subfield-declaration* with *subfield-label*  $S$  contains *subfield-dimension*  $[n]$  then  $n$  subfields are allocated to the containing field, starting with the bits designated by the *subfield-declaration's* *bit-range* and adding the number of bits in the *bit-range* to each integer in the *bit-range* for each successive subfield. For example:

```
type hex digits:
    uns32 container
    [3-0] uns hex digit [8]
    // hex digit[i] is stored in bits [4*i+3, 4*i]

hex digits X:
    int i = 0
    while i < 8:
        X.hex digit[i] = i
        next i = i + 1
    // Now X.container == X#"76543210"
```

A *subfield-declaration* with *subfield-label*  $S$  and more than one *subfield-dimension* is treated in the same manner as a *field-declaration* with more than one *field-dimension*. For example,

---

<sup>10</sup>Thus arrays are stored in row major order: last subscript varies fastest, as in C/C++

$[n1][n2][n3]$  is syntactic sugar for  $[n1*n2*n3]$  with  $S[i1][i2][i3]$  being syntactic sugar for  $S[i1*n2*n3+i2*n2+i3]$ .

If a *field-declaration* with *field-label*  $F$  has a *field-dimension* and also a subfield with *subfield-label*  $S$ , then  $S[i]$  references the subfield in the field value  $F[i]$ . If in addition the subfield has a *subfield-dimension*,  $S[i][j]$  references the subfield selected by  $[j]$  in the field value  $F[i]$ .

In all cases  $][$  may be replaced by  $,$  (the space after the comma is required), so that, for example,  $[i][j]$  is equivalent to  $[i, j]$ .

### 10.1.5 Type Conversions

When the compiler is confronted with code such as:

```
T1 v1 = ...
T2 v2 = v1
```

where  $T1$  and  $T2$  are different types, the compiler just rewrites the code to:

```
T1 v1 = ...
T2 v2 = *IMPLICIT* *CONVERSION* ( v1 )
```

and compiles the rewritten code. If you define a function with the prototype

```
function T2 r = ma? *IMPLICIT* *CONVERSION* ( T1 v )
```

the compiler will use this function. Otherwise the compiler will try to chain implicit conversions together to get to a successful compile. Of course such chaining will only work if there is at least one *\*IMPLICIT\* \*CONVERSION\** function with target type  $T2$ . If there is more than one such function, and none have argument type  $T1$ , ambiguity may lead to a compile error.

You can define *\*IMPLICIT\* \*CONVERSION\** functions provided at least one of the two types  $T1$  and  $T2$  is user defined, and not builtin, and  $T2$  is not **const**. There are builtin *\*IMPLICIT\* \*CONVERSION\** functions in which both types are builtin: see 18.2<sup>p136</sup>.

The set of *\*IMPLICIT\* \*CONVERSION\** functions defines a graph, the **implicit conversion graph** in which types are nodes and *\*IMPLICIT\* \*CONVERSION\** functions are directed edges. A *function-declaration*  $d$  of the form

```
function T2 r = ma? *IMPLICIT* *CONVERSION* ( T1 v )
```

creates an edge labeled  $d$  in this graph from node  $T2$  to node  $T1$ . This graph must be acyclic. A path  $d_1, d_2, \dots, d_n$  in this graph denotes a chain of *\*IMPLICIT\* \*CONVERSION\** *function-declarations* that together convert the result type of  $d_1$  to the argument type of  $d_n$ .

When defining an implicit conversion from type  $T1$  to type  $T2$ , each value of type  $T1$  should be exactly representable by a value of type  $T2$ . This rule should be followed, but is not checked by the compiler.

And there is one notable exception: conversions from `const` which are done at compile-time may fail (the failure will be at compile-time and be a compiler error). For example, conversions from `const` to any integer type will fail if the `const` value cannot be encoded exactly in the integer type.

For types `T1` and `T2` you can also define an explicit conversion:

```
function T2 r = ma? T2 ( T1 v )
```

If the result may not properly represent the value `v`, you may wish to define instead an unchecked conversion:

```
function T2 r = ma? *UNCHECKED* ( T1 v )
```

The compiler will not allow you to define such functions if both `T1` and `T2` are builtin or if `T2` is `const`, but some such functions are builtin: see 18.3<sup>p138</sup>.

The types `T1` and `T2` may also be pointer types: see p71. Or one may be a pointer-type and one a non-pointer type. However, `T2` cannot be `const`, and you cannot define your own `*IMPLICIT*` `*CONVERSION*` function if both types are builtin.

## 10.2 Pointer Type Declarations

A pointer type has an **associated data type** specified by a pointer type declaration. The syntax is:

```
pointer-type-declaration ::=
    pointer type defined-pointer-type-name is type type-name
pointer-type-name ::= see p31
type-name ::= see p31
```

An `*UNCHECKED*` conversion is implicitly defined from the associated data type to the given pointer type, and a conversion is implicitly defined in the other direction.

It is important that there be a 1-1 correspondence between pointer types and their associated data types. In particular, `int` must not be used as the associated data type of more than one pointer type. This is why associated data types are generally user defined types.

A *pointer-type-declaration* ‘`pointer type P is type D`’ implicitly declares the functions:

```
function P Q$1 T$1 @p = ma? *UNCHECKED* ( D d )
function D d = D ( P Q$1 T$1 @p )
```

where `ma?` denotes the *module-abbreviation* of `P`, if any. These just copy values changing type.

For example, the following are builtin:

```
pointer type std dp is type std data for dp
pointer type std ap is type std data for ap
```

```

type std data for dp:
    int address
type std data for ap:
    dp ro int @base
    int offset

function dp Q$1 T$1 @r = std *UNCHECKED* ( std data for dp ddp )
function ap Q$1 T$1 @r = std *UNCHECKED* ( std data for ap dap )
function std data for dp r = std data for dp ( dp Q$1 T$1 @ptr )
function std data for ap r = std data for ap ( ap Q$1 T$1 @ptr )
    // These functions just copy the argument value to the
    // result value changing the type of the value. Here
    // Q$1 is a wild-card that matches any list of qualifier-names,
    // and T$1 is a wild-card that matches any type-name.

```

Reading and writing values using a pointer of type  $P$  can be accomplished by the functions:

```

reference function T$1 r = ma? ( P QR$1 T$1 @p ) ".*"
reference function ma? ( P QW$1 T$1 @p ) ".*" = T$1 r

```

where *ma*, if present here, refers to the module in which  $P$  is defined.

These functions can be defined after  $P$  is defined. They allow the pointer to be used to read a copy of the value pointed at, or write the value, but do not allow members or elements of the value to be accessed (members and elements of the copy may be accessed).

These functions are implicitly called when the target of a pointer variable is read or written. For example:

```

ap int @p:
    p = 5
    // This translates to:
    //   @p.* = 5
int x = p
    // This translates to:
    //   int x = @p.*

```

An alternative strategy is to convert a pointer of type  $P1$  to a pointer of type  $P2$  that allows members and elements to be accessed. Suppose we are given:

```

pointer type  $P1$  is type  $D1$ 
pointer type  $P2$  is type  $D2$ 

```

Then we can define a reference function with the prototype:

```

reference function  $P2$  Q$1 T$1 @p2 = ma? (  $P1$  Q$1 T$1 @p1 ) ".@"

```

which converts a pointer of type  $P1$  to a pointer of type  $P2$ , where *ma*?, if present, refers to a module in which both  $P1$  and  $P2$  are defined. This conversion function is automatically

called without any *module-abbreviation* if a value pointed at by a pointer of type  $P1$  is to be accessed, in preference to calling the  $.*$  functions above. Then if  $P2$  is  $dp$ ,  $ap$ ,  $fp$ ,  $av$ , or  $fv$ , the  $P2$  pointer can be used to not only read or write the value, but to also read or write members or elements of the value.

Thus the above example becomes:

```
ap int @p:
    p = 5
    // This translates to:
    //   @p.@.* = 5
int x = p
    // This translates to:
    //   int x = @p.@.*
```

Since  $@p.*$  and  $@p.@$  are syntactically *reference-calls*, these expressions can only match reference function prototypes, and such matches ignore the prototype result types, and use only the prototype argument types.<sup>p90</sup> Thus the inserted calls, which have no module abbreviation, can be matched only if there is at most one  $.*$  or  $.@$  function in the current context with suitable qualifiers and type (e.g.,  $Q\$1$  and  $T\$1$ ) for a given  $P1$ .

Because there can be at most one matching  $.@$  reference function declaration,  $.@$  calls can be chained by the compiler. In particular, a  $.@$  reference function that produces an  $ap$  result will be chained to the builtin:

```
reference function dp Q$1 T$1 @r = std ( ap Q$1 T$1 @p ) ".@" :
    std data for ap dap = std data for ap ( @p )
    std data for dp ddp:
        ddp.address = dap.base + dap.offset
    @r = *UNCHECKED* ( ddp )
```

You can provide reference function definitions of  $.*$  or  $.@$  with different actual types in place of  $T\$1$ , and these will be used in preference to the definition that has the wildcard  $T\$1$ .

As a convenience feature, instead of defining  $.@$ , you can define a reference function with prototype:

```
reference function D2 d2 =
    ma? *POINTER* *ACCESS* *CONVERSION* ( D1 d1 )
```

where  $ma$  refers to any module in which both  $D1$  and  $D2$  are defined. This implicitly defines the reference function:

```
reference function P2 Q$1 T$1 @p2 =
    ma? ( P1 Q$1 T$1 @p1 ) ".@" :
    D1 d1 = D1 ( @p1 )
    D2 d2 = *POINTER* *ACCESS* *CONVERSION* ( d1 )
    @p2 = *UNCHECKED* ( d2 )
```

where *ma* is the same module as that of the *\*POINTER\** *\*ACCESS\** *\*CONVERSION\** function, if any. An example usage is the builtin:

```
// This function enables conversion of `ap ...' to `dp ...'
// when an ap pointer is being used to access a value or
// member or element of a value. The dp is the sum of the
// base and offset of the ap.
//
function std data for dp r = std *POINTER* *ACCESS* *CONVERSION*
    ( std data for ap dap ):
    std data for dp ddp:
        ddp.address = dap.base + dap.offset
    r = ddp
```

An example implementing a new pointer type is:

```
type file:
    *READ-WRITE* av uns8 @name
    . . . . .
av *READ-WRITE* file @files @= global [1000]
ap *READ-WRITE* int @number of files @= global

// Implement a file descriptor (fd) that addresses a file
// in files. The fd contains an index and addresses
// files[index].

type data for fd:
    int index

pointer type fd is type data for fd

reference function ap Q$1 file @r = ( fd Q$1 file @p ) ".@":
    data for fd d = data for fd ( @p )
    ap file *READ_WRITE* @f = @files[d.index]
    @r = @f // Implicitly converts *READ-WRITE* to Q$1

function fd *READ-WRITE* file @r = allocate fd:
    data for fd d:
        d.index = number of files
    @r = *UNCHECKED* ( d )
    number of files = number of files + 1

fd *READ-WRITE* file @f @= allocate fd
f.@name = ...
```

```

. . . . .
av uns8 @n = f.@name
. . . . .

```

### 10.2.1 Pointer Type Conversions

You can define an implicit conversion of one pointer type to another, after the manner of Section 10.1.5. An example is:

```

// This function enables implicit conversion of `dp ...' to
// `ap ...', where the latter has the constant 0 for a base
// and the dp value for its offset, provided the dp target is
// *GLOBAL*.
//
dp *GLOBAL* int std @zero:
    zero = 0
function std ap QG$1 T$1 @r = std *IMPLICIT* *CONVERSION*
    ( std dp QG$1 T$1 @p ):
    std data for dp ddp = std data for dp ( dp QG$1 T$1 @p )
    std data for ap dap:
        dap.@base = std @zero
        dap.offset = ddp.address
    @r = *UNCHECKED* ( dap )

```

As a convenience feature, we can define a *\*POINTER\* \*IMPLICIT\* \*CONVERSION\** (non-reference) function instead. Suppose we are given:

```

pointer type P1 is type D1
pointer type P2 is type D2

```

Then this function has prototype:

```

function D2 d2 = ma? *POINTER* *IMPLICIT* *CONVERSION* ( D1 d1 )

```

where *ma* refers to any module in which both *D1* and *D2* are defined. This implicitly defines the function:

```

function P2 QG$1 T$1 @p2 =
    ma? *IMPLICIT* *CONVERSION* ( P1 QG$1 T$1 @p1 ):
    D1 d1 = D1 ( @p1 )
    D2 d2 = *IMPLICIT* *ACCESS* *CONVERSION* ( d1 )
    @p2 = *UNCHECKED* ( d2 )

```

where *ma* is the same module as that of the *\*IMPLICIT\* \*ACCESS\* \*CONVERSION\** function, if any.

One can define an *\*UNCHECKED\** function to convert *P1* values to *P2* values. As a convenience,

this can be done by defining:

```
function D2 d2 = ma? *POINTER* *UNCHECKED* *CONVERSION* ( D1 d1 )
```

which implicitly defines the function:

```
function P2 Q$1 T$1 @p2 = ma? *UNCHECKED* ( P1 Q$1 T$1 @p1 ):
  D1 d1 = D1 ( @p1 )
  D2 d2 = *POINTER* *UNCHECKED* *CONVERSION* ( d1 )
  @p2 = *UNCHECKED* ( d2 )
```

An example is the builtin:

```
// This function enables *UNCHECKED* conversion of `ap ...' to
// `dp ...' where the latter is the sum of the base and offset
// of the ap.
//
function std data for dp r = std *POINTER* *UNCHECKED* *CONVERSION*
  ( std data for ap dap ):
  std data for dp ddp:
    ddp.address = dap.base + dap.offset
  r = ddp
```

Lastly, one can define an explicit pointer conversion function with prototype:

```
function P2 Q$1 T$1 @p2 = ma? P2 ( P1 Q$1 T$1 @p1 )
```

### 10.3 Inline Function Declarations

The syntax of a function declaration is:

```
function-declaration ::= function-prototype :
                           statement+
                           | function-prototype : *DEFERRED*

function-prototype ::=
  function-specializer? function prototype-result-list =
    module-abbreviation? prototype-pattern
  | function-specializer? function module-abbreviation? prototype-pattern

function-specializer ::= macro | constant | inclusion

prototype-result-list ::=
  prototype-result-declaration { , prototype-result-declaration }*

prototype-result-declaration
  ::= prototype-result-variable-declaration
     | prototype-next-variable-declaration
```



*module-abbreviation* ::= see p31

***prototype-result-variable-declaration*** ::=

*type-name target-variable*

| *pointer-type-name qualifier-name*<sup>\*</sup> *type-name pointer-variable*

*type-name* ::= see p31

*qualifier-name* ::= see p32

*pointer-type-name* ::= see p31

*variable-name* ::= see p31

*target-variable* ::= see p31

*pointer-variable* ::= see p31

***prototype-next-variable-declaration*** ::= **next** *variable-name*

***prototype-argument-declaration***

::= *prototype-result-variable-declaration* { **?=** *default-value* }<sup>?</sup>

| **macro** *variable-name* { **?=** *default-value* }<sup>?</sup>

| *prototype-result-variable-declaration* **!=** *required-value*

***default-value*** ::= *expression*

***required-value*** ::= *constant-expression*

*expression* ::= see p23

*constant-expression* ::= an **const** valued expression as defined on p78

***prototype-pattern*** ::= *parenthesized-pattern-argument-list*<sup>\*</sup> *pattern-term*<sup>+</sup>

***pattern-term*** ::= *function-term-name* *pattern-argument-list*<sup>\*</sup>

*function-term-name* ::= see p32

***pattern-argument-list***

::= ( *prototype-argument-declaration* { , *prototype-argument-declaration* }<sup>\*</sup> )

| [ *prototype-argument-declaration* { , *prototype-argument-declaration* }<sup>\*</sup> ]

***parenthesized-pattern-argument-list*** ::=

*pattern-argument-list* with parentheses ( ) (and not square brackets [ ])

1. A *prototype-pattern* *function-term-name* must not be an initial segment of any other *function-term-name* in the same *prototype-pattern*.
2. *Function-term-names* (in a *prototype-pattern*) may not be *member-names*<sup>p31</sup> (compare with *reference-function-declaration*<sup>p88</sup>).
3. *Pattern-argument-lists* appearing before the first *function-term-name* may not use square [ ] brackets (compare with *reference-function-declaration*<sup>p88</sup>).
4. There must be a *parenthesized-pattern-argument-list* that is not omissible (it must have a *prototype-argument-declaration* that has no *default-value*) either immediately

before or immediately after the first *function-term-name* in a *prototype-pattern*. This distinguishes a *function-call* from a *reference-expression*: see Rule 4 on page 43.

5. Result and argument *variable-names* in a *function-prototype* must not begin with a *module-abbreviation*.
6. For a *prototype-result-declaration* of the form '**next** *v*', *v* must be the *variable-name* in a *prototype-argument-declaration* of the form '*... type-name v*', and any actual argument associated to the *prototype-argument-declaration* by some *function-call* must be a *reference-expression* that does not have the form '**next** *variable-name*'.
7. Result and argument *variable-names* in a *function-prototype* must be distinct, with an exception for the previous note.
8. In a *pattern-argument-list* a *prototype-argument-declaration* with no *default-value* cannot follow a *prototype-argument-declaration* with a *default-value*.
9. The first *prototype-argument-declaration* in a *pattern-argument-list* that is at the very beginning of a *prototype-pattern*, before the first *function-term*, must not have a *default-value*. I.e., these *pattern-argument-lists* cannot be omitted from *function-calls*.
10. If the first *function-term-name* in the *prototype-pattern* is a *type-name* or *pointer-type-name*, the *function-declaration* must have a *prototype-result* with exactly one *prototype-result-variable-declaration* that has for its type this same *type-name* or has for its pointer type this same *pointer-type-name*, and the *prototype-pattern* may not have any *parenthesized-pattern-argument-lists* before the first *function-term*. The function declared is called a **explicit type conversion function**, and a *function-call* to the function is called an **explicit type conversion**.
11. A wild-card<sup>p32</sup> name of the form **T\$...** is treated in a *function-prototype* as a *type-name*. A wild-card name of the form **P\$...** is treated as a *pointer-type-name*. A wild-card name of the form **Q...\$...** is treated as a *qualifier-name* and must not be combined with other *qualifier-names* in the same *prototype-result-variable-declaration* or *prototype-argument-declaration*.
12. *Function-declarations* with *function-specifiers* declare **special-functions**. These may not compile run-time code, and all their *prototype-result-variable-declarations* must be of the form '**const** *target-variable*'. These functions are referred to as **macro functions**, **constant functions**, and **inclusion functions**, respectively.
13. A **\*DEFERRED\*** *function-declaration* may not be a special function.

An example of an inline function declaration and an inline function call is:

```
function F ( int x ?= 5 ) G ( int y ) H ( int z ?= 7 ) I ( int w ):
    . . . . .
    F I ( 8 ) G ( 6 )      // Equivalent to F ( 5 ) G ( 6 ) H ( 7 ) I ( 8 )
```

The *function-term-names* in the declaration are matched to those in the call, but need not have the same order in the call, except for the first *function-term-name* which must be the same in the declaration and the call. Thus the *call-terms* of the call are re-ordered to match the order of the *pattern-terms* of the declaration. If one of the *pattern-terms* is omitted in the call, but its arguments have *default-values*, the *pattern-term* with its *default-values* will be inserted into the call (here H ( 7 ) is inserted). Similarly with an *argument-list* that is omitted (here ( 5 ) is inserted).

For an argument list in the prototype to match an argument list in the call, both must be surrounded by the same brackets; either both have ( ) or both have [ ], except that implied parentheses in the call are treated as ( ) during matching.

As an example of this last,

$$r = x + y$$

is treated for matching purposes as

$$( r ) = ( ( x ) + ( y ) )$$

Note that *quoted-marks* and *quoted-separators* in *function-term-names* may appear with or without quotes in *call-term-names*.<sup>p43</sup> Thus we have the example:

```
function int z = ( int x ) @@ ( int y ):
    . . . . .
    int v = 5 @@ 6      // Legal
    int w = 5 ":@" 6    // Legal
```

However, quoting an operator will cause it to be not recognized as an operator. For example:

$$x + y * z \text{ parses as } \{ \{ "x" \}, "+", \{ \{ "y" \}, "*", \{ "z" \} \} \}$$

whereas

$$x "+" y * z \text{ parses as } \{ \{ "x", "+", "y" \}, "*", \{ "z" \} \}$$

In the latter, { "x", "+", "y" } cannot be recognized as a *function-call* because the arguments "x" and "y" are not bracketed (i.e., are not { "x" } and { "y" }), and will also not be recognized as a *reference-expression* (because "+" cannot be in a *variable-name* or begin a *member-name*) or *constant*.

A *pattern-term* with the syntax:

```
boolean-pattern-term ::=
    function-term-name ( bool variable-name ?= default-value )
```

triggers special syntax in a call that matches the prototype. In the call:

<i>function-term-name</i>	is equivalent to	<i>function-term-name</i> ( TRUE )
<b>no</b> <i>function-term-name</i>	is equivalent to	<i>function-term-name</i> ( FALSE )
<b>not</b> <i>function-term-name</i>	is equivalent to	<i>function-term-name</i> ( FALSE )
omitted <i>function-term-name</i>	is equivalent to	<i>function-term-name</i> ( <i>default-value</i> )

Thus the example:

```
function F ( int x ) OPTION ( bool y ?= TRUE )
. . . . .
F ( 5 )           // Equivalent to F ( 5 ) OPTION ( TRUE )
F ( 5 ) OPTION    // Equivalent to F ( 5 ) OPTION ( TRUE )
F ( 5 ) no OPTION // Equivalent to F ( 5 ) OPTION ( FALSE )
```

A function prototype result may be named '**next** *v*' if the prototype has an argument named *v*, in which case a *function-call* matching the prototype must match the prototype argument *v* to a *reference-expression* *e* that does not have the form '**next** *variable-name*'. Then the *assignment-result* corresponding to the prototype '**next** *v*' may be omitted, and will be taken to be '**next** *e*' if *e* is a *variable-name* naming a stack **co** variable for which '**next** *e*' is legal, and will otherwise be taken to be simply the *reference-expression* *e*.

For example:

```
function next x = inc ( int x ):
    next x = x + 1
. . . . .
int y = ...
inc ( y ) // Equivalent to `next y = y + 1'.
ap *READ-WRITE* int @z:
    z = ...
inc ( z ) // Equivalent to `z = z + 1'.
```

If a *required-value* is given in a prototype, the call must have an equal **const** valued actual argument value in order for the call to match the prototype. Note that the argument variable type need not be **const**, as **const** values can be converted to run-time values: equality will be checked after conversion to the argument type. Matches to prototypes with more *required-values* are preferred over matches to prototypes with less *required-values*. Thus the example:

```
function F ( int x ) G ( int y != 5 ): // First F declaration
. . . . .
function F ( int x ) G ( int y ?= 5 ): // Second F declaration
. . . . .
int z = 5
F ( 8 )           // Matches only second F declaration
F ( 8 ) G ( 5 )   // Matches preferred first F declaration
F ( 8 ) G ( 6 )   // Matches only second F declaration
F ( 8 ) G ( z )   // Matches only second F declaration
```

```
// (z is not const valued).
```

A *prototype-argument-declaration* with the syntax:

```
prototype-argument-declaration ::=
    macro variable-name { ?= default-value }?
```

causes the argument value in a call to be the parse of the actual argument, which is a **const** value. If the *default-value* is used, it is evaluated as a *constant-expression*.

When a **macro function** is called it must return a **const** result that is a parsed expression which replaces the *function-call*. For example:

```
macro function const r = sum ( macro a1, macro a2 = { 1 } ):
    r = { a1, "+", a2 };

int x = ...
int y = sum ( x, 5 ) // Same as: int y = x "+" 5
                    // Parsed equivalent:
                    //      { "int" "y" } "=" { { x } "+" { 5 } }
                    // a1 is { x }, a2 is { 5 }
int y = sum ( x )   // Same as: int y = x "+" 1
                    // Parsed equivalent:
                    //      { "int" "y" } "=" { { x } "+" { 1 } }
                    // a1 is { x }, a2 is { 1 }</pre

```

When a **constant function** is called its must return a **const** result that replaces the *function-call* if the **const** value is not a map, and effectively replaces the *function-call* if the *const* value is a map. Examples:

```
constant function const r = sum ( const a1, const a2 ):
    r = a1 + a2;

const x = 10
const y = sum ( x, 5 ) // Sets y to 15
                      // a1 is 10, a2 is 5, r is 15
                      // sum ( x, 5 ) can be thought of as
                      // being replaced by 5

constant function const r = list ( const a1, const a2 ):
    r = { a1, a2 }

const z = list ( 4, 5 ) // Sets z to { 4, 5 }
                      // list ( 4, 5 ) can be thought of as being replaced by:
                      // { { 4, 5 }, ".initiator" = "{", ".terminator" = "}" }[0]
                      // which evaluates to { 4, 5 }
```

The `constant` *function-specializer* effectively does nothing but promise that the function will not compile run-time code.

A ***constant-expression*** is an *expression* that is either a *constant* or a *function-call* to a `constant` function. *Constant-expressions* are used to compute parameters that must be known at compile-time.

An **inclusion function** declaration can only be matched to a *function-call* at statement level in a *call-assignment-statement*. When an **inclusion function** is called it must return a `const` result that is a parsed list of *statements* that replaces the *call-assignment-statement*. See Section 10.5<sup>p93</sup> for examples.

Arguments to special functions need not have the `const` type. The values of the arguments cannot be accessed by the functions, but their types can be.

A ‘`*DEFERRED*`’ *function-declaration* permits inline functions defined between it and a later non-`*DEFERRED*` companion *function-declaration* to call the function. An example is:

```
function F2 ( const i): *DEFERRED*
function F1 ( const i):
    if i != 0:
        <do F1 thing>
        F2 ( i - 1 )

F1 ( 1 )    // Compile Error: Call F2(0) cannot be expanded.

function F2 ( const i )
    if i != 0:
        <do F2 thing>
        F1 ( i - 1 )

F1 ( 5 )    // Legal, expands to:
            //    <do F1 thing>
            //    <do F2 thing>
            //    <do F1 thing>
            //    <do F2 thing>
            //    <do F1 thing>
            // Would not be legal if the deferred
            // function declaration were omitted,
            // as then no F2 declaration would be
            // visible to the statements of F1.
```

Here the statements of F1 compile in the context of the declaration of F1 and need the `*DEFERRED*` declaration of F2 in that context to enable these statements to call F2. Given that a call is enabled, the situation where the statements of F2 are provided later is permitted.

A `*DEFERRED*` declaration and its companion non-`*DEFERRED*` declaration must have iden-

tical prototypes, except:

- *Default-values* and *required-values* may appear only in the **\*DEFERRED\*** declaration and be omitted in the companion, but not vice-versa.
- If *default-values* and *required-values* appear in both the **\*DEFERRED\*** declaration and its companion, they must evaluate to the same *const* value. They need not have the same *constant-expressions*, but note that the two *constant-expressions* are each evaluated where their prototype is declared, and therefore are evaluated in two different contexts.

A **\*DEFERRED\*** inline *function-declaration* may have at most one companion.

The prototype of an inline *function-declaration* is visible to the *statements* of that same declaration, and therefore an inline function can call itself without having any **\*DEFERRED\*** companion.

Recursion in inline function calls must be limited by **const** variables such as the counter *i* in the above example, for if it is not, there will be a compile error when the compiler decides the inline nesting is too deep or the code generated by one statement is too much.

A special function cannot be **\*DEFERRED\***.

### 10.3.1 Inline Call-Declaration Matching

Each *function-call* in a statement must be matched to a single *function-declaration*, else compilation of the statement fails with a compile error.

The first step in processing a *statement* is to visit in bottom-to-top left-to-right order all the *expressions* in the *statement* and apply the following algorithm with evaluates *constant-expressions*, analyzes *reference-expressions*, and processes macros and inclusions:

#### Bottom-Up Expression Algorithm

1. This algorithm is applied to an *expression* *E*, and terminates after any step that annotates *E*.
2. If *E* is a *constant*<sup>p34</sup> other than a *rational-constant*, evaluate *E* to a **const** value *C*, annotate *E* with *C* and with the type **const** (*Rational-constants* are evaluated as *function-calls* to a **constant** function in Step 5 below.)
3. If *E* is a *reference-expression*, processing depends upon whether the *reference-expression* is compile-time or run-time. First we consider the case where there are no *reference-calls*<sup>p88</sup> in the *reference-expression*.

Then the *reference-expression* begins with a *variable-name* (not a *function-variable-name*) and is compile time if that variable has type **const** and run-time otherwise.

The according to the rule of Reference Expressions, 6.3<sup>p38</sup>, if the *reference-expression* is compile time compute its reference pointer and annotate  $E$  with that, and if run-time compute the type of its reference pointer and annotate  $E$  with that. Also for compile-time loading *reference-expressions*, dereference the reference pointer to get a **const** value  $C$ , and annotate  $E$  with  $C$ .

For compile-time *reference-offsets* not involved in *reference-calls*, any index *expressions* must have previously been annotated with a **const** value, else it is a compile error.

For run-time *reference-offsets* not involved in *reference-calls*, any index *expressions* are annotated with the **int** target type.

*Reference-calls* are handled as follows:

If the *reference-expression*  $E$  begins with a *function-variable-name*, find the *reference-declaration*  $D$  associated with the *function-variable-name*. If the  $E$  is not loading, exclude any *load reference-declaration*, and if  $E$  is not storing, exclude any *store reference-declaration*. If no *reference-declaration* is found (e.g., because  $E$  is storing and there is only a *load* declaration), it is a compile-error. Then annotate the root of  $E$  with  $D$ .

For **load** or **store**  $D$ , the root *function-variable-name* must be the entire *reference-expression*, else there is a compile error. In this case, annotate a compile-time  $E$  with a pseudo reference pointer indicating that to load or store one must call the function  $F$  of  $D$ , and annotate a run-time  $E$  with a pseudo virtual reference pointer whose target type is the result type of  $F$  for **load**  $D$  and the input type of  $F$  for **store**  $D$ .<sup>11</sup> For compile-time loading  $E$ , execute  $F$  to get a **const** value  $C$  and annotate  $E$  with  $C$ .

For **point**  $D$ ,  $E$  must be run-time (a **point**  $D$  cannot have a **const** type *reference-base* or result). Then  $E$ 's reference pointer type is the type of the value returned by the function  $F$  of  $D$  – annotate the root of  $E$  with this real reference pointer type.

The other *reference-call* case consists of an already processed *reference-base* with a known reference pointer if compile-time or reference pointer type if run-time and its following unprocessed *reference-offset*. With this information a search is made for a matching *reference-function-declaration*  $D$ , and if one is found, the *reference-offset* it matches becomes processed. If the  $E$  is loading,  $D$  cannot be a *store* declaration, and if  $E$  is storing,  $E$  cannot be a *load* declaration. If no *reference-declaration* is found, it is a compile-error. If a **load** or **store** declaration is found and the matching *reference-offset* is not at the very end of  $E$ , it is a compile error. If  $D$  is found annotate the *reference-call* with  $D$ , and annotate each run-time index *expression* with the **int** target type. If a compile-time index is not annotated with a **const** value, it is a compile error.

Note that to get a match for run-time  $E$ , the type of the *reference-base* reference pointer cannot be virtual; to match it must be the exact type of the *reference-pattern-base*<sup>p91</sup>.

---

<sup>11</sup>A virtual reference pointer points at a location in the local or global stack or points at a location storing a pointer. A pseudo virtual pointer is merely associated with a function to load a value or a function to store a value.



For **load** or **store**  $D$ , annotate a compile-time  $E$  with a pseudo reference pointer indicating that to load or store one must call the function  $F$  of  $D$ , and annotate a run-time  $E$  with a pseudo virtual reference pointer whose target type is the result type of  $F$  for **load**  $D$  and the input type of  $F$  for **store**  $D$ . For compile-time loading  $E$ , dereference the reference pointer for the *reference-base* and pass this as an argument to an execution of  $F$  to get a **const** result  $C$ , and then annotate  $E$  with  $C$ .

For **point**  $D$ ,  $E$  must be run-time (a **point**  $D$  cannot have a **const** type *reference-base* or result). Then the processed part of  $E$ 's reference pointer type is the type of the value returned by the function  $F$  of  $D$  – annotate the processed part of  $E$  with this real reference pointer type.

For all run-time *reference-expressions*, whether or not they contain *reference-calls*, the following is true. For a pointing *reference-expression* the reference pointer it computes must be real and its type must have a normal ‘real’ pointer type. For a loading or storing *reference-expression* the reference pointer it computes may be (pseudo) virtual and its type may have a ‘(pseudo) virtual’ pointer type, but the only thing that matters in this case is the type of the value pointed at, which will be a normal ‘real’ type. In the case of a loading *reference-expression* the reference pointer type must allow values to be read (e.g., it cannot have the **\*INIT\*** qualifier), and for a storing *reference-expression*, the reference pointer type must allow values to be stored (e.g., it cannot have the **co** qualifier), else there is a compile error.

4. If the entire *expression*  $E$  has the form:

*module-abbreviation* ( *subexpression* )

where the parentheses may not be implied, move the *module-abbreviation* to the beginning of the parsed *subexpression*, and repeat this step for the modified *expression*. See p44 for an example.

5. If  $E$  is a *function-call*, search for constant *function-declarations* matching  $E$ . If one is found, evaluate the declaration's function to get a **const** value  $C$ , and annotate  $E$  with  $C$  and the **const** type.
6. If  $E$  is a *function-call*, Search for macro *function-declarations* matching  $E$ . If one is found, evaluate the declaration's function to get a **const** value  $R$ , replace  $E$  by  $R$ , and go to Step 1.

Note that macro arguments that are *constant-expressions* (those annotated with a **const** value) or *reference-expressions* are processed before this step.

7. If  $E$  is a *function-call* that is top level in a *call-assignment-statement*  $S$ , search for inclusion *function-declarations* matching  $E$ .

Otherwise evaluate the declaration's function to **const** return values. The first return value replaces  $S$  (not  $E$ ).

Subsequent return values are assigned to  $S$ 's *assignment-results* in left-to-right order. Thus if  $S$  has  $N$  *assignment-results* (all of which must be **const** variables), then the execution must return at least  $N + 1$  results (all of which must be **const** values). If there are excess results, discard them. If there are too few, it is a compile error.

If  $S$  has been replaced, terminate this algorithm.

Note that inclusion arguments that are *constant-expressions* (those annotated with a **const** value), *reference-expressions*, or macros are processed before this step.

The second step in processing a *statement* is to visit in top-down order all the *expressions*  $E$  in the *statement* and locate for each  $E$  that are *function-calls* (and not annotated with a **const** value by the Bottom-Up Algorithm above) a matching *function-declaration*. Or more specifically, a *function-declaration* whose *function-prototype* matches the *function-call*. In this step all non-special *function-declarations* that are in scope are included in the search (special *function-declarations* were processed by the above Bottom-Up Expression Algorithm).

Furthermore in this step each  $E$  has a target type  $T$  (or types), and *function-prototypes* that match the expression are required to have a result of this type (or results of these types).

In an *expression-assignment-statement*<sup>p48</sup> each right-side *expression* has a corresponding left-side *assignment-result* which is a *reference-expression* that is annotated with a reference pointer type which when dereferenced gives the right-side *expression*'s target type.

In a *call-assignment-statement*<sup>p49</sup> in which  $E$  is the *function-call* on the statement's right-side, the statement's left-side *assignment-results* are *reference-expressions* that taken together give a list of the *function-call*'s target types.

For an *expression* that is a *function-call* argument, the declaration matched to the *function-call* specifies the target type of the argument *expression*. For example, in '**int**  $z = x + 5$ ' the target type of  $+$  is **int**, the declaration matched to ' $x + 5$ ' (the only one with an **int** result type) has **int** result and argument types, so **int** is the target type of ' $x$ ' and ' $5$ '.

For an index of a *reference-expression*, the Bottom-Up Algorithm above has annotated the index *expression* with its target type.

As a special case, in a relational expression such as ' $x < y + 5$ ' all the operands are assigned the same target type by the following procedure. If one of the operands is an explicit type conversion<sup>p74</sup>, the type of the explicit type conversion becomes the target type of all the operands (as in ' $x < \text{flt} ( y + 5 )$ '). Otherwise, if one of the operands is a *reference-expression*, its type is tested as the target type of all the operands, and if successful, its type is used (in ' $x < y + 5$ ', the type of ' $x$ ' becomes the target type of ' $y + 5$ '). If several operands are *reference-expressions*, this succeeds if one of these has a type into which the types of the others can be implicitly converted.

Consider the case of *expression*  $C$  which is a *function-call* containing an argument *expression*  $E$ . The various *function-declarations* that might match  $C$  specify various target types for  $E$ . Some of these target types may be the same, so if we find matches for  $E$  with a given

target type, we should remember what we found so we do not re-compute the match for that target type if it is needed again. Therefore, when we find a *function-declaration*  $D$  matching  $E$  for target type  $T$ , we annotate  $E$  with  $T \mapsto D$ . These annotations may then be used to compile the *statement* after this third step is completed.

Given all this, when the third step visits an *expression*  $E$  with target type  $T$  the third step executes:

### Top-Down Expression Algorithm

1. This algorithm is applied to an *expression*  $E$  and its target type  $T$  found by top-to-bottom left-to-right transversal of the *expressions* of the current statement. It annotates *expressions* with maps from possible target types to declarations containing code that can execute the *expressions*. When this algorithm searches for a declaration matching an *expression*, it uses the Declaration Search Algorithm below.
2. If  $E$  already has an annotation  $T \mapsto \dots$ , terminate this algorithm. In what follows, processing of  $E$  is terminated whenever  $E$  is annotated with  $T \mapsto \dots$ .
3. If  $E$  is annotated with a **const** value (from the Bottom-Up Step), then if  $T$  equals **const**, annotate  $E$  with  $T \mapsto *EXACT*$ . Otherwise search the implicit conversion graph<sup>p66</sup> for some shortest path  $D_1, D_2, \dots, D_n$  from  $T$  to **const**, and if one is found annotate  $E$  with  $T \mapsto D_1, D_2, \dots, D_n$ , or if not found, annotate  $E$  with  $T \mapsto *FAIL*$ .
4. If  $E$  is a *reference-expression*<sup>p38</sup>, annotated with a reference pointer type that points at a value of type  $T'$ , then if  $T$  equals  $T'$  annotate  $E$  with  $T \mapsto *EXACT*$ . Otherwise search the implicit conversion graph<sup>p66</sup> for some shortest path  $D_1, D_2, \dots, D_n$  from  $T$  to  $T'$ , and if one is found annotate  $E$  with  $T \mapsto D_1, D_2, \dots, D_n$ , or if not found, annotate  $E$  with  $T \mapsto *FAIL*$ .
5. If  $E$  is a *function-call*, search for non-special *function-declarations* that match  $E$ . If none are found, annotate  $E$  with  $T \mapsto *FAIL*$ . If more than one is found (of highest rank), annotate  $E$  with  $T \mapsto *AMBIGUOUS*$ . Otherwise if just one *function-declaration*  $D$  of highest rank was found, annotate  $E$  with  $T \mapsto D$ .

If  $E$  is the top level *function-call* in a *call-assignment-statement*, and the latter has more than one *assignment-result*, then  $T$  is replaced by a list  $T_1, T_2, \dots, T_m$  of target types (the types of the *assignment-results*), and the search for *function-declarations* is limited to those whose prototypes have at least  $m$  results with the first  $m$  of these being of types  $T_1, T_2, \dots, T_m$  respectively.

The search algorithm used by the above is:

### Declaration Search Algorithm

1. This algorithm examines all (*reference-*)*function-declarations* in the current context <sup>p101</sup> that meet criteria specified by the search and applies the Call-Declaration Matching Algorithm for *function-declarations* (see 10.3.1 <sup>p79</sup>) of the Reference Call-Declaration Matching Algorithm for *reference-function-declarations* (see 10.4.1 <sup>p90</sup>) to each. Search criteria can restrict the search to, for example, **macro** *function-declarations*, or to give another example, to all non-special *function-declarations* with a given target type (type of their first result).
2. After examining all the appropriate declarations, this algorithm has a set of declarations satisfying the (Reference) Call-Declaration Matching Algorithm. If the set is empty, this algorithm reports failure. Otherwise all but the highest ranking matches are discarded. If there is only one match left, this algorithm reports success along with the single highest ranking matching declaration. If there are more than one highest ranking match, this algorithm reports ambiguity failure.

The matching algorithm used by the above to match a *function-call* with a *function-declaration* is as follows. For the corresponding algorithm matching a *reference-call* to a *reference-function-declaration* see 10.4 <sup>p88</sup>.

### Call-Declaration Matching Algorithm

1. If the call begins with a *module-abbreviation* and the *prototype-pattern* in the *function-declaration* either does not have a preceding *module-abbreviation*, or is preceded by one that names a different module from that of the call, the call-declaration match fails.

If the *function-call* begins with a *module-abbreviation* and *prototype-pattern* is preceded by a *module-abbreviation* identifying the same module, or if the *function-call* does not begin with a *module-abbreviation* and *prototype-pattern* is not preceded by a *module-abbreviation* (both are non-external), the match is marked as **module proficient**.

In what follows, any *module-abbreviation* beginning the *function-call* is ignored, and the remainder of the *function-call* is matched to the *function-declaration*'s prototype.

2. The **key** of a *function-declaration* is the number of argument lists before the first *function-term-name* in its *prototype-pattern* followed by that first *function-term-name*. For example, the key of '(...) "+" (...)' is '() "+"'.

The *function-call* must begin with the key of the *function-declaration*, else the call-declaration match fails.

This implies that argument lists before the first *call-term-name* in a *function-call* cannot be omitted and must be bracketed by actual or implied parentheses.

When matching two *function-term-name* lexemes, if the one from the *prototype-pattern* is " quoted, the one in the *function-call* may be quoted or not quoted.

The first *function-term-name* in the call may or may not be followed by *call-argument-lists*.

3. The remainder of the *function-call*, the part after any *call-argument-lists* following the first *function-term-name*, is scanned for *prototype-pattern function-term-names* other than the first one, and also for the words ‘no’ and ‘not’. At each point in the scan one of the following must be found: (1) a *function-term-name* from the *prototype-pattern*, other than the first such, or (2) the word ‘no’, or (3) the word ‘not’, or (4) a bracketed argument list (with explicit or implicit brackets). If none of these is found at some point in the scan, the call-declaration match fails. If a *function-term-name* is found more than once, the call-declaration match fails. Every ‘no’ and ‘not’ must immediately precede a *function-term-name*, else the call-declaration match fails.

If the scan succeeds, the *function-call* is divided into *call-terms*, each beginning with a *function-term-name* possibly preceded by ‘no’ or ‘not’, and ending with argument lists (that may be omitted). If there are argument lists before the first *function-term-name* (in the key), the situation is treated as if both prototype and call began with identical virtual *function-term-names*.

Then each *call-term* in the *function-call* is matched to the *pattern-term* with the same name in the *function-declaration*.

4. If a *call-term* begins with ‘no’ or ‘not’, the *call-term* must have no argument lists and be matched to a *boolean-pattern-term*<sup>p75</sup>, else the call-declaration match fails. In this case the beginning ‘no’ or ‘not’ is removed and the argument list ‘( FALSE )’ is appended to the *call-term*.

If a *call-term* that does not begin with ‘no’ or ‘not’ matches a *boolean-pattern-term* and has no argument lists, the argument list ‘( TRUE )’ is appended to the *call-term*.

(By the rules below, if a *boolean-pattern-term* is not matched to any *call-term*, it will be given its *default-value*.)

5. A *call-term* must match its corresponding prototype *pattern-term* according the rules that follow. Failure of any call-prototype term match causes the prototype-call match to fail.
6. For a *call-term* to match its corresponding *pattern-term*, both must have the same number of *argument-lists*, the same brackets, and the same number of arguments in corresponding *argument-lists*, after the *call-term* has been **adjusted**. The following are permitted adjustments.

For every *pattern-term* that has no corresponding *call-term* (because its *function-term-name* was not found in the call), a *call-term* consisting of just the *pattern-term*’s *function-term-name* is appended to the *function-call*. After this the *call-terms* are re-ordered so their order matches that of their associated *pattern-terms*.

A *call-term argument-list* with implied parentheses is treated as if it had ( ) parentheses.

If in a left-to-right scan of a *call-term*, a *call-argument-list* with ( ) is expected but instead a [ ] bracketed *call-argument-list* or the end of the *call-term* is found, an empty list ( ) is inserted into the *call-term*.

If a *call-argument-list* is shorter than the corresponding *pattern-argument-list*, and all omitted arguments at the end of the *call-argument-list* have *default-values* in the *pattern-argument-list*, the *default-values* corresponding to the omitted arguments are added to the end of the *call-argument-list*. The *default-values* are compiled in the context of the *function-declaration* and not the context of the *function-call*: see p104.

At this point the *pattern-argument-lists* in the prototype *pattern-term* must match in order all the *call-argument-lists* in the *call-term* in type of bracket and number of arguments, else the call-declaration match fails.

7. If all the above is successful, then *actual-arguments* in the call are matched to corresponding *prototype-argument-declarations* in the *function-declaration* according to the rules that follow. Failure of any of these matches causes the call-declaration match to fail.

8. This section is skipped for special functions (functions whose *prototype-result* has the form ‘**macro** *variable-name*’, ‘**constant** *variable-name*’, or ‘**inclusion** *variable-name*’).

The types in the *protocol-result-variable-declarations* are matched left-to-right to the target types for these results. Any wildcards<sup>p32</sup> in a *protocol-result-variable-declaration* are filled in from the corresponding target type, left-to-right. If a wildcard gets more than one value from this process, the call-declaration match fails.

Then if any prototype result type is not identical to its corresponding assignment target type, the call-declaration match fails (i.e., there is no implicit conversion of function result types).

9. *Prototype-argument-declarations* are matched to an *actual-arguments* and processed left to right.

If a *prototype-argument-declaration* *PAD* is matched to an *actual-argument* *AA* and *PAD* has a wildcard, *AA* must be *reference-expression* or a *constant-expression*, (i.e., annotated with a **const** value by the Bottom-Up Algorithm) else the call-declaration match fails. The wildcard is assigned from information in the *reference-expression*’s type (the type of value the reference pointer points at) or *constant-expression*’s type (which is just **const**).

If different values are assigned to the same wildcard by this process (by different prototype-actual argument matches, or by assignments made in Step 8) the call-declaration match fails.

10. If any *prototype-argument-declaration* wildcards are unassigned at this point, the call-declaration match fails.

11. If a *prototype-argument-declaration* has a *required-value*, its matching *actual-argument* must be a *constant-expression* with a value equal to the *required-value* (which is itself the result of a *constant-expression* evaluated in the context of the *function-declaration*), after both are converted to the argument type specified by the *prototype-argument-declaration*, else the call-prototype match fails. Note that the argument type need not itself be `const`.

If the argument type is `const` and the values being compared are maps, the maps must be identical (they are compared as pointers and not as lists of elements).

12. This section is skipped for special functions.

Matches between *prototype-argument-declaration* types and acceptable *actual-argument* subexpression target types are then checked, except for `macro` arguments (that require no run-time typing). Specifically, if a *prototype-argument-declaration* specifies a target type  $T'$  for an *actual-argument expression*  $E'$ , the Declaration Search Algorithm is applied recursively to  $E'$  with target type  $T'$  to get an annotation  $T' \mapsto \dots$  on  $E'$ .

Then if any argument  $T'$  is mapped to `*FAIL*` or `*AMBIGUOUS*` the call-declaration match fails.

If any is mapped to `*EXACT*`, the call-prototype map is marked as **conversion proficient**. Note that only a single argument needs to be `*EXACT*` in order for the entire call-declaration match to be marked conversion proficient.

13. If the call-declaration match has been successful, it is assigned a **rank** that is the sum of:
  - the number of required arguments the prototype has
  - the negative of the number of `T$. . .` wildcards the prototype has; a wildcard name appearing more than once in the prototype is counted only once
  - a very large number if the match is conversion proficient
  - an even larger number if the match is module proficient

The following are examples using the builtin prototypes

```
function N r = std (N v1) "+" ( N v2 )
function bool r = std (N v1) "==" ( N v2 )
function flt64 r = std flt64 (N v1)
```

which exist for every builtin number type N.

```
int32 x = ...
flt64 r1 = x + 5
  // Target type flt64 selects N = flt64 for "+".
  // Implicit conversions flt64 <--- int32 and
  // flt64 <--- const exist.
```

```

bool b1 = ( x == 5 )
    // Target type of "==" is bool. Reference expression x selects
    // N = int32 as target type for "==" operands, which works
    // because implicit conversion int32 <--- const exists.
bool b2 = ( x == 5.5 )
    // Ditto, but when evaluated in the compiler with target type int32,
    // std *IMPLICIT* *CONVERSION* ( 5.5 ) fails and gives a
    // compile error, as 5.5 cannot be represented as an int32.
flt64 y = 5.5
bool b3 = ( x == y )
    // Reference expression y selects N = flt64 as target type
    // for "==" operands, which works because implicit conversion
    // flt64 <--- int32 exists. Reference expression x selects
    // N = int32, which fails because implicit conversion
    // int32 <--- flt64 does NOT exist.
bool b4 = ( flt64 ( x ) == 5 )
    // The explicit type conversion function flt64 selects
    // N = flt64 which works because flt64 <--- const exists.

```

## 10.4 Reference Function Declarations

A **reference function** is a function that can be called as part of evaluating a *reference-expression*. This part is called a *reference-call*.

A *function-variable-name* appearing at the beginning of a *reference-expression* as the root is a *reference-call*.

A compound *reference-expression* can be a *reference-call*.

Note that if a *reference-expression* contains a *module-abbreviation*, it is at the very beginning and is part of the root (*function-*)*variable-name*.

The syntax of a *reference-function-declaration* is:

```

reference-function-declaration ::=
    reference-function-prototype :
        statement+
    | reference-function-prototype : *DEFERRED*
reference-function-prototype

```



```

::=  load reference function
      prototype-result-variable-declaration = function-variable-name
    |  store reference function
      function-variable-name = prototype-result-variable-declaration
    |  point reference function
      prototype-result-variable-declaration = function-variable-name
    |  load reference function
      prototype-result-variable-declaration = reference-prototype-pattern
    |  store reference function
      reference-prototype-pattern = prototype-result-variable-declaration
    |  point reference function
      prototype-result-variable-declaration = reference-prototype-pattern
reference-function-specifier ::= load | store | point
prototype-result-variable-declaration ::= see p73
function-variable-name ::= see p31
reference-prototype-pattern ::= reference-pattern-base reference-pattern-offset
reference-pattern-offset ::=  member-name
                             |  member-name reference-pattern-index-list
                             |  reference-pattern-index-list
reference-pattern-base ::= ( prototype-result-variable-declaration )
reference-pattern-index-list ::=
    [ reference-pattern-index-declaration { , reference-pattern-index-declaration }* ]
reference-pattern-index-declaration ::= prototype-result-variable-declaration
member-name ::= see p31
pattern-argument-list ::= see p73

```

1. A *reference-function-declaration* is compile-time if its *prototype-result-variable-declaration* before or after the = sign in its *reference-function-prototype* has type **const**, and is run-time otherwise. *Reference-pattern-index-declarations* have type **const** if and only if the *reference-function-declaration* is compile-time.
2. A **point** *reference-function-declaration* cannot be compile-time.
3. A *function-variable-name* begins with a *module-abbreviation* if and only if it is external (just like other *variable-names*).
4. A *reference-function-declaration* not containing a *function-variable-name* is external if and only if the target type of its *reference-pattern-base* is external (the full type is a pointer type to the target type). In this case the *reference-function-declaration* must be within the same module (file) as the *type-declaration* of this target type.

5. The *reference-pattern-base* must be followed by a *member-name*<sup>p31</sup> or *square-bracketed-pattern-argument-list*.
6. Default values, required values, and **macro** arguments are not permitted.
7. A wild-card<sup>p32</sup> name of the form **T\$...** is treated in a *reference-function-prototype* as a *type-name*. A wild-card name of the form **P\$...** is treated as a *pointer-type-name*. A wild-card name of the form **Q...\$...** is treated as a *qualifier-name* and must not be combined with other *qualifier-names* in the same *prototype-result-variable-declaration*.
8. At most two *reference-function-declarations* in a context may have the same *function-variable-name*, and in this case, one must have the **load** *reference-function-specifier*, and the other must have the **store** *reference-function-specifier*.
9. At most two *reference-function-declarations* in a context may have the same *reference-pattern-base* argument type and *member-name*, and in this case, one must have the **load** *reference-function-specifier*, and the other must have the **store** *reference-function-specifier*.
10. At most two *reference-function-declarations* in a context may have the same *reference-pattern-base* argument type and have a *square-bracketed-pattern-argument-list*, and in this case, one must have the **load** *reference-function-specifier*, and the other must have the **store** *reference-function-specifier*.

#### 10.4.1 Reference Call-Declaration Matching

A *reference-expression* is one of three types:

- **Loading** The *reference-expression* begins with a *target-variable* (that does not begin with ‘@’) and is used to load a value from the referenced location.
- **Storing** The *reference-expression* begins with a *target-variable* (that does not begin with ‘@’) and is used to store a value into the referenced location.
- **Pointing** The *reference-expression* begins with a *pointer-variable* (that begins with ‘@’) and is used to compute a pointer to the referenced location.

In the case of a *function-variable-name* reference call, the *function-variable-name* is just located in the current context just like any other *variable-name*, and may be a *pointer-variable* of a *target-variable*. The *function-variable-name* begins the *reference-expression* and is the root of the *reference-expression*. There are two cases:

- **Load or Store** The *reference-function-declarations* declaring the *function-variable-name* have **load** or **store** *reference-function-specifiers* (there may be two declarations,

one **load** and one **store**). The *function-variable-name* must be the entire *reference-expression* (there can be no *reference-offsets*). If the *reference-expression* is loading (or storing), there must be a **load** (or **store**) *reference-function-declaration* declaring the *function-variable-name*, and the declared function will be called to load (or store) a value in the referenced location. The *reference-expression* cannot be pointing.

- **Point** There is only one *reference-function-declaration* declaring the *function-variable-name* and it has the **point** *reference-function-specifier*. The *reference-expression* may be loading, or storing, or pointing. The declared function is called and its result is the real reference pointer of the *reference-expression* root. The *reference-expression* may have *reference-offsets* that modify this reference pointer. A **point** *reference-function-declaration* cannot be compile-time.

In the case of a *reference-offset*, the part of the *reference-expression* before the *reference-offset* is the *reference-base* matched to the *reference-pattern-base*. At compile time the type of the reference pointer produced by the *reference-base* has been computed by recursion, and at run-time the reference pointer has already been computed.

### Reference-Call-Reference-Declaration Matching Algorithm

1. The *reference-offset* and the *reference-pattern-offset* must match in that
  - (a) If one has a *member-name*, both must have the same *member-name*, else the call-declaration match fails.
  - (b) If one has an *index-list*, both must have *index-lists* with the same number of elements else the call-declaration match fails (but the types of the elements are not involved in matching).
2. The *reference-base* in the call is matched to the *reference-pattern-base* in the declaration. If the latter has wildcards, the wildcards are assigned information in the *reference-bases*'s type.

If one wildcard is assigned two or more different values, or zero values, the call-declaration match fails.

If after this has been done, the type of the *reference-base* does not exactly match the type of the *reference-pattern-base*, the call-declaration match fails.

3. If the call-declaration match has been successful, it is assigned a **rank** that is the sum of:
  - the negative of the number of T\$. . . wildcards the prototype has; a wildcard name appearing more than once in the prototype is counted only once
  - a very large number if the match *reference-offset* has both a *member-name* and an *index-list*

Example:

```
// The *UNCHECKED* function used below is a builtin function
// that performs a variety of conversions which violate type
// checking. Here it has the prototype:
//
//      av Q$ T$ @r = std *UNCHECKED*
//          ( ap Q$ T$ @p, int offset, int lower, int upper )
//
// that takes the ap @p, adds the offset argument to the
// pointer offset, and returns this as an av with bounds
// lower and upper.

// In my vector X, a vector with flt64 elements is located
// at X.offset from the address of X and allows index range
// from 0 through X.length-1.
//
type my vector:
    int offset          // Offset of first element in bytes.
    int length          // Number of elements.
    align 64
    *LABEL* first       // Offset of first element in bits.

point reference function ap Q$1 flt64 @x =
    ( ap Q$1 my vector @v ) [ int index ]:
    av Q$1 flt64 @p = *UNCHECKED*
        ( @v, v.offset, 0, v.length )
        // See *UNCHECKED* above.
    @x = @p[index]

type my data:
    *INCLUDE* my vector
    flt64[2]

ap *READ-WRITE* my data @D:      // `@= local' is implied
    D.offset = D.first / 8        // 8 converts bits to bytes.
    D.length = 2

D[0] = 5.5          // Computes and uses pointer @D[0]
D[1] = -7.33        // Computes and uses pointer @D[1]
flt64 x = D[0]      // Now x == 5.5
flt64 y = D[1]      // Now y == -7.33
flt64 z = D[2]      // Run time error: 2 >= upper bound of av
```

```

// that equals D.length.

D[2] = 1.0      // Run-time error: bounds limit exceeded.

```

## 10.5 Inclusions

An example of an inclusion is:

```

// Create int V and iterate for V = 0, 1, 2, ..., LIMIT-1.
//
//   for ( V, LIMIT ):
//       STATEMENTS*
//
// is equivalent to:
//
//   int V = 0
//   while V < LIMIT:
//       STATEMENTS*
//       V += 1
//
inclusion function const r = for ( macro V, macro LIMIT ):
    r = { { { "int" } + V, "=", { 0 } },
          { { "while", { V, "<", LIMIT } },
            com *SUBBLOCK* +
              { { "next" } + V, "+=", { 1 } } } }

// Compute sum = 1 + 2 + ... + 15
//
int sum = 0
for ( x, 15 ):
    next sum += x + 1

// The above for ... statement is expanded to:
//
//   int x = 0
//   while x < 15:
//       next sum += x + 1
//       next x += 1
//
// because:
//
//   com *SUBBLOCK* equals:

```

```
//      { { { "next", "sum" }, "+=", { { "x" }, "+", { 1 } } },
//      ".initiator" = ":", ".terminator" = *INDENTED-PARAGRAPH* }
```

Although the value of an inclusion is to be a sequence of parsed *statements*, it is not necessary to include some of the annotations in these. Specifically, it is not necessary to include the `.position` or the following `.initiators` or `.terminators`:

#### Unnecessary Annotations

<u>.initiator</u>	<u>.terminator</u>
*LOGICAL-LINE*	"<LF>"
"("	")"

because the `.position` of the function call will be added if no `.position` is given, logical lines can be identified from context, and `()` bracketed subexpressions are equivalent to subexpressions with implied brackets (i.e., with no `.initiator` or `.terminator`).

However, any `.separator` and the following must be included:

#### Necessary Annotations

<u>.initiator</u>	<u>.terminator</u>
":"	*INDENTED-PARAGRAPH*
"["	"]"
"{"	"}"

In the above example, `com *SUBBLOCK*` evaluates to the subblock in the ‘for ...’ statement, and this subblock has `".initiator" = ":"` and `".terminator" = *INDENTED-PARAGRAPH*`, which are the necessary annotations that are carried over into the concatenation `com *SUBBLOCK* + {...}`.

The *include-assignment-statement* can be used to return a list of parsed *statements*:

```
include-assignment-statement ::=
    const target-variable = *INCLUDE* include-argument-list? :
        statement*
    | const target-variable =
        *INCLUDE* include-argument-list? : restricted-statement

include-argument-list ::= ( ) | ( include-argument { , include-argument }* )
include-argument ::= word beginning with a capital letter
restricted-statement ::= see p56
```

An *include-statement* is executed at compile time; its *statements* are parsed and the parser output is returned.

Each *include-argument* must be a `const` variable assigned a value before the *include-statement* compiles. Everywhere this variable appears in the parsed *statements* of the *include-statement*, the value of the variable is substituted for the variable name.

Substitution for *include-arguments* obeys the following rules:

- If the *include-argument* value is a list, and if the instance being substituted is an element of a list, the *include-argument* list is spliced into the instance containing list. However any *include-argument* dictionary entries are discarded.

Thus if `X = {"A", "B", ".separator" = ","}` then

`"Y", "=", { "X", "C" }` becomes `"Y", "=", { "A", "B", "C" }`

and

`"Y", "=", { "X", "C", ".separator" = "," }`

becomes

`"Y", "=", { "A", "B", "C", ".separator" = "," }`

The *include-argument* value list may be empty. If `X = {}` then

`"Y", "=", { "foo", "X" }` becomes `"Y", "=", { "foo" }`

If you do not want a list valued *include-argument* to be spliced in, use `( )` parentheses around the instance being substituted. Thus if `X = {"A", "*", "B"}` then

`"Y", "=", { ("X"), "+", 1 }`

becomes

`"Y", "=", { ("A", "*", "B"), "+", 1 }`

- Otherwise the non-list value of the *include-argument* replaces the instance in the parsed *statement*. Thus if `X = "A"` then

`"Y", "=", { "X", "*", 2 }` becomes `"Y", "=", { "A", "*", 2 }`

So the above example for inclusion could have written as:

```
function inclusion r = for ( macro V, macro LIMIT ):
  const P = com *SUBBLOCK*
  r = *INCLUDE* ( V, LIMIT, P ):
    int V = 0
    while V < LIMIT:
      P
      next V += 1
```

## 10.6 Out-of-Line Function Declarations

An out-of-line function prototype is a limited subset of an inline function prototype which ensures that there is a single ordered list of arguments. To obtain a more flexible interface, an out-of-line function call should be embedded in an inline function that pre-processes the arguments.

The syntax of an out-of-line function declaration is:

```

out-of-line-function-declaration ::=
    out-of-line-function-prototype :
        statement+
    | out-of-line-function-prototype : *DEFERRED* foreign-function-name?

out-of-line-function-prototype ::=
    out-of-line function { prototype-result-list = }?
    out-of-line-function-name parenthesized-pattern-argument-list?
out-of-line-function-name ::= module-abbreviation? basic-name
foreign-function-name ::= quoted-string
prototype-result-list ::= see p72
module-abbreviation ::= see p31
basic-name ::= see p31
parenthesized-pattern-argument-list ::= see p73

```

1. The rules for inline *function-declarations* on p72 must be followed where applicable.
2. *Out-of-line-function-declarations* must be top level; they cannot be inside sub-blocks.
3. **macro** and required arguments are not allowed.
4. Wild-cards are not allowed.
5. Functions with *foreign-function-names* are called **foreign** and are **\*DEFERRED\*** but have no companions. Foreign functions are called using their associated *out-of-line-function-name*.
6. Arguments and results of foreign C and C++ functions cannot have user defined types or user defined pointer types, but may builtin pointer types (**dp**, **ap**, **fp**, etc.) pointing at builtin or user defined target types.
7. The rules for inline '**\*DEFERRED\***' *function-declarations* and their companions on p79 must be followed for **\*DEFERRED\*** non-foreign *out-of-line-function-declarations* and their companions.

An out-of-line functions can be called with a normal *function-call*<sup>p42</sup>.

Unlike inline functions, an out-of-line function can be called from a statement for which only a **\*DEFERRED\*** declaration of the out-of-line function is visible. A missing companion declaration is not a compile-time error, but will be a run-time error if the function is actually called at run-time.

Like inline functions, a **\*DEFERRED\*** non-foreign *out-of-line-function-declaration* can have only one companion. If a **\*DEFERRED\*** non-foreign *out-of-line-function-declaration* is external,<sup>p103</sup> its companion may be anywhere in the scope of the declaration, including in



another module or another module's body that imports the declaration's module. This allows a module to call out-of-line functions defined by a companion in another module that imports the first module.

### 10.6.1 Function Type Declarations

A function type whose values are pointers to out-of-line functions may be declared by:

```
function-type-declaration ::=
    type function-type-name is function-type-prototype
function-type-name ::= type-name
type-name ::= see p31
function-type-prototype ::=
    function { prototype-result-list = }? ( ) parenthesized-pattern-argument-list?
```

1. *Function-type-declarations* must be top level; they cannot be inside subblocks.

Here the *function-type-prototype* is just like an *out-of-line-function-prototype* except that the *out-of-line-function-name* is replaced by ( ) and the word 'out-of-line' is omitted as being superfluous.

The only operations defined on function type values are copying them, comparing them with == and !=, and calling them. A call to such a value must be a *call-expression*<sup>p98</sup> and must be the right side (after the =) of a *call-assignment-statement*.<sup>p49</sup>

A function constant can be declared by:

```
function-constant-declaration ::=
    function-type-name function-constant-name :
        statement+
    | function-type-name
        function-constant-name : *DEFERRED* foreign-function-name
function-constant-name ::= target-variable
target-variable ::= see p31
foreign-function-name ::= see p96
```

1. *Function-constant-declarations* must be top level; they cannot be inside subblocks.
2. The first line of a *function-constant-declaration* behaves like an *out-of-line-function-declaration* first line made by replacing 'function-type-name function-constant-name' by the *function-type-prototype* specified by the *function-type-name* and:
  - (a) adding 'out-of-line' to the beginning
  - (b) replacing the ( ) by the *function-constant-name*

3. Non-foreign **\*DEFERRED\*** function constants are not allowed.

The *function-constant-name* is declared as a run-time **co** variable whose value has the type named by the *function-type-name*. Internally, this value is a run-time pointer to the out-of-line function. In the **\*DEFERRED\*** case this value is a pointer to the named foreign function.

Functions accessed by function type pointers must be called by:

```
call-expression ::=
    call function-expression parenthesized-call-argument-list?
function-expression ::= reference-expression
reference-expression ::= see p38
parenthesized-call-argument-list ::= see p43
```

1. The *function-expression* must evaluate to a function-type value.

## 10.7 Module and Body Declarations

A **module** is a file whose first statement is a *module-declaration*:

```
module-declaration ::= simple-module-declaration
                        | simple-module-declaration:
                          import-clause*
simple-module-declaration ::= module module-name as module-abbreviation
module-name ::= quoted-string
module-abbreviation ::= see p31
import-clause ::= import module-name as module-abbreviation
```

1. A *module-declaration* may only appear as the first statement of a module file.
2. In a *module-declaration* all *module-abbreviations* must be distinct, and all *module-names* must be distinct.

The compiler maps *module-names* to POSIX file names in an implementation dependent manner. The file that contains the module cannot contain anything else.

The *module-abbreviation* associated with a *module-name* may differ in different files. Specifically, the *module-abbreviation* for a module used in the module's own module file need not be the same as the *module-abbreviations* used for the module in files that import the module.

The module **"standard"** with module abbreviation **std** is builtin and contains the builtin types and functions. The *import-clause*

```
import "standard" as std
```

is implied in every *module-declaration* and *body-declaration*.

A **body** is a file whose first statement is a *body-declaration*:

```
body-declaration ::= body body-name of module-name:
                        body-clause★
body-name ::= quoted-string
module-name ::= see p98
body-clause ::= import-clause | after-clause
import-clause ::= see p98
after-clause ::= initialize after body-name
```

1. A *body-declaration* may only appear as the first statement of a body file.
2. In a *body-declaration* the *module-abbreviations* of imported modules must be distinct and must be different from the *module-abbreviation* used by the body's module, and all *module-names* and *body-names* must be distinct.

The compiler maps *body-names* to POSIX file names in an implementation dependent manner. The file that contains the body cannot contain anything else.

A **body** is an extension of the module named in the first line of the *body-declaration*.

A body implicitly imports the module it extends. Within the body that module has the same *module-abbreviation* that it had in the module's own file. The other modules imported in the module's own file are not implicitly imported to the body. The body must import whatever other modules it uses explicitly.

The *after-clauses* name other bodies, not necessarily in the same module, and determine the order in which bodies are initialized: see 10.7.1 <sup>p99</sup>.

### 10.7.1 Program Initialization

A module is initialized by executing its top level *statements* in the order in which they appear in the module. Similarly a body is initialized by executing its top level *statements* in the order in which they appear in the body.

The order in which modules and bodies are initialized is determined by the following rules.

1. If a module or body imports another module, the imported module is initialized before the importing module or body.
2. A module is initialized before any of its bodies.
3. If a body contains an *after-clause*, the body is initialized after the body named in the *after-clause*.

The conceptual directed graph whose nodes are modules and bodies and whose arrows connect each module or body to the modules and bodies it must be initialized after is called the ‘**initialization graph**’ and must be acyclic.

## 11 Parser Output

The output produced by the parser when it parses code is as follows. In the following **\*LOGICAL-LINE\*** and **\*INDENTED-PARAGRAPH\*** name special constants.

Recall that the input is a sequence of logical lines. Also, *rational-constants*<sup>p35</sup> are not produced by the parser: they are parsed as an operator name *word* followed by a *quoted-string*.

For a logical line, the parser produces a list with the annotations:

```
".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>"
```

The list elements are strings and numbers representing lexemes, and lists representing subexpressions.

Recall that an indented paragraph may appear at the end of a logical line.

For an indented paragraph the parser produces a list which has the annotations:

```
".initiator" => ":", ".terminator" => *INDENTED-PARAGRAPH*
```

The list elements are logical lines.

For an explicitly bracketed subexpression the parser produces a list which has the annotations:

```
".initiator" => "(", ".terminator" => ")"
```

or

```
".initiator" => "[", ".terminator" => "]"
```

The list elements are strings and numbers representing lexemes, and lists representing subexpressions.

For an implicitly bracketed subexpression the parser produces a list which has no **.initiator** and **.terminator** annotations. The list elements are strings and numbers representing lexemes, and lists representing subexpressions.

The parser does not introduce implied brackets where there are explicit or implied brackets, but will introduce implied brackets surrounding quoted strings. For example,

```
x + y parses as { { "x" }, "+", { "y" } }
( x ) + y parses as
    { { "x", ".initiator" => "(", ".terminator" => ")" },
      "+", { "y" } }
```

```
( x, "y" ) parses as
    { { "x" }, { { "y", ".type" => "<Q>" } },
      ".initiator" => "(", ".terminator" => ")" ,
      ".separator" => "," }
```

Operators that are separators, such as ‘,’ are not included as elements of a list, but become a **.separator** annotation of the list. Thus,

```
( x, y ) parses as { "x", "y",
                     ".separator" => ",",
                     ".initiator" => "(",
                     ".terminator" => ")" }
```

Quoted strings become a list with the string as a single element and a **.type** annotation equal to "<Q>" (recall that <Q> in a quoted string represents the double quote "). Thus the lexeme "Hello" becomes:

```
{ "Hello", ".type" => "<Q>" }
```

Operator operands become lists in parser output; for example, the statement ‘X = Y’ outputs ‘{ { "X" }, "=", { "Y" } }’.

An example is given in Figure 6<sup>p102</sup>.

## 12 Scope

A *declaration* has a **scope**, that is the set of statements in which any names or prototypes defined by the *declaration* are recognized.

Generally the scope of a *declaration* includes the *statements* in any *block* at the end of the *statement* containing the *declaration* (recall that a *statement* is a logical line that can end in a *block*), and all *statements* following the *statement* containing the *declaration* up to the end of the smallest *block* containing the *declaration*.

The **context** of a statement is the set of declarations whose scope the statement is in.

A **top-level declaration** is a *declaration* that is not in a *statement* inside any *block*. The scope of a top-level *declaration* lasts to the end of the file containing the *declaration*. The scope of a top-level *declaration* in a module file is extended to include each body file of the module.

Some *declarations* are **external**. These must be top-level declarations in a module (and not in a body). The scope of an external *declaration* is extended to include all modules and bodies that import the module containing the *declaration*.

A *result-variable-declaration* or *block-variable-declaration* is external if the variable-name declared begins with a *module-abbreviation*.

A *reference-function-declaration* containing a *function-variable-name* is external if the func-

Parser Input:

```
if X < Y:
    X = Y
    Y = Y + 5 * Z
    A 1, B = B, A 1
    const P = "HOHO"
    const Q = 5 + P
    const R = ( 5 + Q )
```

Parser Output:

```
{ "if",
  { { "X" }, "<", { "Y" } },
  { { { "X" }, "=", { "Y" } },
    ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    { { "Y" }, "+",
      { { "Y" }, "+", { { 5 }, "*", { "Z" } } },
      ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    { { { "A", 1 }, { "B" }, ".separator" => ",", " },
      "=",
      { { "B" }, { "A", 1 }, ".separator" => ",", " },
      ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    { { "const", "P" }, "=", { { "HOHO", ".type" => "<Q>" } },
      ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    { { "const", "Q" }, "=",
      { { 5 }, "+", { "P" } },
      ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    { { "const", "R" }, "=",
      { { 5 }, "+", { "Q" },
        ".initiator" => "(", ".terminator" => ")" },
        ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>" },
    ".initiator" => ":", ".terminator" => *INDENTED-PARAGRAPH*
  },
  ".initiator" => *LOGICAL-LINE*, ".terminator" => "<LF>"
}
```

Figure 6: Parser Output Example

tion-variable-name begins with a *module-abbreviation*.

A *next-variable-declaration* is external if the variable-name declared begins with a *module-abbreviation*. However, the *next-variable-declaration* must be in the same module file as the *result-variable-declaration* whose variable name it shares.

A *type-declaration*, *pointer-type-declaration*, or *function-type-declaration* is external if the *type-name*, *pointer-type-name*, or *function-type-name* declared begins with a *module-abbreviation*.

A *function-declaration* or *out-of-line-function-declaration* is external if the *prototype-pattern* in the *declaration* is immediately preceded by a *module-abbreviation*.

A *reference-function-declaration* containing a *prototype-reference-base* is external if the target type of the *prototype-reference-base* is external.

*Prototype-result-declaration* and *prototype-argument-declaration* variable-names cannot begin with a *module-abbreviation*, and therefore these *declarations* can never be external.

In general, a deferred declaration in a module may have a companion in that module or in a body of that module, but not in modules or bodies that import the declaration's module. As one exception, a deferred external *out-of-line-function-declaration* may have its companion anywhere within the scope of the original declaration. As a second exception, a deferred *type-declaration* must have its companion in the same file as the deferred *type-declaration*. Note that a deferred *type-declaration* may have only one companion, but the companion may have many expansions in the scope of the companion (the companion is the root of its expansion tree: see 10.1.1<sup>p60</sup>).

*Type-declarations* that end with the **\*EXTERNAL\*** sub-declaration must have external *type-names* (beginning with a *module-abbreviation*). Expansions of such a *type-declaration* may appear anywhere within scope of the initial root *type-declaration*<sup>p61</sup>, but must have a *type-name* that references the same module as the *type-declaration* they are expanding (they need not use the same *module-abbreviation* to do so).

If two *type-declarations* declaring the same *defined-type-name* have overlapping scope, they must follow the expansion tree rules of 10.1.1<sup>p60</sup>. The scope of a **\*LABEL\*** *type-subdeclaration* consists of the *type-subdeclarations* following it in its *type-declaration* and of the entirety of all *type-declarations* that are descendents of its *type-declaration* in the *defined-type-name*'s expansion tree.

A *module-abbreviation* that makes a *declaration* external must abbreviate the module in which the *declaration* occurs, with the exception of expansions of *type-declarations* that end with the **\*EXTERNAL\*** sub-declaration<sup>p61</sup> and companions of deferred *out-of-line-function-declarations*.<sup>p96</sup>

If two difference declarations of a *variable-name* have overlapping scope, one of these must necessarily include the other, and the declaration with the smaller scope is said to ‘**hide**’ the other declaration.

The same applies to *type-names*, *pointer-type-names*, *function-type-names*, *function-variable-names*, and *function-constant-names*, except that hiding does not apply to *type-declarations* that expand previous *type-declarations*.

All these names have the property that a name with a *module-abbreviation* is not the same name as that name with the *module-abbreviation* dropped. E.g., ‘mom X’ is not the same name as ‘X’ if mom is a *module-abbreviation*.

The hiding rules do not apply to *out-of-line-function-names* or *function-term-names*. *Module-abbreviations* may be omitted from *function-calls* without changing the function called, as long as there is no ambiguity (see Step 1 of the Call-Declaration Matching Algorithm, p84).

A *next-variable-declaration* is allowed within the scope of a previous declaration of its *variable-name*, including *next-variable-declaration* of the same *variable-name*, if it is not within a smaller block than the previous declaration. Note that a *next-variable-declaration* has the same syntax as a particular kind of *reference-expression*, and its use as an implicitly *\*INIT\**<sup>p41</sup> *reference-expression* is allowed within a subblock of the *block-assignment-statement* or *loop-assignment-statement* that assigns a value to the declared *next* variable. Also note that *next-variable-declarations* can be implied in *block-assignment-statements*<sup>p52</sup> and *loop-assignment-statements*<sup>p55</sup>.

Function prototypes cannot hide each other. If the current context contains two function declarations whose prototypes both match a call, the call is ambiguous and in error, even if the scope of one declaration is within the scope of the other.

*Statement-labels* (*block-labels*, *exit-labels*, and *loop-labels*), have as their scope the block in which they are defined. It is a compile error if *statement-labels* hide each other.

When a *function-call* to an inline function is expanded, the context of the expansion is not the current context but rather the context of the inline *function-declaration* that provided the *statements* executed by the call. Also the context in which any *default-value* expression provided by a *function-declaration* is compiled is the not the current context but rather the context of that *function-declaration*.

Similarly when a *reference-call* to a reference function is expanded, the context of the expansion is not the current context but rather the context of the inline *reference-function-declaration* that provided the *statements* executed by the call.

Code produced by inclusions during *statement* compilation is compiled in the context of the *statement* replaced by the code. See Inclusions (p93).

An example is:

```
module "my_own_module" as mom:
  // `import "standard" as std' is implied
  import "George's_own_module" as gom
  // gom contains:
  //      function int32 z = gom ( int32 x ) "+" ( int32 y )
```



```

int32 mom my constant = 44
int32 my constant = 55

int32 x1 = mom my constant // == 44
int32 x2 = my constant      // == 55

function int32 y = mom my function ( int32 x ): // [A]
    ... function body omitted ...
function int32 y = my function ( int32 x ):      // [B]
    ... function body omitted ...

int32 y1 = mom my function ( 100 ) // Uses [A]
int32 y2 = my function ( 100 )     // Compile error:
                                   // ambiguity between [A] and [B]

function int32 z = my inline function ( int32 x, int32 y ):
    int32 z1 = gom ( x + y )
        // Uses gom's + operator.
        // Compiles as as `gom (x) "+" (y)'.
    int32 z2 = std ( x + y )
        // Uses builtin std's + operator.
        // Compiles as as `std (x) "+" (y)'.
    z = z1 + z2
        // Compiles as `z = ( (x) "+" (y) )'.
        // Compile error, ambiguous: both std + operator
        // and gom's + operator match the call to "+".

```

More specifically, when a function declaration is used, the *module-abbreviation* beginning the function call may be omitted if the function declaration is the only function declaration within scope that matches the usage, according to Step 1 of the Call-Declaration Matching Algorithm, p84. Thus given:

```

function int32 y = mom my external function ( int32 x ):
    ... function body omitted ...

```

the lines:

```

int32 y = mom my external function ( x )
int32 y = my external function ( x )

```

are equivalent if no *function-declarations*

```

function int32 r = ma my external function ( int32 v )
function int32 r = my external function ( int32 v )

```

are in the current context, where *ma* is a module abbreviation for a module other than

"my\_own\_module".

## 13 Lifetimes

The **lifetime** of a variable, i.e., a piece of memory, is the time interval from the time that the variable is allocated to the time that the variable is deallocated. The compiler tracks lifetimes by assigning each variable a lifetime type and for variables in the local stack a separate lifetime depth.

The possible variable lifetimes are:

**global** The variable is stored in the global stack<sup>p117</sup>. The variable lifetime starts when the variable is created and stops when the program terminates.

Global variables are external variables created by a *result-variable-declaration* or *next-variable-declaration* of an *assignment-statement*, or by an *allocation-call* to the **global** allocator function.

**local** The variable is stored in the local stack<sup>p117</sup>. The variable lifetime starts when the variable is created and stops when the scope of the declaration creating the variable ends.

Local variables are non-external variables created by a *result-variable-declaration* or *next-variable-declaration* of an *assignment-statement*, or by a *prototype-argument-result-declaration* or *prototype-argument-variable-declaration* during a function call, or by an *allocation-call* to the **local** allocator function.

**heap** The variable is stored in the heap (i.e., garbage collectible memory). The variable lifetime starts when the variable is allocated to the heap, and stops when the variable can no longer be referenced by following a chain of pointer values the root of which is a global variable or is a local variable with a lifetime that has not yet terminated.

A pointer value has a pointer type that may have a **lifetime qualifier** which tells something about the lifetimes of the target variables in the datum the pointer points at. The possible lifetime qualifiers are:

<b>*GLOBAL*</b>	The target variables are in the global stack.
<b>*HEAP*</b>	The target variables are either in the heap or they are in the global stack.  Note: allowing <b>*HEAP*</b> pointers to point into the global stack requires the garbage collector to be able to distinguish global stack and heap addresses and treat them differently.
<b>(undeclared)</b>	The pointer type has no lifetime qualifiers. There are two cases:
<b>(local)</b>	The compiler knows that the target variables are in the local stack, and also knows the lexical depth of the statement that created the variables.
<b>(anywhere)</b>	The compiler does <u>not</u> know whether the target variables are in the global stack, the local stack, or the heap. However, the compiler does know that the lifetime of the target variables contains the lifetime of the variable holding the pointer value.

A pointer value whose type has the **\*GLOBAL\*** lifetime qualifier is called a **global pointer**. A pointer value whose type has the **\*HEAP\*** lifetime qualifier is called a **heap pointer**. A pointer value with undeclared pointer type that is known to point at target variables in the local stack is called a **local pointer**. A pointer value with undeclared pointer type that is not known to be a local pointer is called an **anywhere pointer**.

Somewhat similarly for variables. A **pointer variable** is a variable storing a pointer. A variable whose type is a pointer type with the **\*GLOBAL\*** lifetime qualifier is called a **global pointer variable**. A variable whose type is a pointer type with the **\*HEAP\*** lifetime qualifier is called a **heap pointer variable**. A variable whose type is a pointer type with undeclared lifetime qualifier is called an **undeclared pointer variable**.

We also divide variables into the following three classes:

<b>target variables</b>	The variable is located in the target datum of a pointer.
<b>local non-target variables</b>	The variable is stored in the local stack and is <u>not</u> a target variable.
<b>global non-target variables</b>	The variable is stored in the global stack and is <u>not</u> a target variable.

The `null` allocator function<sup>p144</sup> is special in that it can set a pointer of any lifetime type to a particular address that addresses a block of virtual memory that is inaccessible, and causes a memory fault when accessed. A pointer allocated by `null` is always a global, heap, or local pointer, depending on whether the pointer's type has a **\*GLOBAL\*** or **\*HEAP\*** qualifier or is undeclared, and is never an anywhere pointer. The lifetime assigned to target variables of a pointer allocated by `null` is a convenient fiction, since such variables can never be referenced.

The following rules prevent a pointer to a target with a given lifetime from being stored in a

variable with a longer lifetime. The first of these rules govern global and heap pointers and pointer variables and are:

- (L1) A global pointer value can be stored in any global pointer variable.
- (L2) A heap pointer value can be stored in any heap pointer variable.
- (L3) A global pointer value can be stored in any heap pointer variable.  
Note: This requires the garbage collector to be able to distinguish global stack and heap addresses and treat them differently.
- (L4) A value read from a global pointer variable is a global pointer.
- (L5) A value read from a heap pointer variable is a heap pointer (has pointer type with *\*HEAP\** qualifier), even if in fact it points at the global stack.
- (L6) Undeclared pointer variables that are in the target of a global pointer are global pointer variables.  
Undeclared pointer variables that are in the target of a heap pointer are heap pointer variables.  
In other words, a lifetime qualifier of a pointer *P* is added to the type of any undeclared pointer variables in the target of *P*.

An example is:

```

type list element:
  ap list element @successor
    // When in the global stack, @successor has *GLOBAL*
    // lifetime qualifer implied by (L6).

// In the following, `@= global' is implied because the pointers
// are *GLOBAL*.

ap *GLOBAL* list element @list empty @= null
  // $list empty is now a global pointer

// Circular list:
//
ap *GLOBAL* list element @last: // `@= global' is implied
  last.@successor = @list empty
  // Last element is pointed at by last.@successor
  // First element is pointed at by last.successor.@successor
  // Empty list has last.@successor == @list empty

// Put two elements in list.
//

```

```

ap *GLOBAL* list element @X // `@= global = *DEFERRED*' is implied
ap *GLOBAL* list element @Y // `@= global = *DEFERRED*' is implied

ap *GLOBAL* list element @X:
    // Put X on empty list
    X.@successor = @X
    last.@successor = @X
    // List now consists of (X)
ap *GLOBAL* list element @Y:
    // Add Y to end of list
    Y.@successor = last.successor.@successor
    last.successor.@successor = @Y
    last.@successor = @Y
    // List now consists of (X, Y)

```

A local pointer is tagged automatically by the compiler with the lexical depth of the *statement* that created the pointer. Top level *statements* have lexical depth 1. *Statements* in a subblock of a top level *statement* have lexical depth 2, and so forth. Details, including how to handle inline function calls, are below.

- (L7) A pointer into the local stack created by an *allocation-call* in an *assignment-statement* of depth  $D$  is a local pointer of depth  $D$ .
- (L8) A local pointer of depth  $D$  may be stored in an undeclared local non-target pointer variable that is not an **out-of-line** function argument variable (it may be an inline function argument variable). The compiler then annotates the pointer variable as holding a local pointer of depth  $D$ .
- (L9) A pointer value read from an undeclared non-target pointer variable that is annotated as holding a local pointer of depth  $D$  is a local pointer of depth  $D$ .
- (L10) A local pointer of depth  $D$  may be stored in an undeclared target pointer variable that is in the target of a local pointer of depth  $D$ .
- (L11) A pointer value read from an undeclared target pointer variable in the target of a local pointer of depth  $D$  is a local pointer of depth  $D$ .

Note that local pointers cannot be stored in global non-target variables or in pointer variables in the target of a global or heap pointer. If a local non-target variable holds a local pointer  $P$  of depth  $D$ , all the undeclared target pointer variables reachable by tracing undeclared target pointer variable values starting at  $P$  necessarily hold local pointers of depth  $D$ . So in a network of data completely connected by local pointers, all these local pointers have the same depth.

An example is:

```
type list element:
```

```

    ap list element @successor

ap list element @list empty @= null
    // Depth 1 null value.

// In the following, '@= local' is implied because the pointers
// are (lifetime) undeclared.

// Circular list:
//
ap list element @last: // '@= local' is implied
    last.@successor = @list empty
    // Last element is pointed at by last.@successor
    // First element is pointed at by last.successor.@successor
    // Empty list has last.@successor == @list empty

// Put two elements in list.
//
ap list element @X // '@= local = *DEFERRED*' is implied
ap list element @Y // '@= local = *DEFERRED*' is implied

// Note: @last, @X, @Y, last.@successor, X.@successor, etc.
// all have depth 1

ap list element @X:
    // Put X on empty list
    X.@successor = @X
    last.@successor = @X
    // List now consists of (X)
ap list element @Y:
    // Add Y to end of list
    Y.@successor = last.successor.@successor
    last.successor.@successor = @Y
    last.@successor = @Y
    // List now consists of (X, Y)

```

The last kind of pointer is the **anywhere pointer**. *Out-of-line* argument undeclared pointer variables must be anywhere pointers. The rules are:

- (L12) If a global or heap pointer is stored in an undeclared local non-target pointer variable (specifically including *out-of-line* argument undeclared pointer variables), the value stored becomes an anywhere pointer, and the compiler annotates the pointer variable as holding an anywhere pointer.
- (L13) If an anywhere pointer is stored in an undeclared local non-target pointer variable (specifically including *out-of-line* argument undeclared pointer variables), the value stored becomes an anywhere pointer, and the compiler annotates the pointer variable as holding an anywhere pointer.
- (L14) A pointer value read from an undeclared non-target target pointer variable that is annotated as holding an anywhere pointer is an anywhere pointer.
- (L15) A pointer value read from an undeclared target pointer variable in the target of an anywhere pointer is an anywhere pointer.

Note that because of (L6) the pointer value may actually point at the global stack or the heap.

Note that because of (L11) the pointer value may actually point at the local stack.

Note that an anywhere pointer can only be stored in local non-target variables, and any undeclared target pointer variable value that is reachable from an anywhere pointer becomes an anywhere pointer when it is read.

The rules for assigning depth to *statements* are as follows:

- (S1) A *statement* that is not inside any other statement (i.e., is not in a sub-block; i.e., is top-level) is assigned depth 1.
- (S2) A *statement* that is inside a sub-block  $S$  at the end of an *assignment-statement* of depth  $D$ , and is not also inside a sub-block of  $S$ , is assigned depth  $D + 1$ .

- (S3) An inline function-call is treated as creating a sub-block immediately inside the *statement* containing the *function-call*. The argument and result variables created by the inline *function-prototype* are treated as having been created by this *statement*.

Thus if an inline function is called from a *statement* of depth  $D$ , the *statements* in the sub-block  $S$  at the end of the inline function declaration that are not inside a sub-block of  $S$  will have depth  $D + 1$  and the argument and result variables of the inline function declaration will have depth  $D$ .

Note: If an inline function is called from a *statement* of depth  $D$ , the depth  $D'$  of the function's declaration must such that  $D' \leq D$ , since the calling *statement* must be in the scope of the declaration.

Note that because of (S1) and (S2) and the fact that an out-of-line function declaration must be top level, the sub-block  $S$  at the end of an out-of-line declaration is assigned depth 2.

The last example modified to use inline functions is:

```

type list element:
    ap *READ-WRITE* list element @successor
        // List elements must be *READ-WRITE*

ap *READ-WRITE* list element @list empty @= null
    // Depth 1 null value.

// In the following, '@= local' is implied because the pointers
// are (lifetime) undeclared.

// Circular list:
//
ap *READ-WRITE* list element @last: // '@= local' is implied
    last.@successor = @list empty
    // Last element is pointed at by last.@successor
    // First element is pointed at by last.successor.@successor
    // Empty list has last.@successor == @list empty

// Put two elements in list.
//
ap *READ-WRITE* list element @X // '@= local = *DEFERRED*' is implied
ap *READ-WRITE* list element @Y // '@= local = *DEFERRED*' is implied

// Note: @last, @X, @Y, last.@successor, X.@successor, etc.

```



```

// all have depth 1

// Add element to end of circular list:
//
function add ( ap *READ-WRITE* list element @element ):
    // element depth is taken from actual argument
    if last.@successor == @list empty:
        element.@successor = @element
    else:
        element.@successor = last.successor.@successor
        last.successor.@successor = @element
    last.@successor = @element

// Put elements in list.
//
add ( @X )           // X is first element
add ( @Y )           // Y is second element

```

A *reference-expression* with no *reference-calls* that computes a pointer assigns to that pointer the lifetime qualifiers given for the root of the *reference-expression*. E.g., a pointer to a member of the target of a global pointer is a global pointer. When the *reference-expression* does not contain a *reference-call*, this makes sense because a member of the target of a global pointer is contained by the target of the global pointer.

A **point reference function** assigns lifetime qualifiers according to instructions in its *reference-function-prototype*. By using wildcards the prototype may copy root lifetime qualifiers to the result or change these qualifiers.

The garbage collector must be able to find all heap pointer variables in the local and global stacks. Since anywhere pointer variables in the local stack may also point at heap data, the garbage collector must also be able to find them.

## 14 Memory Management

Space for variables allocated by *variable-declarations* is allocated to the currently executing out-of-line function frame or to the stack after this frame: see p46 and p48 for details.

Pointers to the heap (**heap pointers**) normally use the stub-body concept: the heap pointer points not at the body of a heap datum, but instead at a stub which begins with a body pointer at the body. This can be used in a variety of garbage collection schemes. All these schemes require that some special action be taken when a heap pointer is read into a stack variable, or when a heap pointer is written into a heap datum, or when any location in the stack or heap that stores a heap pointer has its value changed.

However instead of using `stub-body`, heap pointers can optionally be interpreted as pointing directly at the heap datum.

Specifically, the compiler recognizes the following options:

**stub** or **no-stub**

With the **stub** option, heap pointers point at a stub and the first word of the stub points at the heap datum body. With the **no-stub** option, heap pointers point directly at the body.

**copying-gc**, **marking-gc**, **counting-gc**, or **no-gc**

These options specify garbage collection (**GC**) algorithm being used. These algorithms are described below.

**read-gc** or **write-gc**

These are sub-options of GC, indicating whether the GC is read-oriented or write-oriented. See the descriptions of GC below.

All kinds of GC run interleaved with non-GC execution. These compiler options control default inline functions that do the following during non-GC execution:

- Read a non-pointer from a heap datum.
- Read a pointer from a heap datum.
- Write a pointer to a heap datum.
- Write a non-pointer to a heap datum.
- Write a pointer to a non-loop iteration stack variable.
- Write a pointer to a loop iteration stack variable.
- Deallocate a location that contains a pointer.

The three kinds of GC are discussed in detail in the following sub-sections.

## 14.1 Copying Garbage Collection

In copying garbage collection the stub of a datum is the datum's first word. When the datum is first allocated, this stub points at itself. Then during GC the body will be copied and for a time have two stubs, the stub in the old body that was the source of the copy, and the stub of the new body that was the destination of the copy. Both will point at the new body, and the new body will hold the datum itself, while the old body will no longer be accessed except for its stub.

GC works in cycles. At the start of each cycle, all heap data are in a contiguous virtual memory space called the old space. A new large contiguous virtual memory space is allocated called the new space. The boundary address between these can be use to tell if a body is in old space or new space: just compare the body pointer with the boundary address. The object of the GC cycle is to copy all active data from old space to new space, update all active heap pointers to point at new space stubs, and then discard old space completely.

GC performs a basic operation on heap pointers which we will call **pointer-update**. In this a heap pointer is checked to see if it points at new space, and if not, is replaced by a pointer that points at new space. If the heap pointer points at a body pointer in old space that itself points at old space, the body pointed at is moved to new space, and the heap pointer is replaced by a pointer to the body in new space. If the heap pointer points at a body pointer in old space that points at new space, the heap pointer is simply replaced by that body pointer.

When a new body is created, it is allocated to new space. Places for new or copied bodies in new space are allocated at the ‘end’ of new space.

GC goes through new space from beginning to end updating all the pointers in bodies it encounters. This is called ‘scavenging’. At any time there is an address that is the boundary between the scavenged bodies at the beginning of new space and the non-scavenged bodies at the end of new space. This address can be use to tell if a new space body has been scavenged.

The root pointers of GC are in the global memory (memory allocated at load time) and the stack.

The GC can be either read-oriented or write-oriented.

A read-oriented GC updates heap pointers when they are read from bodies by non-GC execution. The GC begins by updating all heap pointers in global memory and the stack, and from this point on, all pointers in global memory and the stack point to new space and no special action is required when a pointer is written to a body (which itself will be in new space) by non-GC execution.

A write-oriented GC updates heap pointers when they are written into scavenged bodies by non-GC execution. After all objects in new space have been scavenged, the GC updates all pointers in global memory and the stack, and if this does not move any bodies to new space, GC is done; otherwise GC resumes scavenging. Heap pointers in global memory and the stack need not be updated during non-GC execution, and no special action is taken when reading a heap pointer from a body.

The advantage of write-oriented over read-oriented is that write operations are less frequent than read operations and therefore write-oriented may be more efficient. The disadvantage is that in order to finish, the GC must update all pointers in global memory and the stack without non-GC execution changing the stack.

It is possible to implement a deallocate operation which deallocates a body, except for its

body pointer. A deallocated body has a body pointer pointing at a large area of inaccessible virtual memory, so a memory fault will occur if the body is accessed. To copy a deallocated body one just makes a copy of just the body pointer without changing this body pointer, which is left pointing at inaccessible memory. The update operation must do extra work to detect deallocated bodies if they are permitted.

The `no-stub` option may not be used with copying GC.

## 14.2 Marking Garbage Collection

In marking GC, stubs are allocated to a separate space from bodies, and bodies are not copied during GC. Bodies are copied by a separate activity called compaction that is independent of GC. The advantages are that there is less body copying and also that less memory space is required. Also deallocated bodies do not require the update operation to do extra work.

The simplest marking GC uses stubs that begin with a body pointer followed by two list pointers (for doubly linked lists), a marked flag, and a scavenged flag (the flags can generally be put in the same words as the list pointers). There are two lists of stubs: an old space list and a new space list. To move a stub from old space to new space, it is unlinked from the old space list and linked onto the end of the new space list, and its marked flag is set. When a datum is scavenged, its scavenged flag is set.

Otherwise marking GC is just like copying GC.

A variant has only one list pointer associated with the stub and there is just one stub list. The marked and scavenged flags are used as before. At its end, GC goes through the list of all stubs and frees unmarked stubs along with their bodies. However, the list of stubs to be scavenged must be maintained separately, typically as a list of vectors whose elements point at stubs to be scavenged. When a stub is first marked it is put on the list of stubs to be scavenged.

## 14.3 Counting Garbage Collection

In counting GC each stub has a reference count. The fundamental non-GC operation is storing a pointer P in a location. The required steps are:

- (1) save the location's previous value S
- (2) add one to the reference count of the stub pointed at by P
- (3) subtract one from the reference count of the stub pointed at by S;  
if that reference count is now zero, collect the stub and its body
- (4) store P in the location

This operation must be used when a pointer location is updated in the stack or in a body. There is also an operation for deallocating a location containing a pointer, which omits steps

(2) and (4).

Bodies may or may not be allocated separately from stubs. If separate (the `stub` option), deallocated bodies may be implemented and bodies may be compacted separately from GC. Or the `no-stub` option may be used with counting GC.

Of course reference counting GC cannot collect data containing pointer loops, such as circular lists.

## 14.4 Locating Global and Local Heap Pointers

A list of global and local variables that contain `*HEAP*` pointers needs to be made available to the garbage collector.

From the point of view of the garbage collector, variables are held in two stacks: the **global stack** and the **local stack**. These stacks are each a sequence of blocks. Each block has at its beginning a **block type** ID which references load time data that tells the length of the block and contains a map specifying which words of the block contain `*HEAP*` pointers. Some types of blocks contain a vector of similar elements, and for these there is a separate count of the number of vector elements at the beginning of the block and the block type data only specifies that length of an element and which words of the element contain `*HEAP*` pointers.

An out-of-line function call begins by allocating a block in the local stack to hold its local `co` variables. All the variables are allocated at the beginning of the call execution, so this block does not vary in size or layout during the function call execution. Executions of ‘`@= local`’ during the function call will add a block to the local stack if the allocated memory size cannot be determined at compile time. At the end of the out-of-line function call, all the blocks it allocated to the local stack are deallocated.

In the case of a statement containing ‘`@= local`’ in a loop iteration, execution of the statement will re-use the block allocated by the last execution of that statement, unless that block is too small, in which case a new block of at least twice the size of the last block will be allocated. This scheme allocates at most 4 times as much memory as is actually used by the statement during any of its executions.

When a block is allocated it is zeroed. This allows the garbage collector to avoid variables containing `*HEAP*` pointers that have not yet been set.

The execution of each module and body file initialization is treated the same as an execution of an out-of-line function call, except that at load time, before initialization, a block holding the external variables of each module is allocated to the global stack. This allows addresses of external variables to be computed at load time.

Statements containing `@= global` can be executed anytime and allocate blocks to the global stack.

Blocks in the global stack are never deallocated.

## 15 Non-Function Operators

Some operators map onto functions. For example,

$x + y$  maps onto `x "+" y`

However the following operators do not map onto functions:

```
prefix type
prefix pointer type
prefix function
prefix macro function
prefix constant function
prefix inclusion function
prefix load reference function
prefix store reference function
prefix point reference function
prefix out-of-line function
afix infix is type
afix infix is function
    See Declarations p57.
```

```
prefix call
    See Call-Expression p98
```

```
prefix if
prefix else if
initial else
afix right :
    See Conditional Statements p56.
```

```
afix subblock
postfix subblock
    See Assignment Statements p44 and Conditional Statements p56.
```

```
prefix loop
prefix while
prefix until
prefix exactly ... times
prefix at most ... times
    See iteration-control p54.
```

```
infix =
    See Assignment Statements p44.
```

infix +=  
 infix -=  
 infix \*=  
 infix /=  
 infix |=  
 infix &=  
 infix ^=  
 infix <<=  
 infix >>=

The statement ‘`x += y`’ is syntactic sugar for ‘`next x = x + y`’ if `x` is a local `co` variable, and for ‘`x = x + y`’ otherwise.

Similarly for the other operators of the form ‘`B=`’ where `B` is a binary operator, the statement ‘`x B= y`’ is syntactic sugar for ‘`next x = x B y`’ or ‘`x = x B y`’.

infix @=

See Allocation Call<sup>p46</sup>.

infix --->

See Abbreviation Statements<sup>p33</sup>.

nofix ,

Becomes a `.separator` annotation on a list. See the operator separator format<sup>p28</sup>.

infix **if**

infix afix **else**

Must be used in an *else-expression* with target type *T* which has the syntax:

***else-expression*** ::= *if-expression* { **else** *if-expression* }<sup>\*</sup> **else** *T-expression*

***if-expression*** ::= *T-expression* **if** *bool-expression*

*bool-expression* ::= *expression* with target type **bool** if *T* is not **const**  
 and otherwise target type **const**

*T-expression* ::= *expression* with target type *T*

The *bool-expressions* are evaluated left to right until one evaluates to **true** or **TRUE**. Then the corresponding *T-expression* (the one in the same *if-expression* as the *bool-expression*) is evaluated and returned. If all *bool-expressions* evaluate to **false** or **FALSE**, the *T-expression* after the last **else** is evaluated and returned.

infix **BUT NOT**

‘`x BUT NOT y`’ is syntactic sugar for ‘`x AND ( NOT ( y ) )`’.

infix **AND**

‘`x AND y`’ is syntactic sugar for ‘`y if x else FALSE`’.

infix **OR**

‘`x OR y`’ is syntactic sugar for ‘`TRUE if x else y`’.

prefix **NOT**

‘**NOT** *x*’ is syntactic sugar for ‘**FALSE** if *x* else **TRUE**’.

## 16 Builtin Abbreviations

*Module-abbreviations* are automatically deduced for function calls, but not for data types, pointer types, or variables used as global constants, such as **true** or **false**. In order to avoid having to input a *module-abbreviation* with every type name, *abbreviation-statements* are used (p33). The following are the builtin abbreviations:



int	---	std int
intd	---	std intd
intq	---	std intq
int8	---	std int8
int16	---	std int16
int32	---	std int32
int64	---	std int64
int128	---	std int128
uns	---	std uns
unsd	---	std unsd
unsq	---	std unsq
uns8	---	std uns8
uns16	---	std uns16
uns32	---	std uns32
uns64	---	std uns64
uns128	---	std uns128
bool	---	std bool
true	---	std true
false	---	std false
TRUE	---	std TRUE
FALSE	---	std FALSE
NONE	---	std NONE
UNDEF	---	std UNDEF
LOGICAL-LINE*	---	std *LOGICAL-LINE*
INDENTED-PARAGRAPH*	---	std *INDENTED-PARAGRAPH*
flt	---	std flt
fltd	---	std fltd
fltq	---	std fltq
flt8	---	std flt8
flt16	---	std flt16
flt32	---	std flt32
flt64	---	std flt64
dp	---	std dp
ap	---	std ap
fp	---	std fp
av	---	std av
fv	---	std fv

## 17 Constant Functions and Compiler Constants

Constant functions have `const` results and do not produce run-time code.<sup>p77</sup> The functions described in the following sections are builtin constant functions.

Some compilation related functions and constants are in the ‘`compiler`’ module, which is abbreviated here as ‘`com`’.

Unless stated otherwise, builtin constant functions obey the following rules:

1. Boolean values are represented by the special constants `TRUE` and `FALSE`.
2. Errors in arguments, such as passing a `string` when a `number` or `rational` is required, result in the function doing nothing but returning the `UNDEF` special constant and producing a compiler error message.
3. If a result or argument is said to be an integer, it may be either a `number` with an integral value, or a `rational` with denominator 1.
4. A `number` is a `const` value representable by a *number-constant*.<sup>p34</sup>.

A function (e.g., `+` or `==`) with at least one `number` argument will convert all `rational` arguments to `numbers` before using them, will do all internal calculations with `numbers` and not `rationals`, and will return any numeric results as `numbers`.

Number values too positive or negative to store are converted to `+Inf` or `-Inf`. Number values too small to store are converted to `+0` or `-0`, preserving the sign of the value.

### 17.1 Compile Time General Functions

```
constant function const r = std (const v1) "==" ( const v2 )
constant function const r = std (const v1) "!=" ( const v2 )
```

If any argument is a number and the other is rational, the rational is converted to a number before the comparison. Otherwise comparisons of `const` values of different types treat the values as unequal.

```
constant function const r = std type ( const v1 )
```

Returns the type of `v1` as one of the strings:

```
"special"    "number"    "rational"    "string"    "map"
```

### 17.2 Compile Time Numeric Functions

Unless specified otherwise, if one argument is a number and the others are rational, the rational arguments are converted to numbers before the function executes.

```
constant function const r = std number ( const v1 )
constant function const r = std rational ( const v1 )
```

These convert their argument to a number or rational. If the argument is a string, it must have the format of a number or rational constant (rational operator followed by quoted string). If the argument is a map, the map must have two elements that are strings, with the first being a rational operator and the second being the quoted string it operates on. Map annotations are ignored, so the map may be ‘ ’ quoted. E.g.,

```
`B# "1.1" { "B#", "1.1" }
```

A conversion error produces an UNDEF result and an error message. Note that finite numbers can always be converted to rationals, and rationals can always be converted to numbers, though these may be +Inf or -Inf.

```
constant function const r = std "+" ( const n1 )
constant function const r = std "-" ( const n1 )
constant function const r = std (const n1) "+" ( const n2 )
constant function const r = std (const n1) "-" ( const n2 )
constant function const r = std (const n1) "*" ( const n2 )
constant function const r = std (const n1) "/" ( const n2 )
```

Standard arithmetic operators on numbers or rationals *n1* and *n2*, done using IEEE number or rational arithmetic. For numbers, dividing by 0, adding +Inf to -Inf, a NaN argument, etc. return NaN and no compiler error message. For rationals, dividing by 0 returns UNDEF and outputs a compiler error message.

```
constant function const r = std (const i1) "&" ( const i2 )
constant function const r = std (const i1) "|" ( const i2 )
constant function const r = std (const i1) "^" ( const i2 )
constant function const r = std (const i1) "<<" ( const i2 )
constant function const r = std (const i1) ">>" ( const i2 )
```

Standard bitwise operators on integers *i1* and *i2* that are treated as two's complement. For the shift operators "<<" and ">>", *i2*, the amount of the shift, must not be negative. Overflows for number << shift produce an UNDEF result and a compiler error message, as do non-integer arguments.

```
constant function const r = std (const n1) "==" ( const n2 )
constant function const r = std (const n1) "!=" ( const n2 )
constant function const r = std (const n1) "<" ( const n2 )
constant function const r = std (const n1) "<=" ( const n2 )
constant function const r = std (const n1) ">" ( const n2 )
constant function const r = std (const n1) ">=" ( const n2 )
```

Standard comparison operators on numbers or rationals *n1* and *n2*. Infinities are treated as actual numbers with absolute value larger than any real number: e.g., if *x* is not a NaN, '*x* <= +Inf' is always TRUE and '*x* == +Inf' is TRUE iff *x* is +Inf. If an argument

is a NaN, all comparisons return FALSE except `!=` which returns TRUE, but there is no compiler error message.

```
constant function const r1, const r2 = std floor
    (const n1, const n2 ?= 1 )
constant function const r1, const r2 = std ceiling
    (const n1, const n2 ?= 1 )
constant function const r1, const r2 = std truncate
    (const n1, const n2 ?= 1 )
constant function const r1, const r2 = std round
    (const n1, const n2 ?= 1 )
```

These divide `n1` by `n2` and return `r1` as the result rounded to an integer and `r2` as the remainder. Here `floor` rounds toward negative infinity, `ceiling` rounds towards positive infinity, `truncate` rounds toward zero, and `round` rounds to the nearest integer, or to the even integer if there are two nearest integers.

If an argument is a number, return NaNs if the divisor is zero, an argument is a NaN, or `n1` is an infinity, but do not output a compiler error message. If both arguments are rationals and the divisor is zero, return UNDEF and output a compiler error message.

```
constant function const r = std numerator ( const r1 )
constant function const r = std denominator ( const r1 )
```

These functions return the numerator and denominator of `r1`, which must be a rational. Both numerator and denominator are integer rationals.

```
constant function const r = std is nan ( const v1 )
constant function const r = std is infinite ( const v1 )
constant function const r = std is finite ( const v1 )
```

Return TRUE if `v1` is a NaN number (`is nan`), is +Inf or -Inf (`is infinite`), or is a number that is neither of these (`is finite`), and FALSE otherwise. `v1` must be a number or a rational; if it is a rational, it is converted to a number before it is tested.

### 17.3 Compile Time String Functions

```
constant function const r = std "#" ( const s )
```

Returns the length of string `s` as a non-negative integer **number**.<sup>12</sup> Note that `#` is a prefix operator.

```
constant function const r = std (const s1) "+" ( const s2 )
```

Returns the concatenation of string `s1` and string `s2`.

---

<sup>12</sup>The length of a **string** cannot be above  $2^{48}$  while **numbers** can precisely store integers up to  $2^{53}$ .

```
constant function const r = std sprintf ( const format, const a1 = "",
                                         const a2 = "", const a3 = "",
                                         const a4 = "", const a5 = "" )
```

Returns the string made by calling the UNIX **sprintf** function as per:

```
sprintf ( format, a1, a2, a3, a4, a5 )
```

where **format** is a string. Not all of the data arguments **a1**, **a2**, **a3**, **a4**, and **a5** need be used by the **format**. Data arguments may be numbers or strings. Rational data arguments are converted to numbers first. Map data arguments are not allowed.

```
constant function const r = std (const s1) "==" ( const s2 )
constant function const r = std (const s1) "!=" ( const s2 )
constant function const r = std (const s1) "<" ( const s2 )
constant function const r = std (const s1) "<=" ( const s2 )
constant function const r = std (const s1) ">" ( const s2 )
constant function const r = std (const s1) ">=" ( const s2 )
```

Standard lexicographic comparison operators on strings **s1** and **s2**. Characters are compared by comparing their UTF-8 representations as strings of unsigned 8-bit bytes. With exceptions for unnormalized UTF-8 encodings,<sup>13</sup> this is equivalent to comparing the characters by comparing their UNICODE codes as unsigned 32-bit integers.

```
constant function const r = std explode ( const s )
```

Returns a map that is a vector whose elements are unsigned integer **numbers** equal to the UNICODE codes of the characters of string **s**.

```
constant function const r = std implode ( const m )
```

Given a map **m** that is a vector whose elements are unsigned integer **numbers** that are UNICODE codes of characters, return the string whose characters are those specified by the map elements in the order specified by the map.

```
constant function const r = std compile re ( const s )
```

Compile the regular expression represented by the string **s** and return an integer that references the compiled expression.

Regular expressions are those recognized by the **pcre32** subroutine library for linux: see **pcrpattern[3]** in the linux documentation. The only line ends recognized by **\R** and **\$** are LF, CR, and CRLF (no other **pcre32** options are used). By default **^** matches the beginning of the string being matched and **\$** matches the end. This can be changed by the **(?i)** option setter in the regular expression.

```
function free re ( const i )
```

Free the memory used by the compiled regular expression referenced by the integer **i**. Does nothing if **i** does not reference a compiled regular expression.

---

<sup>13</sup>An unnormalized UTF-8 encoding for a character is one taking more bytes than necessary. For example, NUL with UNICODE code 0, can be encoded in 1-byte if normalized, or in 2-, 3-, or 4- bytes unnormalized.

**constant function** `const r = std match re ( const i, const s )`

Matches the string `s` to the compiled regular expression referenced by the integer `i`. Returns a map `r` that is a vector of substrings matched. If there is no match this is an empty list. If there is a match, `r[0]` is the string matched. If there are subpattern matches, `r[i]` is the string matched by the `i`'th subpattern.

During matching `s` is stored as an exploded vector of unsigned 32-bit unicode values. Matched strings are subvectors which are imploded to make `const` string values.

**constant function** `const r = std scan ( const s )`

Scan the string `s` and return a map that is a vector containing the list of lexemes in `s`. Brackets and operators are not specially recognized and are returned as strings. Quoted strings inside `s` are returned as vector elements that are maps of the form:

`{ represented-string, ".type" => "<Q>" }`

Syntax errors produce compiler error messages and return `UNDEF`.

**constant function** `const r = std parse brackets ( const s )`

Equivalent to '*value-of-s*'. See *phrase-constants*: p37.

Specifically, parse the string `s` recognizing brackets but not recognizing operators and return a map. Syntax errors produce compiler error messages and return `UNDEF`.

**constant function** `const r = std unparse brackets ( const v, const f ?= "%0.16g" )`

Inverse of `parse brackets`. Return a string `S` such that '`"S"`' equals `v` with numeric rounding differences. Numbers are printed in `S` using `f` as a printf format.

**constant function** `const r = std parse ( const s )`

Equivalent to `{* value-of-s *}`. See *expression-constants*: p37.

Specifically, parse the string `s` and return a map. Syntax errors produce compiler error messages and return `UNDEF`.

**constant function** `const r = std unparse ( const v, const f ?= "%0.16g" )`

Inverse of `parse`. Return a string `S` such that `{* "S" *}` equals `v` with numeric rounding differences. Numbers are printed in `S` using `f` as a printf format.

## 17.4 Compile Time Map Functions

A `const` map value is actually a pointer to the map, and not the whole map itself. A *map-constant* creates a new map, distinct from every other map (so you can have multiple different empty maps).

A map may be read-write or read-only. Read-only maps cannot be modified. Each *map-constant* makes a separate read-only map that can be made read-write permanently or temporarily by the following:

```
constant function const r = std read-write ( const m )
constant function const r = std read-only ( const m )
```

Makes the map *m* read-write or read-only and returns *m*.

When the map is created by a *map-constant*, it is made read-only.

Each map *dictionary-entry* can be separately made read-write or read-only. When created, the entry is read-only. This can be changed by the following:

```
constant function const r = std read-write ( const m, const s )
constant function const r = std read-only ( const m, const s )
```

Makes the map label *s* (a string) of the map *m* read-write or read-only, and returns *m*. The dictionary entry labelled *s* in the map *m* can be written if it is read-write and the whole map is separately read-write.

When a value is first written at a label, the label is created for the map and set to read-write.

In addition, the compiler will mark some map labels as **protected**. Such entries are read-only to the code being compiled, and may either be permanently read-only or may be written only by the compiler during compilation.

```
constant function const r = std "#" ( const m )
```

Returns the length of the vector part of the map *m* as a non-negative integer **number**.<sup>14</sup> Note that *#* is a prefix operator.

```
constant function const r = std labels ( const m )
```

Returns a list of the *dictionary-labels* (see p36) of map *m*. The *dictionary-labels* are strings. The list may be empty.

```
constant reference function const r = std ( const m ) [ const s ?= NONE ]
constant reference function std ( const m ) [ const s ?= NONE ] = const v
```

Here *m* is map and *m[s]* is used to reference a vector element or dictionary entry of *m* as follows:

1. If the value of *s* is a non-negative non-rational integer number, the *s*+1'st element of the vector of *m* is referenced. If this is being read and it does not exist, **NONE** is returned and there is no compile error. If the element is being written but does not exist, or the map is read-only, a compile error results; otherwise the element value is changed.
2. If the value of *s* is a negative non-rational integer, *s* is replaced by *# m + s*, and things are as in the last paragraph (note *# m + s < # m*). The element does not exist if *# m + s < 0*.
3. If the value of *s* is a string, the dictionary entry of *m* with label *s* is referenced.

---

<sup>14</sup>The length of a **map** cannot be above  $2^{48}$  while **numbers** can precisely store integers up to  $2^{53}$ .

If this is being read and it does not exist, `NONE` is returned. If it is being written and it does not exist, and if the map is read-write, the entry is created and made read-write. Else if the entry exists and is read-write, and the map is read-write, the entry value is changed. Else if the entry exists and is read-only, or the map is read-only, a compile error results.

4. If the value of `s` is `NONE`, reading pops a value from the end of the vector of `m` and returns the value popped (as in '`v = m[]`'), or just returns `NONE` if the vector is empty, and writing pushes the value written to the end of the vector of `m` (as in '`m[] = v`').
5. Otherwise if `s` is neither a non-rational integer or a string, a compile-error results.

```
constant function const r = std copy ( const m )
constant function const r = std copy top ( const m )
```

Returns a new map whose contents is a copy of the contents of map `m`. The new map is read-only if and only if `m` is, and the labels in the new map are read-only if and only if the corresponding labels in `m` are.

If any vector or dictionary element values are maps, they are copied recursively by `copy`, but not by `copy top`, which only copies the element values of `m` and does not copy recursively.

Changing the values of elements of the new map will not change the contents of `m`. For `copy` modifying the element values that are maps will not change `m`, but for `copy top`, modifying these element values will change the elements of `m`.

```
constant function const r = std duplicate ( const m )
constant function const r = std duplicate top ( const m )
```

Ditto, but if any read-only map is to be copied, the pointer to the map is copied and no new map is made.

```
constant function const r = std slice ( const m, const i, const n )
```

`i` and `n` must be non-rational integers.

If `i < 0` then `i` is replaced by `# m + i` before the following is done.

Then if `n > 0`, returns a new map consisting of just a vector of the elements `m[i]`, `m[i+1]`, ..., `m[i+n-1]`. If any of these elements do not exist, they are omitted (e.g., if `i >= # m` or `i + n <= 0` the empty map is returned).

If `n == 0` the empty map is returned.

If `n < 0` the elements returned are `m[i+n]`, `m[i+n+1]`, ..., `m[i-1]`.

```
constant function const r = std splice ( const m, const i, const n, const v )
i and n must be non-rational integers.
```

If `i < 0` then `i` is replaced by `# m + i` before the following is done.



Then if  $n > 0$ , edits  $m$  by replacing the vector element sequence  $m[i], m[i+1], \dots, m[i+n-1]$  by the vector elements of  $v$ . Dictionary elements of  $v$  are ignored; dictionary elements of  $m$  are unchanged.

If  $n == 0$  the elements of  $v$  are pushed into  $m$  just after  $m[i]$ .

If  $n < 0$  the elements replaced are  $m[i+n], m[i+n+1], \dots, m[i-1]$ .

The elements being replaced need not (all) exist.  $m$  is thought of as an infinite sequence of existing and non-existing elements indexed by integers, including negative integers. The members of  $m$  to be removed are made non-existent, then the elements of  $v$  are pushed into the sequence, and then non-existent elements are deleted.

So if  $i \geq \# m$  and  $n \geq 0$  then the elements of  $v$  are appended to  $m$ , and if  $i = -1$  and  $n \leq 0$ , the elements of  $v$  are prepended to  $m$ .

The edited map  $m$  is returned.

**constant function** `const r = std truncate ( const m, const i )`

An optimized version of `splice` that removes the elements  $m[i], m[i+1], \dots$ , from the end of the vector of  $v$ . The edited map  $m$  is returned. It is not an error if no elements are removed.

If  $i < 0$  it is replaced by  $\# m + i$ . If  $\# m + i < 0$ , all elements of the vector are removed.

**constant function** `const r = std push ( const m, const v )`

Appends  $v$  to the vector of  $m$  and returns  $m$ .

**constant function** `const r = std push ( const m, const v, const i )`

Executes `push(m,v)`  $i$  times.  $i$  must be a non-rational, non-negative integer.

**constant function** `const r = std append ( const m1, const m2 )`

Appends the vector elements of the map  $m2$  to the vector of  $m1$  and returns  $m1$ .

**constant function** `const r = std pop ( const m )`

Deletes the last vector element of  $m$  and returns it. Returns `NONE` if  $m$  is empty.

**constant function** `const r = std pop ( const m, const i )`

Deletes the last  $i$  vector elements of  $m$  and returns a map containing them in the same order. If there are fewer than  $i$  vector elements in  $m$ , the returned vector will have only  $\# m$  elements.  $i$  must be a non-rational, non-negative integer.

## 17.5 Type, Field, Subfield, and Pointer Type Maps

Types, fields, subfields, and pointer types are described at compile-time by `const` map values which user code can access. These are read-write as a whole, but some of their labels are

protected. The following sections describe protected labels provided by the compiler. Unless otherwise specified, these have values that do not change during compilation.

Compiled code may add its own labels to these maps. To prevent conflict, the labels provided by the compiler begin with '.', so that to use them to access a map dictionary entry you must use double dots: '..'. E.g., `int..size`.

In the following a **name string** is a string consisting of a sequence of one or more *words* and *natural-numbers*, separated by single spaces, and beginning with a *word*. *Natural-numbers* are represented by strings of 1 to 9 decimal digits with no high-order zeros (zero is represented by '0'). Name strings are used to represent type, field, and subfield names.

*Module abbreviations* in a name string are replaced by **compiler module abbreviations** which are words of the form `M$n`, where *n* is a natural number. `M$0` is always the abbreviation for the `std` module. These compiler module abbreviations are specific to the entire compilation and are not dependent on which module or body a definition appears in.

`com module dictionary`

A dictionary mapping compiler module abbreviation numbers to strings that are *module-names*. Specifically: `com module dictionary[n] == "N"` means `M$n` maps to *N*. For example,

```
com module dictionary[0] == "standard"
```

### 17.5.1 Type Maps

At compile-time a *type-name* can be used as a `const` type *variable-name* that names a read-only variable with a map value called a **type map**.

The compiler defined attributes of a type map are:

`.type => "type"`

`.name`

The name of the type as a name string.

`.size`

`.alignment`

The `.size` is the number of bits taken by a value of the given type at run-time. The `.alignment` is the alignment in bits of an aligned value of the given type at run-time. E.g., `int64..size == 64`, `int64..alignment == 64`.

These may increase during compilation of type expansions, and will be `UNDEF` for `*DEFERRED*` types not yet defined by the compilation.

`.expandable`

`.external`

The `.expandable` attribute is `TRUE` if the current list of type subdeclarations ends with

\*\*\* or **\*EXTERNAL\***, and **FALSE** otherwise. The **.external** attribute is **TRUE** if the current list of type subdeclarations ends with **\*EXTERNAL\***, and **FALSE** otherwise.

These may change during compilation of type expansions, and are **UNDEF** for **\*DEFERRED\*** types not yet defined by the compilation.

#### **.fields**

A map listing field maps<sup>132</sup> for the fields of the type. The dictionary entries list named fields by name. The vector entries list unnamed fields (which have subfields).

Fields may be added during compilation of type expansions. Will be empty if a type has no fields, or if the type is currently **\*DEFERRED\*** and not yet defined by the compilation.

#### **.min**

#### **.max**

The minimum and maximum values of a number type  $N$ . Not defined for non-number types. These are **const** values which must be converted to the run-time type  $N$  before being used (e.g., by the expression ' $N(N..max)$ '). These values are exact; for some  $N$ , these values can be *number-constants*, but for others they must be *rational-constants* (e.g., **uns64..max** is **X#"7FFFFFFFFFFFFFFF"**).

#### **.indefinite**

The value of the indefinite integer for a signed integer type  $I$ . Not defined for non-integer and unsigned integer types.

The **indefinite integer** is returned by some operations, e.g. **round**, when they return a correct integer value.<sup>15</sup>

The value is typically  $-2^{S-1}$  where  $S$  is the size of  $I$  in bits.

This is a **const** value which must be converted to the run-time type  $I$  before being used (e.g., by the expression ' $I(I..indefinite)$ '). This value is exact; for some  $I$ , the values can be a *number-constant*, but for others it must be a *rational-constant* (e.g., **int64..indefinite** is **-B#"1e63"**).

Example:

```
int64 = { .type => "type",
          .name => "int",
          .size => 64,
          .alignment => 64,
          .expandable => FALSE,
          .external => FALSE,
          .fields => {},
          .min => -X#"8000000000000000",
          .max => X#"7FFFFFFFFFFFFFFF",
```

<sup>15</sup>See documentation of the intel IA-64 FIST instruction.

```
.indefinite => -X#"8000000000000000" }
```

### 17.5.2 Field Maps

Each field of a type has a **const** map value called a **field map** which is in the **.fields** dictionary of a type map. The compiler defined attributes of a field map are:

**.type** => "field"

**.name**

The name of the field (*target-label* or *pointer-label*) as a name string. May be **NONE** for a field with subfields.

**.parent**

Type map of the type of containing this field.

**.offset**

Offset in bits of the field within a value of its parent type.

**.pointer-type**

Pointer type map for the pointer type of the field, or **NONE**.

**.pointer-qualifiers**

List of strings, each a *word* naming a qualifier of the field pointer type, or **NONE** if there is no pointer type. May be empty list.

**.field type**

Type map for the type of the field if the **.pointer-type** is **NONE**, or the **.pointer-type** target if the **.pointer-type** is not **NONE**, or **NONE** for a *\*LABEL\**.

**.qualifiers**

List of strings, each a *word* naming a qualifier of the field. May be empty list. If **.pointer-type** is not **NONE**, these qualifiers apply to the pointer value of the field and not to its target.

**.dimensions**

List of strictly positive integers, the dimensions of the field, or **NONE** if no dimensions.

**.subfields**

Dictionary of subfield maps for the subfields of the type. The labels of the dictionary entries are the names of the subfields. Empty if there are no subfields.

Example:

```
type my type:
  int32 X[4,3]
```

```

    av *READ-WRITE* flt @Y

// The value of the global const variable `my type' is:
{ .type => "type",
  .name => "my type",
  .size => 128,
  .alignment => 64,
  .expandable => FALSE,
  .external => FALSE,
  .fields => {
    { .type => "field",
      .name => "X",
      .parent => my type, // Note absence of quotes
      .offset => 0,
      .pointer-type => NONE,
      .pointer-qualifiers => {},
      .field type => int32, // Note absence of quotes
      .qualifiers => {},
      .dimensions => {4, 3},
      .subfields => {}
    },
    { .type => "field",
      .name => "@Y",
      .parent => my type, // Note absence of quotes
      .offset => 384,      // 12 * 32
      .pointer-type => av, // Note absence of quotes
      .pointer-qualifiers => {},
      .field type => flt, // Note absence of quotes
      .qualifiers => { "*READ-WRITE*" },
      .dimensions => {},
      .subfields => {}
    }
  }
}

```

### 17.5.3 Subfield Maps

Each subfield of a field has a `const` map value called a **subfield map** which is in the `.subfields` dictionary of a field map. The compiler defined attributes of a subfield map are:

**.type** => "subfield"

**.name**

The name of the subfield (*target-label*) as a name string.

**.parent**

Field map of the field of containing this subfield.

**.bits**

A list of two integers: *{highbit, lowbit}*.

**.subfield type**

Type map for the type of the subfield. This is always a **std** number type or **std bool**.

**.dimensions**

List of strictly positive integers, the dimensions of the subfield, or **NONE** if no dimensions.

#### 17.5.4 Pointer Type Maps

At compile-time a *pointer-type-name* can be used as a **const** type *variable-name* that names a read-only variable with a map value called a **pointer type map**.

The compiler defined attributes of a pointer type map are:

**.type** => "pointer type"

**.name**

The name of the pointer type as a name string.

**.data type**

Type map for the data type of the pointer type.

## 17.6 Compile Time Compilation Functions

These functions are principally of use in **macro** or **inclusion** functions, but can be used in any inline function.

**load reference function const r = com \*STATEMENT\***

This *function-variable-name* returns the parsed *statement* containing the inline function currently executing at compile-time.

**load reference function const r = com \*SUBBLOCK\***

This *function-variable-name* returns the subblock at the end of the parsed *statement* containing the inline function currently executing at compile-time. This is annotated with **".initiator" = ":"** and **".terminator" = \*INDENTED-PARAGRAPH\***.

If instead of ending with a subblock, the statement ends with the ":" operator followed by a *restricted-statement*  $S$ , this function returns:

```
{  $S$ , ".initiator" = ":", ".terminator" = *INDENTED-PARAGRAPH* }
```

In other words, this function packages  $S$  in the form of a 1-*statement* subblock.

load reference function `const r = com new variable name`

This function returns a *variable-name* of the form "V\$..." that is unique and distinct from any other variable name in the current compilation. In particular, the function does not return the same *variable-name* twice.

constant function `const r = com name of ( const variable name )`

Here '`variable name`' is a *variable name* declared in a non-macro *prototype-argument-declaration*. The type of the variable in this *prototype-argument-declaration* cannot be `const`.

This function returns a *variable-name* of the form V\$... created by calling `com new variable name` that can be used inside run-time code produced by the inline function to reference the value of the actual argument associated with the *prototype-argument-declaration* of the '`variable name`'. More explicitly, if the *prototype-argument-declaration* has the form ' $TTT V$ ' where  $TTT$  consists of runtime types and qualifiers and  $V$  is a *variable-name*, and if

```
 $W = \text{name of ( "V" )},$ 
```

is executed in the inline function, and if "V\$..." is returned as the value of  $W$ , then code of the form:

```
 $TTT V\$... = \text{actual-argument}$ 
```

is executed at runtime just before the *statement* containing the executing inline function.

For example:

```
function macro r = inc ( macro v, int w ):
    const W = name of ( "w" )
    return { v, "+=", { W } }
ap *READ-WRITE* int @x:
    x = 5
inc ( x, 10 ) // Same as:
                //      int V$1 = 10
                //      {"x"}, "+=", {V$1}.
// Now x == 15.
```

## 17.7 Compile Time Exception and Trace Support

An L-Language **ID** is a `const` integer storable at run time in an `uns` variable that identifies something. *Throw-exception-statements* may have **exception IDs** and *trace-statements* may

have **trace IDs**.

The **std** module defines the following **const** maps and functions:

```
const std exception ID map = { "NONE" }
```

```
const std trace ID map = { }
```

```
constant function const r = std new exception ID ( const name )
```

A call to this function pushes **name** to the end of **std exception ID map** and returns the new length of the map minus 1.

```
constant function const r = std new trace ID ( const name )
```

A call to this function pushes **name** to the end of **std trace ID map** and returns the new length of the map minus 1.

There must be no more than 64 trace IDs.

## 17.8 Compile Time Machine Parameters

```
const com atomc types = { "int", "uns", ... }
```

These are the types for which atomic operations<sup>p146</sup> are defined.

```
const com hardware overflow = ... [TRUE or FALSE]
```

TRUE iff hardware computes the overflow **bool** for integer addition and subtraction.<sup>p143</sup>  
FALSE if this is computed when needed by software (much more slowly).

## 18 Builtin Run-Time Functions and Constants

Run-time functions execute at run-time, and but may have parts that execute at compile-time, and may even return **const** results.

The L-Language built-in run-time functions are very basic and provide only functionality that cannot be efficiently provided by library functions.

### 18.1 Builtin Run-Time Constants

```
bool std true = 1
bool std false = 0
```

### 18.2 Builtin Implicit Conversions

See 10.1.5<sup>p66</sup> for non-builtin conversions.



### 18.2.1 Numeric Implicit Conversions

Any value of number or `bool` type `N1` can be implicitly converted to a value of number type `N2` if every value of type `N1` can be precisely represented by a value of type `N2`, or if `N1` is an integer type and `N2` is a floating point type.

Note that a larger floating point type cannot be implicitly converted to a smaller floating point type, as such would create a cyclic loop in the implicit conversion graph<sup>p66</sup>. Also note that implicit conversions are the shortest path in this graph, e.g., the exact path `int32`  $\rightarrow$  `flt64` will be used and the inexact path `int32`  $\rightarrow$  `flt32`  $\rightarrow$  `flt64` will not be.

More specifically, the implicit conversions are defined by:

```
function N2 r = std *IMPLICIT* *CONVERSION* ( N1 v )
```

in the following cases:

N2	N1		
	flt64	flt32	flt16
flt64	no	yes	yes
flt32	no	no	yes
flt16	no	no	no
int...	no	no	no
uns...	no	no	no

N2	N1			
	int64	int32	int16	int8
flt64	yes	yes	yes	yes
flt32	yes	yes	yes	yes
flt16	yes	yes	yes	yes
int64	no	yes	yes	yes
int32	no	no	yes	yes
int16	no	no	no	yes
int8	no	no	no	no
uns...	no	no	no	no

N2	N1				
	uns64	uns32	uns16	uns8	bool
flt64	yes	yes	yes	yes	yes
flt32	yes	yes	yes	yes	yes
flt16	yes	yes	yes	yes	yes
int64	no	yes	yes	yes	yes
int32	no	no	yes	yes	yes
int16	no	no	no	yes	yes
int8	no	no	no	no	yes
uns64	no	yes	yes	yes	yes
uns32	no	no	yes	yes	yes
uns16	no	no	no	yes	yes
uns8	no	no	no	no	yes

### 18.2.2 Pointer Implicit Conversions

An aligned pointer may be implicitly converted to a direct pointer:

```
function dp Q$ T$ @r = std *IMPLICIT* *CONVERSION ( ap Q$ T$ @p )
```

The base address of @p is added to the offset of @p to produce the value of @r.

### 18.2.3 Qualifier Implicit Conversions

Implicit conversions of qualifiers may occur whenever a pointer value is copied, unlike other implicit conversions. The following are qualifier conversions:

1. `co` may be replaced by `ro`
2. `*READ-WRITE*` may be replaced by `ro`
3. `*READ-WRITE*` may be replaced by `*WRITE-ONLY*`
4. `*GLOBAL*` may be replaced by `*HEAP*`
5. `*GLOBAL*` may be replaced by undeclared (an anywhere pointer)
6. `*HEAP*` may be replaced by undeclared (an anywhere pointer) from a *reference-expression* that is nothing but a *pointer-variable* (i.e., is a stack variable which is `co`).

## 18.3 Builtin Explicit Conversions

See 10.1.5<sup>p66</sup> for non-builtin conversions.

### 18.3.1 Numeric Explicit Conversions

```
function F r = std F (N v)
```

Where *F* is any builtin floating point type and *N* is any builtin number or `bool` type.

Converts *v* to the type *F*. The result may be `+Inf` or `-Inf`, or precision may be lost.

```
function I r = std floor (F v1, F v2 ?= 1.0 )
function I r = std ceiling (F v1, F v2 ?= 1.0 )
function I r = std truncate (F v1, F v2 ?= 1.0 )
function I r = std round (F v1, F v2 ?= 1.0 )
```

Where *I* is any builtin signed integer type and *F* is one of `flt`, `flt64`, or `flt32`.

These divide *v1* by *v2* and return *r* as the result rounded to an integer. Here `floor` rounds toward negative infinity, `ceiling` rounds towards positive infinity, `truncate` rounds toward zero, and `round` rounds to the nearest integer, or to the even integer if there are two nearest integers.

The floating point flags set are those set by division (see below), plus the inexact flag may be set if the division quotient is not a integer, plus the invalid flag is set if the result is outside the range storable in *I*. In the last case, and the result is an indefinite integer.<sup>p131</sup>

```
function I1 r = std *UNCHECKED* ( I2 v )
```

Where *I1* and *I2* are any builtin integer types such that at least one of the following is true:

1. *I1* is shorter than *I2*
2. *I1* and *I2* are of equal length and one is `int...` while the other is `uns...`
3. *I2* is `int...` while *I1* is `uns....`

These in effect convert *v* to a bit-string of unbounded length (e.g., by two's complement sign extension) and then truncate it to the length of *I1*.

```
function N r, std FP flags f = std D# ( ap ro C s )
function N r, std FP flags f = std B# ( ap ro C s )
function N r, std FP flags f = std X# ( ap ro C s )
```

Where *N* is any number type and *C* is `uns8`, `uns16`, or `uns32` (for UTF8, UTF16, or UTF32 strings).

These convert the string *s* to the number *r*, where the string is formatted as in Section 6.2.1<sup>p35</sup>.

Error flags are set in *f* (see p142). If there are no errors, no flags are set. If *s* does not have the proper format, or its value is negative and *N* is an unsigned integer, the `Invalid` flag is set, `NaN` is returned for floating point types, and the indefinite integer<sup>p131</sup>

is returned for integer types. If the value is too large to store, the `Overflow` flag is set,  $\pm\text{Inf}$  is returned for floating point types, and the most positive or negative storable value is returned for integer types. If the value must be rounded when it is stored, the `Inexact` flag is set.

### 18.3.2 Pointer Explicit Conversions

```
function ap Q$ T$ @r = std *UNCHECKED* ( dp Q$ T$ @p )
```

The base pointer of `r` is set to point at a location that is always 0 and the offset of `r` is set to point to the address stored as the value of `p`.

```
function av Q$ T$ r = std *UNCHECKED*
( ap Q$ T$ p, int offset, int lower, int upper )
```

The base pointer of `@r` is set to the base pointer of `@p`, the offset of `@r` is set to the sum of the offset of `@p` and the `offset` argument, and the bounds of `@r` are set from the `lower` and `upper` arguments.

## 18.4 Builtin Floating Point Operations

A floating point NaN is a quiet NaN with zero significand bits, except for the highest order bit which is one (to indicate that the NaN is quiet).

```
function F r = std "+" ( F v1 )
function F r = std "-" ( F v1 )
function F r = std (F v1) "+" ( F v2 )
function F r = std (F v1) "-" ( F v2 )
function F r = std (F v1) "*" ( F v2 )
function F r = std (F v1) "/" ( F v2 )
```

Where `F` is one of `flt`, `flt64`, or `flt32`.

Standard arithmetic operators on numbers `v1` and `v2`, done using IEEE floating point arithmetic.

Floating point operations may set the following floating point flags:

Invalid	Set in the following cases. Returns NaN.
---------	--

	$+\text{Inf} + -\text{Inf}$	$-\text{Inf} + +\text{Inf}$
	$+\text{Inf} - +\text{Inf}$	$-\text{Inf} - -\text{Inf}$
	$+\text{Inf} * 0$	$0 * +\text{Inf}$
	$-\text{Inf} * 0$	$0 * -\text{Inf}$
	$+\text{Inf} / +\text{Inf}$	$+\text{Inf} / -\text{Inf}$
	$-\text{Inf} / +\text{Inf}$	$-\text{Inf} / -\text{Inf}$
	$+0 / +0$	$+0 / -0$
	$-0 / +0$	$-0 / -0$
Divide by Zero	Set when a non-zero value is divided by a zero value. Returns $+\text{Inf}$ or $-\text{Inf}$ with sign determined by the signs of the zero and non-zero values in the usual way.	
Overflow	Set when the computed value is a number outside the range that can be stored because its absolute value is too large. Returns $+\text{Inf}$ or $-\text{Inf}$ .	
Underflow	Set when the computed value is a number outside the range that can be stored because its absolute value is too small. Returns $+0$ or $-0$ .	
Inexact	Set when the computed value cannot be precisely stored but is inside the range of absolute values that can be stored. Returns the nearest value that can be stored, with ties going to the value whose least significant bit is zero.	

```

function F r = std floor (F v1, F v2 ?= 1.0 )
function F r = std ceiling (F v1, F v2 ?= 1.0 )
function F r = std truncate (F v1, F v2 ?= 1.0 )
function F r = std round (F v1, F v2 ?= 1.0 )

```

Where  $F$  is one of `flt`, `flt64`, or `flt32`.

These divide  $v1$  by  $v2$  and return  $r$  as the result rounded to an integer. Here `floor` rounds toward negative infinity, `ceiling` rounds towards positive infinity, `truncate` rounds toward zero, and `round` rounds to the nearest integer, or to the even integer if there are two nearest integers.

The floating point flags set are those set by division (see above), plus the inexact flag may be set if the division quotient is not a integer. If the division quotient is an infinity, no flags are set and  $r$  is set to the quotient.

```

function bool r = std (F v1) "==" ( F v2 )
function bool r = std (F v1) "!=" ( F v2 )
function bool r = std (F v1) "<" ( F v2 )
function bool r = std (F v1) "<=" ( F v2 )
function bool r = std (F v1) ">" ( F v2 )
function bool r = std (F v1) ">=" ( F v2 )

```

Where F is one of `flt`, `flt64`, or `flt32`.

Standard comparison operators on floating point numbers `v1` and `v2`. Infinities are treated as actual numbers with absolute value larger than any real number: e.g., if `x` is not a NaN, '`x <= +Inf`' is always true and '`x == +Inf`' is true iff `x` is `+Inf`. If an argument is a NaN, the result is undefined and an invalid flag is set.

```
function bool r = std is nan ( F v1 )
function bool r = std is infinity ( F v1 )
function bool r = std is finite ( F v1 )
```

Where F is one of `flt`, `flt64`, `flt32`, or `flt16`.

<code>is nan</code>	Returns true if <code>v1</code> is any NaN number (not just NaN), and false otherwise.
<code>is infinity</code>	Returns true if <code>v1</code> is <code>+Inf</code> or <code>-Inf</code> , and false otherwise.
<code>is finite</code>	Returns true if <code>is nan</code> and <code>is infinity</code> both return false, and returns false otherwise.

type std FP flags:

```
uns flags
[...] bool invalid (operand for a given operation)
[...] bool divide by zero
[...] bool overflow
[...] bool underflow
[...] bool inexact
```

```
function std FP flags r = std FP flags register
function std FP flags register = std FP flags v
```

The hardware floating point flags can be read into a datum of type `FP flags` and an `FP flags` datum can be written to the hardware floating point flags by using the `FP flags register` functions. The exact bits in the data that contain the flags are implementation dependent, and are here represented by '...'.

If a memory space has more than one process (a.k.a., thread - i.e., local stack<sup>p117</sup>), each process has its own `std FP flags register`.

## 18.5 Builtin Integer Operations

```
function I r, bool cout, bool ovfl = std "+" ( I v1, bool cin = 0 )
function I r, bool cout, bool ovfl = std "-" ( I v1, bool cin = 1 )
function I r, bool cout, bool ovfl = std (I v1) "+" ( I v2, bool cin = 0 )
function I r, bool cout, bool ovfl = std (I v1) "-" ( I v2, bool cin = 1 )
```

Where I is one of: `int int128 int64 int32 int16 int8`  
`uns int128 uns64 uns32 uns16 uns8`

Standard arithmetic operators on `v1` and `v2` treated as binary unsigned integers. When values are interpreted as two's complement signed integers, these operations also give valid results.

`cin` is added to the result; `cout` is the carry from the result. Operands are made negative by bitwise complementing them and adding 1 by setting `cin = 1`.

`ovfl` is set to 1 if and only if the operation overflows when values are interpreted as signed two's complement integers. If `S0`, `S1`, and `Sr` are the signs of `v1`, `v2`, and `r`, for two operand "+" this would equal `S0 = S1 ≠ Sr`. `ovfl` is computed by some hardware, but is expensive to compute if not supported by hardware. See `com hardware overflow`.<sup>p136</sup>

```
function I r = std (I v1) "*" ( I v2 )
function U r, U cout = std (U v1) "*" ( U v2, U cin1 = 0, U cin2 = 0 )
```

Where I is one of: `int int128 int64 int32 int16`

and U is one of: `uns uns64 uns32`

The version without carries is the standard arithmetic multiply which truncates results that are outside the range of I.

The version with carries is integer multiply of N-bit unsigned integers to produce a 2N-bit product to which both `cin1` and `cin2` are added. Of the result `r` is the low order N bits and `cout` is the high order N bits.

```
function I r = std (I v1) "/" ( I v2 )
function U r, U cout = std (U v1, U cin = 0) "/" ( U v2 )
```

Where I is one of: `int int128 int64 int32 int16`

and U is one of: `uns uns64 uns32`

The version without carries is the standard arithmetic divide. An exception trap occurs if `v2 = 0`.

The version with carries is integer divide of a 2N-bit unsigned dividend made by concatenating `cin` (high order) and `v1` (low order) by an N-bit unsigned divisor `v2`. The result is an N-bit quotient `r` and an N-bit remainder `cout`. An exception trap occurs if `v2 ≤ cin` (this includes that case where `v2 = 0`).

```
function I r = std "~" ( I v1 )
function I r = std (I v1) "&" ( I v2 )
function I r = std (I v1) "|" ( I v2 )
function I r = std (I v1) "^" ( I v2 )
```

Where I is one of: `int int128 int64 int32 int16 int8`  
`uns uns128 uns64 uns32 uns16 uns8 bool`

Standard bitwise operators, complement (`~`), and (`&`), or (`|`), and exclusive or (`^`), on integers `v1` and `v2` that are treated as two's complement if signed.

```
function I r = std (I v1) "<<" ( int v2 )
function I r = std (I v1) ">>" ( int v2 )
```

Where I is one of:   int int128 int64 int32 int16 int8  
                          uns uns128 uns64 uns32 uns16 uns8

Standard bitwise shifts of integer *v1* by the amount *v2*. If signed, *v1* is treated as two's complement. The amount of shift, *v2*, must be in the range  $[0, I..size)$ ; values out of range produce undefined results. Bits shifted out at the left or right side are discarded.

```
function bool r = std (I v1) "==" ( I v2 )
function bool r = std (I v1) "!=" ( I v2 )
function bool r = std (I v1) "<" ( I v2 )
function bool r = std (I v1) "<=" ( I v2 )
function bool r = std (I v1) ">" ( I v2 )
function bool r = std (I v1) ">=" ( I v2 )
```

Where I is one of:   int int128 int64 int32 int16 int8  
                          uns uns128 uns64 uns32 uns16 uns8 bool

Standard comparison operators on integers *v1* and *v2*.

## 18.6 Builtin Pointer Operations

```
function ap Q$1 T$1 r =
    std ( uns length, uns alignment ) null
function av Q$1 T$1 r =
    std ( uns length, uns alignment ) null [ uns count ]
```

These functions allocate a value of type *T\$1* (or *count* values of type *T\$1*) to null memory (memory in inaccessible virtual pages that memory fault if accessed) and return a pointer to the value(s).

These functions can only be called by an *allocation-call*<sup>p46</sup>. See p51.

```
function ap QU$1 T$1 r =
    std ( uns length, uns alignment ) local
function av QU$1 T$1 r =
    std ( uns length, uns alignment ) local [ uns count ]
```

These functions allocate a value of type *T\$1* (or *count* values of type *T\$1*) to local memory (the current out-of-line function execution's frame in the local stack: see p117) and return a pointer to the value(s).

These functions can only be called by an *allocation-call*<sup>p46</sup>. See p51.

```
function ap QU$1 *GLOBAL* T$1 r =
    std ( uns length, uns alignment ) global
function av QU$1 *GLOBAL* T$1 r =
```



```
std ( uns length, uns alignment ) global [ uns count ]
```

These functions allocate a value of type T\$1 (or count values of type T\$1) to global memory (the global stack: see p117) and return a pointer to the value(s).

These functions can only be called by an `allocation-call`<sup>p46</sup>. See p51.

## 18.7 Builtin Exception and Trace Support Operations

The following functions can be used in an *exception-subblock* to determine which variables of its containing *block-assignment-statement* or *loop-assignment-statement* have been set.

```
function bool r = std is set ( N value )
function bool r = std is set ( P$1 Q$1 T$1 pointer )
```

where N is any number type.

Returns `true` if the `value` is not zero or the `pointer` is not null, and `false` otherwise. These functions should only be used inside *exception-subblocks*<sup>p50</sup>.

Information about the last exception is recorded in the following:

```
type std exception data:
    uns ID          // exception ID from throw statement
    dp uns8 @pc     // program counter of throw statement
function std exception data r = std current exception data
function std current exception data = std exception data v
```

The current exception data contain the exception ID and program counter of the last exception. These are set by a *throw-statement* that gives an exception ID. A *throw-statement* without an exception ID does not change the current exception data.

If a memory space has more than one process (a.k.a., thread - i.e., local stack<sup>p117</sup>), each process has its own `std current exception data`.

A program fault executes the equivalent of a *throw-statement* with one of the following exception IDs:

```
std divide exception = std new exception ID ( "DIVIDE" )
    // Integer divide by zero.
std inaccessible exception = std new exception ID ( "INACCESSIBLE" )
    // Read or write of inaccessible memory location.
std write exception = std new exception ID ( "WRITE" )
    // Write of accessible but write-protected memory location.
```

See Compile Time Exception and Trace Support 17.7<sup>p135</sup> for the `std new exception ID` function.

A mask determining which *trace-statements* are active is recorded in the following:

```
function uns64 r = std current trace mask
```

```
function std current trace mask = uns64 v
```

Read and write the current trace mask. A *trace-statement* with trace ID X will be executed if the current trace mask has bit  $1 \ll X$  on, and will be a no-operation otherwise.

If a memory space has more than one process (a.k.a., thread - i.e., local stack<sup>p117</sup>), each process has its own `std current trace mask`.

The following is an example trace mask:

```
uns64 trace file errors = 1 << std new trace ID ( "FILE ERRORS" )
// Note: 1 << X is an exact integer in the IEEE floating point
//       format used for const numbers even when X is
//       a large integer.
```

See Compile Time Exception and Trace Support 17.7<sup>p135</sup> for the `std new trace ID` function.

## 19 Atomic Operations

**Atomic operations** read and write memory locations that are shared between multiple CPUs or processes using the same RAM memory.

When a process executes a program, the process may move memory reads and writes around so they are no longer done when they would be done were the program statements executed in strict sequential order. The execution does this if the effect of the program is not changed, under the assumption that the program is the only user of the RAM memory. But if there are multiple CPUs, or a multi-tasking system asynchronously switching one CPU between processes, this assumption is not correct.

There is also the possibility that if a memory location is being read by CPU 1 and at the same time written by CPU 2, what CPU 1 reads will consist partly of the location value before CPU 2's write and partly of the location value after CPU 2's write.

An operation is **atomic** if:

1. All read and or write operations and all atomic operations for the current process that would be before (or after) this atomic operation in strict sequential program execution are before (or after) this atomic operation in actual optimized program execution.
2. This atomic operation cannot be interrupted by a read or write executed by a different CPU or process of part of the memory being read or written by this atomic operation.

Atomic operations can only be performed on locations of **atomic type**. Atomic types are listed in the `com atomic types`<sup>p136</sup> compile-time variable. The word-length integer types,

`int` and `uns`, are always atomic types.

`function A r = std atomic read ( ap QR$1 A p )`

For `A` an atomic type, read and return the location pointed at by `p`. In addition:

1. All read or atomic operations for the current process that would be before (or after) this operation in strict sequential program execution are before (or after) this operation in actual optimized program execution.
2. The read cannot be interrupted by a write executed by a different CPU or process of part of the memory being read.

`function std atomic write ( ap QW$1 A p, A v )`

For `A` an atomic type, write the value `v` to the location pointed at by `p`. In addition:

1. All write or atomic operations for the current process that would be before (or after) this operation in strict sequential program execution are before (or after) this operation in actual optimized program execution.
2. The write cannot be interrupted by a read executed by a different CPU or process of part of the memory being read.

`function std bool r = atomic compare and set ( ap QRW$1 A p, A vr, A vw )`

For `A` an atomic type, read the location pointed at by `p` and compare it to `vr`. If equal, write `vw` to the location, and return `true`. If not equal, just return `false`. In addition:

1. All read and write and atomic operations for the current process that would be before (or after) this operation in strict sequential program execution are before (or after) this operation in actual optimized program execution.
2. The operation cannot be interrupted by a read or write executed by a different CPU or process of any of the memory this operation reads or writes.

Example 1:

A device has registers in global memory which are shared between the device and a process. The registers are either owned by the process and the device is inactive, or the registers are owned by the device which is executing an operation. There is a register with a GO bit which is turned on by the process to activate the device, and another register with a READY bit which is set by the device when its current operation is done.

The GO bit is set by an atomic write, which guarantees that all writes to registers in the code before the GO bit is set are actually done before the GO bit is set.

The READY bit is read by an atomic read, which guarantees that all reads from registers in the code after the READY bit has been read as being on are actually done after the READY bit has been read as being on.

**Example 2:**

A device has registers as in Example 1. The device also has a large memory accessed via two registers: A and D. A holds the address of a location in device memory, and D holds the contents of that location: reading D reads the location contents, and writing D writes the location contents.

Register A is set by an atomic write and then register D is read by an atomic read. Because atomic operations execute in the same order as they appear in the code, the read will be done after the write.

**Example 3:**

A data structure which is shared among processes perhaps executing on different CPUs is guarded by a lock consisting of two integer memory locations: B (before) and A (after). When the structure is not being written,  $B == A$ . A writer first increments B, then updates the structure, and then increments A.

To get a write lock, the writer reads A atomically and then does a compare and set on B that checks that  $B == A$  and if so writes  $B+1$  to B and acquires the lock.

To read, the reader reads A atomically and saves the value V, then reads data from the structure, then reads B atomically and checks that the value read equals V. If the check passes, the data is uncorrupted by writing that is simultaneous with the reading. If the check fails, the data may be corrupted. The reader must be sure corrupted data does not destroy the integrity of the reader's execution, but can read B atomically and check the value against V at any time to see if the data read so far is uncorrupted.