

🔍 Search the docs ...

matplotlib

matplotlib.afm

matplotlib.animation

matplotlib.artist

matplotlib.axes

matplotlib.axes.SubplotBase

matplotlib.axes.subplot_class_factory

matplotlib.axes.Axes.plot

matplotlib.axes.Axes.errorbar

matplotlib.axes.Axes.scatter

matplotlib.axes.Axes.plot_date

matplotlib.axes.Axes.step

matplotlib.axes.Axes.loglog

matplotlib.axes.Axes.semilogx

matplotlib.axes.Axes.semilogy

matplotlib.axes.Axes.fill_between

matplotlib.axes.Axes.fill_betweenx

matplotlib.axes.Axes.bar

matplotlib.axes.Axes.barh

matplotlib.axes.Axes.bar_label

matplotlib.axes.Axes.stem

matplotlib.axes.Axes.eventplot

matplotlib.axes.Axes.pie

matplotlib.axes.Axes.stackplot

matplotlib.axes.Axes.broken_barh

matplotlib.axes.Axes.vlines

matplotlib.axes.Axes.hlines

matplotlib.axes.Axes.plot

Axes.plot(*args, *scalex=True*, *scaley=True*, *data=None*, **kwargs)

[\[source\]](#)

Plot *y* versus *x* as lines and/or markers.

Call signatures:

```
plot([x], y, [fmt], *, data=None, **kwargs)
plot([x], y, [fmt], [x2], y2, [fmt2], ..., **kwargs)
```

The coordinates of the points or line nodes are given by *x*, *y*.

The optional parameter *fmt* is a convenient way for defining basic formatting like color, marker and linestyle. It's a shortcut string notation described in the *Notes* section below.

```
>>> plot(x, y)           # plot x and y using default line style and color
>>> plot(x, y, 'bo')      # plot x and y using blue circle markers
>>> plot(y)              # plot y using x as index array 0..N-1
>>> plot(y, 'r+')         # ditto, but with red plusses
```

You can use [Line2D](#) properties as keyword arguments for more control on the appearance. Line properties and *fmt* can be mixed. The following two calls yield identical results:

```
>>> plot(x, y, 'go--', linewidth=2, markersize=12)
>>> plot(x, y, color='green', marker='o', linestyle='dashed',
...       linewidth=2, markersize=12)
```

When conflicting with *fmt*, keyword arguments take precedence.

Plotting labelled data

There's a convenient way for plotting objects with labelled data (i.e. data that can be accessed by index `obj['y']`). Instead of giving the data in *x* and *y*, you can provide the object in the *data* parameter and just give the labels for *x* and *y*:

```
>>> plot('xlabel', 'ylabel', data=obj)
```

All indexable objects are supported. This could e.g. be a [dict](#), a [pandas.DataFrame](#) or a structured numpy array.

Plotting multiple sets of data

There are various ways to plot multiple sets of data.

- The most straight forward way is just to call [plot](#) multiple times. Example:

```
>>> plot(x1, y1, 'bo')
>>> plot(x2, y2, 'go')
```

- If *x* and/or *y* are 2D arrays a separate data set will be drawn for every column. If both *x* and *y* are 2D, they must have the same shape. If only one of them is 2D with shape (N, m) the other must have length N and will be used for every data set m.

Example:

```
>>> x = [1, 2, 3]
>>> y = np.array([[1, 2], [3, 4], [5, 6]])
>>> plot(x, y)
```

is equivalent to:

```
>>> for col in range(y.shape[1]):
...     plot(x, y[:, col])
```

- The third way is to specify multiple sets of *[x]*, *y*, *[fmt]* groups:

```
>>> plot(x1, y1, 'g^', x2, y2, 'g-')
```

In this case, any additional keyword argument applies to all datasets. Also this syntax cannot be combined with the *data* parameter.

By default, each line is assigned a different style specified by a 'style cycle'. The *fmt* and line property parameters are only necessary if you want explicit deviations from these defaults. Alternatively, you can also change the style cycle using `rcParams["axes.prop_cycle"]` (default: `cycler('color', ['#1f77b4', '#ff7f0e', '#2ca02c', '#d62728', '#9467bd', '#8c564b', '#e377c2', '#7f7f7f', '#bcbd22', '#17becf'])`).

Parameters:**x, y** : *array-like or scalar*

The horizontal / vertical coordinates of the data points. x values are optional and default to `range(len(y))`.

Commonly, these parameters are 1D arrays.

They can also be scalars, or two-dimensional (in that case, the columns represent separate data sets).

These arguments cannot be passed as keywords.

fmt : *str, optional*

A format string, e.g. 'ro' for red circles. See the *Notes* section for a full description of the format strings.

Format strings are just an abbreviation for quickly setting basic line properties. All of these and more can also be controlled by keyword arguments.

This argument cannot be passed as keyword.

data : *indexable object, optional*

An object with labelled data. If given, provide the label names to plot in x and y.

Note

Technically there's a slight ambiguity in calls where the second label is a valid *fmt*. `plot('n', 'o', data=obj)` could be `plt(x, y)` or `plt(y, fmt)`. In such cases, the former interpretation is chosen, but a warning is issued. You may suppress the warning by adding an empty format string `plot('n', 'o', '', data=obj)`.

Returns:**list of** [Line2D](#)

A list of lines representing the plotted data.

Other Parameters: **scalex, scaley** : *bool, default: True*

These parameters determine if the view limits are adapted to the data limits. The values are passed on to [autoscale_view](#).

****kwargs** : *Line2D properties, optional*

kwargs are used to specify properties like a line label (for auto legends), linewidth, antialiasing, marker face color. Example:

```
>>> plot([1, 2, 3], [1, 2, 3], 'go-', label='line 1', linewidth=2)
>>> plot([1, 2, 3], [1, 4, 9], 'rs', label='line 2')
```

If you specify multiple lines with one plot call, the *kwargs* apply to all those lines. In case the label object is iterable, each element is used as labels for each set of data.

Here is a list of available [Line2D](#) properties:

Property	Description
agg_filter	a filter function, which takes a (m, n, 3) float array and a dpi value, and returns a (m, n, 3) array
alpha	scalar or None
animated	bool
antialiased or <i>aa</i>	bool
clip_box	Bbox
clip_on	bool
clip_path	Patch or (Path, Transform) or None
color or <i>c</i>	color
dash_capstyle	CapStyle or {'butt', 'projecting', 'round'}
dash_joinstyle	JoinStyle or {'miter', 'round', 'bevel'}
dashes	sequence of floats (on/off ink in points) or (None, None)
data	(2, N) array or two 1D arrays
drawstyle or <i>ds</i>	{'default', 'steps', 'steps-pre', 'steps-mid', 'steps-post'}, default: 'default'
figure	Figure
fillstyle	{'full', 'left', 'right', 'bottom', 'top', 'none'}
gid	str
in_layout	bool
label	object
linestyle or <i>ls</i>	{ '-', '--', '-.', ':', ' ', (offset, on-off-seq), ... }
linewidth or <i>lw</i>	float
marker	marker style string, Path or MarkerStyle
markeredgecolor or <i>mec</i>	color
markeredgewidth or <i>mew</i>	float
markerfacecolor or <i>mfc</i>	color
markerfacecoloralt or <i>mfcalt</i>	color
markersize or <i>ms</i>	float
markevery	None or int or (int, int) or slice or list[int] or float or (float, float) or list[bool]
path_effects	AbstractPathEffect
picker	float or callable[[Artist, Event], tuple[bool, dict]]
pickradius	float
rasterized	bool
sketch_params	(scale: float, length: float, randomness: float)
snap	bool or None
solid_capstyle	CapStyle or {'butt', 'projecting', 'round'}
solid_joinstyle	JoinStyle or {'miter', 'round', 'bevel'}
transform	unknown
url	str
visible	bool
xdata	1D array
ydata	1D array
zorder	float

See also[scatter](#)

XY scatter plot with markers of varying size and/or color (sometimes also called bubble chart).

Notes**Format Strings**

A format string consists of a part for color, marker and line:

```
fmt = '[marker][line][color]'
```

Each of them is optional. If not provided, the value from the style cycle is used. Exception: If `line` is given, but no `marker`, the data will be a line without markers.

Other combinations such as `[color][marker][line]` are also supported, but note that their parsing may be ambiguous.

Markers

character	description
'.'	point marker
'.'	pixel marker
'o'	circle marker
'v'	triangle_down marker
'^'	triangle_up marker
'<'	triangle_left marker
'>'	triangle_right marker
'1'	tri_down marker
'2'	tri_up marker
'3'	tri_left marker
'4'	tri_right marker
'8'	octagon marker
's'	square marker
'p'	pentagon marker
'p'	plus (filled) marker
'*'	star marker
'h'	hexagon1 marker
'H'	hexagon2 marker
'+'	plus marker
'x'	x marker
'X'	x (filled) marker
'D'	diamond marker
'd'	thin_diamond marker
' '	vline marker
'_'	hline marker

Line Styles

character	description
'_'	solid line style
'--'	dashed line style

character	description
'-.''	dash-dot line style
':'	dotted line style

Example format strings:

```
'b'      # blue markers with default shape
'or'     # red circles
'-g'     # green solid line
'--'     # dashed line with default color
'^k:'    # black triangle_up markers connected by a dotted line
```

Colors


The supported color abbreviations are the single letter codes

character	color
'b'	blue
'g'	green
'r'	red
'c'	cyan
'm'	magenta
'y'	yellow
'k'	black
'w'	white


and the 'CN' colors that index into the default property cycle.

If the color is the only part of the format string, you can additionally use any [matplotlib.colors](#) spec, e.g. full names ('green') or hex strings ('#008000').


Examples using `matplotlib.axes.Axes.plot`




[Plotting categorical variables](#)



[CSD Demo](#)




[Curve with error band](#)




[EventCollection Demo](#)




[Fill Between and Alpha](#)




[Filling the area between lines](#)



[Fill BetweenX Demo](#)




[Customizing dashed line styles](#)




[Lines with a ticked patheffect](#)




[Marker reference](#)




[Markevery Demo](#)




[prop_cycle property markevery in rcParams](#)








[Psd Demo](#)



[Simple Plot](#)








[Using span_where](#)



[with lines, dates, and text](#)

[irregularly spaced data](#)








[pcolormesh grids and shading](#)

[Streamplot](#)

[Spectrogram Demo](#)

[Watermark image](#)

[Aligning Labels](#)








[Axes box aspect](#)

[Axes Demo](#)

[Controlling view limits using margins and sticky edges](#)

[Axes Props](#)

[axhspan Demo](#)








[Broken Axis](#)

[Resizing axes with constrained layout](#)

[Resizing axes with tight layout](#)

[Figure labels: suptitle, supxlabel, supylabel](#)

[Invert Axes](#)








[Secondary Axis](#)

[Sharing axis limits and views](#)

[Figure subfigures](#)

[Multiple subplots](#)

[Creating multiple subplots using plt.subplots](#)








[Plots with different scales](#)

[Boxplots](#)

[Using histograms to plot a cumulative distribution](#)

[Some features of the histogram\(hist\) function](#)

[Polar plot](#)





[Polar Legend](#)

[Using accented text in matplotlib](#)

[Scale invariant angle label](#)

[Annotating Plots](#)

[Composing Custom Legends](#)








[Date tick labels](#)

[Custom tick formatter for time series](#)


[AnnotationBbox demo](#)

[Labeling ticks using engineering notation](#)


[Annotation arrow style reference](#)




defined labels




Rendering math equations using TeX




Text Rotation Relative To Line




Title positioning




Text watermark




Annotate Transform




Annotating a plot




Annotation Polar




Programmatically controlling subplot adjustment




Dollar Ticks




Simple axes labels



Text Commands




Color Demo




Color by y-value




PathPatch object




Bezier Curve




Dark background style sheet




FiveThirtyEight style sheet




ggplot style sheet




Axes with a fixed physical size




Parasite Simple




Simple Axisline4




Axis line styles




Parasite Axes demo




Parasite axis demo




Custom spines with axisartist




Simple Axisline




Anatomy of a figure



Bachelor's degrees by gender



Integral as the area under a curve




XKCD




Decay




The Bayes update








The double pendulum problem










































Animated 3D random walk



Animated line plot







[UNCHAINED](#)[events](#)[Looking Glass](#)[Path Editor](#)[Pick Event Demo2](#)[Resampling Data](#)[Timers](#)[Frontpage histogram example](#)[Frontpage plot example](#)[Changing colors of lines intersecting a box](#)[Cross hair cursor](#)[Custom projection](#)[Load converter](#)[Patheffect Demo](#)[Pythonic Matplotlib](#)[SVG Filter Line](#)[TickedStroke patheffect](#)[Zorder Demo](#)[Plot 2D data on 3D plot](#)[3D box surface plot](#)[Parametric Curve](#)[Lorenz Attractor](#)[2D and 3D Axes in same Figure](#)[Loglog Aspect](#)[Scales](#)[Symlog Demo](#)[Anscombe's quartet](#)[Radar chart \(aka spider or star chart\)](#)[Centered spines with arrows](#)[Multiple Yaxis With Spines](#)[Spine Placement](#)[Spines](#)[Custom spine bounds](#)[Centering labels between ticks](#)[Formatting date ticks using ConciseDateFormatter](#)[Date Demo Convert](#)[Date Index Formatter](#)

[Epochs](#)

[formatter](#)

[labels on the right](#)

[a list of values](#)








[Set default x-axis tick labels on the top](#)

[Evans test](#)

[CanvasAgg demo](#)

[Annotate Explain](#)

[Connect Simple01](#)



© Copyright 2002 - 2012 Jc
Matplotlib development team
Created using [Sphinx](#) 4.3.0.






[Connection styles for annotations](#)

[Nested GridSpec](#)

[Pgf Fonts](#)

[Pgf Textsystem](#)

[Simple Annotate01](#)








[Simple Legend01](#)

[Simple Legend02](#)

[Annotated Cursor](#)

[Check Buttons](#)

[Cursor](#)








[Multicursor](#)

[Radio Buttons](#)

[Rectangle and ellipse selectors](#)

[Span Selector](#)

[Textbox](#)








[Usage Guide](#)

[Artist tutorial](#)

[Legend guide](#)

[Styling withycler](#)

[Customizing Figure Layouts Using GridSpec and Other Functions](#)






[Constrained Layout Guide](#)

[Tight Layout guide](#)

[Autoscaling](#)

[Faster rendering by using blitting](#)

[Path Tutorial](#)






[Transformations Tutorial](#)

[Specifying Colors](#)

[Text in Matplotlib Plots](#)

[plot\(x,y\)](#)

[fill_between\(x,y1,y2\)](#)



[`tricontour\(x,y,z\)`](#)

[`tricontourf\(x,y,z\)`](#)

[`tripcolor\(x,y,z\)`](#)