

**RL notes**

## MARKOV DECISION PROCESSES (MDP)

The at time  $t$  the state is  $S_t \in \mathcal{S}$ , the action is  $A_t \in \mathcal{A}$ , and the reward (received before seeing the state and doing the action) is  $R_t \in \mathcal{R}$ , where  $\mathcal{S}$  is the state space,  $\mathcal{A}$  is the action space, and  $\mathcal{R} \subset \mathbb{R}$  is the reward space.

The **trajectory** is

$$S_0, A_0, R_1, S_1, A_1, R_2, S_2, A_2, R_3, \dots \quad (1)$$

The probability of getting to state  $s'$  and getting reward  $r$  after taking action  $a$  in state  $s$  is well defined, and given by

$$p(s', r \mid s, a) = \Pr \{S_t = s', R_t = r \mid S_{t-1} = s, A_{t-1} = a\} \quad (2)$$

where the function  $p$  defines **dynamics** of the MDP, and is called the **dynamics function**. The probabilities given  $p$  completely characterize the environment's dynamics. This also confirms that an MDP has the Markov property.

We can obtain the **state-transition probabilities** with

$$p(s' \mid s, a) = \Pr(S_t = s' \mid S_{t-1} = s, A_{t-1} = a) = \sum_{r \in \mathcal{R}} p(s', r \mid s, a) \quad (3)$$

And the expected rewards for a state-action pair:

$$r(s, a) = \mathbb{E}[R_t \mid S_{t-1} = s, A_{t-1} = a] = \sum_{r \in \mathcal{R}} r \sum_{s' \in \mathcal{S}} p(s', r \mid s, a) \quad (4)$$

and the expected reward given the next state:

$$r(s, a, s') = \mathbb{E}[R_t \mid S_{t-1} = s, A_{t-1} = a, S_t = s'] = \sum_{r \in \mathcal{R}} r \frac{p(s', r \mid s, a)}{p(s' \mid s, a)} \quad (5)$$

## RETURNS AND EPISODES

The **return** is the discounted sum of rewards (if we are using discounting).

In an episodic task, this is

$$G_t = R_{t+1} + \gamma R_{t+2} + \gamma^2 R_{t+3} + \dots + \gamma^{T-t-1} R_T \quad (6)$$

where  $T$  is the final time step. We think of each episode ending in the **same** terminal state - can be thought of as an artificial state that occurs right *after* the real terminal state of the episode.

The final reward is given in this final terminal state.

For continuing tasks, the return is

$$G_t = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1} \quad (7)$$

If we define the reward to be zero after the final state, this also holds for episodic tasks.

There is a recursive relationship between  $G_t$  and  $G_{t+1}$ :

$$G_t = \sum_{k=0}^{\infty} \gamma^k R_{t+k+1} \quad (8)$$

$$= R_t + \sum_{k=1}^{\infty} \gamma^k R_{t+k+1} \quad (9)$$

$$= R_t + \gamma \sum_{k=1}^{\infty} \gamma^{k-1} R_{t+k+1} \quad (10)$$

$$= R_t + \gamma \sum_{k=0}^{\infty} \gamma^k R_{t+k+2} \quad (11)$$

$$= R_t + \gamma G_{t+1} \quad (12)$$

$$(13)$$

## POLICIES AND VALUE FUNCTION

The **value** function is defined to be

$$v_{\pi}(s) = \mathbb{E}_{\pi} [G_t \mid S_t = s] \quad (14)$$

$$= \mathbb{E} \left[ \sum_{k=0}^{\infty} \gamma^k R_{t+k+1} \mid S_t = s \right] \quad (15)$$

and the **action-value** function is

$$q_{\pi}(s, a) = \mathbb{E}_{\pi} [G_t \mid S_t = s, A_t = a] \quad (16)$$

$$= \mathbb{E}_{\pi} \left[ \sum_{k=0}^{\infty} \gamma^k R_{t+k+1} \mid S_t = s, A_t = a \right] \quad (17)$$

$$(18)$$

The **Bellman equation** for the value function is

$$v_{\pi}(s) = \mathbb{E}_{\pi} [G_t \mid S_t = s] \quad (19)$$

$$= \mathbb{E}_{\pi} [R_{t+1} + \gamma G_{t+1} \mid S_t = s] \quad (20)$$

$$= \sum_a \pi(a \mid s) \sum_{s'} \sum_r p(s', r \mid s, a) [r + \gamma \mathbb{E}_{\pi} [G_{t+1} \mid S_{t+1} = s']] \quad (21)$$

$$= \sum_a \pi(a \mid s) \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_{\pi}(s')] \quad (22)$$

$$(23)$$

And the Bellman equation for the action-value function is

$$q_\pi(s, a) = \mathbb{E}_\pi [G_t \mid S_t = s, A_t = a] \quad (24)$$

$$= \mathbb{E}_\pi [R_{t+1} + \gamma G_{t+1} \mid S_t = s, A_t = a] \quad (25)$$

$$= \sum_{s'} \sum_r p(s', r \mid s, a) (r + \gamma \mathbb{E}_\pi [G_{t+1} \mid S_{t+1} = s']) \quad (26)$$

$$= \sum_{s', r} p(s', r \mid s, a) \left( r + \gamma \sum_{a'} \pi(a' \mid s') \mathbb{E} [G_{t+1} \mid s', a'] \right) \quad (27)$$

$$= \sum_{s', r} p(s', r \mid s, a) \left( r + \gamma \sum_{a'} \pi(a' \mid s) q_\pi(a', s') \right) \quad (28)$$

$$(29)$$

We can write  $v_\pi$  in terms of  $q_\pi$  :

$$v_\pi(s) = \mathbb{E}_\pi [q_\pi(a, s) \mid S_t = s] \quad (30)$$

$$= \sum_a \pi(a \mid s) q_\pi(a, s) \quad (31)$$

$$(32)$$

Or we could write  $q_\pi$  in terms of  $v_\pi$ :

$$q_\pi(s, a) = \mathbb{E} [R_{t+1} + \gamma v_\pi(S_{t+1}) \mid S_t = s, A_t = a] \quad (33)$$

$$= \sum_{s', r'} p(s', r' \mid s, a) (r + \gamma v_\pi(s')) \quad (34)$$

$$(35)$$

## OPTIMAL POLICIES AND OPTIMAL VALUE FUNCTION

The **optimal policies** are denoted  $\pi_*$ , and they define the optimal value function

$$v_*(s) = \max_{\pi} v_\pi(s) = v_{\pi_*}(s), \text{ for all } s \in \mathcal{S} \quad (36)$$

They also define the optimal action-value function

$$q_*(s, a) = \max_{\pi} q_\pi(s, a) = q_{\pi_*}(s, a), \quad (37)$$

for all  $s \in \mathcal{S}$  and  $a \in \mathcal{A}(s)$ .

$q_*(s, a)$  follows an optimal policy after the action  $a$ , so we have

$$q_*(s, a) = \mathbb{E} [R_{t+1} + \gamma v_*(S_{t+1}) \mid S_t = s, A_t = a] \quad (38)$$

Now, the **Bellman optimality equation** for  $v_*$  is

$$v_*(s) = \max_{a \in \mathcal{A}(s)} q_{\pi_*}(s, a) \quad (39)$$

$$= \max_a \mathbb{E}_{\pi_*} [G_t \mid S_t = s, A_t = a] \quad (40)$$

$$= \max_a \mathbb{E}_{\pi_*} [R_{t+1} + \gamma G_{t+1} \mid S_t = s, A_t = a] \quad (41)$$

$$= \max_a \mathbb{E} [R_{t+1} + \gamma v_*(S_{t+1}) \mid S_t = s, A_t = a] \quad (42)$$

$$= \max_a \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_*(s')] \quad (43)$$

$$(44)$$

The corresponding equation for  $q_*$  is

$$q_*(s, a) = \mathbb{E} \left[ R_{t+1} + \gamma \max_{a'} q_*(S_{t+1}, a') \mid S_t = s, A_t = a \right] \quad (45)$$

$$= \sum_{s', r} p(s', r \mid s, a) \left[ r + \gamma \max_{a'} q_*(s', a') \right] \quad (46)$$

## POLICY EVALUATION

If the environment's dynamics are completely known, we can approximate  $v_\pi$  by starting with an arbitrary value function  $v_0$  (but with the value of the terminal state equal to zero), and continuously perform the following iteration:

$$v_{k+1} = \mathbb{E}_\pi [R_{t+1} + \gamma v_k(S_{t+1}) \mid S_t = s] \quad (47)$$

$$= \sum_a \pi(a \mid s) \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_k(s')] \quad (48)$$

for all  $s \in \mathcal{S}$ . In this case,  $v_k \rightarrow v_\pi$  as  $k \rightarrow \infty$ . This is called **iterative policy evaluation**.

The analogous iteration for  $q_\pi(s, a)$  is

$$q_{k+1}(s, a) = \mathbb{E}_\pi [R_{t+1} + \gamma G_{t+1} \mid S_t = s, A_t = a] \quad (49)$$

$$= \sum_{s', r} p(s', r \mid s, a) \left( r + \gamma \sum_{a'} \pi(a' \mid s) q_k(a', s) \right) \quad (50)$$

$$(51)$$

## POLICY IMPROVEMENT

If we have a deterministic policy  $\pi$  and its value function  $v_\pi$ , then suppose  $\pi'$  is such that in state  $s$ , we choose the next action  $a$  greedily with respect to  $v_\pi$ , then the value of this behavior is

$$q_\pi(s, a) = \mathbb{E} [R_{t+1} + \gamma v_\pi(S_{t+1}) \mid S_t = s, A_t = a] \quad (52)$$

$$= \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_\pi(s')] \quad (53)$$

$$(54)$$

Then  $\pi'$  is better than  $\pi$  overall.

The **policy improvement theorem** states that if  $\pi$  and  $\pi'$  is a pair of deterministic policies such that

$$\forall s \in \mathcal{S} : q_\pi(s, \pi'(s)) \geq v_\pi(s) \quad (55)$$

Then  $\pi'$  is as good or better than  $\pi$ , that is

$$\forall s \in \mathcal{S} : v_{\pi'}(s) \geq v_\pi(s) \quad (56)$$

And if there is a strict inequality in (55) in  $s$ , then there is also a strict inequality in (56), in  $s$ .

Now, if we have a policy  $\pi$ , and  $q_\pi(s, a)$ , then we can construct the new *greedy* policy

$$\pi'(s) = \operatorname{argmax}_a q_\pi(s, a) \quad (57)$$

$$= \operatorname{argmax}_a \mathbb{E}[R_{t+1} + \gamma v_\pi(S_{t+1} \mid S_t = s, A_t = a)] \quad (58)$$

$$= \operatorname{argmax}_a \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_\pi(s')] \quad (59)$$

$$(60)$$

This policy satisfies (55), so it is as good as or better than  $\pi$ . This process is called *policy improvement*. If  $\pi'$  is not better than  $\pi$  but exactly as good, then we have

$$v_{\pi'}(s) = \max_a \mathbb{E}[R_{t+1} + \gamma v_{\pi'}(S_{t+1}) \mid S_t = s, A_t = a] \quad (61)$$

$$= \max_a \sum_{s', r} p(s', r \mid s, a) [r + \gamma v_{\pi'}(s')] \quad (62)$$

$$(63)$$

which is the Bellman optimality equation, so  $v_{\pi'} = v_*$ , and  $\pi$  and  $\pi'$  are optimal policies.

For stochastic policies, this also works - as long as we assign a zero probability to non-optimal actions, all probability assignments are allowed.

## POLICY ITERATION

**Policy iteration** is the process of taking a policy, calculating its value function, improving the policy, calculating the value function, and so on:

$$\pi_0 \xrightarrow{E} v_{\pi_0} \xrightarrow{I} \pi_1 \xrightarrow{E} v_{\pi_1} \xrightarrow{I} \dots \xrightarrow{I} \pi_* \xrightarrow{E} v_* \quad (64)$$