```
**************************************
1
 2
                                   EXERCISE 4
3
4
                                  CONTOURS
    5
 6
7
    #include <opencv2/opencv.hpp>
    #include "Ex4-CV-header.h"
8
9
    #include <iostream>
10
    #include <stdio.h>
11
    #include <math.h>
12
13
    #define LINES 'L'
14
    #define RECTS 'R'
15
16
    using namespace std;
17
    using namespace cv;
18
19
20
21
    int main(int argc, char **argv) {
        22
23
                                  Gradient Method
        24
25
        IplImage * img = cvLoadImage(argv[1] , CV_LOAD_IMAGE_GRAYSCALE);
26
27
        cvNamedWindow("Grey scale"
        cvShowImage("Grey scale"
28
29
        cvSaveImage("Grey_Scale.png" , img);
30
31
        /// Create a binary image
32
        IplImage * his = getHistogram(img , LINES);
33
34
        cvNamedWindow("histogram"
        cvShowImage("histogram"
                               , his);
35
36
        cvSaveImage("Histogram.png" , his);
37
38
        cvWaitKey(0);
39
40
        IplImage * bin = simpleThresholding(img , his);
41
42
        cvNamedWindow("Binary Image"
        cvShowImage("Binary Image"
                                  , bin);
43
        cvSaveImage("Binary_Image.png" , bin);
44
45
46
        /// Doesn't produce a very good result and requires some priori knowledge about the scene
47
        /// (e.g. if one expects darker objects on a less dark background, or viceversa).
        IplImage * gradContour = cvCreateImage(cvSize(img->width - 2, img->height - 2), IPL_DEPTH 8U, 1);
48
        cvSet(gradContour , 0);
gradSearchContour(img , gradContour);
49
50
51
        cvNamedWindow("Gradient Method" , 0);
52
        53
54
55
56
        IplImage * I = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 3);
57
        cvCvtColor(img , I , COLOR_GRAY2RGB);
        IplImage * m = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
58
59
        cvSet(m , 0);
60
        cvSetImageROI(m , cvRect(1, 1, img->width - 2, img->height - 2) );
61
62
        cvCopy(gradContour , m);
63
        cvResetImageROI(m);
```

```
const CvMat M = cvarrToMat(m);
cvSet(I , cvScalar(255,0,0) , &M);
cvShowImage("Show Gradient" , 0);
cvSaveImage("Character , 1):
cvSaveImage("Show_Gradient.png" , I);
/// Every black pixel that has an adjacent white pixel is a border
IplImage * binGradContour = cvCreateImage(cvSize(img->width-2, img->height-2), IPL_DEPTH_8U, 1);
cvSet(binGradContour , 0);
searchContour(bin , binGradContour);
cvNamedWindow("Binary-Gradient Contour"
                                        , 0);
cvCvtColor(img , I , COLOR_GRAY2RGB);
m = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
cvSet(m , 0);
cvSetImageROI(m , cvRect(1 , 1 , img->width - 2 , img->height - 2));
cvCopy(binGradContour , m);
cvResetImageROI(m);
const CvMat M 1 = cvarrToMat(m);
cvSet(I, cvScalar(0 , 0 , 255) , &M_1);
cvNamedWindow("Show Binary Contour" , 0);
cvShowImage("Show Binary Contour" , I);
cvShowImage("Show Binary Contour" , I);
cvSaveImage("Show_Binary_Contour.png" , I);
Gradient Method - the right way
IplImage * Xim = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
IplImage * Yim = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
IplImage * gradientImage = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
float Prewitt_x [3][3] = \{ \{ -1, 0, 1\},
                         { -1 , 0 , 1},
{ -1 , 0 , 1} };
float Prewitt_y [3][3] = { { -1 , -1 , -1},
                         { 0 , 0 , 0},
{ 1 , 1 , 1} };
CvMat PrewittXK, PrewittYK;
cvInitMatHeader(&PrewittXK , 3 , 3 , CV_32F , Prewitt_x);
cvInitMatHeader(&PrewittYK , 3 , 3 , CV_32F , Prewitt_y);
cvFilter2D(img , Xim , &PrewittXK , cvPoint(-1 , -1) );
cvFilter2D(img , Yim , &PrewittYK , cvPoint(-1 , -1) );
for(int i = 0 ; i < Xim->height ; i++) {
   char * px = Xim->imageData + i * Xim->widthStep;
   char * py = Yim->imageData + i * Yim->widthStep;
   char * pmag = gradientImage->imageData + i * gradientImage->widthStep;
```

```
128
            for(int j = 0; j < Xim->width; j++) {
129
130
                float x = (float)(uchar)(*px);
                float y = (float)(uchar)(*py);
131
132
133
                *pmag = (uchar)sqrt(x * x + y * y);
134
                px++;
135
                py++;
136
                pmag++;
137
            }
138
         }
139
140
         cvNamedWindow("Prewitt" , 0);
141
         cvShowImage("Prewitt" , gradientImage);
         cvSaveImage("Prewitt.png" , gradientImage);
142
143
144
145
         146
         float Sobel_x [3][3] = \{ \{ -1, 0, 1 \},
147
148
                               \{-2,0,2\},
149
                               { -1 , 0 , 1}
         float Sobel_y [3][3] = { { -1 , -2 , -1},
150
                                 0,
151
                                      0, 0},
                                 1,
152
153
154
         CvMat SobelXK, SobelYK;
155
         cvInitMatHeader(&SobelXK , 3 , 3 , CV_32F , Sobel_x);
         cvInitMatHeader(&SobelYK , 3 , 3 , CV_32F , Sobel_y);
156
157
158
         cvFilter2D(img , Xim , &SobelXK , cvPoint(-1 , -1) );
159
         cvFilter2D(img , Yim , &SobelYK , cvPoint(-1 , -1) );
160
161
         for(int i = 0 ; i < Xim->height ; i++) {
162
163
            char * px = Xim->imageData + i * Xim->widthStep;
            char * py = Yim->imageData + i * Yim->widthStep;
164
            char * pmag = gradientImage->imageData + i * gradientImage->widthStep;
165
166
167
            for(int j = 0 ; j < Xim->width ; j++) {
168
169
                float x = (float)(uchar)(*px);
170
                float y = (float)(uchar)(*py);
171
172
                *pmag = (uchar)sqrt(x*x + y*y);
173
                px++;
174
                py++;
175
                pmag++;
176
            }
177
         }
178
179
         cvNamedWindow("Sobel" , 0);
180
         cvShowImage("Sobel" , gradientImage);
181
         cvSaveImage("Sobel.png" , gradientImage);
182
183
         184
185
         IplImage * CannyIm = cvCreateImage(cvGetSize(img) , IPL DEPTH 8U , 1);
         cvLaplace(img , CannyIm , 5);
186
         cvNamedWindow("Laplace" , 0);
187
                               , gradientImage);
188
         cvShowImage("Laplace"
         cvSaveImage("Laplace.png" , gradientImage);
189
190
         191
```

192 193

194

195

196 197

198 199

200

201

202 203

204

205 206

207 208

209 210

211212

213214

215

216217

218

219

220

221

222

223

224 225

226

227 228

229 230

231232233

234235

236

237

238

239

240

241242

243

244

245 246

247248

249

250 251

252253

254 255

```
// Resulting image very dark
float Roberts_x [2][2] = { {
                         0,1},
                       { -1 , 0} };
float Roberts_y [2][2] = { { 1 , 0},
                       { 0 , -1} };
CvMat RobertsXK, RobertsYK;
cvInitMatHeader(&RobertsXK , 2 , 2 , CV_32F , Roberts_x);
cvInitMatHeader(&RobertsYK , 2 , 2 , CV_32F , Roberts_y);
cvFilter2D(img , Xim , &RobertsXK , cvPoint(-1 , -1) );
cvFilter2D(img , Yim , &RobertsYK , cvPoint(-1 , -1) );
for(int i = 0 ; i < Xim->height ; i++) {
   char * px = Xim->imageData + i * Xim->widthStep;
   char * py = Yim->imageData + i * Yim->widthStep;
   char * pmag = gradientImage->imageData + i * gradientImage->widthStep;
   for(int j = 0 ; j < Xim->width ; j++) {
       float x = (float)(uchar)(*px);
      float y = (float)(uchar)(*py);
       *pmag = (uchar)sqrt(x*x + y*y);
      px++;
      py++;
      pmag++;
   }
}
cvNamedWindow("Roberts" , 0);
cvShowImage("Roberts" , gradientImage);
cvSaveImage("Roberts.png" , gradientImage);
Laplacian Method
IplImage * LG_contour = cvCreateImage(cvGetSize(img) , IPL_DEPTH_8U , 1);
/*double LG_mat [9][9] = { {0 , 0 , 1 ,
                                    2,
                                            2, 2, 1, 0, 0},
                       {0, 1, 5, 10,
                                           12 , 10 , 5 , 1 , 0},
                       {1, 5, 15, 19,
                                          16 , 19 , 15 , 5 , 1},
                       {2,10,19,-19,-64,-19,19,10,2},
                       {2 , 12 , 16 , -64 , -148 , -64 , 16 , 12 , 2},
                       {2 , 10 , 19 , -19 , -64 , -19 , 19 , 10 , 2},
                       {1, 5, 15, 19, 16, 19, 15, 5, 1}, {0, 1, 5, 10, 12, 10, 5, 1, 0},
                       {0,
                            0,1,
                                     2,
                                          2,
                                                2, 1, 0, 0}
                     };*/
/*double LG_mat [7][7] = { {0, 1, 2, 4, 2, 1, 0},
                       {1, 7,
                                24 , 31 , 24 , 7 , 1},
                       {2,24,17,-51,17,24,2},
                       {4 , 31 , -51 , -248 , -51 , 31 , 4},
                       {2, 24, 17, -51, 17, 24, 2}, {1, 7, 24, 31, 24, 7, 1},
                       {0, 1, 2, 4, 2, 1, 0}
                     };*/
```

```
double LG_mat [5][5] = { { 1 , 9 ,
                   { 9,58, 12,58, 9},
                   \{19, 12, -432, 12, 19\},\
                   { 9,58, 12,58, 9},
                            19, 9, 1}
                  };
  /*double LG_mat [3][3] = { { 1, 4, 1},}
                    { 4, -20, 4},
{ 1, 4, 1}
                   };*/
  CvMat LG_kernel;
  cvInitMatHeader(&LG_kernel , 5 , 5 , CV_64F , LG_mat);
  cvFilter2D(img , LG_contour , &LG_kernel , cvPoint(-1 , -1) );
  cvNamedWindow("Laplacian Contour" , 0);
cvShowImage("Laplacian Contour" , LG_contour);
  cvSaveImage("Laplacian_Contour.png" , LG_contour);
  Contour Search
  /// To implement
  cvWaitKey(0);
  Clean-Up
  cvReleaseImage(&img);
  cvReleaseImage(&his);
  cvReleaseImage(&bin);
  cvReleaseImage(&gradContour);
  cvReleaseImage(&binGradContour);
  cvReleaseImage(&LG_contour);
  cvDestroyAllWindows();
  return 0;
}
```