



LENGUAJES DE PROGRAMACIÓN

2020 — 2º SEMESTRE

CLASE 3:

- ▶ Functions as values
- ▶ A good programming practice
- ▶ Pattern matching

Federico Olmedo



Anonymous and higher-order functions

Anonymous functions

SYNTAX: $(\lambda (arg_1 \dots arg_n) func-body)$

EXAMPLE: $(\lambda (n) (+ n 3))$

Higher-order functions

- That takes **as argument** a function:

$(\text{map } (\lambda (n) (+ n 3)) \text{'(1 2 3)}) \rightsquigarrow \text{'(4 5 6)}$

$(\text{filter even? } \text{'(1 2 3)}) \rightsquigarrow \text{'(2)}$

- That returns a function **as output**:

$(\text{define } (\text{add-}n \text{ } n) (\lambda (x) (+ x n)))$

Anonymous and higher-order functions

Anonymous functions

SYNTAX: $(\lambda (arg_1 \dots arg_n) func-body)$

EXAMPLE: $(\lambda (n) (+ n 3))$

Higher-order functions

- That takes **as argument** a function:

$(\text{map } (\lambda (n) (+ n 3)) \text{'(1 2 3)}) \rightsquigarrow \text{'(4 5 6)}$

$(\text{filter even? } \text{'(1 2 3)}) \rightsquigarrow \text{'(2)}$

- That returns a function **as output**:

$(\text{define } (\text{add-n } n) (\lambda (x) (+ x n)))$

1. Define function `(negate p)` that takes a predicate `p` and returns its negation.
2. Define function `(reject p l)` that takes a list `l` and a predicate `p` and removes from the list the elements satisfying `p`.
3. Define a function `(apply-twice f)` that takes a function $f:A \rightarrow A$ and returns the functions that applies `f` twice to its argument.

Currying



Currying is the technique that transforms a function that takes simultaneously two (or more) arguments into a function that takes them one by one.

Currying



Currying is the technique that transforms a function that takes simultaneously two (or more) arguments into a function that takes them one by one.

```
(define (curry f) (λ (a) (λ (b) (f a b))))
```

Currying



Currying is the technique that transforms a function that takes simultaneously two (or more) arguments into a function that takes them one by one.

```
(define (curry f) (λ (a) (λ (b) (f a b))))
```

BENEFIT: allows for partial application.

```
> (map ((curry +) 1) '(1 2 3))  
'(2 3 4)
```

Currying



Currying is the technique that transforms a function that takes simultaneously two (or more) arguments into a function that takes them one by one.

```
(define (curry f) (λ (a) (λ (b) (f a b))))
```

BENEFIT: allows for partial application.

```
> (map ((curry +) 1) '(1 2 3))  
'(2 3 4)
```

```
> (filter ((curry <) 1) '(1 2 3))  
'(2 3)
```


Currying



Currying is the technique that transforms a function that takes simultaneously two (or more) arguments into a function that takes them one by one.

```
(define (curry f) (λ (a) (λ (b) (f a b))))
```

BENEFIT: allows for partial application.

```
> (map ((curry +) 1) '(1 2 3))
'(2 3 4)
```

```
> (filter ((curry <) 1) '(1 2 3))
'(2 3)
```

```
((curry <) 1)
[def. curry]
((λ (a) (λ (b) (< a b))) 1)
[funct. application]
(λ (b) (< 1 b))
```

Methodology for defining functions

Methodology for defining functions

1

Understand what
the function does

Methodology for defining functions

```
:: double-list :: (listof Number) -> (listof Number)
```

2

Write the function
contract

Methodology for defining functions

```
:: double-list :: (listof Number) -> (listof Number)  
;; Doubles the elements of the list
```

3

Write the function
purpose

Methodology for defining functions

```
:: double-list :: (listof Number) -> (listof Number)  
;; Doubles the elements of the list
```

```
(test (double-list '(1 2 3)) '(2 4 6))  
(test (double-list empty) empty)
```

Requires
#lang play

4

Provide tests

Methodology for defining functions

```
;; double-list :: (listof Number) -> (listof Number)
```

```
;; Doubles the elements of the list
```

```
(define (double-list l)  
  (map (λ (x) (* 2 x)) l))
```

```
(test (double-list '(1 2 3)) '(2 4 6))  
(test (double-list empty) empty)
```

5

Write the function
implementation

Methodology for defining functions

```
;; double-list :: (listof Number) -> (listof Number)
```

```
;; Doubles the elements of the list
```

```
(define (double-list l)  
  (map (λ (x) (* 2 x)) l))
```

```
(test (double-list '(1 2 3)) '(2 4 6))  
(test (double-list empty) empty)
```

- **Implementation** should be the **last** step!!!
- Tests should cover all “significant” cases
- GIGO: garbage-in garbage-out

6

What else provides `#lang play`?

What else provides `#lang play`?

- Support for testing functions on inputs that throw an (error “bla ...”)
 - ▶ See [PrePLAI](#) [Section 5.2]

What else provides #lang play?

- Support for testing functions on inputs that throw an (error “bla ...”)
 - ▶ See [PrePLAI](#) [Section 5.2]
- Support for defining data structures (via typedef)
 - ▶ Next lecture

What else provides #lang play?

- Support for testing functions on inputs that throw an (error “bla ...”)
 - ▶ See [PrePLAI](#) [Section 5.2]
- Support for defining data structures (via typedef)
 - ▶ Next lecture
- Pattern matching over expressions via def

What else provides #lang play?

- Support for testing functions on inputs that throw an (error “bla ...”)
 - ▶ See [PrePLAI](#) [Section 5.2]
- Support for defining data structures (via typedef)
 - ▶ Next lecture
- Pattern matching over expressions via def

```
> (def (list x y z) '(1 2 3))  
> y  
2  
>
```

What else provides #lang play?

- Support for testing functions on inputs that throw an (error “bla ...”)
 - ▶ See [PrePLAI](#) [Section 5.2]
- Support for defining data structures (via typedef)
 - ▶ Next lecture
- Pattern matching over expressions via def

```
> (def (list x y z) '(1 2 3))
> y
2
>
```

```
;; distance :: (cons Int Int) (cons Int Int) -> Float
;; Calcula la distancia entre dos puntos
(define (distance p1 p2)
  (def (cons x1 y1) p1)
  (def (cons x2 y2) p2)
  (sqrt (+ (expt (- x1 x2) 2) (expt (- y1 y2) 2))))
```


Define function `(apply-f-n f n)` that returns the function obtained by composing `f` with itself `n` times

Functions are values

And therefore they can:

- Be the argument of other functions
- Be the output (or return value) of other functions

Functions are values

And therefore they can:

- Be the argument of other functions
- Be the output (or return value) of other functions

Function implementation as last step

Bibliography

- [PrePLAI](#): Introduction to functional programming in Racket [Sections 3, 4.1 and 5.1]

For a more detailed reference, see the online Racket documentation:

- [Racket Guide](#): tutorial
- [Racket Reference](#): reference manual