



Created 01/03/2013
Rev. 2 – 12/09/2019
Rev. 3 – 06/06/2024

PRODUCT TECHNICAL AND SAFETY DATA SHEET:

UNICO

UNICO5




UNICO12.5



DESCRIPTION:

Breathable water-repellent paint for interiors, it is characterized by excellent covering power and excellent white point. Easy to apply, it does not require the application of any base product, it has excellent brushability and a good yield. Suitable for kitchens, bathrooms and in general for rooms subject to the formation of condensation.

CHARACTERISTICS:

I WAIT	Opaque
SPECIFIC WEIGHT	1.60 Kg/l \pm 0.03 at 20°C
VOC (Directive 2004/42/EC):	1.29% - 20.00 g/litre
WASHING RESISTANCE	Average
WATER VAPOR PERMEABILITY	Average
DIRT GRIP	Low
COLOR	White (Colourable with Universal Dyes)
DRYING	for covering: 6 hours
(data referred to 20°C and 65% RH)	complete: 48 hours
PRACTICAL YIELD	12-16 m ² / lt. per coat depending on the absorption of the substrate
	1st coat: add 30% drinking water, in the case of very powdery substrates add up to 100% drinking water.
DILUTION	2nd coat: add 25% drinking water
	Airless spray: add between 30% and 40% of drinking water.
	Recommended tips: LP419-LP519-LP619- LP421-LP521-LP624
TOOLS	 brush  roller  spray
SUPPORTS	civil plaster, plasterboard, fibre cement, stuccoed walls

APPLICATION

PREPARATION OF THE SUPPORT

The substrate must be healthy, dry, clean and consistent, free from damp stains, traces of dirt, grease, mold, etc. Old inconsistent or flaking paint must be removed by brushing or sanding the surface. Imperfections, cracks, flaking must be eliminated and filled with an appropriate filler.

	NEW SUPPORTS				ALREADY PAINTED SUPPORTS			
	PLASTER	HANDS	PLASTERBOARD	HANDS	BREATHABLE OR CRUMBLING	HANDS	WASHABLE WELL ANCHORED	HANDS
FUND	UNIQUE	1	UNIQUE	1	UNIQUE	1	UNIQUE	1
FINISH	UNIQUE	1	UNIQUE	1	DILUTED FROM 50% 100% UNIQUE	2	UNIQUE	1

GENERAL WARNINGS

In order not to alter the typical breathable properties of the product, the quantity of base dye must not exceed 20%. Store the product in a cool place and protect from frost. Do not apply the product at temperatures below 5° or above 30° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.