



Created 01/08/2007
Rev. 2 – 12/09/2019
Rev. 3 – 06/06/2024

PRODUCT TECHNICAL AND SAFETY DATA SHEET:

NEFRIT

NEFRIT5

NEFRIT12.5




KGNEFRIT



DESCRIPTION:

Breathable water-based paint for interiors is characterized by good covering power and good white point. Easy to apply with a brush and roller, it has excellent brushability and good yield, ideal for the interiors of private residential environments and public offices.

CHARACTERISTICS:

I WAIT	Opaque
SPECIFIC WEIGHT	NEPHRIT: 1.58 Kg/lit. \pm 0.05 at 20°C (KGNEFRIT: 1.50 Kg/lit. \pm 0.05 at 20°C)
DRY RESIDUE	60 \pm 0.5 % w/w
WASHING RESISTANCE	Low
WATER VAPOR PERMEABILITY	High
DIRT GRIP	Low
COLOR	White (Colourable with Universal Dyes)
DRYING	for covering: 6 hours
(data referred to 20°C and 65% RH)	complete: 48 hours
PRACTICAL YIELD	9-13 m ² / lt. per coat
	depending on the absorption of the support
DILUTION	1st hand: add 30% drinking water
	2nd hand: add 25% drinking water
TOOLS	 brush  roller  spray
SUPPORTS	civil plaster, plasterboard, fibre cement, stuccoed walls

APPLICATION

PREPARATION OF THE SUPPORT

The substrate must be healthy, dry, clean and consistent, free from damp stains, traces of dirt, grease, mold, etc. Old inconsistent or flaking paint must be removed by brushing or sanding the surface. Imperfections, cracks, flaking must be eliminated and filled with an appropriate filler.

	NEW SUPPORTS				ALREADY PAINTED SUPPORTS			
	PLASTER	HANDS	PLASTERBOARD	HANDS	BREATHABLE OR CRUMBLING	HANDS	WASHABLE WELL ANCHORED	HANDS
FUND FINISH	JANTAR	1	REFONDO	1	JANTAR	1		
	NEFRIT	2	NEFRIT	1	NEFRIT	2	NEFRIT	2

GENERAL WARNINGS

In order not to alter the typical breathable properties of the product, the quantity of base dye must not exceed 20%. Store the product in a cool place and protect from frost. Do not apply the product at temperatures below 5° or above 30° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.