

ITALMONT S.R.L.
DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 1 / 14
Replaced revision:1 (Dated 10/11/2025)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name **DIAMANT BASE BIANCA**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Acrylic siloxane paint for exteriors**

Identified Uses	Industrial	Professional	Consumer
paint product	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 7, 8b. PC: 9a. LCS: IS.	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 8a. PC: 9a. LCS: PW.	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 8a. PC: 9a. LCS: C.
paint product production	ERC: 2. PROC: 5, 8b, 9. PC: 9a. LCS: F, M.		

1.3. Details of the supplier of the safety data sheet

Name **ITALMONT S.R.L.**
Full address **VIA IV NOVEMBRE 13**
District and Country **63078 Spinetoli ITALIA** (AP)
Tel. **+39 0736 899238**
Fax **+39 0736 899489**
e-mail address of the competent person responsible for the Safety Data Sheet **info@italmont.it**
Supplier: **ITALMONT S.R.L.**

1.4. Emergency telephone number

For urgent inquiries refer to **UE general number - 112 (Available 24h. Safety Data Sheets or Product information could not available for emergency service)**

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 2 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 2. Hazards identification ... / >>

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
2-OCTYL-2H-ISOTHIAZOL-3-ONE
1,2-BENZISOTHIACOLIN-3-ONE
May produce an allergic reaction.

Precautionary statements:

P273 Avoid release to the environment.

Contains: QUARTZ

VOC (Directive 2004/42/EC) :

Exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 11.70
Limit value: 40.00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	Conc. %	Classification (EC) 1272/2008 (CLP)
TITANIUM DIOXIDE		
INDEX	12	
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-XXXX	
TALC		
INDEX	4	
EC	238-877-9	
CAS	14807-96-6	
QUARTZ		
INDEX	3.12	STOT RE 1 H372
EC	238-878-4	
CAS	14808-60-7	
CALCIUM CARBONATE		
INDEX	2.7	
EC	207-439-9	
CAS	471-34-1	
1,2-BENZISOTHIACOLIN-3-ONE		
INDEX	613-088-00-6	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1 Skin Sens. 1A H317: ≥ 0.036%
EC	220-120-9	LD50 Oral: 450 mg/kg, LC50 Inhalation mists/powders: 0.21 mg/l/4h
CAS	2634-33-5	
REACH Reg.	Biocida	
2-OCTYL-2H-ISOTHIAZOL-3-ONE		
INDEX	613-112-00-5	Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1 H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071 Skin Sens. 1A H317: ≥ 0.0015% LD50 Oral: 125 mg/kg, LD50 Dermal: 311 mg/kg, LC50 Inhalation mists/powders: 0.27 mg/l/4h
EC	247-761-7	
CAS	26530-20-1	
REACH Reg.	Biocida	

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 3 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 3. Composition/information on ingredients ... / >

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)			
INDEX	613-167-00-5	0.001	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to Annex VI to the CLP Regulation: B
EC			Skin Corr. 1C H314: ≥ 0.6%, Skin Irrit. 2 H315: ≥ 0.06% - < 0.6%, Skin Sens. 1A H317: ≥ 0.0015%, Eye Dam. 1 H318: ≥ 0.6%, Eye Irrit. 2 H319: ≥ 0.06% - < 0.6%
CAS	55965-84-9		ATE Oral: 100 mg/kg, LD50 Dermal: 87.12 mg/kg, LC50 Inhalation mists/powders: 0.171 mg/l/4h
TERBUTRINA			
INDEX		0.001	Acute Tox. 4 H302, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100
EC	212-950-5		ATE Oral: 500 mg/kg
CAS	886-50-0		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 4 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 5. Firefighting measures ... / >>

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 5 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 8. Exposure controls/personal protection ... / >>

POL	Polska	agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężen czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
GBR EU	United Kingdom OEL EU	EH40/2005 Workplace exposure limits (Fourth Edition 2020) Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
TLV-ACGIH	ACGIH 2023	

TALC

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLA	ESP	2				RESP
TGG	NLD	0.25				RESP
NDS/NDSCh	POL	4				INHAL
NDS/NDSCh	POL	1				RESP
TLV	ROU	2				
WEL	GBR	1				RESP
TLV-ACGIH		2				RESP

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
MAK	DEU	0.3		2.4		RESP Hinweis
VLA	ESP	10				
VLEP	FRA	10				
NDS/NDSCh	POL	10				INHAL
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
TLV-ACGIH		0.2				RESP

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
AGW	DEU	0.05		0.1		INHAL
AGW	DEU	0.05		0.1		SKIN
MAK	DEU	0.05		0.1		INHAL
MAK	DEU	0.05		0.1		SKIN

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE

(3:1)

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
MAK	DEU	0.2		0.4		INHAL

CALCIUM CARBONATE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLEP	FRA	10				
NDS/NDSCh	POL	10				INHAL
TLV-ACGIH		10				INHAL
TLV-ACGIH		3				RESP

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 6 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 8. Exposure controls/personal protection ... / >>

QUARTZ						
Threshold Limit Value						
Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLA	ESP		0.05			RESP
VLEP	FRA	0.1				RESP
VLEP	ITA	0.1				RESP
TGG	NLD	0.075				RESP
VLE	PRT	0.025				RESP
NDS/NDSCh	POL	0.1				RESP
TLV	ROU	0.1				RESP
OEL	EU	0.1				RESP
TLV-ACGIH		0.025				RESP

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR)

The following should be considered when choosing work glove material: compatibility, degradation, permeability time.

Thickness: 0.3 mm

Glove thickness must be selected based on the minimum required breakthrough time.

Breakthrough time: 30 min

Glove resistance depends on various elements, such as temperature and other environmental factors.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	dense liquid	
Colour	white	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	> 100 °C	Substance:WATER Initial boiling point: 100 °C
Flammability	not flammable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 7 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 9. Physical and chemical properties ... / >

Decomposition temperature	not available	
pH	8	Method:ph meter
Kinematic viscosity	not available	
Dynamic viscosity	290 KcP	Method:Brookfield
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1.4	Method:pycnometer
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

CALCIUM CARBONATE

Incompatible with: acids.

10.6. Hazardous decomposition products

CALCIUM CARBONATE

May develop: calcium oxides,carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 8 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 11. Toxicological information ... / >>

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: Not classified (no significant component)

TALC

LC50 (Inhalation mists/powders): > 2.1 mg/l/4h Rat

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

1,2-BENZISOTHIAZOLIN-3-ONE

LD50 (Dermal): > 2000 mg/kg Rat

LD50 (Oral): 450 mg/kg Rat

LC50 (Inhalation mists/powders): 0.21 mg/l/4h

2-OCTYL-2H-ISOTHIAZOL-3-ONE

LD50 (Dermal): 311 mg/kg

LD50 (Oral): 125 mg/kg Rat

LC50 (Inhalation mists/powders): 0.27 mg/l/4h Rat

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LD50 (Dermal): 87.12 mg/kg Rabbit

LD50 (Oral): 457 mg/kg Rat

LC50 (Inhalation mists/powders): 0.171 mg/l/4h Rat

CALCIUM CARBONATE

LD50 (Oral): 6450 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

2-OCTYL-2H-ISOTHIAZOL-3-ONE

1,2-BENZISOTHIAZOLIN-3-ONE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TALC

Overall IARC evaluation: Perineal use of talc-based body powder is possibly carcinogenic to humans (Group 2B). Inhaled talc not containing asbestos or asbestiform fibres is not classifiable as to its carcinogenicity (Group 3).

REPRODUCTIVE TOXICITY

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 9 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 11. Toxicological information ... / >

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

1,2-BENZISOTHIAZOLIN-3-ONE

LC50 - for Fish	2.15 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	2.9 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0.11 mg/l/72h <i>Pseudokirchneriella subcapitata</i>
Chronic NOEC for Algae / Aquatic Plants	0.0403 mg/l <i>Pseudokirchneriella subcapitata</i>

2-OCTYL-2H-ISOTHIAZOL-3-ONE

EC50 - for Algae / Aquatic Plants	0.00129 mg/l/72h <i>Navicula pelliculosa</i>
EC10 for Algae / Aquatic Plants	0.000224 mg/l/72h <i>Navicula pelliculosa</i>

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish	0.19 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	0.16 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0.0052 mg/l/72h <i>Skeletonema costatum</i>
Chronic NOEC for Fish	0.02 mg/l <i>Danio rerio</i>
Chronic NOEC for Crustacea	0.1 mg/l <i>Daphnia magna</i>
Chronic NOEC for Algae / Aquatic Plants	0.00049 mg/l <i>Skeletonema costatum</i>

12.2. Persistence and degradability

TALC

Solubility in water	< 0.1 mg/l
---------------------	------------

TITANIUM DIOXIDE

Solubility in water	< 0.001 mg/l
Degradability: information not available	

1,2-BENZISOTHIAZOLIN-3-ONE

Solubility in water	1288 mg/l
Rapidly degradable	

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Solubility in water	500 mg/l
NOT rapidly degradable	

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Solubility in water	> 10000 mg/l
NOT rapidly degradable	

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 10 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 12. Ecological information ... / >>

CALCIUM CARBONATE

Solubility in water 0,1 - 100 mg/l

12.3. Bioaccumulative potential

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water 0.7
BCF 6.62

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: n-octanol/water 2.61
BCF 19.21

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Partition coefficient: n-octanol/water 0.75
BCF < 54

12.4. Mobility in soil

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: soil/water 0.97

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: soil/water 2.25

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 12 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 15. Regulatory information ... / >>

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Use descriptor system:

ERC 2	Formulation into mixture
ERC 8a	Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor)
ERC 8d	Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)
LCS C	Consumer use
LCS F	Formulation or repacking
LCS IS	Use at industrial sites
LCS M	Manufacture
LCS PW	Widespread use by professional workers
PC 9a	Coatings and paints, thinners, paint removers
PROC 10	Roller application or brushing
PROC 11	Non industrial spraying
PROC 13	Treatment of articles by dipping and pouring
PROC 5	Mixing or blending in batch processes
PROC 7	Industrial spraying
PROC 8a	Transfer of substance or mixture (charging and discharging) at non- dedicated facilities
PROC 8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC 9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
SU 19	Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in EESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 13 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 16. Other information ... / >

- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

ITALMONT S.R.L.

DIAMANT BASE BIANCA

Revision nr.2
Dated 10/11/2025
Printed on 10/11/2025
Page n. 14 / 14
Replaced revision:1 (Dated 10/11/2025)

SECTION 16. Other information ... / >>

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01.