



PRODUCT SPECIFICATIONS:

SUPER TRASPIRA

P1012.5




P1005

KGP1014

DESCRIPTION:

Super breathable water-based paint for interiors. It is characterized by good covering power. Easy to apply, it has excellent brushability and good yield. Ideal for indoor applications such as sheds and garages directly on concrete or after priming on plaster and old paint.

CHARACTERISTICS:

I WAIT	Opaque
SPECIFIC WEIGHT	P1012.5: 1.62 Kg/l \pm 0.05 at 20°C (KGP1014: 1.50 Kg/l \pm 0.05 at 20°C)
DRY RESIDUE	55 \pm 0.5 % w/w
WATER VAPOR PERMEABILITY	High
DIRT CATCHING	Low
COLOR	White (Can be colored with Universal Dyes)
DRYING (data referred to 20°C and 65% RH)	for recoating: 6 hours complete: 48 hours
PRACTICAL MAKE	9-11 m ² /L per coat depending on the absorption of the support
DILUTION	1 st hand: add 30% drinking water 2 nd hand: add 25% drinking water Airless spray: add between 30% and 40% drinking water. Recommended nozzles: LP419–LP519–LP619- LP421–LP521–LP621
TOOLS	 brush  Roller  spray
SUPPORTS	civil plaster, plasterboard, fiber cement, plastered walls

APPLICATION**SUBSTRATE PREPARATION**

The support must be healthy, dry, clean and consistent, free from humidity stains, traces of dirt, grease, mold, etc. Old inconsistent or flaking paint must be removed by brushing or sanding the surface. Imperfections, cracks, flaking, must be eliminated and filled with appropriate filler.

	NEW SUPPORTS				SUPPORTS ALREADY PAINTED			
	PLASTER	HANDS	DRYWALL	HANDS	BREATHABLE OR CHALKY	HANDS	WASHABLE WELL ANCHORED	HANDS
BOTTOM	JANTAR	1	REFUND	1	JANTAR	1		
FINISH	SUPER TRASPIRA	2	SUPER TRASPIRA	1	SUPER TRASPIRA	2	SUPER TRASPIRA	2

GENERAL WARNINGS

In order not to alter the typical breathable properties of the product, the quantity of base color must not exceed 20%. Store the product in a cool place and protect from frost. Do not apply the product with temperatures lower than 5° or higher than 30° centigrade, with relative humidity higher than 85% or on walls exposed to wind or sun.