Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 1 / 13

(AP)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name QUARZO BIANCO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Painting product

Identified Uses	Industrial	Professional	Consumer
paint product	SU: 19.	SU: 19.	SU: 19.
	ERC: 8a, 8d.	ERC: 8a, 8d.	ERC: 8a, 8d.
	PROC: 10, 11, 13, 7, 8b.	PROC: 10, 11, 13, 8a.	PROC: 10, 11, 13, 8a.
	PC: 9a.	PC: 9a.	PC: 9a.
	LCS: IS.	LCS: PW.	LCS: C.
paint product production	ERC: 2.		
	PROC: 5, 8b, 9.		
	PC: 9a.		
	LCS: F, M.		

1.3. Details of the supplier of the safety data sheet

Name ITALMONT S.R.L.
Full address VIA IV NOVEMBRE 13
District and Country 63078 Spinetoli

ITALIA

Tel. +39 0736 899238 Fax +39 0736 899489

e-mail address of the competent person

responsible for the Safety Data Sheet info@italmont.it

Supplier: ITALMONT S.R.L.

1.4. Emergency telephone number

For urgent inquiries refer to UE general number - 112 (Available 24h. Safety Data Sheets or Product information

could not available for emergency service)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210 Safety data sheet available on request.

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 2 / 13

SECTION 2. Hazards identification

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **EUH208**

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND

2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) 1,2-BENZISOTHIAZOLIN-3-ONE

May produce an allergic reaction.

Precautionary statements:

P501 Dispose of the product / container in accordance with local and national provisions

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

QUARTZ Contains:

VOC (Directive 2004/42/EC): Exterior walls of mineral substrate.

VOC given in g/litre of product in a ready-to-use condition : 7.94 Limit value: 40.00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification		Conc. %	Classification (EC) 1272/2008 (CLP)
CALCIUM CA	RBONATE		
INDEX		8.7	
EC	207-439-9		
CAS	471-34-1		
KAOLIN		7.04	
INDEX		7.24	
EC	4000 50 7		
CAS	1332-58-7		
TITANIUM DIC	JXIDE	7.04	
INDEX EC	236-675-5	7.24	
CAS	230-075-5 13463-67-7		
		17 VVVV	
REACH Reg. TALC	01-2119409379-	17-XXXX	
INDEX		4.35	
EC	238-877-9	4.33	
CAS	14807-96-6		
QUARTZ	14007-90-0		
INDEX		3.046	STOT RE 1 H372
EC	238-878-4	3.040	3101 RE 1 11372
CAS	14808-60-7		
	THIAZOLIN-3-ONE		
INDEX	613-088-00-6	0.011	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,
INDEX	070 000 00 0	0.011	Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC	220-120-9		Mi−1 Skin Sens. 1A H317: ≥ 0.036%
CAS	2634-33-5		LD50 Oral: 450 mg/kg, LC50 Inhalation mists/powders: 0.21 mg/l/4h
REACH Reg.	Biocida		EDOU OTAL 400 mg/kg, EDOU milalation mists/powders. 0.21 mg///411
,, .o, , , , , , , , , , , , , , , , , ,	5,00,00		

QUARZO BIANCO

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 3 / 13

SECTION 3. Composition/information on ingredients .../>>

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

INDEX 613-167-00-5 0.001 Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C

H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to

Annex VI to the CLP Regulation: B

EC Skin Corr. 1C H314: ≥ 0.6%, Skin Irrit. 2 H315: ≥ 0.06% - < 0.6%, Skin Sens.

1A H317: ≥ 0.0015%, Eye Dam. 1 H318: ≥ 0.6%, Eye Irrit. 2 H319: ≥ 0.06% - <

0.6%

CAS 55965-84-9 ATE Oral: 100 mg/kg, LD50 Dermal: 87.12 mg/kg, LC50 Inhalation

mists/powders: 0.171 mg/l/4h

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 4 / 13

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur
		Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 5 / 13

dla zdrowia w środowisku pracy

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru ROU România

modificarea și completarea hotărârii guvernului nr. 1.093/2006

EH40/2005 Workplace exposure limits (Fourth Edition 2020)
Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) GBR United Kingdom EU

OEL EU 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive

2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive

91/322/EEC.

TLV-ACGIH **ACGIH 2023**

				KAOLIN					
Threshold Limit Value									
Туре	Country	TWA/8h		STEL/15mir	1	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
VLA	ESP	2				RESP			
TGG	NLD	10							
NDS/NDSCh	POL	10				INHAL			
WEL	GBR	2				RESP			
TLV-ACGIH		2				RESP			

				TALC			
Threshold Limit \	/alue						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLA	ESP	2				RESP	
TGG	NLD	0.25				RESP	
NDS/NDSCh	POL	4				INHAL	
NDS/NDSCh	POL	1				RESP	
TLV	ROU	2					
WEL	GBR	1				RESP	
TLV-ACGIH		2				RESP	

TITANIUM DIOXIDE									
Threshold Limit Value									
Туре	Country	TWA/8h		STEL/15mir	า	Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm				
MAK	DEU	0.3		2.4		RESP Hinweis			
VLA	ESP	10							
VLEP	FRA	10							
NDS/NDSCh	POL	10				INHAL			
TLV	ROU	10		15					
WEL	GBR	10				INHAL			
WEL	GBR	4				RESP			
TLV-ACGIH		0.2				RESP			

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE								
	(3:1)							
Threshold Li	imit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	DEU	0.2		0.4		INHAL		

CALCIUM CARBONATE										
Threshold Limit \	Threshold Limit Value									
Type	Country	TWA/8h		STEL/15mi	n	Remarks / Observations				
		mg/m3	ppm	mg/m3	ppm					
VLEP	FRA	10								
NDS/NDSCh	POL	10				INHAL				
TLV-ACGIH		10				INHAL				
TLV-ACGIH		3				RESP				

QUARZO BIANCO

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 6 / 13

SECTION 8. Exposure controls/personal protection/>>

				QUARTZ			
Threshold Limit \	√alue						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
VLA	ESP		0.05			RESP	
VLEP	FRA	0.1				RESP	
VLEP	ITA	0.1				RESP	
TGG	NLD	0.075				RESP	
VLE	PRT	0.025				RESP	
NDS/NDSCh	POL	0.1				RESP	
TLV	ROU	0.1				RESP	
OEL	EU	0.1				RESP	
TLV-ACGIH		0.025				RESP	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR)

The following should be considered when choosing work glove material: compatibility, degradation, permeability time.

Thickness: 0.3 mm

Glove thickness must be selected based on the minimum required breakthrough time.

Breakthrough time: 30 min

Glove resistance depends on various elements, such as temperature and other environmental factors.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance Colour Odour Melting point / freezing point		Value dense liquid white mild not available		Information
Initial boiling point	>	100	°C	Substance:WATER Initial boiling point: 100 °C
Flammability Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature Decomposition temperature	>	not flammable not available not available 60 not available not available	°C	

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 7 / 13

SECTION 9. Physical and chemical properties .../>>

PH 8
Kinematic viscosity 0.03 m2/s
Solubility not available
Partition coefficient: n-octanol/water not available

Vapour pressure not available

Density and/or relative density 1.2 g/cm3

Relative vapour density not available Particle characteristics not applicable Method:pycnometer

Method:ph meter

Method:FORD CUP

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

CALCIUM CARBONATE Incompatible with: acids.

10.6. Hazardous decomposition products

CALCIUM CARBONATE

May develop: calcium oxides, carbon oxides.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 8 / 13

SECTION 11. Toxicological information .../>>

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

TALC

LC50 (Inhalation mists/powders): > 2.1 mg/l/4h Rat

TITANIUM DIOXIDE

LD50 (Oral): > 10000 mg/kg Rat

1,2-BENZISOTHIAZOLIN-3-ONE

 LD50 (Dermal):
 > 2000 mg/kg Rat

 LD50 (Oral):
 450 mg/kg Rat

 LC50 (Inhalation mists/powders):
 0.21 mg/l/4h

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LD50 (Dermal): 87.12 mg/kg Rabbit LD50 (Oral): 457 mg/kg Rat LC50 (Inhalation mists/powders): 0.171 mg/l/4h Rat

CALCIUM CARBONATE

LD50 (Oral): 6450 mg/kg Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) 1,2-BENZISOTHIAZOLIN-3-ONE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TALC

Overall IARC evaluation: Perineal use of talc-based body powder is possibly carcinogenic to humans (Group2B). Inhaled talc not containing asbestos or asbestiform fibres is not classifiable as to its carcinogenicity (Group 3).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 9 / 13

SECTION 11. Toxicological information .../>>

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-BENZISOTHIAZOLIN-3-ONE

LC50 - for Fish 2.15 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 2.9 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

0.11 mg/l/72h Pseudokirchneriella subcapitata

Chronic NOEC for Algae / Aquatic Plants

0.0403 mg/l Pseudokirchneriella subcapitata

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish 0.19 mg/l/96h Oncorhynchus mykiss EC50 - for Crustacea 0.16 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0.0052 mg/l/72h Skeletonema costatum

Chronic NOEC for Fish

0.02 mg/l Danio rerio
Chronic NOEC for Crustacea

0.1 mg/l Daphnia magna

Chronic NOEC for Algae / Aquatic Plants 0.00049 mg/l Skeletonema costatum

12.2. Persistence and degradability

TALC

Solubility in water < 0.1 mg/l

TITANIUM DIOXIDE

Solubility in water < 0.001 mg/l

Degradability: information not available

1,2-BENZISOTHIAZOLIN-3-ONE

Solubility in water 1288 mg/l

Rapidly degradable

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Solubility in water > 10000 mg/l

NOT rapidly degradable

CALCIUM CARBONATE

Solubility in water 0,1 - 100 mg/l

12.3. Bioaccumulative potential

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water 0.7 BCF 6.62

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Partition coefficient: n-octanol/water 0.75 BCF < 54

12.4. Mobility in soil

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: soil/water 0.97

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 10 / 13

SECTION 12. Ecological information .../>>

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point

75

AMMONIA

REACH Reg.: 01-2119982985-14-XXXX

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 11 / 13

SECTION 15. Regulatory information .../>>

Point 75 TITANIUM DIOXIDE

REACH Reg.: 01-2119489379-17-XXXX

Point 75 REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND

2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Point 75 CALCIUM CARBONATE

 Point
 75
 2-(2-BUTOXYETHOXY)ETHANOL

 REACH Reg.: 01-2119475104-44-XXXX

 Point
 75
 1,2-BENZISOTHIAZOLIN-3-ONE

REACH Reg.: Biocida

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC):

Exterior walls of mineral substrate.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2 Acute toxicity, category 2
Acute Tox. 3 Acute toxicity, category 3
Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Skin Corr. 1C
Skin Corr. 1
Skin corrosion, category 1C
Skin corrosion, category 1
Eye Dam. 1
Serious eye damage, category 1
Eye Irrit. 2
Skin Irrit. 2
Skin irritation, category 2
Skin Sens. 1A
Skin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H310 Fatal in contact with skin.
H330 Fatal if inhaled.
H301 Toxic if swallowed.
H302 Harmful if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.
EUH210 Safety data sheet available on request.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 12 / 13

SECTION 16. Other information .../>>

Use descriptor system:

ERC 2 Formulation into mixture

ERC 8a Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor)
 ERC 8d Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)

LCS C Consumer use

LCSFFormulation or repackingLCSISUse at industrial sites

LCS M Manufacture

LCS PW Widespread use by professional workersPC 9a Coatings and paints, thinners, paint removers

PROC 10 Roller application or brushing
PROC 11 Non industrial spraying

PROC 13 Treatment of articles by dipping and pouring
PROC 5 Mixing or blending in batch processes

PROC 7 Industrial spraying

PROC 8a Transfer of substance or mixture (charging and discharging) at non- dedicated facilities
PROC 8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

SU 19 Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- $\hbox{-}\, {\sf TLV}\, {\sf CEILING:}\, {\sf Concentration}\, \, {\sf that}\, \, {\sf should}\, \, {\sf not}\, \, {\sf be}\, \, {\sf exceeded}\, \, {\sf during}\, \, {\sf any}\, \, {\sf time}\, \, {\sf of}\, \, {\sf occupational}\, \, {\sf exposure}.$
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)

Revision nr.1 Dated 02/06/2025 First compilation Printed on 02/06/2025 Page n. 13 / 13

SECTION 16. Other information .../>>

- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.