



Created: 12/15/2019
Rev.1: 04/05/2023

PRODUCT TECHNICAL AND SAFETY DATA SHEET:

RETITAN

RETITAN12.5




RETITAN5



DESCRIPTION:

Water-repellent, breathable and anti-mold paint for interiors. It is characterized by good covering power and a good white point. Easy to apply, it has excellent brushability and a good yield. Suitable for kitchens, bathrooms and in general for rooms subject to the formation of condensation and mold.

CHARACTERISTICS:

I WAIT	Opaque
SPECIFIC WEIGHT	1.58 Kg/l \pm 0.03 at 20°C
DRY RESIDUE	67 \pm 0.5 % w/w
WASHING RESISTANCE	Average
WATER VAPOR PERMEABILITY	High
DIRT GRIP	Low
COLOR	White (Colourable with Universal Dyes)
DRYING	for covering: 6 hours
(data referred to 20°C and 65% RH)	complete: 48 hours
PRACTICAL YIELD	11-13 m ² /L per coat
	depending on the absorption of the support
	1st coat: add 30% drinking water
DILUTION	2nd coat: add 25% drinking water
	spray: add between 30% and 40% of drinking water. Recommended nozzles: LP419-LP519-LP619- LP421-LP521-LP624
TOOLS	 brush  roller  spray
SUPPORTS	civil plaster, plasterboard, fibre cement, stuccoed walls

APPLICATION

PREPARATION OF THE SUPPORT

The substrate must be healthy, dry, clean and consistent, free from damp stains, traces of dirt, grease, mold, etc. Old inconsistent or flaking paint must be removed by brushing or sanding the surface. Imperfections, cracks, flaking must be eliminated and filled with an appropriate filler.

	NEW SUPPORTS				ALREADY PAINTED SUPPORTS			
	PLASTER	HANDS	PLASTERBOARD	HANDS	BREATHABLE OR CRUMBLING	HANDS	WASHABLE WELL ANCHORED	HANDS
CLEANSING	RE23	1	RE23	1	RE23	1	RE23	1
FUND	JANTAR	1	BACKGROUND	1	JANTAR	1	JANTAR	1
FINISH	TITAN	2	TITAN	1	TITAN	2	TITAN	2

GENERAL WARNINGS

In order not to alter the typical breathable properties of the product, the quantity of base dye must not exceed 20%. Store the product in a cool place and protect from frost. Do not apply the product at temperatures below 5° or above 30° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.