

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 1 / 14
Replaced revision:1 (Dated 23/04/2025)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RETITAN base bianca

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Painting product

Identified Uses	Industrial	Professional	Consumer
paint product	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 7, 8b. PC: 9a. LCS: IS.	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 8a. PC: 9a. LCS: PW.	SU: 19. ERC: 8a, 8d. PROC: 10, 11, 13, 8a. PC: 9a. LCS: C.
paint product production	ERC: 2. PROC: 5, 8b, 9. PC: 9a. LCS: F, M.	-	-

1.3. Details of the supplier of the safety data sheet

Name ITALMONT S.R.L.
Full address VIA IV NOVEMBRE 13
District and Country 63078 Spinetoli (AP)
ITALIA
Tel. +39 0736 899238
Fax +39 0736 899489
e-mail address of the competent person responsible for the Safety Data Sheet info@italmont.it
Supplier: ITALMONT S.R.L.

1.4. Emergency telephone number

For urgent inquiries refer to UE general number - 112 (Available 24h. Safety Data Sheets or Product information could not available for emergency service)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal word: --

Hazard statements:
EUH210 Safety data sheet available on request.

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2

Dated 10/01/2026

Printed on 20/01/2026

Page n. 2 / 14

Replaced revision:1 (Dated 23/04/2025)

SECTION 2. Hazards identification ... / >>

EUH208

Contains:

2-OCTYL-2H-ISOTHIAZOL-3-ONE
4,5-dicloro-2-ottil-2H-isotiazol-3-one
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND
2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
1,2-BENZISOTHIAZOLIN-3-ONE
May produce an allergic reaction.

Precautionary statements:

P501

P102

P101

Dispose of the product / container in accordance with local and national provisions
Keep out of reach of children.
If medical advice is needed, have product container or label at hand.

VOC (Directive 2004/42/EC) :

Interior matt walls and ceilings (Gloss < 25@60°).

VOC given in g/litre of product in a ready-to-use condition :

Limit value:

6.27

30.00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	Conc. %	Classification (EC) 1272/2008 (CLP)
CALCIUM CARBONATE		
INDEX	44.09	
EC	207-439-9	
CAS	471-34-1	
TITANIUM DIOXIDE		
INDEX	8.76	
EC	236-675-5	
CAS	13463-67-7	
REACH Reg.	01-2119489379-17-XXXX	
TALC		
INDEX	4.38	
EC	238-877-9	
CAS	14807-96-6	
1,2-BENZISOTHIAZOLIN-3-ONE		
INDEX	613-088-00-6	0.00611
EC	220-120-9	
CAS	2634-33-5	
REACH Reg.	Biocida	
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)		
INDEX	613-167-00-5	0.00146
EC		
CAS	55965-84-9	
2-OCTYL-2H-ISOTHIAZOL-3-ONE		
INDEX	613-112-00-5	0.000950
EC	247-761-7	

Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315,
Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410
M=1
Skin Sens. 1A H317: ≥ 0.036%
LD50 Oral: 450 mg/kg, LC50 Inhalation mists/powders: 0.21 mg/l/4h

Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C
H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100,
Aquatic Chronic 1 H410 M=100, EUH071, Classification note according to
Annex VI to the CLP Regulation: B
Skin Corr. 1C H314: ≥ 0.6%, Skin Irrit. 2 H315: ≥ 0.06% - < 0.6%, Skin Sens.
1A H317: ≥ 0.0015%, Eye Dam. 1 H318: ≥ 0.6%, Eye Irrit. 2 H319: ≥ 0.06% - <
0.6%
ATE Oral: 100 mg/kg, LD50 Dermal: 87.12 mg/kg, LC50 Inhalation
mists/powders: 0.171 mg/l/4h

Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1 H314,
Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100,
Aquatic Chronic 1 H410 M=100, EUH071
Skin Sens. 1A H317: ≥ 0.0015%

EPY 12.1.0 - SDS 1004.14

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 3 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 3. Composition/information on ingredients ... / >>

CAS 26530-20-1

REACH Reg. Biocida

4,5-dicloro-2-ottil-2H-isotiazol-3-one

INDEX 613-335-00-8 0.000950

EC 264-843-8

CAS 64359-81-5

LD50 Oral: 125 mg/kg, LD50 Dermal: 311 mg/kg, LC50 Inhalation mists/powders: 0.27 mg/l/4h

Acute Tox. 1 H330, Acute Tox. 4 H302, Skin Corr. 1 H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071

Skin Sens. 1A H317: $\geq 0.0015\%$

ATE Oral: 500 mg/kg, ATE Inhalation mists/powders: 0.005 mg/l, ATE

Inhalation vapours: 0.05 mg/l

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

ITALMONT S.R.L.		Revision nr.2 Dated 10/01/2026 Printed on 20/01/2026 Page n. 4 / 14 Replaced revision:1 (Dated 23/04/2025)
RETITAN base bianca		
<p>Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.</p> <p>SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS</p> <p>Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).</p>		
SECTION 6. Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
<p>Block the leakage if there is no hazard.</p> <p>Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.</p>		
6.2. Environmental precautions		
<p>The product must not penetrate into the sewer system or come into contact with surface water or ground water.</p>		
6.3. Methods and material for containment and cleaning up		
<p>Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.</p> <p>Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.</p>		
6.4. Reference to other sections		
<p>Any information on personal protection and disposal is given in sections 8 and 13.</p>		
SECTION 7. Handling and storage		
7.1. Precautions for safe handling		
<p>Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.</p>		
7.2. Conditions for safe storage, including any incompatibilities		
<p>Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.</p>		
7.3. Specific end use(s)		
<p>Information not available</p>		
SECTION 8. Exposure controls/personal protection		
8.1. Control parameters		
Regulatory references:		
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr. 2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția
EPY 12.1.0 - SDS 1004.14		

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 5 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 8. Exposure controls/personal protection ... / >>

GBR United Kingdom lucrătorilor împotriva riscurilor legate de expunerea la agenți ca
ACGIH EH40/2005 Workplace exposure limits (Fourth Edition 2020)
ACGIH 2025

TALC

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLA	ESP	2				RESP
TGG	NLD	0.25				RESP
NDS/NDSch	POL	4				INHAL
NDS/NDSch	POL	1				RESP
TLV	ROU	2				
WEL	GBR	1				RESP
ACGIH		2				RESP

TITANIUM DIOXIDE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
MAK	DEU	0.3		2.4		RESP Hinweis
VLA	ESP	10				
VLEP	FRA	10				
NDS/NDSch	POL	10				INHAL
TLV	ROU	10		15		
WEL	GBR	10				INHAL
WEL	GBR	4				RESP
ACGIH		0.2				RESP

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
AGW	DEU	0.05		0.1		INHAL
AGW	DEU	0.05		0.1		SKIN
MAK	DEU	0.05		0.1		INHAL
MAK	DEU	0.05		0.1		SKIN

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE

(3:1)

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
MAK	DEU	0.2		0.4		INHAL
NDS/NDSch	POL	0.2		0.4		SKIN

CALCIUM CARBONATE

Threshold Limit Value

Type	Country	TWA/8h mg/m3	ppm	STEL/15min mg/m3	ppm	Remarks / Observations
VLEP	FRA	10				
NDS/NDSch	POL	10				INHAL
ACGIH		10				INHAL
ACGIH		3				RESP

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 6 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 8. Exposure controls/personal protection ... / >>

time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:
Material: Nitrile rubber (NBR)
Thickness: 0.3 mm
Glove thickness must be selected based on the minimum required breakthrough time.
Breakthrough time: 30 min
Glove resistance depends on various elements, such as temperature and other environmental factors.

SKIN PROTECTION
Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION
Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS
The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	dense liquid	
Colour	white	
Odour	mild	
Melting point / freezing point	not available	
Initial boiling point	> 100 °C	Substance:WATER Initial boiling point: 100 °C
Flammability	not flammable	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	> 60 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	8	Method:ph meter
Kinematic viscosity	0.03 m2/s	Method:FORD CUP
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1.2 g/cm3	Method:pycnometer
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

EPY 12.1.0 - SDS 1004.14

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 7 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

CALCIUM CARBONATE

Decomposes at temperatures above 800°C/1472°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

CALCIUM CARBONATE

Incompatible with: acids.

10.6. Hazardous decomposition products

CALCIUM CARBONATE

May develop: calcium oxides, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

CALCIUM CARBONATE

LD50 (Oral):

6450 mg/kg Rat

TITANIUM DIOXIDE

LD50 (Oral):

> 10000 mg/kg Rat

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 8 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 11. Toxicological information ... / >>

TALC
LC50 (Inhalation mists/powders): > 2.1 mg/l/4h Rat

1,2-BENZISOTHIAZOLIN-3-ONE
LD50 (Dermal): > 2000 mg/kg Rat
LD50 (Oral): 450 mg/kg Rat
LC50 (Inhalation mists/powders): 0.21 mg/l/4h

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
LD50 (Dermal): 87.12 mg/kg Rabbit
LD50 (Oral): 457 mg/kg Rat
LC50 (Inhalation mists/powders): 0.171 mg/l/4h Rat

2-OCTYL-2H-ISOTHIAZOL-3-ONE
LD50 (Dermal): 311 mg/kg
LD50 (Oral): 125 mg/kg Rat
LC50 (Inhalation mists/powders): 0.27 mg/l/4h Rat

4,5-dicloro-2-ottil-2H-isotiazol-3-one
LD50 (Dermal): 5000 mg/kg
LD50 (Oral): 5000 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

2-OCTYL-2H-ISOTHIAZOL-3-ONE

4,5-dicloro-2-ottil-2H-isotiazol-3-one

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

1,2-BENZISOTHIAZOLIN-3-ONE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TALC

Overall IARC evaluation: Perineal use of talc-based body powder is possibly carcinogenic to humans (Group2B). Inhaled talc not containing asbestos or asbestiform fibres is not classifiable as to its carcinogenicity (Group 3).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 9 / 14
Replaced revision:1 (Dated 23/04/2025)

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-BENZISOTHIAZOLIN-3-ONE	
LC50 - for Fish	2.15 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	2.9 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0.11 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Algae / Aquatic Plants	0.0403 mg/l Pseudokirchneriella subcapitata

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LC50 - for Fish	0.19 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	0.16 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	0.0052 mg/l/72h Skeletonema costatum
Chronic NOEC for Fish	0.02 mg/l Danio rerio
Chronic NOEC for Crustacea	0.1 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants	0.00049 mg/l Skeletonema costatum

2-OCTYL-2H-ISOTHIAZOL-3-ONE

EC50 - for Algae / Aquatic Plants	0.00129 mg/l/72h Navicula pelliculosa
EC10 for Algae / Aquatic Plants	0.000224 mg/l/72h Navicula pelliculosa

4,5-dicloro-2-ottil-2H-isotiazol-3-one

LC50 - for Fish	0.0078 mg/l/96h
EC50 - for Crustacea	0.0097 mg/l/48h
EC50 - for Algae / Aquatic Plants	0.025 mg/l/72h
Chronic NOEC for Crustacea	0.0004 mg/l
Chronic NOEC for Algae / Aquatic Plants	0.015 mg/l

12.2. Persistence and degradability

CALCIUM CARBONATE

Solubility in water	0,1 - 100 mg/l
---------------------	----------------

TITANIUM DIOXIDE

Solubility in water	< 0.001 mg/l
Degradability: information not available	

TALC

Solubility in water	< 0.1 mg/l
---------------------	------------

1,2-BENZISOTHIAZOLIN-3-ONE

Solubility in water	1288 mg/l
Rapidly degradable	

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Solubility in water	> 10000 mg/l
NOT rapidly degradable	

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Solubility in water	500 mg/l
NOT rapidly degradable	

12.3. Bioaccumulative potential

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: n-octanol/water	0.7
BCF	6.62

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 10 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 12. Ecological information ... / >>

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

Partition coefficient: n-octanol/water 0.75

BCF < 54

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: n-octanol/water 2.61

BCF 19.21

12.4. Mobility in soil

1,2-BENZISOTHIAZOLIN-3-ONE

Partition coefficient: soil/water 0.97

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: soil/water 2.25

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 11 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 14. Transport information ... / >>

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point	75	TITANIUM DIOXIDE REACH Reg.: 01-2119489379-17-XXXX
Point	75	GLYOXAL
Point	75	2-(2-BUTOXYETHOXY)ETHANOL REACH Reg.: 01-2119475104-44-XXXX
Point	75	1,2-BENZISOTHIAZOLIN-3-ONE REACH Reg.: Biocida
Point	75	3-iodo-2-propynyl butylcarbamate
Point	75	REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
Point	75	CALCIUM CARBONATE

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC):

Interior matt walls and ceilings (Gloss < 25@60°).

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 1	Acute toxicity, category 1
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 12 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 16. Other information ... / >>

Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
H330	Fatal if inhaled.
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

Use descriptor system:

ERC	2	Formulation into mixture
ERC	8a	Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor)
ERC	8d	Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)
LCS	C	Consumer use
LCS	F	Formulation or repacking
LCS	IS	Use at industrial sites
LCS	M	Manufacture
LCS	PW	Widespread use by professional workers
PC	9a	Coatings and paints, thinners, paint removers
PROC	10	Roller application or brushing
PROC	11	Non industrial spraying
PROC	13	Treatment of articles by dipping and pouring
PROC	5	Mixing or blending in batch processes
PROC	7	Industrial spraying
PROC	8a	Transfer of substance or mixture (charging and discharging) at non- dedicated facilities
PROC	8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC	9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
SU	19	Building and construction work

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006

ITALMONT S.R.L.

RETITAN base bianca

Revision nr.2
Dated 10/01/2026
Printed on 20/01/2026
Page n. 13 / 14
Replaced revision:1 (Dated 23/04/2025)

SECTION 16. Other information ... / >>

- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

SECTION 16. Other information ... / >>

02 / 03 / 08 / 11 / 12 / 15.