



Created 01/03/2013
Rev. 2 – 12/09/2019
Rev. 3 – 06/06/2024

PRODUCT TECHNICAL AND SAFETY DATA SHEET:

LAVABILE






Code: **LAVABILE12.5** **LAVABILE12.5BO**

DESCRIPTION:

Water-based wall finishing paint with excellent resistance to washing, slightly breathable for interiors, characterized by good covering power and good white point. It has excellent brushability and excellent yield, it differs from normal water-based paints for its particular velvety appearance, which enhances the quality of the finish, enhancing the environments where it is applied. Easy to apply, it allows both private and professional users to obtain finishes with a high aesthetic appearance.

CHARACTERISTICS:

I WAIT	Opaque
SPECIFIC WEIGHT	WHITE - 1.52 Kg/l \pm 0.03 at 20°C BASE BO - 1.44 Kg/l \pm 0.03 at 20°C
DRY RESIDUE	52 \pm 0.5 % w/w
WASHING RESISTANCE	High
WATER VAPOR PERMEABILITY	Low
DIRT GRIP	Low
COLOR	White (Colourable with Universal Dyes)
DRYING	for covering: 6 hours
(data referred to 20°C and 65% RH)	complete: 48 hours
PRACTICAL YIELD	9-13 m ² /L per coat depending on the absorption of the support 1st coat: add 10% drinking water – Base BO 0% 2nd coat: add max 5% of drinking water – Base BO 0% BO base to be used only after adding colorant. Airless spray: add between 20% and 30% of drinking water. Recommended tips: LP419-LP519-LP619- LP421-LP521-LP624
TOOLS	 brush  roller  spray
SUPPORTS	civil plaster, plasterboard, fibre cement, stuccoed walls

APPLICATION

PREPARATION OF THE SUPPORT

The substrate must be healthy, dry, clean and consistent, free from damp stains, traces of dirt, grease, mold, etc. Old inconsistent or flaking paint must be removed by brushing or sanding the surface. Imperfections, cracks, flaking must be eliminated and filled with an appropriate filler.

NEW SUPPORTS

ALREADY PAINTED SUPPORTS

	PLASTER	HANDS	PLASTERBOARD	HANDS	BREATHABLE OR CRUMBLING	HANDS	WASHABLE WELL ANCHORED	HANDS
FUND	JANTAR	1	BACKGROUND	1	JANTAR	1		
FINISH	LABABLE	2	WASHABLE	1 or 2	WASHABLE	2	WASHABLE	2

GENERAL WARNINGS

In order not to alter the typical breathable properties of the product, the quantity of base dye must not exceed 20%. Store the product in a cool place and protect from frost. Do not apply the product at temperatures below 5° or above 30° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.