



TYRKYS




TYRKYS5

TYRKYS12.5

DESCRIPTION:

Breathable water-based paint for interiors, characterized by good hiding power and good white point. Easy to apply, it has a good brushability excellent to use even with a roller and a good yield.

FEATURES:

ASPECT	Opaque
OWN WEIGHT	TYRKYS: 1,54 Kg/l \pm 0,05 a 20°C
DRY RESIDUE	57 \pm 0,5 % p/p
WASHING RESISTANCE	POOR
PERMEABILITY TO WATER VAPOUR	Loud
DIRT GRIP	Low
COLORE	White (Colorable with Universal Dyes)
DRYING (data referring to 20°C and 65% R.H.)	for cover: 6 hours Full: 48 hours
PRACTICAL YIELD	8-10 m ² /L per coat depending on the absorption of the support
DILUTION	1st hand: add 35% drinking water 2nd hand: add 30% drinking water
PARAPHERNALIA	 brush  roller  spray
SUPPORTI	civil plaster, plasterboard, fiber cement, stucco shaved walls

APPLICATION

MEDIA PREPARATION

The substrate must be healthy, dry, clean and consistent, free from moisture stains, traces of dirt, grease, mold, etc. Old inconsistent or chalking paints must be removed by brushing or sanding the surface. Imperfections, cracks, peeling, must be eliminated and puttied with appropriate putty.

	NEW MEDIA				SUPPORTS ALREADY PAINTED			
	PLASTER	HANDS	PLASTERBOARD	HANDS	BREATHABLE OR CHALKING	HANDS	WASHABLE WELL ANCHORED	HANDS
BOTTOM	JANTAR	1	REFONDO	1	JANTAR	1		
FINISH	TYRKYS	2	TYRKYS	1	TYRKYS	2	TYRKYS	2

GENERAL WARNINGS

In order not to alter the breathable properties typical of the product, the amount of base color must not exceed 20%. Keep the product cool and preserve from frost. Donot apply the product with temperatures below 5 ° or above 30 ° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.