



SUPER TRASPIRA

P1012.5




P1005

KGP1014

DESCRIPTION:

Super breathable water-based paint for interiors. It is characterized by good covering power. Easy to apply, it has excellent brushability and a good yield.

FEATURES:

| | |
|---|--|
| ASPECT | Opaque |
| OWN WEIGHT | P1014: 1,61 Kg/l \pm 0,05 a 20°C (KGP1014: 1,50 Kg/l \pm 0,05 a 20°C) |
| DRY RESIDUE | 55 \pm 0,5 % p/p |
| PERMEABILITY TO WATER VAPOR | Loud |
| DIRT GRIP | Low |
| COLOR | White (Colorable with Universal Dyes) |
| DRYING (data referring to 20°C and 65% R.H.) | per cover: 6 hours Full: 48 hours |
| PRACTICAL YIELD | 7-9 m ² /L per coat depending on the absorption of the support |
| DILUTION | 1st hand: add 30% drinking water 2nd hand: add 25% drinking water |
| PARAPHERNALIA |  brush  Roller  spray |
| MEDIA | civil plaster, plasterboard, fiber cement, stucco shaved walls |

APPLICATION

MEDIA PREPARATION

The substrate must be healthy, dry, clean and consistent, free from moisture stains, traces of dirt, grease, mold, etc. Old inconsistent or chalking paints must be removed by brushing or sanding the surface. Imperfections, cracks, peeling, must be eliminated and puttied with appropriate putty.

| | NEW MEDIA | | | | SUPPORTS ALREADY PAINTED | | | |
|--------|-------------------|-------|-------------------|-------|--------------------------|-------|------------------------------|-------|
| | PLASTER | HANDS | PLASTERBOARD | HANDS | BREATHABLE OR CHALKING | HANDS | WASHABLE WELL ANCHORED | HANDS |
| BOTTOM | JANTAR | 1 | REFONDO | 1 | JANTAR | 1 | | |
| FINISH | SUPER TRASPIRA | 2 | SUPER TRASPIRA | 1 | SUPER TRASPIRA | 2 | SUPER TRASPIRA | 2 |

GENERAL WARNINGS

In order not to alter the breathable properties typical of the product, the amount of base color must not exceed 20%. Keep the product cool and preserve from frost. Donot apply the product with temperatures below 5 ° or above 30 ° centigrade, with relative humidity above 85% or on walls exposed to wind or sun.