

A5: Relational schema, validation and schema refinement

Our project, answerly, is a web application for collaborative questions and answers.

This artifact contains the Relational Schema obtained by mapping from the Conceptual Data Model. The Relational Schema includes the relation schema, attributes, domains, primary keys, foreign keys and other integrity rules: UNIQUE, DEFAULT, NOT NULL, CHECK

1. Relational Schema

Relation Reference	Relation Compact Notation
R01	user(id , first_name <i>NN</i> , last_name <i>NN</i> , email <i>UK NN</i> , bio, username <i>UK NN</i> , password <i>NN</i> , score <i>NN DF 0</i>)
R02	label(id , name <i>NN</i>)
R03	notification(id , content <i>NN</i> , date <i>DF Now NN</i> , viewed <i>DF False NN</i> , user_id → user <i>NN</i>)
R04	user_management(id , status <i>NN DF user CK status IN UserStatus</i> , date_last_changed <i>NN DF Now</i> , user_id → user <i>UK NN</i>)
R05	vote(id , vote <i>NN</i> , user_id → user <i>NN</i> , question_id → question, answer_id → answer <i>CK question_id = NN XOR answer_id = NN</i>)
R06	question(id , user_id → user <i>NN</i> , title <i>NN</i> , description <i>NN</i> , nr_likes <i>NN DF 0</i> , nr_dislikes <i>NN DF 0 CK nr_likes >= 0 AND nr_dislikes >= 0</i> , question_date <i>NN DF Now</i>)
R07	answer(id , user_id → user <i>NN</i> , question_id → question <i>NN</i> , answer_date <i>NN DF Now</i> , content <i>NN</i> , nr_likes <i>NN DF 0</i> , nr_dislikes <i>NN DF 0 CK nr_likes >= 0 AND nr_dislikes >= 0</i> , marked_answer <i>NN DF FALSE</i>)
R08	comment(id , user_id → user <i>NN</i> , question_id → question, answer_id → answer <i>CK question_id = NN XOR answer_id = NN</i> , content <i>NN</i> , comment_date <i>NN DF Now</i>)
R09	report(id , reporter_id → user <i>NN</i> , user_id → user, question_id → question, answer_id → answer, comment_id → comment <i>CK user_id = NN XOR question_id = NN XOR answer_id = NN XOR comment_id = NN</i>)
R10	report_status(id , report_id → report <i>ODC NN</i> , state <i>NN DF unresolved CK state IN ReportStates</i> , comment, responsible_user → user <i>NN ODC</i>)
R11	question_following(user_id → user, question_id → question)
R12	label_following(user_id → user, label_id → label)
R13	question_label(question_id → question, label_id → label)

- UK means UNIQUE KEY

- NN means NOT NULL
- DF means DEFAULT
- CK means CHECK
- ODC means ON DELETED CASCADE

2. Domains

Specification of additional domains:

Domain Name	Domain Specification
Now	DATE DEFAULT CURRENT_TIMESTAMP_
ReportStates	ENUM ('unresolved', 'reviewing', 'resolved')
UserStatus	ENUM ('user', 'moderator', 'administrator', 'banned')

3. Functional Dependencies and schema validation

In the following tables, all relations are in the Boyce-Codd Normal Form, since for each non trivial functional dependency $A \rightarrow B$, A is a (super)key of the relation.

Table R01 (user)

Keys: {id}, {username}, {email}	
Functional Dependencies	
FD0101	{id} \rightarrow {first_name, last_name, email, bio, username, password, score}
FD0102	{username} \rightarrow {id, first_name, last_name, email, bio, password, score}
FD0103	{email} \rightarrow {id, first_name, last_name, bio, username, password, score}
NORMAL FORM	BCNF

Table R02 (label)

Keys: {id}	
Functional Dependencies	
FD0201	{id} \rightarrow {name}
NORMAL FORM	BCNF

Table R03 (notification)

Keys: {id}	
Functional Dependencies	
FD0301	{id} \rightarrow {content, date, viewed, user_id}
NORMAL FORM	BCNF

Table R04 (user_management)**Keys:** {id}**Functional Dependencies**

FD0401 {id} → {status, date_last_changed, user_id}

NORMAL FORM BCNF**Table R05 (vote)****Keys:** {id}**Functional Dependencies**

FD0501 {id} → {vote, user_id, question_id, answer_id}

NORMAL FORM BCNF**Table R06 (question)****Keys:** {id}**Functional Dependencies**

FD0601 {id} → {user_id, title, description, nr_likes, nr_dislikes, question_date}

NORMAL FORM BCNF**Table R07 (answer)****Keys:** {id}**Functional Dependencies**

FD0701 {id} → {user_id, question_id, answer_date, content, nr_likes, nr_dislikes, marked_answer}

NORMAL FORM BCNF**Table R08 (comment)****Keys:** {id}**Functional Dependencies**

FD0801 {id} → {user_id, question_id, answer_id, content, comment_date}

NORMAL FORM BCNF**Table R09 (report)****Keys:** {id}

Table R09 (report)**Functional Dependencies**

FD0901 {id} → {reporter_id, user_id, question_id, answer_id, comment_id}

NORMAL FORM BCNF**Table R10 (report_status)****Keys:** {id}**Functional Dependencies**

FD1001 {id} → {report_id, state, comment, responsible_user}

NORMAL FORM BCNF**Table R11 (question_following)****Keys:** {user_id, question_id}**Functional Dependencies**

(none)

NORMAL FORM BCNF**Table R12 (label_following)****Keys:** {user_id, label_id}**Functional Dependencies**

(none)

NORMAL FORM BCNF**Table R13 (question_label)****Keys:** {question_id, label_id}**Functional Dependencies**

(none)

NORMAL FORM BCNF

4. SQL Code

```

-----
-- Drop old schmemma
-----

```

```

DROP TABLE IF EXISTS "user" CASCADE;
DROP TABLE IF EXISTS label CASCADE;
DROP TABLE IF EXISTS notification CASCADE;
DROP TABLE IF EXISTS user_management CASCADE;
DROP TABLE IF EXISTS question CASCADE;
DROP TABLE IF EXISTS answer CASCADE;
DROP TABLE IF EXISTS comment CASCADE;
DROP TABLE IF EXISTS vote CASCADE;
DROP TABLE IF EXISTS report CASCADE;
DROP TABLE IF EXISTS report_status CASCADE;
DROP TABLE IF EXISTS question_following CASCADE;
DROP TABLE IF EXISTS label_following CASCADE;
DROP TABLE IF EXISTS question_label CASCADE;

-----
-- Tables
-----

-- Table: user
CREATE TABLE "user" (
    id                SERIAL                PRIMARY KEY,
    first_name        TEXT                  NOT NULL,
    last_name         TEXT                  NOT NULL,
    email             TEXT                  NOT NULL UNIQUE,
    bio               TEXT,
    username          TEXT                  NOT NULL UNIQUE,
    password          TEXT                  NOT NULL,
    score             INTEGER               NOT NULL DEFAULT 0
);

-- Table: label
CREATE TABLE label (
    id                SERIAL                PRIMARY KEY,
    name              TEXT                  NOT NULL
);

-- Table: notification
CREATE TABLE notification (
    id                SERIAL                PRIMARY KEY,
    content           TEXT                  NOT NULL,
    date              DATE                  DEFAULT 'Now' NOT NULL,
    viewed            BOOLEAN               DEFAULT FALSE NOT NULL,
    user_id           INTEGER               REFERENCES "user" (id) NOT NULL
);

-- Table: user_management
CREATE TABLE user_management (
    id                SERIAL                PRIMARY KEY,
    status            TEXT                  DEFAULT 'user' NOT NULL,
    date_last_changed DATE                  DEFAULT 'Now' NOT NULL,
    user_id           INTEGER               REFERENCES "user" (id) NOT NULL
UNIQUE,
CHECK (
    status = 'user' OR status = 'moderator' OR status = 'administrator'
);

```

```
OR status = 'banned'
    )
);

-- Table: question
CREATE TABLE question (
    id SERIAL PRIMARY KEY,
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    title TEXT NOT NULL,
    description TEXT NOT NULL,
    nr_likes INTEGER DEFAULT 0 NOT NULL,
    nr_dislikes INTEGER DEFAULT 0 NOT NULL,
    question_date DATE DEFAULT 'Now' NOT NULL,
    CHECK (
        nr_likes >= 0 AND nr_dislikes >= 0
    )
);

-- Table: answer
CREATE TABLE answer (
    id SERIAL PRIMARY KEY,
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    question_id INTEGER REFERENCES "question" (id) NOT NULL,
    answer_date DATE DEFAULT 'Now' NOT NULL,
    content TEXT NOT NULL,
    nr_likes INTEGER DEFAULT 0 NOT NULL,
    nr_dislikes INTEGER DEFAULT 0 NOT NULL,
    marked_answer BOOLEAN DEFAULT FALSE NOT NULL,
    CHECK (
        nr_likes >= 0 AND nr_dislikes >= 0
    )
);

-- Table: comment
CREATE TABLE comment (
    id SERIAL PRIMARY KEY,
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    question_id INTEGER REFERENCES "question" (id),
    answer_id INTEGER REFERENCES "answer" (id),
    content TEXT NOT NULL,
    comment_date DATE DEFAULT 'Now' NOT NULL,
    CHECK (
        (question_id IS NOT NULL AND answer_id IS NULL) OR
        (question_id IS NULL AND answer_id IS NOT NULL)
    )
);

-- Table: vote
CREATE TABLE vote (
    id SERIAL PRIMARY KEY,
    "vote" BOOLEAN NOT NULL,
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    question_id INTEGER REFERENCES "question" (id),
    answer_id INTEGER REFERENCES "answer" (id),
```

```
CHECK (
    (question_id IS NOT NULL AND answer_id IS NULL) OR
    (question_id IS NULL AND answer_id IS NOT NULL)
);

-- Table: report
CREATE TABLE report (
    id SERIAL PRIMARY KEY,
    reporter_id INTEGER REFERENCES "user" (id) NOT NULL,
    user_id INTEGER REFERENCES "user" (id),
    question_id INTEGER REFERENCES "question" (id),
    answer_id INTEGER REFERENCES "answer" (id),
    comment_id INTEGER REFERENCES "comment" (id),
    report_date DATE DEFAULT 'Now' NOT NULL,
    description TEXT NOT NULL,
    CHECK(
        (user_id IS NOT NULL AND question_id IS NULL AND answer_id IS NULL
AND comment_id IS NULL) OR
        (user_id IS NULL AND question_id IS NOT NULL AND answer_id IS NULL
AND comment_id IS NULL) OR
        (user_id IS NULL AND question_id IS NULL AND answer_id IS NOT NULL
AND comment_id IS NULL) OR
        (user_id IS NULL AND question_id IS NULL AND answer_id IS NULL AND
comment_id IS NOT NULL)
    )
);

-- Table: report_status
CREATE TABLE report_status (
    id SERIAL PRIMARY KEY,
    report_id INTEGER REFERENCES "report" (id) ON DELETE
CASCADE NOT NULL,
    state TEXT DEFAULT 'unresolved' NOT NULL,
    comment TEXT,
    responsible_user INTEGER REFERENCES "user" (id) ON DELETE
CASCADE NOT NULL,
    CHECK (
        state = 'unresolved' OR state = 'reviewing' OR state = 'resolved'
    )
);

-- Table: question_following
CREATE TABLE question_following (
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    question_id INTEGER REFERENCES "question" (id) NOT NULL,
    PRIMARY KEY (user_id, question_id)
);

-- Table: label_following
CREATE TABLE label_following (
    user_id INTEGER REFERENCES "user" (id) NOT NULL,
    label_id INTEGER REFERENCES "label" (id) NOT NULL,
    PRIMARY KEY (user_id, label_id)
```

```
);

-- Table: question_label
CREATE TABLE question_label (
  question_id      INTEGER      REFERENCES "question" (id) NOT NULL,
  label_id         INTEGER      REFERENCES "label" (id) NOT NULL,
  PRIMARY KEY (question_id, label_id)
);
```

Revision history

1. First submission (23/03/2020).
2. Deleted Administrator and Moderator tables. Changed all id's to "id" and other minor changes (28/03/2020).
3. Tested sql code, fixed some errors (29/03/2020).

GROUP2064, 29/03/2020

- [Editor] Antonio Pedro Reis Ribeiro Sousa Dantas, up201703878@fe.up.pt
- Eduardo João Santana Macedo, up201703658@fe.up.pt
- Nuno Miguel Teixeira Cardoso, up201706162@fe.up.pt
- Paulo Roberto Dias Mourato, up201705616@fe.up.pt