

Mass, Not Frontier: What Inference-Time Interventions and Weight Consolidation Do and Do Not Buy in Open-Ended Generation

Roberto I. Ono Filho
Independent researcher
ono.roberto@gmail.com ORCID [0009-0006-8650-629X](https://orcid.org/0009-0006-8650-629X)

Draft v0.1 for review, August 22, 2026

Abstract

A companion study [6] found that a base language model left to write for thousands of tokens gains judged surprise from one cheap operation, a new subject injected every few hundred tokens, and that the gains do not compose: no arm produced an integrated document, and on a problem with a verifier the same operation multiplied valid candidates without improving the best. Here we ask what would make local gains compose, by giving the loop, one piece at a time, what a discovering mind has and the loop did not: a schematic memory instead of a verbatim one, a standing question instead of a neutral subject, selection over its candidates, a verifier inside its stream, and, finally, consolidation of its verified finds into its weights. Every battery was pre-registered and measured under the generated-only, fresh-only, document-level protocol of the companion study, or by a deterministic verifier. At inference time one thing worked: a schematic recap written by the model and re-injected with the new subject raises document-level integration above every earlier arm (+1.65 over the verbatim context, $p = 0.001$, ten premises), at no local cost; a standing question helps a little; neither, nor their combination, moves development above about 2 on a 0–10 scale. Selection over the interruption’s candidates adds nothing to selection alone; a verifier whose verdicts are written into the notebook does not raise the ceiling, and the model writes its own verdicts instead, 16.4 fabricated “# Verifier:” lines per notebook against three real ones. Consolidation is different in kind: five cycles of LoRA fine-tuning on the model’s own value-filtered candidates shift what it writes on distributions it never trained on toward value (−1.7 points of excess over the base, $p = 0.008$; −3.1 against a same-size random-consolidation control, $p = 0.004$), without collapsing diversity; an anchored repulsion from the worst candidates moves the mass further, onto the best classic heuristic exactly, with every candidate at that level. But across every consolidation we ran, including two objectives built to keep the tails, the ceiling does not move, the shift does not transfer to other families, and the rate of candidates better than the classics on new families is highest in the untrained base and falls with training. Inference-time stimulation reorganizes a fixed prior; weight consolidation moves its mass toward the known good and pays for it with the tails where discovery would have to come from.

1 Introduction

Ono Filho [6] dismantled a cognitively inspired generation loop over 24 conditions and found that most of its effect on judged novelty lives in one operation, the *interruption*: a new subject injected every few hundred tokens into a stream whose literal repetition is damped. On windows of fresh generated text the interruption raises judged surprise by 1.2 to 1.4 points over habituation alone, on three base models, a post-trained one and two genres, and a pre-registered replication confirms it. The same study closed with three negatives. Read as whole documents,

none of the streams builds anything (no arm above 2.5 on integration, development, coherence or surprise, 0–10, judged on 4,500 tokens with the injected text removed); a judge-gated review that decides when not to interrupt does not change that; and on online bin packing, where a deterministic verifier replaces the judge, the interruption multiplies the valid, distinct candidate heuristics a base model writes three- to fourfold without raising the quality of the best. The interruption is a variation operator, and variation without selection is organized noise.

This paper takes up the question that study left: what would make local gains compose? We proceed by giving the loop, one piece at a time, the things a mind that discovers has and the loop did not, and measuring each under the protocol that the companion study showed to be necessary (generated-only windows, fresh-only estimates, a document-level reading, the premise as the unit of inference, a deterministic verifier where one exists). The pieces are (i) a *schematic* memory, in which the model carries a compressed recap of its own stream instead of the verbatim text that entrains it [1]; (ii) a *standing question*, in which the interruption points into the stream’s own unresolved matter rather than away from it [12]; (iii) *selection*, a FunSearch-style evolution over the candidates the interruption multiplies [8]; (iv) a *verifier inside the stream*, whose verdict on each candidate is written back into the notebook; and (v) *consolidation*, STaR/ReST cycles in which the model is fine-tuned (LoRA) on its own verified finds and generates again [2, 10, 13], followed by preference-based repulsion [7] and by quality-diversity selection [3, 4] designed to keep the tails. Every battery was pre-registered before it ran; the pre-registrations, their dated amendments and the results are in the laboratory notebook released with the code.

Contributions. (1) A schematic recap, written by the model and re-injected at each interruption, is the first intervention of the program to raise the document-level reading: integration +1.65 over the verbatim context and the highest integration score of any arm, at no cost on fresh windows. (2) A standing question raises integration and development modestly; its combination with the recap does not raise development further. Across all injections development stays near 2/10: the *progression wall*. (3) Selection over the interruption’s candidates and a verifier inside the stream both leave the ceiling where it was; the latter produces a new phenomenon, fabricated verifier verdicts, which we quantify. (4) Consolidation by LoRA on verified finds moves the candidate distribution on never-seen variants of the trained family toward value ($p = 0.008$ after five cycles; vs a random-consolidation control $p = 0.004$), keeps diversity over five cycles, leaves the ceiling where it was and does not transfer to other families; anchored repulsion from the worst moves the mass onto the best classic heuristic exactly; two tail-preserving objectives restore functional diversity and not the tails, and across every consolidation the rate of better-than-classic candidates on new families is highest in the untrained base. (5) A reading of the whole: the bit distance between a fixed prior and a target is not shortened by inference-time stimulation; weight consolidation moves the mass, not the frontier, and pays for the mass with the tails.

2 Related work

Self-training on one’s own outputs. STaR [13] fine-tunes a model on its own rationales that led to correct answers; ReST [2] and ReST-EM [10] alternate sampling, filtering by a reward and supervised fine-tuning, and report gains that saturate after a few iterations. Our attract arm is that recipe at office scale (an 8B model, forty examples per cycle, a rank-8 adapter) with three additions: a same-size random-consolidation control, which separates “trained on its own outputs” from “trained on what the verifier approved”; transfer measured on variants and families that never entered any training set; and the rate of candidates better than the classic heuristics, which is where the cost of self-training shows.

Preference optimization. DPO [7] optimizes a policy against a frozen reference from chosen/rejected pairs. Our repulsion arms use it with the model’s own worst candidates, or the clones of the known optimum, as rejected examples; unanchored it degenerates, anchored with a supervised term on the chosen side it sharpens the policy onto the known optimum. Both behaviours are known failure and success modes of preference optimization; what we add is their effect on the tails of a candidate distribution measured by a verifier.

Quality-diversity. MAP-Elites [4] and novelty search [3, 11] keep the best solution per behavioural niche rather than the best overall. Our qd arm consolidates one elite per niche of the verifier’s per-instance behaviour profile; it keeps functional diversity and, in this regime, loses value and the tails alike.

Verified search. FunSearch [8] and AlphaEvolve [5] pair an untrained proposal model with a hard evaluator and many samples, without fine-tuning the proposer. Our results are consistent with that choice: the untrained prior has the highest rate of better-than-classic candidates, and every consolidation we ran lowered it.

Memory, tension, and the judge. Schematic memory as reconstruction [1]; unfinished tasks as retained tension [12]; compression progress as intrinsic reward [9]. On the instrument, the companion study documents what a windowed LLM judge cannot see (injected text, self-copy beyond its horizon, windows against wholes); the fabricated verdicts of Section 5 are the same entrainment acting on a verifier’s output placed in the prompt.

3 Setup

Generators and loop. Unless stated, the generator is Qwen3-30B-A3B-Base (mixture of experts, 8-bit, MLX on an Apple M5 Pro); battery C uses Qwen3-8B-Base (8-bit) because it is fine-tuned. A cell is one premise (the ten premises of the companion study) continued for 4,500 tokens with the end-of-text token masked; habituation (windowed repetition penalty, window 512, factor 1.15) is on in every arm; interruptions fire on a clock every 300 tokens. Arms differ in what is injected and in whether the context is kept or rebuilt.

Judging. Windows of generated text only (96 tokens, starting 32 after any injected text, never crossing an injection), judged by Claude Opus 5 ($k = 5$, median) on surprise, connection and coherence with 600 tokens of context; windows flagged as self-copy (half their 12-token shingles seen earlier in the stream) are excluded from the fresh-only estimates. The whole stream, injected text removed, is judged once per cell ($k = 3$) on integration, development, coherence and surprise. The premise is the unit: cell means, bootstrap intervals over cells, exact sign-flip permutation tests on paired cells, one-sided where pre-registered.

The problem with a verifier. Online bin packing in the FunSearch form: the model writes a notebook of `priority(item, remaining)` functions; the verifier packs instances and reports the mean excess over the lower bound. Batteries S and V use the ten distribution variants of the companion study (item ranges within $[0.1, 0.8]$, where best fit is near-optimal); battery C moves to a family of small-item distributions in which best fit is measurably beatable (Section 6).

arm (Qwen3-30B-A3B-Base, period 300)	integration	development	coherence	surprise
habituation, no interruption	1.40	1.10	1.50	1.40
verbatim context (clock300)	0.80	0.40	1.50	0.50
reset + new subject	2.00	1.60	2.20	2.50
schema: reset + recap + new subject	2.70	1.80	2.30	2.70
question: preserved + open question	1.50	1.10	1.90	1.00
agenda: reset + recap + open question	2.50	2.00	1.90	2.60

Table 1: Document-level reading (whole 4,500-token stream, injected text removed; Opus 5, $k = 3$; cell means over ten premises, 0–10). The schematic recap gives the highest integration of the program; no arm passes 2.0 on development.

4 Memory and tension: what the loop remembers and what it is asked

Arms. *Verbatim* (clock300): the context is kept across interruptions. *Reset* (reset300): the cache is rebuilt from the premise and the injected sentence only. *Schema* (schema300): at each interruption the model is asked, by a completion cue on its last 1,200 tokens, to write a two- to three-sentence past-tense recap; the cache is rebuilt from the premise, the recap (“*By then, this much had happened: ...*”) and the new subject. The recap counts as injected text (never inside a judged window; removed from the document). *Question* (anomaly300): the context is kept, and the injection is the open question the model itself extracts from its last 1,200 tokens (“*But one question remained: ...*”). *Agenda* (agenda300): reset context, recap and question in the same injection. An anti-copy ladder retries the model’s recap or question at higher temperatures when it reproduces the previous one (it tends to), and falls back to the plain rotation when it cannot; the oracle acts only after 200 tokens of stream.

Results. Table 1 gives the document-level reading. Pre-registered contrasts (one-sided, exact paired permutation over ten premises): M2, schema > verbatim on (integration+development)/2: +1.65 [+1.15, +2.25], $p = 0.001$, positive on every dimension (integration +1.90, development +1.40, coherence +0.80, surprise +2.20; 10/10 premises on integration and surprise). M3, question > neutral subject: +0.70 [+0.40, +1.05], $p = 0.004$, with integration and development each +0.70 ($p = 0.03$). M1, schema > reset on the composite: +0.45 [-0.15, +1.05], $p = 0.13$, not supported; decomposed, integration +0.70 [+0.10, +1.30] and development +0.20: the recap gives the model something to integrate and nothing to advance. M4, on fresh windows the recap costs nothing (surprise +0.15, connection -0.08, coherence -0.27, all n.s.; self-copy 0%; the schema arm’s fresh windows, 3.90 / 3.22 / 6.60, are the best local scores of the program). The agenda arm (A1, primary: agenda > schema on development) gives +0.20 [-0.40, +0.80], $p = 0.38$; the question changes the cast of each restart, not its progression (document judge: “restarts the premise over and over with new casts and genres”).

Reading. Remembering the schema beats re-reading the text: the verbatim context, which entrains the model on thousands of tokens of its own past, reads worst as a whole; a reset reads better; a reset carrying a compressed memory reads best. But three injections (schema, question, agenda), all pre-registered, move integration and never development above about 2/10. We call this the progression wall.

5 Selection and the verifier

Battery S: the interruption inside a selection loop. A FunSearch-style evolution (10 variants $\times$ 8 generations $\times$ 16 samples per generation; the prompt shows the current population; paired by variant) with and without the interruption’s angle line injected into the prompt. S1 (gain of the champion on held-out instances): +0.0013 [-0.0015, +0.0047], $p = 0.38$. S2 (cumulative distinct valid candidates): 89.5 vs 95.1, $p = 0.86$ against the hypothesis. S3 (generation of first escape from best fit): +0.5, n.s. Under selection the interruption adds nothing, not even the diversity it added in a single stream: the population prompt already supplies what the interruption supplied.

Battery V: the verifier inside the stream. The notebook of the companion study’s battery B, generated in chunks; whenever a `priority` function closes, the harness scores it on the training instances and writes the verdict into the notebook as a comment (“# Verifier: `priority_x` scored mean excess 0.0812 on the training instances (worse than best fit, 0.0752); no improvement.”). A second arm adds, every 300 tokens, a deterministic scoreboard (“# So far: N functions tried; the best is ...; best fit sits at ...”) and a value-anchored open question. Ten variants $\times$ two seeds; baselines are battery B’s plain and angle arms re-scored in text order. V1 (held-out gain, feedback vs angle): +0.0003, $p = 0.48$. V2 (candidates improving on the notebook’s own training best, the verifier’s measure of progression): 0.1 vs 0.3 per notebook, opposite direction. V4 (scoreboard adds to feedback): nothing; the scoreboard arm writes fewer functions than every other arm (1.1 per notebook). Progression is near zero in every arm (0.1–0.3 improvements per notebook), with the standing caveat that best fit is near-optimal on these distributions.

Fabricated verdicts. The model wrote on average 16.4 “# Verifier:” lines per notebook in the feedback arm (6.2 with the scoreboard) against about three real ones: verdicts with invented scores and “new best of this notebook” that the harness never issued. Injecting the *format* of a reward signal into the context makes a base model generate its own reward; entrainment on the verdict is the code cousin of the self-copy the companion study found on narrative. Any design that places a verifier’s output in a model’s prompt should expect this and measure it.

6 Consolidation: moving the prior

Design (pre-registered 2026-08-21, extensions 2026-08-22). Qwen3-8B-Base (8-bit), QLoRA (rank 8, 16 layers, $\text{lr } 10^{-5}$, batch 2, prompt masked, ≈ 4 epochs over the consolidation set). Domain: a family of small-item bin-packing distributions in which best fit is beatable by simple heuristics (headroom 0.3–0.5 points of excess; first fit ties or beats best fit), ten training variants and eight held-out variants that never enter any training set; six far families (Weibull, triangular, bimodal, OR-library) for far transfer; verification on 20×200 -item instances; a *find* beats the better of best fit and first fit by 0.001 on the variant’s training instances. Cycle 0 is a shared base generation (3 notebooks $\times$ 1,200 tokens per variant, an angle comment every 250 tokens). Cycles 1–5: *attract* trains a fresh adapter on the finds plus the top-40 candidates by training excess from its own lineage; *random* trains on a same-size random sample of valid candidates (the control that separates “trained on itself” from “trained on what is worth”); *base* generates without an adapter at the same seeds. On the cycle-5 lineage we then trained: *repel* (DPO, $\beta = 0.1$, 80 steps, chosen = the attract set, rejected = the worst valid candidate of the same variant), *repel-anch* (the same plus a token-mean supervised term on the chosen side, $\alpha = 1$), *repel-early* (plain DPO, 20 steps), *qd* (supervised, one elite per behavioural niche of the verifier’s per-instance profile, $k = 3$ niches per variant plus one seat for the best clone of the

arm	cycle	candidates	mean excess	rel. to min(BF,FF)	best	distinct	copies
base	0	65	0.0633	+0.0322	0.0408	0.99	–
base	1	53	0.0562	+0.0251	0.0327	1.00	–
attract	1	235	0.0559	+0.0248	0.0319	0.98	10%
random	1	276	0.0708	+0.0397	0.0332	1.00	5%
base	2	42	0.0583	+0.0272	0.0317	0.97	–
attract	2	198	0.0430	+0.0119	0.0312	0.99	6%
random	2	274	0.0697	+0.0386	0.0310	0.99	8%
base	3	55	0.0644	+0.0333	0.0414	1.00	–
attract	3	214	0.0516	+0.0204	0.0311	0.99	7%
random	3	334	0.0653	+0.0342	0.0312	0.99	1%
base	4	57	0.0532	+0.0221	0.0323	1.00	–
attract	4	195	0.0420	+0.0109	0.0311	0.98	16%
random	4	276	0.0510	+0.0199	0.0307	1.00	0%
base	5	47	0.0556	+0.0244	0.0325	1.00	–
attract	5	226	0.0386	+0.0074	0.0311	1.00	1%
random	5	287	0.0695	+0.0383	0.0311	0.99	0%

Table 2: Battery C on the eight held-out variants (never in any training set; test instances): candidates per arm and cycle, mean test excess of valid candidates (cell means over variants), the same relative to the better of best fit and first fit, the best candidate, the distinct/valid ratio and the share of literal copies of the arm’s training set. The value-filtered adapter lowers the mean without moving the best.

classic attractor) and *repel-mode* (anchored DPO whose rejected examples are the best-fit clones themselves). Hypotheses, on the held-out variants: C1 (primary), attract < base on the mean test excess of valid candidates (the prior moved on variants it never saw); C2, attract < random; C3, higher find rate; C4 (two-sided), the diversity cost; R1’ repulsion adds to attraction; R2’ the best moves; T1 the tail rate (share of candidates better than the classics) on far families; T2 functional collapse.

Attraction. Table 2 gives the held-out reading by arm and cycle. At the pre-registered final cycle (3), C1 was -0.0129 $[-0.0317, +0.0027]$, $p = 0.109$, not supported at $\alpha = 0.05$, with the direction consistent (7 of 8 variants better) and the cycle-2 contrast supported (-0.0153 , $p = 0.016$); a pre-registered extension to five cycles closed it: -0.0170 $[-0.0268, -0.0079]$, $p = 0.008$, the attract arm ending at 3.86% mean excess, 0.74 points above the better classic heuristic, against 5.6–6.4% for the base. C2: attract vs random, -0.0138 ($p = 0.035$) at cycle 3 and -0.0309 ($p = 0.004$) at cycle 5: the value filter matters. The random control hurts at cycle 1 (+1.5 points over base: consolidating mediocre functions makes the next ones worse) and is neutral to harmful later. C3: strict finds are zero in every arm and cycle, and the best candidate per variant is nearly the same in every arm ($\approx 3.1\%$ excess, the level of best fit): the ceiling did not move. C4: no collapse over five cycles; the distinct/valid ratio is 0.97–1.00 throughout, literal copies of the training set 1–16% (attract); every adapter makes the model write 3.6–4 $\times$ more functions per notebook. Far transfer: on six distributions of other families the final attract adapter equals the base on the mean ($+0.001$, $p = 0.69$, $n = 5$) and beats the random adapter by -0.020 ($p = 0.016$); the random adapter is worse than the base there too ($+0.017$). What moved is the prior for the family it was trained on. The adapter of the last cycle was taught mostly tight-bin functions (24 of 40 of the form $1/(\mathbf{r}^{**2}+\mathbf{eps})$, 13 best-fit-like): consolidation pulls the mass toward the best attractor the verifier has approved.

Repulsion. Unanchored DPO (loss $0.69 \rightarrow 0.0015$) degenerated: 1.1 closed functions per notebook (attract 9, base 2), 60% comment lines and recursive non-code; the few valid candidates were far worse than the base (10.6% vs 5.6% excess). Pushing the policy away from bad

adapter (cycle-5 lineage)	held-out variants (8)				far families	
	candidates	mean excess	at classic level	score levels	mean excess	better
base (none)	47	0.0556	20%	0.81	0.0838	
random	287	0.0695	15%	–	0.1004	
repel-early (DPO, 20 steps)	71	0.0721	30%	–	0.0994	
attract (SFT on value)	226	0.0386	72%	0.14	0.0803	
repel-anch (DPO + anchor)	144	0.0311	100%	0.07	0.0758	
qd (SFT on niche elites)	293	0.0598	25%	0.33	0.1012	
repel-mode (DPO from the attractor)	62	0.0792	2%	0.50	0.0935	
repel (DPO, unanchored)	13	0.1056	0%	–	–	

Table 3: The ladder of adapters. Held-out: mean test excess of valid candidates, share scoring exactly at the level of the better classic heuristic, distinct score levels per valid candidate; far families: mean excess and share of candidates better than the classics. The mass walks onto the known attractor; the tails live in the untrained base.

functions, unanchored, pushes it away from writing functions. Anchored (the same loss plus a token-mean supervised term on the chosen side; pre-registered), the repulsion writes again (144 valid candidates, +12 per cell over the base, $p = 0.02$) and adds to attraction: mean held-out excess 3.11% against 3.86% (-0.0074 $[-0.0104, -0.0047]$, $p = 0.008$), which is exactly the level of the better classic heuristic. The best candidate does not move (0.0311 in both arms), and the reason is the finding: **every** held-out candidate of the anchored-repulsion adapter scores exactly at the best-fit level (all are monotone “fullest bin” variants), against 72% for attraction, 15–20% for the base and the random control, 30% for an early-stopped plain DPO (otherwise worse than attraction, +0.034, $p = 0.008$) and 0% for the degenerate one (Table 3). Hash-level diversity survives (1.00); functional diversity does not. On the far families the anchored adapter is the best arm on the mean (7.6% vs 8.4% base) because “be best fit” is good everywhere, and the only arm with no candidate better than the classics.

Keeping the tails. Two objectives built to keep the tails (pre-registered) recovered functional diversity and nothing else. The qd adapter has 25% of candidates at the classic level (attract 72%, $p = 0.004$) and 2.4× the distinct score levels, at a cost of +2.1 points of mean excess ($p = 0.008$), and its better-than-classic rate on the far families is *lower* than attraction’s (0.6% vs 3.9%; T1, primary, not supported). Repulsion from the attractor itself removes the collapse entirely (2% at the classic level) and with it most of the value (7.9% mean excess, best 4.8%, worse than the base; no far tail). The diversity these objectives keep is diversity of the mediocre. Across every consolidation we ran, the rate of better-than-classic candidates on new families is highest in the untrained base (10%) and falls with training (attract 3.9%, every other adapter $\leq 2\%$): consolidation pays for mass with tails.

7 Discussion

What can be bought. Across the two studies the ledger is now complete for the interventions we could build. Variation is cheap: the interruption raises fresh surprise by more than a point and multiplies valid candidates three- to fourfold. Integration can be bought with the right memory: a schematic recap carried across resets is the only inference-time intervention that raised the document-level reading, and it did so reliably. Mass can be bought with the right training: a few cycles of consolidation on what the verifier approved move the candidate distribution of a never-seen variant onto the known good, and an anchored repulsion from the bad moves it there exactly. Progression and frontier cannot, by anything we tried: three

injections, selection over the candidates, a verifier in the stream, a judge-gated review, five cycles of attraction, four kinds of repulsion and a quality-diversity consolidation all leave development near 2/10 and the verified ceiling where it was.

The bit distance. A generative model is a distribution, not a store; the question is not whether an answer is “inside” it but how much probability mass sits near it, how many bits of search separate the prior from the target. Inference-time stimulation reorganizes the surface of a fixed prior: it buys variation and, with a schematic memory, integration, but it does not move the mass. Weight consolidation moves the mass, and battery C shows its present reach: toward the best thing the verifier had already approved, within the family it was trained on, and at the cost of the tails where the rare better-than-classic candidates appear; objectives built to keep the tails kept diversity of the mediocre instead. This is also why the known successes of verified search [5, 8] pair an untrained proposal distribution with a hard evaluator and many samples rather than fine-tune the proposer. For discovery our results argue for a portfolio, the broad untrained prior to propose and the consolidated one to exploit, and for spending on selection.

Design rules. For long open-ended generation: damp repetition; interrupt with something new each time or reset the context; carry a compressed recap rather than the text; do not expect the whole to advance from any of this. For search with a verifier: spend on sampling and selection, not on stimulation; keep the verifier’s verdicts out of the prompt or measure the fabrication they induce; if reliability is the goal, consolidate on what the verifier approved (and never without the filter); if discovery is the goal, keep the untrained prior in the loop.

8 Limitations

Ten premises and ten variants per battery; 8–30B base models at 8 bits; the document judge is a single LLM family at $k = 3$ and its absolute levels are low for every arm, so “integration 2.7” is a relative statement; the bin-packing distributions of batteries S and V have little headroom, which bounds what selection and feedback could show there (battery C’s family was chosen for headroom for that reason, and its headroom is still small: 0.3–0.5 points); the oracle that writes recaps and questions is the generator itself and sometimes repeats itself, which the anti-copy ladder mitigates but does not remove; battery C is five cycles of forty examples on an 8B model with a rank-8 adapter, its primary contrast missed α at the pre-registered third cycle ($p = 0.11$) and closed at the pre-registered extension to five ($p = 0.008$), its base arm varies by seed, the far families are six and the tail rates rest on tens of candidates, and the strict find criterion admits lucky candidates (training finds lose on test), which is why the primary measure is the mean and not the best. The negative results are resolution-bounded nulls, not proofs of absence; the tail finding in particular deserves replication at a larger sample and on a domain with more headroom.

9 Conclusion

Given memory, tension, selection and a verifier, the interrupted loop composes better and advances no further. A schematic memory is worth having; a standing question helps a little; selection and in-stream verification add nothing to what they replace, and the latter teaches the model to invent its own verdicts. Consolidating verified finds into the weights is the one intervention that moved what the model writes on problems it had not seen, and it moved it toward what it already knew to be good; repelling the bad, anchored, moved it all the way there

and no further; keeping the tails kept the mediocre. The untrained prior remained the better discoverer. Mass can be bought; the frontier, so far, cannot.

A Reproducibility

Code, run data, judgments, pre-registrations and the dated laboratory notebook are in the repository of the companion study (<https://github.com/RobertoOno/interrupting-the-loop>): the oracle arms (`schema_reseed`, `anomaly_reseed`, `agenda_reseed` in `scripts/dream_run.py`), battery S (`scripts/evolve_interrupt.py`), battery V (`scripts/problem_loop.py`), battery C and its extensions (`scripts/consolidate.py`, `dpo_lora.py`, `run_c.sh`, `run_c_ext.sh`, `run_c_repel*.sh`, `run_n.sh`) and the analyses that generate the tables (`docs/APPENDIX_GEN.md`, `APPENDIX_S.md`, `APPENDIX_V.md`, `APPENDIX_C*.md`, `APPENDIX_N.md`). Judging used `anthropic.claude-opus-5` on Amazon Bedrock (20–21 August 2026) under the prompts of the companion study; fine-tuning used `mlx_lm` (QLoRA on the 8-bit model, peak 14 GB, about 8 minutes per adapter) and a small DPO trainer in MLX released with the code. Every hypothesis, amendment and result is dated in `docs/PLANO.md`.

References

- [1] Frederic C. Bartlett. *Remembering: A Study in Experimental and Social Psychology*. Cambridge University Press, 1932.
- [2] Caglar Gulcehre, Tom Le Paine, Srivatsan Srinivasan, Ksenia Konyushkova, Lotte Weerts, Abhishek Sharma, Aditya Siddhant, Alex Ahern, Miaosen Wang, Chenjie Gu, Wolfgang Macherey, Arnaud Doucet, Orhan Firat, and Nando de Freitas. Reinforced self-training (ReST) for language modeling, 2023.
- [3] Joel Lehman and Kenneth O. Stanley. Abandoning objectives: Evolution through the search for novelty alone. *Evolutionary Computation*, 19(2):189–223, 2011.
- [4] Jean-Baptiste Mouret and Jeff Clune. Illuminating search spaces by mapping elites, 2015.
- [5] Alexander Novikov et al. Alphaevolve: A coding agent for scientific and algorithmic discovery, 2025. Google DeepMind; arXiv:2506.13131.
- [6] Roberto I. Ono Filho. Interrupting the loop: Periodic subject changes raise judged surprise and connection in base language models, 2026.
- [7] Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, 2023.
- [8] Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M. Pawan Kumar, Emilien Dupont, Francisco J. R. Ruiz, Jordan S. Ellenberg, Pengming Wang, Omar Fawzi, Pushmeet Kohli, and Alhussein Fawzi. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475, 2024. doi: 10.1038/s41586-023-06924-6.
- [9] Jürgen Schmidhuber. Formal theory of creativity, fun, and intrinsic motivation (1990–2010). *IEEE Transactions on Autonomous Mental Development*, 2(3):230–247, 2010.
- [10] Avi Singh, John D. Co-Reyes, Rishabh Agarwal, Ankesh Stanton, Kai Yang, et al. Beyond human data: Scaling self-training for problem-solving with language models, 2023.

- [11] Kenneth O. Stanley and Joel Lehman. *Why Greatness Cannot Be Planned: The Myth of the Objective*. Springer, 2015.
- [12] Bluma Zeigarnik. Das behalten erledigter und unerledigter handlungen. *Psychologische Forschung*, 9:1–85, 1927.
- [13] Eric Zelikman, Yuhuai Wu, Jesse Mu, and Noah D. Goodman. STaR: Bootstrapping reasoning with reasoning. In *Advances in Neural Information Processing Systems*, 2022.