

## M2 AIC

### TC2: Introduction to Optimization

Black-Box Optimization Benchmarking  
with the COCO platform

-

Multiobjective Optimizer adaptive IBEA ( $\epsilon$ -indicator)

*Group 1:* Martin BAUW, Robin DURAZ, Jiaxin GAO,  
Hao LIU, Luca VEYRON-FORRER


- 1 Introduction
- 2 The algorithm
  - Overview of IBEA
  - Selection and variation
- 3 Our implementation
  - Code structure
  - Improvements regarding the execution speed
- 4 CPU timing and results
  - CPU timing and results
  - Comparision with Random Search and NSGA-II
- 5 Conclusion
- 6 Bibliography

## IBEA: Indicator-Based Evolutionary Algorithm

- optimization: find decision space vectors leading to objective space minima
- multiobjective: the objective space is multidimensional
- evolutionary: decision space candidates follows an natural selection-like evolution
- indicator-based: binary quality indicators to compare two Pareto set approximations

## Successive steps of IBEA:

- ① Initialization
- ② Fitness assignment
- ③ Environmental selection
- ④ Termination
- ⑤ Mating selection
- ⑥ Variation



<sup>1</sup>Illustration from:


*A Tutorial on Evolutionary Multiobjective Optimization* - E. Zitzler,  
M. Laumanns, and S. Bleuler

- Binary quality indicators:

$$I_{\epsilon^+}(A, B) = \min_{\epsilon} \{ \forall x^2 \in B \exists x^1 \in A : f_i(x^1) - \epsilon \leq f_i(x^2) \text{ for } i \in \{1, \dots, n\} \} \quad (1)$$

- Fitness values:

$$F(x^1) = \sum_{x^2 \in P \setminus \{x^1\}} -e^{-\frac{I(\{x^1\}, \{x^2\})}{ck}} \quad (2)$$



<sup>1</sup>Illustration from:

*Indicator-Based Selection in Multiobjective Search* - E. Zitzler and S. Künzli

## Recombination

For recombination, we use a Simulated Binary Crossover (SBX) operator. A uniform probability pick in  $[0, 1]$  written  $u$  determines the parameter used in computing the features (decision space coordinates) of the children.

- if the uniform probability pick  $\leq 0.5$ :

$$\beta_q = (2u)^{\frac{1}{\mu+1}} \quad (3)$$

- else:

$$\beta_q = \left(\frac{1}{2(1-u)}\right)^{\frac{1}{\mu+1}} \quad (4)$$

# Recombination

Thus, we can compute the children's coordinates:

- first child:

$$child0[j] = 0.5((1 + \beta_q)parent0[j] + (1 - \beta_q)parent1[j]) \quad (5)$$

- second child:

$$child1[j] = 0.5((1 - \beta_q)parent0[j] + (1 + \beta_q)parent1[j]) \quad (6)$$

## Mating selection and mutation

Polynomial mutation operator:

The mutation operator modifies individuals by changing small parts in the associated vectors according to a given mutation rate.

- if the uniform probability pick  $\leq 0.5$ :

$$\sigma_L = (2u)^{\frac{1}{\mu+1}} - 1 \quad (7)$$

$$p_{mut}[j] = ind[j] + \sigma_L(ind[j] - Lo) \quad (8)$$

- else:

$$\sigma_R = (2(1 - u))^{\frac{1}{\mu+1}} \quad (9)$$

$$p_{mut}[j] = ind[j] + \sigma_R(Up - ind[j]) \quad (10)$$



- Code built for the most general case
- The IBEA code is in the class IBEA, where each method implements one step of the algorithm
- No difficulty to get to the best asymptotic complexity

- Good data structures choices
- The Indicator function was the key
- From the first implementation to the last we divided the execution time by 4.5

## Computer specifications and batch options

- Intel(R) Core(TM) i7-7500U CPU @ 2.70GHz
- Quad core CPU with 16GB RAM

Everything ran with a budget of 100

- Three batches for dimensions 2, 3, 5, 10, 20
- First batch running alone, and two others together
- One batch for dimensions 40

## Options chosen to run the algorithm

- Population size : 100
- Maximum number of generation : 100
- Scaling factor : 0.05
- Mutation rate : 0.01
- Recombination and mutation  $\mu$  : 1
- Population initialization in range  $(-5, 5)$

Dimension \ Batch	2	3	5
Batch 1 on 3	6.0e-04	6.3e-04	8.1e-04
Batch 2 and 3 on 3 run simultaneously	8.6e-04	8.6e-04	9.1e-04
	8.3e-04	8.4e-04	8.9e-04


  

Dimension \ Batch	10	20
Batch 1 on 3	8.3e-04	1.1e-03
Batch 2 and 3 on 3 run simultaneously	1.1e-03	1.3e-03
	1.0e-03	1.3e-03

Dimension \ Batch	40
Whole test suite	4.2e-03

# Results




## Results analysis

- Comparatively better in higher dimensions
- Results globally good for an EMOA
- More budget could have given better results
- A better initialization of population could lead to a sharper increase at the beginning

## Random Search


- The introduce of Random Search:
- Its effect is directly proportional to its evaluations
- It doesn't work well when the dimension of input is too high





# NSGA-II

- The introduce of NSGA-II:
- The gap between our algorithm and it



In our experiments, we majorly focused on the comparison with NSGA-II and Random search:

IBEA VS Random search: IBEA outperformed Random search, a relatively good Pareto set approximation was given by IBEA.

IBEA VS NSGA-II: IBEA performed worse than NSGA-II.

Choosing a representation of the problem addressed, an initial population, a method of selection, a crossover operator, mutation operator, the probabilities of crossover and mutation, and the insertion method creates a variant of MOEAs algorithms.

## Non-exhaustive bibliography

- *Indicator-Based Selection in Multiobjective Search* - Zitzler, E. and Künzli, S.
- *A Tutorial on Evolutionary Multiobjective Optimization* - Zitzler, E. and Laumanns, M. and Bleuler, S.
- *Biobjective Performance Assessment with the COCO Platform* - Brockhoff, D. and Tušar, T. and Tušar, D. and Wagner, T. and Hansen, N. and Auger, A.