

Earthquake Forecasting

Dissertation Project 2

Robin Lin s2435943

July 2023

```
1 require(ETAS.inlabru)
2 require(ggplot2)
3 require(dplyr)
4 require(magrittr)
5 require(tidyquant)
6 require(rnaturalearth)
7 require(terra)
8 require(sf)
9 require(ggspatial)
10 require(rnaturalearthdata)
11 require(lubridate)
12
13 # Increase/decrease num.cores if you have more/fewer cores on your computer.
14 # future::multisession works on both Windows, MacOS, and Linux
15 num.cores <- 8
16 future::plan(future::multisession, workers = num.cores)
17 INLA::inla.setOption(num.threads = num.cores)
18 # To deactivate parallelism, run
19 #   future::plan(future::sequential)
20 #   INLA::inla.setOption(num.threads = 1)
```

Copula transformation of the priors

```
1 # set copula transformations list
2 link.f <- list(
3   mu = \(x) gamma_t(x, 0.3, 0.6),
4   K = \(x) unif_t(x, 0, 10),
5   alpha = \(x) unif_t(x, 0, 10),
6   c_ = \(x) unif_t(x, 0, 10),
```

```

7   p = \ (x) unif_t(x, 1, 10)
8   )
9
10  # set inverse copula transformations list
11  inv.link.f <- list(
12    mu = \ (x) inv_gamma_t(x, 0.3, 0.6),
13    K = \ (x) inv_unif_t(x, 0, 10),
14    alpha = \ (x) inv_unif_t(x, 0, 10),
15    c_ = \ (x) inv_unif_t(x, 0, 10),
16    p = \ (x) inv_unif_t(x, 1, 10)
17  )

```

Italy

```

1  # transform time string in Date object
2  horus$time_date <- as.POSIXct(
3    horus$time_string,
4    format = "%Y-%m-%dT%H:%M:%OS",
5    tz = "UTC"
6  )
7  # There may be some incorrectly registered data-times in the original data set,
8  # that as.POSIXct() can't convert, depending on the system.
9  # These should ideally be corrected, but for now, we just remove the rows that
10 # couldn't be converted.
11 # horus <- na.omit(horus)
12
13 # set up parameters for selection
14 start.date <- as.POSIXct("2009-01-01T00:00:00",
15                           format = "%Y-%m-%dT%H:%M:%OS")
16 end.date <- as.POSIXct("2010-01-01T00:00:00", format = "%Y-%m-%dT%H:%M:%OS")
17 min.longitude <- 10.5
18 max.longitude <- 16
19 min.latitude <- 40.5
20 max.latitude <- 45
21 M0 <- 2.5
22
23 # set up conditions for selection
24 aquila.sel <- (horus$time_date >= start.date) &
25   (horus$time_date < end.date) &
26   (horus$lon >= min.longitude) &
27   (horus$lon <= max.longitude) &
28   (horus$lat >= min.latitude) &


```

```

29   (horus$lat <= max.latitude) &
30   (horus$M >= M0)
31
32   # select
33   aquila <- horus[aquila.sel, ]

1   italy.map <- ne_countries(country = 'Italy', returnclass = "sf",
2                               scale = 'medium')
3
4   aquila.sf <- st_as_sf(aquila,
5                           coords = c("lon", "lat"),
6                           crs = st_crs('EPSG:4326'))
7   ggplot() +
8     geom_sf(data = aquila.sf[aquila$M > 3,], size = 0.4) +
9     geom_sf(data = italy.map, fill = alpha("lightgrey", 0), color = 'green',
10             linewidth = 0.7) +
11     geom_sf(data = aquila.sf[aquila$M > 5,], size = 0.5, color = 'orange') +
12     geom_sf(data = aquila.sf[aquila$M > 6,], size = 0.6, color = 'red') +
13     ggtitle("Map of event locations")

```



```

1 ggplot(aquila, aes(time_date, M)) +
2   geom_point() +
3   theme_bw()

```




Figure 1: L'Aquila seismic sequence, times versus magnitudes

```

1 # set up data.frame for model fitting
2 aquila.bru <- data.frame(
3   ts = as.numeric(
4     difftime(aquila$time_date, start.date, units = "days")
5   ),
6   magnitudes = aquila$M,
7   idx.p = 1 : nrow(aquila)
8 )

1 # set up list of initial values
2 th.init <- list(
3   th.mu = inv.link.f$mu(0.5),
4   th.K = inv.link.f$K(0.1),
5   th.alpha = inv.link.f$alpha(1),
6   th.c = inv.link.f$c_(0.1),

```

```

7   th.p = inv.link.f$p(1.1)
8   )

1   # set starting and time of the time interval used for model fitting.
2   # In this case, we use the interval covered by the data.
3   T1 <- 0
4   T2 <- max(aquila.bru$ts) + 0.2 # Use max(..., na.rm = TRUE) if there may
5   # still be NAs here

1   # set up list of bru options
2   bru.opt.list <- list(
3     bru_verbose = 3, # type of visual output
4     bru_max_iter = 70, # maximum number of iterations
5     # bru_method = list(max_step = 0.5),
6     bru_initial = th.init # parameters' initial values
7   )

1   ETAS <- function(data = aquila.bru, m0 = M0, t1 = T1, t2 = T2,
2                     ncore = num.cores, n.samp = 1000, max.batch = 1000,
3                     mag = 4, n.breaks = 100, t.end.tri.post = 5,
4                     t.end.tri.prior = 10, t.end.omori.post = 5,
5                     t.end.omori.prior = 5){
6
7     # maximum likelihood estimator for beta
8     beta.p <- 1 / (mean(data$magnitudes) - m0)
9
10    # fit the model
11    model.fit <- Temporal.ETAS(
12      total.data = data,
13      M0 = m0,
14      T1 = t1,
15      T2 = t2,
16      link.functions = link.f,
17      coef.t. = 1,
18      delta.t. = 0.1,
19      N.max. = 5,
20      bru.opt = bru.opt.list
21    )
22
23    # create input list to explore model output

```

```

24 input_list <- list(
25   model.fit = model.fit,
26   link.functions = link.f
27 )
28
29 # get marginal posterior information
30 post.list <- get_posterior_param(input.list = input_list)
31
32 # plot marginal posteriors
33 postplot <- post.list$post.plot
34
35 # posterior sampling
36 post.samp <- post_sampling(
37   input.list = input_list,
38   n.samp = n.samp,
39   max.batch = max.batch,
40   ncore = num.cores
41 )
42
43 # pair plot
44 pair.plot <- post_pairs_plot(
45   post.samp = post.samp,
46   input.list = NULL,
47   n.samp = NULL,
48   max.batch = max.batch
49 )
50 pairplot <- pair.plot$pair.plot
51
52 # set additional elements of the list
53 input_list$T12 <- c(t1, t2)
54 input_list$M0 <- m0
55 input_list$catalog.bru <- data
56
57 # posterior number of events
58 N.post <- get_posterior_N(input.list = input_list)
59 Npostplot <- N.post$post.plot
60
61 # triggering function plots
62 # posterior
63 triplotpost <- triggering_fun_plot(
64   input.list = input_list,

```

```

65     post.samp = post.samp,
66     n.samp = NULL, magnitude = mag,
67     t.end = t.end.tri.post, n.breaks = n.breaks
68   )
69
70   # prior
71   triplotprior <- triggering_fun_plot_prior(input.list = input_list,
72                                           magnitude = mag, n.samp = n.samp,
73                                           t.end = t.end.tri.prior)
74
75   # omori plots
76   # posterior
77   omoripost <- omori_plot_posterior(input.list = input_list,
78                                    post.samp = post.samp,
79                                    n.samp = NULL, t.end = t.end.omori.post)
80
81   # prior
82   omoriprior <- omori_plot_prior(input.list = input_list, n.samp = n.samp,
83                                 t.end = t.end.omori.prior)
84
85   # returns the whole environment
86   envir <- as.list(environment())
87   return(tibble::lst(envir))
88 }
89 etas <- ETAS()

```

Start creating grid...

Finished creating grid, time 3.307242

Synthetic catalogues generation

```

1  set.seed(2)
2  mult.synth.ETAS <- function(t1 = NULL, t2 = NULL, n.cat = 1,
3                             ht = etas$envir$data[which.max(
4                               etas$envir$data$magnitudes), ]){
5
6     # inherits the environment of `etas`
7     envir <- etas$envir
8
9     # updates environments if specified by users
10    envir$t1 <- ifelse(!is.null(t1), t1, envir$t1)

```

```

11  envir$t2 <- ifelse(!is.null(t2), t2, envir$t2)
12
13  # generate catalogues as list of lists
14  multi.synth.cat.list <- lapply(seq_len(n.cat), \(x)
15  generate_temporal_ETAS_synthetic(
16    theta = envir$post.samp[x, ], beta.p = envir$beta.p,
17    M0 = envir$m0, T1 = envir$t1,
18    T2 = envir$t2, Ht = ht, ncore = envir$ncore))
19
20  # store catalogues as list of data.frames
21  multi.synth.cat.list.df <- lapply(multi.synth.cat.list,
22    \(x) do.call(rbind, x))
23
24  # set catalogue identifier
25  multi.synth.cat.list.df <- lapply(seq_len(n.cat),
26    \(x) cbind(
27      multi.synth.cat.list.df[[x]],
28      cat.idx = x))
29
30  # merge catalogues in unique data.frame
31  multi.synth.cat.df <- do.call(rbind, multi.synth.cat.list.df)
32
33  # we need to bind the synthetics with the observed catalogue for plotting
34  cat.df.for.plotting <- rbind(
35    multi.synth.cat.df,
36    cbind(envir$data[, c("ts", "magnitudes")],
37      gen = NA, cat.idx = "observed"
38    )
39  )
40
41  # plot them
42  multi.synth.cat.plot <- ggplot(cat.df.for.plotting,
43    aes(ts, magnitudes)) +
44    geom_point(size = 0.5) +
45    geom_point(
46      data = ht, mapping = aes(ts, magnitudes), color = "red"
47    ) +
48    facet_wrap(facets = ~cat.idx)
49
50  # modelling
51  multi.synth.etas <- ETAS(data = multi.synth.cat.df,
    t1 = envir$t1, t2 = envir$t2)

```



```

52     # returns the synthetic dataset with plots, as well as the modelling
53     # results
54     return(tibble::lst(cat.df.for.plotting, multi.synth.cat.plot,
55                        multi.synth.etas))
56   }
57   mult.synth.fit <- mult.synth.ETAS()

```

Start creating grid...

Finished creating grid, time 1.788598

Forecasting

```

1  ETAS.forecast <- function(){
2
3     # inherits the environment of `etas`
4     envir <- etas$envir
5
6     # express 1 minute in days
7     min.in.days <- 1 / (24 * 60)
8     # find time of the event with the greatest magnitude
9     t.max.mag <- envir$data$ts[which.max(envir$data$magnitudes)]
10    # set starting time of the forecasting period
11    T1.fore <- t.max.mag + min.in.days
12    # set forecast length
13    fore.length <- 1
14    # set end time of the forecasting period
15    T2.fore <- T1.fore + fore.length
16    # set known data
17    Ht.fore <- envir$data[envir$data$ts < T1.fore, ]
18
19    # produce forecast
20    daily.fore <- Temporal.ETAS.forecast(
21      post.samp = envir$post.samp, # ETAS parameters posterior samples
22      n.cat = nrow(envir$post.samp), # number of synthetic catalogues
23      beta.p = envir$beta.p, # magnitude distribution parameter
24      M0 = envir$m0, # cutoff magnitude
25      T1 = T1.fore, # forecast starting time
26      T2 = T2.fore, # forecast end time
27      Ht = Ht.fore, # known events
28      ncore = envir$ncore # number of cores
29    )

```

```

30
31   # find number of events per catalogue
32   N.fore <- vapply(
33     seq_len(daily.fore$n.cat),
34     \(x) sum(daily.fore$fore.df$cat.idx == x), 0
35   )
36   # find number of observed events in the forecasting period
37   N.obs <- sum(envir$data$ts >= T1.fore & envir$data$ts <= T2.fore)
38   # plot the distribution
39   histfore <- ggplot() +
40     geom_histogram(aes(x = N.fore, y = after_stat(density)),
41                   binwidth = 1) +
42     geom_vline(xintercept = N.obs) +
43     xlim(100, 500)
44
45   return(histfore)
46 }
47 histfore <- ETAS.forecast()

1  # save.image()

```