

# IR Assignment-1 (Domain Specific Search Engine)

Abhinav Kumar 2015B5A70674H  
Yashdeep Thorat 2015B5A70675H  
Shivam Bhagat 2015B5A70460H

## Implementation details:

Language used: **Python**

Packages used:

- numpy
- scipy
- nltk
- Dash
- Plotly
- BeautifulSoup4
- csv
- requests

The nltk package was used for natural language processing as it provides libraries for tokenization, stemming, lemmatization, etc. The numpy package was used for creating the various data structures. BeautifulSoup4 was used for web scraping.

## Data Structures Used

The following inbuilt/library imported data structures have been used:

1. **Word Vocabulary:** This is implemented as a hashtable with the python inbuilt dictionary to get the index of the each term in the tf-idf matrix.
2. **tf-idf matrix:** This is stored using the NumPy matrix with the terms/dictionary index in representing the row number and the document number representing the columns of the matrix.

3. **Query\_vector:** This is a boolean vector for the query in the dictionary space i.e is the dimension of the vector is equal to the dictionary. This is also implemented with the numpy vector.
4. **Document-term list:** This is the list of list of all the document and their corresponding words/terms in the document.

## **Architecture of the Application**

- **WebScraper.py** scrapes data from various pages of <https://arxiv.org/> according to their domain and saves the data in different csv files. The files contain a collection of articles/research papers in the domains of AI, Data Science, Data Mining, Condensed Matter Physics, etc.
- **IndexData.py** reads all the csv files and creates a “**bag of words**” after tokenizing, stemming, lementizing and removing the stop words. It is also responsible for creating the **tf-idf matrix** and storing it in the .npz format. Thus we can find out vectors corresponding to each document from it.
- **SearchQuery.py** is used to process a query entered by the user. It creates a query vector, for which we find cosine similarity with each document.

$$\text{Cosine Similarity} = \frac{q \cdot d}{|q| \cdot |d|}$$

- **gui.py** is used to generate the GUI for the search engine. Plotly and Dash are used to generate a two dimensional visualization of the query results. It is observed that the results belonging to the same subdomain tend to cluster together.

## **Efficiency**

### **Precision**

- For the query “Artificial Intelligence” - 0.7
- For the query “Machine Learning” - 0.9
- For the query “Information Retrieval” - 0.7

- For the query “General Relativity and Quantum Cosmology” - 0.5

## **Recall**

- For the query “Artificial Intelligence” - 0.1
- For the query “Machine Learning” - 0.059210526
- For the query “Information Retrieval” - 0.269230769
- For the query “General Relativity and Quantum Cosmology” - 0.142857143

## **Search and Retrieval Time**

- For the query “Machine Learning” - 0.0019s
- For the query “Artificial Intelligence” - 0.0018s
- For the query “Quantum Machine Learning” - 0.0019s