

Machine Learning for IoT

Homework 1

*****DUE DATE: 17 Nov (h23:59)*****

Submission Instructions:

Each group will send an e-mail to andrea.calimera@polito.it and valentino.peluso@polito.it (in cc) with subject <ML4IOT21 GroupN> (N is the group ID). Attached with the e-mail the following files:

1. One single .py file for each exercise, titled <HW1_exM_GroupN.py>, where M is the exercise number and N is the group ID, containing the Python code. The code must use only the packages that get installed with *rpi_requirements.txt* and *requirements.txt*.
2. One-page pdf report, titled <GroupN_Homework1.pdf>, organized in different sections (one for each exercise). Each section should motivate the main adopted design choices and discuss the outcome of the exercise.

Late messages, or messages not compliant with the above specs, will be automatically discarded.

Background 1: Sensor Fusion

Many prediction tasks can benefit from exploiting data originating from different sources. We refer to this kind of applications with *sensor fusion*. Some popular examples are: (i) scene classifications, which relies on image, audio, and temperature to classify the environment (indoor or outdoor); (ii) position and velocity estimation, which combines several inertial sensors (accelerometer, gyroscope, magnetometer, altimeter); (iii) activity recognition, which can complement measurements from inertial sensors with electrocardiography and electromyography data.

Inspired by humans that use the five basic senses to sense and process information, sensor fusion relies on the hypothesis that the analysis of multiple sources of data improves the prediction accuracy.

In sensor fusion applications, the training pipeline is therefore fed with structured data. An efficient implementation requires to organize and prepare the data in order to create datasets compliant with the specifications of standard training frameworks.

HowTo 2: TFRecord Datasets

Data movement represents one of the major bottlenecks in neural network training. Indeed, standard training pipelines encompasses the transfer of a massive amount of data from the main storage to the computational units, e.g. from the hard drive to the GPU memory. Fetching data from large storages is slow and energy costly. To mitigate this issue, raw data should be packed in serialized sequences of binary records. In this way, the data will reside in consecutive locations of memory, thus accelerating parallel fetching operations.

The TensorFlow Data API introduced the *TFRecord* format (see *tf.train.TFRecord*) to enable users to easily serialize structured data. Specifically, the user needs to specify:

- the structure of each record through the definition of a key-value based dictionary, called *Example* (see *tf.train.Example*);
- the value for each key of the record, i.e. the *Feature* (see *tf.train.Feature*);
- the data-type for each value (see *tf.train.BytesList*, *tf.train.FloatList*, *tf.train.Int64List*)

The following example builds a *TFRecord* Dataset composed by 10 records of random float and integer numbers:

```
filename = './numbers.tfrecord'
x = np.random.randint(0, 5, 10)
y = np.random.randn(10)

with tf.io.TFRecordWriter(filename) as writer:
    for i in range(10):
        Feature=Features
        x_feature = tf.train.Feature(int64_list=tf.train.Int64List(value=[x[i]]))
        y_feature = tf.train.Feature(float_list=tf.train.FloatList(value=[y[i]]))

        mapping = {'integer': x_feature,
                   'float'   : y_feature}

        example = tf.train.Example(features=tf.train.Features(feature=mapping))

        writer.write(example.SerializeToString())
```

For more information, check the official documentation and tutorial:

https://www.tensorflow.org/api_docs/python/tf/io/TFRecordWriter

https://www.tensorflow.org/tutorials/load_data/tfrecord

Background 3: Power management with Dynamic Voltage Frequency Scaling

Dynamic Voltage Frequency Scaling (DVFS) is today a standard power management strategy for System-on-Chips (SoCs). It relies on the observation that the power consumption of a digital circuit has a quadratic dependance from voltage (V_{dd}) and a linear dependance from clock frequency (f_{clk}).

Voltage Frequency (VF) scaling therefore enables a cubic reduction of power.

??

$$P \propto V_{dd}^2 \cdot f_{clk}$$

To limit the power consumption, the SoC should run at maximum performance (VF_{max}) only for short periods, e.g. to meet tight timing constraints in critical and intensive tasks. Otherwise, the SoC can operate into a low-power state (VF_{min}) and save power without impact on the user experience.

HowTo 4: DVFS on the Raspberry Pi

On Unix-based operating systems (e.g. Raspian), the DVFS is managed by an operating system routine called governor. The standard governor can select two main policies: *performance* and *powersave*. In *performance* mode, the VF level is set to the maximum value $VF_{\max}=0.86V$ @ 1.5GHz, whereas in *powersave* mode, it is set to the minimum value $VF_{\min}=0.81V$ @ 600MHz.

To manually change the operating mode, modify the content of the *scaling_governor* system file:

```
# Set 1.5GHz
sudo sh -c "echo performance > /sys/devices/system/cpu/cpufreq/policy0/scaling_governor"

# Set 600MHz
sudo sh -c "echo powersave > /sys/devices/system/cpu/cpufreq/policy0/scaling_governor"
```

To check the current VF, read the *file* system file, that stores the operating clock frequency in Hertz:

```
cat /sys/devices/system/cpu/cpufreq/policy0/scaling_cur_freq
```

To monitor the operating time at different VF levels, the operating system provides performance monitors, that work as follows:

```
# Reset the monitors
sudo sh -c "echo 1 > /sys/devices/system/cpu/cpufreq/policy0/stats/reset"

# Read the monitors
cat /sys/devices/system/cpu/cpufreq/policy0/stats/time_in_state
```

Note that there exists intermediate VF levels and other governor policies, which will be not considered in this homework.

Exercise 4: Data Preparation: Sensor Fusion Dataset with TFRecord (3pt)

Write a Python script on your notebook to build a *TFRecord* Dataset containing temperature, humidity, and one-second audio samples (Int16 resolution at 48KHz), collected at different datetimes and stored as raw data in a single folder as shown in following example:

to minimize storage, do not apply lossy compression, but I can minimize with a proper selection of the datatype in the tfr 3 options. Also lossless compression isn't needed. I need the exact value as the original signal, just play with the datatypes

```
./raw_data
samples.csv          Select the methodology so that we reduce the storage size of the TFRecord dataset. If I need
audio1.wav           operations for ?? I can explain them in the report (like pseudocode), but the the python code to submit
audio2.wav           must contains only the code for the specific task
audio3.wav
audio4.wav
```

encode_wav-> a normalization is applied, the output is a floating point number (float32). Does this reduce the output?

scipy wavefile-> just encode original signal and keeps the original datatype

to check the data, it's not sufficient to play the file, but compare arrays (in tensorflow or numpy) to check if they are similar and such

consider all datatypes available in tfr and chose those that enable data reduction

Content of *samples.csv*: to read the wav file, we used already 2 method on the labs, 1 returns integere, the other floats, but check also a third option to find the one that reduces the size

```
18/10/2020,09:45:34,21,65,audio1.wav
18/10/2020,09:46:40,21,65,audio2.wav
18/10/2020,09:47:45,21,65,audio3.wav
18/10/2020,09:48:51,21,65,audio4.wav
```

N.B.: The *raw_data* folder is an input of the script. The script should contain only the code to build the *TfRecord* Dataset. not build the colfer

Each *Example* in the *TfRecord* must have four fields:

- datetime (stored as POSIX timestamp);
- temperature;
- humidity;
- audio.

da chiedere/chiarire

Select the proper datatype depending on the field in order to minimize the storage requirements while keeping the original quality of the data. Motivate your choices.

No assumptions must be done on the number of records contained in the dataset.

SYNOPSIS:

```
python HW1_ex4_GroupN.py --input <INPUT DIR> --output <OUTPUT FILE>
```

EXAMPLE:

```
python HW1_ex4_Group1.py --input ./raw_data --output ./fusion.tfrecord
```

Exercise 5: Low-power Data Collection and Pre-processing (3pt)

Write a Python script that iteratively samples 1-second audio signals, process the MFCCs, and store the output on disk. The script takes as input the number of samples to collect and the output path where to store the MFCCs.

Set the resampling, STFT, and MFCCs parameters to the same values as Lab 2 – Ex6.

The pre-processing latency must be <80ms (hard constraint). Identify which steps of the acquisition&pre-processing loop can be performed @VF_{min} such that the time @VF_{min} is maximized and the pre-processing latency is met.

The script should print the latency of each iteration of the loop and the total time spent at the different VF levels. Comment the results.

Suggestion #1: Avoid writing intermediate data on disk to reduce the processing time (check the *BytesIO* class from the *io* package).

use BytesIO for intermediary results


Suggestion #2: Use the *Popen* class from the *subprocess* package to run DVFS commands in non-blocking mode.

set the governor at performance and achieve the time constraints. Then do the same for the other. MAKE Shue that the code without power amangement respect the constraints

which is the freq and resolution for audio signal? freq 48Khz, res = ?? (forse 16 bits)
check ex number 6

SYNOPSIS:

```
python HW1_ex5_GroupN.py --num-samples <NUM SAMPLES> --output <OUTPUT>
```



acquisition and prep ?? loop do
same steps multiple times

EXAMPLE:

```
python HW1_ex5_Group1.py --num-samples 5 --output ./out
```

Output:

```
1.054
1.069
1.068
1.069
1.068
600000 465
750000 0
1000000 0
1500000 64
```

any opeeration must be inside the
profiling, I can't have some operations
that aren't profiled

it may happen that the first iteration of the
loop is longer than the other, this is something
that could happen in cached based sysmtes
(like embedded ones), at the begiining of the
execution the cach could be empty.., but the
other iterations must be shorter than the time
constraints

Content of the out folder:

```
./out
mfccs0.bin
mfccs1.bin
mfccs2.bin
mfccs3.bin
mfccs4.bin
```